

Product Information



DELFLLEET F384

PRODUCT

Delfleet Epoxy Accelerator F384
Delfleet Epoxy Primers

PRODUCT DRSCRIPTION

Delfleet Epoxy Accelerator is an additive used to assist the drying of Delfleet Epoxy products only, when the temperature is below 15°C.

SUBSTRATE PRE-TREATMENT

Please refer to the relevant product data sheet for preparation details

APPLICATION GUIDE

The accelerator should be added to the mixed primer when ready-to-spray stage in the proportion of 3 % by weight (30 g/l). The potlife is 4 hours.

PERFORMANCE AND LIMITATIONS

An excess of accelerator affects drying and can reduce durability.



HEALTH AND SAFETY

These products are for professional use only, and are not to be used for purposes other than those specified. The information on this TDS is based on present scientific and technical knowledge, and it is the responsibility of the user to take all necessary steps in order to ensure the suitability of the product for the intended purpose. For Health and Safety information please refer to the material Safety Data Sheet, also available at: [http://www.ppg.com/PPG MSDS](http://www.ppg.com/PPG_MSDS)

**PPG Industries (UK) Limited.
Auto Refinish
Customer Service and Sales Group,
Needham Road,
Stowmarket,
Suffolk.
IP14 2AD,
England.
Tel: 01449 771775
Fax: 01449 773480**

