



TECHNICAL DATASHEET

6-580

Brushing Additive

PRODUCT DESCRIPTION

6-580 is a brushing additive that can be used with Selemix 1K Alkyd Primers and topcoats – 7-610, 7-611, 7-630 and 7-810, 7-820.

SELECTION AND PREPARATION OF SUBSTRATES

Refer to the relevant primer / topcoat technical datasheet

APPLICATION GUIDE

		<i>Min.</i>	<i>Max.</i>
Mix by weight:	Primer / Topcoat	1000	1000
	Brushing Additive	15	20

Brushes Good quality, clean brushes are recommended

HEALTH AND SAFETY

Please refer to Material Safety Data Sheet for full health and safety details and storage regulations

This product is for professional use only.

The information given in this sheet is for guidance only. Any person using the product without first making further enquiries as to the stability of the product for the intended purpose does so at his own risk and we can accept no liability for the performance of the product or for any loss or damage (other than death or personal injury resulting from our negligence) arising out of such use. The information contained in this sheet is liable to modification from time to time in the light of our experience and our policy of continuous product development. Drying times quoted are average times at 20°C. Film thickness, humidity and shop temperature can all affect drying times.

SELEMIX SYSTEM is a brand of PPG Group.

PPG Industries (UK) Ltd, Auto refinish, Customers Service and Sales Group, Needham Road, Stowmarket, Suffolk, IP14 2AD, England, Tel : 01449 771775, Fax : 01449 771547