

## TECHNICAL DATASHEET

Issue date:  
July 2020

# SELEMIX® BRUSHING ADDITIVE 6-580

### PRODUCT DESCRIPTION

*Selemix* 6-580 Brushing Additive can be added to Selemix 1K Synthetic Primers and Topcoats in order to improve the brushing capabilities. The additive extends the open time and gives more flow to help eliminate brush marks.

It can be used in Selemix 7-610, 7-611, and 7-630 Topcoats, and 7-810 and 7-820 Primers.


### PRODUCTS

6-580      *Selemix* Brushing Additive

### SUBSTRATES AND PREPARATION

Refer to the relevant Selemix Primer or Topcoat Technical Datasheet

### MIXING



Features	Brush Application		
	7-610 / 7-611 Fast Dry Topcoat	7-630 1K Urethane Topcoat	7-810 / 7-820 Fast Dry Primer
<b>By Weight:</b> Selemix Primer / Topcoat	1000	1000	1000
6-580 Brushing Additive	15-20	15-20	15-20

## APPLICATION

Good quality, clean brushes are recommended.

## TECHNICAL DATA

Data for Additive as supplied:

Specific Gravity:	0.92
Solids Content:	35.6%
Solvent Content:	64.4%
VOC (g/L)	594g/L

## PRODUCT CODES AND DESCRIPTIONS

Selemix Code	Short Code	Product Description	Packsize
1.965.8000/E1	6-580	Selemix Brushing Additive	1 Ltr

## HEALTH AND SAFETY

For comprehensive Health, Safety and Environmental advice, please refer to the relevant Material Safety Data Sheets and Product can labels.

## THIS PRODUCT IS FOR PROFESSIONAL USE ONLY

The information given in this sheet is for guidance only. Any person using the product without first making further enquiries as to the stability of the product for the intended purpose does so at his own risk and we can accept no liability for the performance of the product or for any loss or damage (other than death or personal injury resulting from our negligence) arising out of such use. The information contained in this sheet is liable to modification from time to time in the light of our experience and our policy of continuous product development. Drying times quoted are average times at 20°C. Film thickness, humidity and shop temperature can all affect drying times.

### FOR FURTHER INFORMATION PLEASE CONTACT:

Selemix Customer Service and Sales Group  
Needham Road  
Stowmarket, Suffolk  
IP14 2AD, England  
Tel: 01449 771771