



DIRECT TOPCOATS

FULL EFFICIENCY IN ONE SINGLE STAGE



Selemix System and the Selemix logo are trademarks of PPG Industries © 2003 PPG Industries. All rights reserved.

C.420.0203



Needham Road, Stowmarket Suffolk
P142AD - United Kingdom
Tel. (+44) 1449 613 161 - Fax (+44) 1449 773 476



Among others, SELEMIX SYSTEM offers a range of topcoats to be applied directly onto substrates and providing outstanding performances in terms of adhesion, protection, productivity, and price.



HIGH TECHNOLOGY FOR HIGH PRODUCTIVITY



The direct binders of SELEMIX SYSTEM rely on a 2K polyurethane technology. Combined to the tinting pastes, they produce high quality topcoats with good adhesion and protection properties. These topcoats can meet a wide range of applications in the light industrial market (shelving, garage doors...).

SELEMIX SYSTEM DIRECT TOPCOATS can be sprayed directly onto a great diversity of substrates either metallic or plastics, without the need for a primer.



Due to the high pigment opacity and the possibility of applying the topcoats at high thickness, most of the paint job can be achieved in one single stage enabling to reduce substantially the process time and product consumption.

Productivity can also be increased, by reducing drying and therefore handling times.



FLEXIBILITY AND DIVERSITY

SELEMIX SYSTEM DIRECT TOPCOATS are available in four levels of gloss from 10 to 70%. The gloss level is adjusted during the manufacturing of the binders which means that batch after batch it will remain consistent.

For each gloss levels, two binders are available.
 > One pre-pigmented binder assuring outstanding hiding power for whites and off-whites.
 > One binder for other colours.

SELEMIX SYSTEM DIRECT TOPCOATS can be applied with any type of spraying equipment available on the light industrial market : conventional, airless, air assisted airless, electrostatic. They even can be rolled using a specific dilution ratio.



INDUSTRIAL COLOUR OFFER

The direct topcoats of Selemix System cover a wide variety of industrial colours (RAL, NCS). Each colour will be available in each of the four gloss levels and in both lead containing and lead free versions.



DIRECT TOPCOATS AND ENVIRONMENT

When mixed with the specific HS hardener and applied with airless or air assisted airless equipments, Selemix System direct topcoats are compliant with the EU VOC legislation.