SAFETY DATA SHEET



Date of issue/Date of revision 14 July 2023 Version 1

Section 1. Identification		
Product name	: TITANIUM METALLIC HYBRID	
Product code	: PCF75127	
Other means of identification	: Not available.	
Product type	: Powder.	
Relevant identified uses o	f the substance or mixture and uses advised against	
Product use	: Industrial applications.	
Use of the substance/ mixture	: Coating. Paints. Painting-related materials.	
Uses advised against	: Not applicable.	
Manufacturer Emergency telephone	 PPG Industries, Inc. One PPG Place Pittsburgh, PA 15272 : (412) 434-4515 (U.S.) 	
number	(514) 645-1320 (Canada) SETIQ Interior de la República: 800-00-214-00 (México) SETIQ Ciudad de México: (55) 5559-1588 (México)	
Technical Phone Number	: 1-888-774-2001 (US and Canada)	

Section 2. Hazards identification

OSHA/HCS status Classification of the substance or mixture	 This material is considered hazardous by the OSHA Hazard Communication Standard (29 CFR 1910.1200). COMBUSTIBLE DUSTS CARCINOGENICITY - Category 2
	Percentage of the mixture consisting of ingredient(s) of unknown acute toxicity: 54.5% (oral), 52.9% (dermal), 90.2% (inhalation)
GHS label elements	
Hazard pictograms	
Signal word	: Warning
Hazard statements	: Suspected of causing cancer. May form combustible dust concentrations in air.
Precautionary statements	

United States

Page: 1/13

Product name TITANIUM METALLIC HYBRID

Section 2. Hazards identification

Prevention	: Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Wear protective gloves, protective clothing and eye or face protection.	
Response	 IF exposed or concerned: Get medical advice or attention. Photosensitive agents : In case of accidental eye contact, avoid direct exposure to the sun or other sources of UV light as severe irritation including burns may result. These reactions can be delayed – get medical attention if pain, irritation or blistering occurs after contact. In case of accidental skin contact, avoid direct exposure to the sun or other sources of UV light as severe irritation including burns may result. These reactions can be delayed – get medical attention if pain, irritation, rash or blistering occurs after contact. 	
Storage	: Store locked up.	
Disposal	: Dispose of contents and container in accordance with all local, regional, national and international regulations.	
Supplemental label elements	 Keep container tightly closed. Keep away from heat, sparks, open flames and hot surfaces No smoking. Prevent dust accumulation. Emits toxic fumes when heated. 	
Hazards not otherwise classified	: Fine dust clouds may form explosive mixtures with air. Handling and/or processing of this material may generate a dust which can cause mechanical irritation of the eyes, skin, nose and throat.	

Section 3. Composition/information on ingredients

Substance/mixture Product name : Mixture

: TITANIUM METALLIC HYBRID

Ingredient name	%	CAS number
F F. ·	≥1.0 - ≤5.0 ≥1.0 - ≤5.0 ≤1.0	Not available. 7429-90-5 1333-86-4

SUB codes represent substances without registered CAS Numbers.

Any concentration shown as a range is to protect confidentiality or is due to batch variation.

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment and hence require reporting in this section.

Occupational exposure limits, if available, are listed in Section 8.

Section 4. First aid measures

If ingestion, irritation, any type of overexposure or symptoms of overexposure occur during or persists after use of this product, contact a POISON CONTROL CENTER, EMERGENCY ROOM OR PHYSICIAN immediately; have Safety Data Sheet information available. Never give anything by mouth to an unconscious or convulsing person. Description of necessary first aid measures

Description of necessary first aid measures

Eye contact: Remove contact lenses, irrigate copiously with clean, fresh water, holding the eyelids
apart for at least 10 minutes and seek immediate medical advice.
In case of accidental eye contact, avoid direct exposure to the sun or other sources of
UV light as severe irritation including burns may result. These reactions can be delayed
– get medical attention if pain, irritation or blistering occurs after contact.

United States Page: 2/13	
--------------------------	--

Product name TITANIUM METALLIC HYBRID

Section 4. First aid measures

Inhalation	: Remove to fresh air. Keep person warm and at rest. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel.
Skin contact	 Remove contaminated clothing and shoes. Wash skin thoroughly with soap and water or use recognized skin cleanser. Do NOT use solvents or thinners.
	In case of accidental skin contact, avoid direct exposure to the sun or other sources of UV light as severe irritation including burns may result. These reactions can be delayed – get medical attention if pain, irritation, rash or blistering occurs after contact.
Ingestion	: If swallowed, seek medical advice immediately and show this container or label. Keep person warm and at rest. Do NOT induce vomiting.
Most important sympton	ns/effects, acute and delayed
Potential acute health e	<u>ffects</u>
Eye contact	: Exposure to airborne concentrations above statutory or recommended exposure limits may cause irritation of the eyes.
Inhalation	: Exposure to airborne concentrations above statutory or recommended exposure limits may cause irritation of the nose, throat and lungs.
Skin contact	: No known significant effects or critical hazards.
Ingestion	: No known significant effects or critical hazards.
Over-exposure signs/sy	
Eye contact	: Adverse symptoms may include the following: irritation redness
Inhalation	: Adverse symptoms may include the following: respiratory tract irritation
	coughing
Skin contact	: No specific data.
Ingestion	: No specific data.
Indication of immediate	medical attention and special treatment needed, if necessary
Notes to physician	 Treat symptomatically. Contact poison treatment specialist immediately if large quantities have been ingested or inhaled.

Specific treatments : No specific treatment.

Protection of first-aiders : No action shall be taken involving any personal risk or without suitable training. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation.

See toxicological information (Section 11)

Section 5. Fire-fighting measures

Extinguishing media	
Suitable extinguishing media	: Use dry chemical powder.
Unsuitable extinguishing media	: Avoid high pressure media which could cause the formation of a potentially explosible dust-air mixture.
Specific hazards arising from the chemical	: Fine dust clouds may form explosive mixtures with air.

United States

Page: 3/13

Product name TITANIUM METALLIC HYBRID

Section 5. Fire-fighting measures

Hazardous thermal decomposition products	: Decomposition products may include the following materials: carbon oxides metal oxide/oxides
Special protective actions for fire-fighters	: Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training. Move containers from fire area if this can be done without risk. Use water spray to keep fire-exposed containers cool.
Special protective equipment for fire-fighters	: Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode.

Section 6. Accidental release measures

Personal precautions, protective equipment and emergency procedures

For non-emergency personnel	 No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilled material. Shut off all ignition sources. No flares, smoking or flames in hazard area. Avoid breathing dust. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment.
For emergency responders	
Environmental precautions	: Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air).
Methods and materials for co	ontainment and cleaning up
Small spill	: Move containers from spill area. Use spark-proof tools and explosion-proof equipment. Avoid dust generation. Do not dry sweep. Vacuum dust with equipment fitted with a HEPA filter and place in a closed, labeled waste container. Dispose of via a licensed waste disposal contractor.
Large spill	: Move containers from spill area. Use spark-proof tools and explosion-proof equipment. Approach release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Avoid dust generation. Do not dry sweep. Vacuum dust with equipment fitted with a HEPA filter and place in a closed, labeled waste container. Avoid creating dusty conditions and prevent wind dispersal. Dispose of via a licensed waste disposal contractor. Note: see Section 1 for emergency contact information and Section 13 for waste disposal.

Section 7. Handling and storage

Precautions for safe handling

Product name TITANIUM METALLIC HYBRID

Section 7. Handling and storage

Protective measures	: Put on appropriate personal protective equipment (see Section 8). Avoid exposure - obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Do not get in eyes or on skin or clothing. Do not ingest. Avoid breathing dust. Avoid the creation of dust when handling and avoid all possible sources of ignition (spark or flame). Prevent dust accumulation. Use only with adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Electrical equipment and lighting should be protected to appropriate standards to prevent dust coming into contact with hot surfaces, sparks or other ignition sources. Take precautionary measures against electrostatic discharges. To avoid fire or explosion, dissipate static electricity during transfer by grounding and bonding containers and equipment before transferring material. Empty containers retain product residue and can be hazardous. Do not reuse container.
Special precautions	: If this material is part of a multiple component system, read the Safety Data Sheet(s) for the other component or components before blending as the resulting mixture may have the hazards of all of its parts.
Advice on general occupational hygiene	: Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.
Conditions for safe storage, including any incompatibilities	: Do not store below the following temperature: 5°C (41°F). Store in accordance with local regulations. Store in a segregated and approved area. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Store locked up. Eliminate all ignition sources. Separate from oxidizing materials. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabeled containers. Use appropriate containment to avoid environmental contamination.

Section 8. Exposure controls/personal protection

Control parameters

Occupational exposure limits

Ingredient name	Exposure limits
proprietary monomer	ACGIH TLV (United States).
	TWA: 5 mg/m ³ 8 hours.
aluminium powder (stabilised)	ACGIH TLV (United States, 1/2022).
	[Aluminum, metal and insoluble
	compounds]
	TWA: 1 mg/m³ 8 hours. Form: Respirable
	fraction
	OSHA PEL (United States, 5/2018).
	TWA: 5 mg/m³, (as Al) 8 hours. Form:
	Respirable fraction
	TWA: 15 mg/m³, (as Al) 8 hours. Form: Total
	dust
carbon black	ACGIH TLV (United States, 1/2022).
	TWA: 3 mg/m ³ 8 hours. Form: Inhalable
	fraction
<u></u>	United States Page: 5/13

Product name TITANIUM METALLIC HYBRID

Section 8. Exposure controls/personal protection

OSHA PEL (United States, 5/2018).

		TWA: 3.5 mg/m ³ 8 hours.	
	Key to abbreviations		
C = Ceiling Limit F = Fume IPEL = Internal Permissible Expo OSHA = Occupational Safety and I R = Respirable	Governmental Industrial Hygienists. sure Limit Health Administration. 9 Subpart Z - Toxic and Hazardous Substances	S= Potential skin absorptionSR= Respiratory sensitizationSS= Skin sensitizationSTEL= Short term Exposure limit valuesTD= Total dustTLV= Threshold Limit ValueTWA= Time Weighted Average	
Recommended monitoring procedures		priate monitoring standards. Reference to national r the determination of hazardous substances will	
Appropriate engineering controls	or mist, use process enclosures, loc to keep worker exposure to airborne limits. The engineering controls also	If user operations generate dust, fumes, gas, vapor al exhaust ventilation or other engineering controls contaminants below any recommended or statutory o need to keep gas, vapor or dust concentrations se explosion-proof ventilation equipment.	
Environmental exposure controls	Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.		
Individual protection measure	<u>S</u>		
Hygiene measures	eating, smoking and using the lavate Appropriate techniques should be us	roughly after handling chemical products, before bry and at the end of the working period. sed to remove potentially contaminated clothing. reusing. Ensure that eyewash stations and safety n location.	
Eye/face protection	: Safety glasses with side shields.		
Skin protection Hand protection	: Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. Considering the parameters specified by the glove manufacturer, check during use that the gloves are still retaining their protective properties. It should be noted that the time to breakthrough for any glove material may be different for different glove manufacturers. In the case of mixtures, consisting of several substances, the protection time of the gloves cannot be accurately estimated.		
Gloves	: polyethylene		
Body protection		e body should be selected based on the task being d should be approved by a specialist before	
Other skin protection	: Appropriate footwear and any addition	onal skin protection measures should be selected and the risks involved and should be approved by a ct.	

Product name TITANIUM METALLIC HYBRID

Section 8. Exposure controls/personal protection

Respiratory protection: Respirator selection must be based on known or anticipated exposure levels, the
hazards of the product and the safe working limits of the selected respirator. If workers
are exposed to concentrations above the exposure limit, they must use appropriate,
certified respirators. Use a properly fitted, air-purifying or air-fed respirator complying
with an approved standard if a risk assessment indicates this is necessary.
The respiratory protection shall be in accordance to 29 CFR 1910.134.

Section 9. Physical and chemical properties

<u>Appearance</u>			
Physical state	1	Solid.	
		Powder.	
Color	4	Silver.	
Odor	1	Not available.	
Odor threshold	1	Not available.	
рН	÷	Not applicable.	
Melting point	4	Not available.	
Boiling point	4	Not available.	
Flash point	1	Closed cup: Not applicable.	
Auto-ignition temperature	1	Not applicable.	
Decomposition temperature	1	Not available.	
Flammability	1	Not available.	
Lower and upper explosive (flammable) limits	1	Not applicable.	
Evaporation rate	1	Not available.	
Vapor pressure	1	Not available.	
Vapor density	1	Not applicable.	
Relative density	1	1.18	
Density(lbs / gal)	1	9.85	
		Media	Result
Solubility(ies)	-	cold water	Not soluble
Partition coefficient: n- octanol/water	:	Not applicable.	
Viscosity	1	Kinematic (40°C (104°F)): N	Not applicable.
Volatility	:	0% (v/v), 0.04% (w/w)	
% Solid. (w/w)	:	99.96	

Product name TITANIUM METALLIC HYBRID

Section 10. Stability and reactivity

Reactivity	: No specific test data related to reactivity available for this product or its ingredients.
Chemical stability	: The product is stable.
Possibility of hazardous reactions	: Under normal conditions of storage and use, hazardous reactions will not occur.
Conditions to avoid	: When exposed to high temperatures may produce hazardous decomposition products. Refer to protective measures listed in sections 7 and 8.
Incompatible materials	: Keep away from the following materials to prevent strong exothermic reactions: oxidizing agents, strong alkalis, strong acids.
Hazardous decomposition products	: Depending on conditions, decomposition products may include the following materials: carbon oxides metal oxide/oxides

Section 11. Toxicological information

Information on toxicological effects

Acute toxicity

Product/ingredient name	Result			Species	Dose	Exposure
proprietary monomer	LC50 Inhal	ation Dusts a	nd mists	Rat	>3750 g/m³	4 hours
	LD50 Dern			Rabbit	>2000 mg/kg	-
aluminium powder (stabilised)		ation Dusts a	nd mists	Rat	>5 mg/l	4 hours
	LD50 Oral			Rat	>15900 mg/kg	-
carbon black	LD50 Oral			Rat	>10 g/kg	-
Conclusion/Summary	: There are	e no data avai	lable on th	e mixture itself.		
Irritation/Corrosion						
Conclusion/Summary						
Skin	: There are	e no data avai	lable on th	e mixture itself.		
Eyes	: There are	e no data avai	lable on th	e mixture itself.		
Respiratory	: There are	e no data avai	lable on th	e mixture itself.		
<u>Sensitization</u>						
Conclusion/Summary						
Skin	: There are	e no data avai	lable on th	e mixture itself.		
Respiratory	: There are	There are no data available on the mixture itself.				
<u>Mutagenicity</u>						
Conclusion/Summary	: There are	e no data avai	lable on th	e mixture itself.		
<u>Carcinogenicity</u>						
Conclusion/Summary	ummary : There are no data available on the mixture itself.					
Classification						
Product/ingredient name	OSHA	IARC N	ТР			
carbon black	-	2B -				
L		1 I			United States	Page: 8/13

Product name TITANIUM METALLIC HYBRID

Section 11. Toxicological information

Carcinogen Classification code:

IARC: 1, 2A, 2B, 3, 4 NTP: Known to be a human carcinogen; Reasonably anticipated to be a human carcinogen OSHA: + Not listed/not regulated: -

Reproductive toxicity

Conclusion/Summary : There are no data available on the mixture itself.

Teratogenicity

Conclusion/Summary : There are no data available on the mixture itself.

Specific target organ toxicity (single exposure)

Not available.

Specific target organ toxicity (repeated exposure)

Not available.

Target organs

: Contains material which causes damage to the following organs: eye, lens or cornea. Contains material which may cause damage to the following organs: lungs, the nervous system, upper respiratory tract, skin.

Aspiration hazard

Not available.

Information on the likely routes of exposure

Potential acute health effects

Potential acute nealth end	
Eye contact	: Exposure to airborne concentrations above statutory or recommended exposure limits may cause irritation of the eyes.
Inhalation	: Exposure to airborne concentrations above statutory or recommended exposure limits may cause irritation of the nose, throat and lungs.
Skin contact	: No known significant effects or critical hazards.
Ingestion	: No known significant effects or critical hazards.
Over-exposure signs/sym	<u>iptoms</u>
Eye contact	: Adverse symptoms may include the following: irritation redness
Inhalation	: Adverse symptoms may include the following: respiratory tract irritation coughing
Skin contact	: No specific data.
Ingestion	: No specific data.
Delayed and immediate eff	ects and also chronic effects from short and long term exposure
Conclusion/Summary	: There are no data available on the mixture itself. Acrylate components of the mixture have irritating properties. Prolonged or repeated contact with skin or mucous membrane may result in irritation symptoms, such as redness, blistering, dermatitis etc. May cause allergic skin reactions with repeated exposure. The inhalation of airborne droplets or aerosols may cause irritation of the respiratory tract. Ingestion may cause nausea, weakness and central nervous system effects. Repeated exposure of the eyes to a low level of dust can produce eye irritation. Repeated or prolonged inhalation of dust may lead to chronic respiratory irritation. This takes into account, where known, delayed and immediate effects and also chronic effects of components from short-term

United States Page: 9/13

Product name TITANIUM METALLIC HYBRID

Section 11. Toxicological information

and long-term exposure by oral, inhalation and dermal routes of exposure and eye contact.

Short term exposure	
Potential immediate effects	: There are no data available on the mixture itself.
Potential delayed effects	: There are no data available on the mixture itself.
<u>Long term exposure</u>	
Potential immediate effects	: There are no data available on the mixture itself.
Potential delayed effects	: There are no data available on the mixture itself.
Potential chronic health eff	<u>ects</u>
General	: Repeated or prolonged inhalation of dust may lead to chronic respiratory irritation.
Carcinogenicity	 Suspected of causing cancer. Risk of cancer depends on duration and level of exposure.
Mutagenicity	: No known significant effects or critical hazards.
Reproductive toxicity	: No known significant effects or critical hazards.

Numerical measures of toxicity

Acute toxicity estimates

Product/ingredient name	Oral (mg/ kg)	Dermal (mg/kg)	Inhalation (gases) (ppm)	(vapors)	Inhalation (dusts and mists) (mg/ I)
	N/A	43112.0	N/A	N/A	N/A
	N/A	2500	N/A	N/A	N/A

Section 12. Ecological information

Toxicity

Not available.

Persistence and degradability

Not available.

Bioaccumulative potential

Product/ingredient name	LogPow	BCF	Potential
proprietary monomer	0.95	3.2	Low

Mobility in soil

Soil/water partition coefficient (Koc)

: Not available.

United States Page: 10/13

Product name TITANIUM METALLIC HYBRID

Section 13. Disposal considerations

Disposal methods

: The generation of waste should be avoided or minimized wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible. This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.

Disposal should be in accordance with applicable regional, national and local laws and regulations. Refer to Section 7: HANDLING AND STORAGE and Section 8: EXPOSURE CONTROLS/PERSONAL PROTECTION for additional handling information and protection of employees. Section 6. Accidental release measures

14. Transport information

			1
	DOT	IMDG	ΙΑΤΑ
UN number	Not regulated.	Not regulated.	Not regulated.
UN proper shipping name	-	-	-
Transport hazard class (es)	-	-	-
Packing group	-	-	-
Environmental hazards	No.	No.	No.
Marine pollutant substances	Not applicable.	Not applicable.	Not applicable.

Additional information

- DOT: None identified.IMDG: None identified.
- IATA : None identified.

Special precautions for user : Transport within user's premises: always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage.

Transport in bulk according : Not applicable. to IMO instruments

Product name TITANIUM METALLIC HYBRID

Section 15. Regulatory information

United States

United States inventory (TSCA 8b) : All components are active or exempted.

SARA 302/304

SARA 304 RQ : Not applicable.

Composition/information on ingredients

No products were found.

SARA 311/312

Classification

: COMBUSTIBLE DUSTS CARCINOGENICITY - Category 2

Composition/information on ingredients

Name	%	Classification
carbon black		COMBUSTIBLE DUSTS CARCINOGENICITY - Category 2

SARA 313

Chemical name

: Aluminium powder (stabilized)

CAS number 7429-90-5 Concentration 0.5 - 1.5

SARA 313 notifications must not be detached from the SDS and any copying and redistribution of the SDS shall include copying and redistribution of the notice attached to copies of the SDS subsequently redistributed.

Additional environmental information is contained on the Environmental Data Sheet for this product, which can be obtained from your PPG representative.

California Prop. 65

Supplier notification

WARNING: Cancer - www.P65Warnings.ca.gov.

Section 16. Other information

Hazardous Material Information System (U.S.A.)	
--	--

Health : 1 * Flammability : 0 Physical hazards : 0 (*) - Chronic effects

Caution: HMIS® ratings are based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks. Although HMIS® ratings and the associated label are not required on MSDSs or products leaving a facility under 29 CFR 1910.1200, the preparer may choose to provide them. HMIS® ratings are to be used with a fully implemented HMIS® program. HMIS® is a registered trademark and service mark of the American Coatings Association, Inc.

The customer is responsible for determining the PPE code for this material. For more information on HMIS® Personal Protective Equipment (PPE) codes, consult the HMIS® Implementation Manual.

National Fire Protection Association (U.S.A.)

Health : 1 Flammability : 0 Instability : 0

Date of previous issue : No previous validation

Organization that prepared : EHS the SDS

Product name TITANIUM METALLIC HYBRID

Section 16. Other information

Key to abbreviations	: ATE = Acute Toxicity Estimate
-	BCF = Bioconcentration Factor
	GHS = Globally Harmonized System of Classification and Labelling of Chemicals
	IATA = International Air Transport Association
	IBC = Intermediate Bulk Container
	IMDG = International Maritime Dangerous Goods
	LogPow = logarithm of the octanol/water partition coefficient
	MARPOL = International Convention for the Prevention of Pollution From Ships, 1973 as modified by the Protocol of 1978. ("Marpol" = marine pollution)
	N/A = Not available
	SGG = Segregation Group
	UN = United Nations
—	

Indicates information that has changed from previously issued version.

Disclaimer

The information contained in this data sheet is based on present scientific and technical knowledge. The purpose of this information is to draw attention to the health and safety aspects concerning the products supplied by PPG, and to recommend precautionary measures for the storage and handling of the products. No warranty or guarantee is given in respect of the properties of the products. No liability can be accepted for any failure to observe the precautionary measures described in this data sheet or for any misuse of the products.