# **SAFETY DATA SHEET**



Date of issue/Date of revision8 December 2023Version 3

| Section 1. Identification                  |  |
|--|--|
| Product name                               | : PMS 695 C HYBRID   |
| Product code                               | : PCFA60154  |
| Other means of identification              | : Not available.   |
| Product type                               | : Powder.  |
| Relevant identified uses of                | f the substance or mixture and uses advised against  |
| Product use                                | : Industrial applications.   |
| Use of the substance/<br>mixture           | : Coating. Paints. Painting-related materials.   |
| Uses advised against                       | : Not applicable.  |
| Manufacturer<br><u>Emergency telephone</u> | <ul> <li>PPG Industries, Inc.</li> <li>One PPG Place</li> <li>Pittsburgh, PA 15272</li> <li>: (412) 434-4515 (U.S.)</li> </ul>       |
| <u>number</u>                              | (514) 645-1320 (Canada)<br>SETIQ Interior de la República: 800-00-214-00 (México)<br>SETIQ Ciudad de México: (55) 5559-1588 (México) |
| Technical Phone Number                     | : 1-888-774-2001 (US and Canada)   |

# Section 2. Hazards identification

| OSHA/HCS status                            | : This material is considered hazardous by the OSHA Hazard Communication Standard (29 CFR 1910.1200).                             |
|--|---|
| Classification of the substance or mixture | : COMBUSTIBLE DUSTS<br>CARCINOGENICITY - Category 2<br>TOXIC TO REPRODUCTION - Category 2   |
|  | Percentage of the mixture consisting of ingredient(s) of unknown acute toxicity: 40.2% (oral), 41.7% (dermal), 68.4% (inhalation) |
| GHS label elements<br>Hazard pictograms    |   |
| Signal word                                | : Warning   |

Product name PMS 695 C HYBRID

### Section 2. Hazards identification

| Hazard statements                   | : Suspected of causing cancer.   |
|-------------------------------------|--|
|                                     | Suspected of damaging fertility or the unborn child.   |
|                                     | May form combustible dust concentrations in air.   |
| Precautionary statements            |  |
| Prevention                          | : Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Wear protective gloves, protective clothing and eye or face protection.        |
| Response                            | : IF exposed or concerned: Get medical advice or attention.  |
| Storage                             | : Store locked up.   |
| Disposal                            | : Dispose of contents and container in accordance with all local, regional, national and international regulations.  |
| Supplemental label elements         | : Keep container tightly closed. Keep away from heat, sparks, open flames and hot<br>surfaces No smoking. Prevent dust accumulation. Emits toxic fumes when heated.                                |
| Hazards not otherwise<br>classified | : Fine dust clouds may form explosive mixtures with air. Handling and/or processing of this material may generate a dust which can cause mechanical irritation of the eyes, skin, nose and throat. |

### Section 3. Composition/information on ingredients

| Substance/mixture | 1 | Mixture          |
|-------------------|---|------------------|
| Product name      | 1 | PMS 695 C HYBRID |

| Ingredient name                | %         | CAS number     |
|--------------------------------|-----------|----------------|
| polyester resin                | ≥20 - ≤50 | Not available. |
| titanium dioxide               | ≥20 - ≤50 | 13463-67-7     |
| titanium dioxide (<10 microns) | ≤1.0      | 13463-67-7     |
| propylidynetrimethanol         | ≤1.0      | 77-99-6        |
| carbon black                   | ≤1.0      | 1333-86-4      |

SUB codes represent substances without registered CAS Numbers.

Any concentration shown as a range is to protect confidentiality or is due to batch variation.

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment and hence require reporting in this section.

Occupational exposure limits, if available, are listed in Section 8.

### Section 4. First aid measures

If ingestion, irritation, any type of overexposure or symptoms of overexposure occur during or persists after use of this product, contact a POISON CONTROL CENTER, EMERGENCY ROOM OR PHYSICIAN immediately; have Safety Data Sheet information available. Never give anything by mouth to an unconscious or convulsing person. **Description of necessary first aid measures** 

| Eye contact | : Remove contact lenses, irrigate copiously with clean, fresh water, holding the eyelids<br>apart for at least 10 minutes and seek immediate medical advice.   |
|-------------|--|
| Inhalation  | <ul> <li>Remove to fresh air. Keep person warm and at rest. If not breathing, if breathing is<br/>irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained<br/>personnel.</li> </ul> |

Product name PMS 695 C HYBRID

### Section 4. First aid measures

| Skin contact | : Remove contaminated clothing and shoes. Wash skin thoroughly with soap and water     |
|--------------|--|
|              | or use recognized skin cleanser. Do NOT use solvents or thinners.                      |
| Ingestion    | : If swallowed, seek medical advice immediately and show this container or label. Keep |
|              | person warm and at rest. Do NOT induce vomiting.                                       |

#### Most important symptoms/effects, acute and delayed

| Most important symptoms/    | effects, acute and delayed   |
|-----------------------------|--|
| Potential acute health effe | <u>cts</u>   |
| Eye contact                 | : Exposure to airborne concentrations above statutory or recommended exposure limits may cause irritation of the eyes.   |
| Inhalation                  | : Exposure to airborne concentrations above statutory or recommended exposure limits may cause irritation of the nose, throat and lungs.                                   |
| Skin contact                | : No known significant effects or critical hazards.  |
| Ingestion                   | : No known significant effects or critical hazards.  |
| Over-exposure signs/sym     | <u>otoms</u>   |
| Eye contact                 | : Adverse symptoms may include the following:<br>irritation<br>redness   |
| Inhalation                  | : Adverse symptoms may include the following:<br>respiratory tract irritation<br>coughing<br>reduced fetal weight<br>increase in fetal deaths<br>skeletal malformations    |
| Skin contact                | : Adverse symptoms may include the following:<br>reduced fetal weight<br>increase in fetal deaths<br>skeletal malformations  |
| Ingestion                   | : Adverse symptoms may include the following:<br>reduced fetal weight<br>increase in fetal deaths<br>skeletal malformations  |
| Indication of immediate me  | dical attention and special treatment needed, if necessary   |
| Notes to physician          | : In case of inhalation of decomposition products in a fire, symptoms may be delayed.<br>The exposed person may need to be kept under medical surveillance for 48 hours.   |
| Specific treatments         | : No specific treatment.   |
| Protection of first-aiders  | : No action shall be taken involving any personal risk or without suitable training. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. |

See toxicological information (Section 11)

**United States** 

Page: 4/13

Product name PMS 695 C HYBRID

# Section 5. Fire-fighting measures

| Extinguishing media                            |  |
|--|--|
| Suitable extinguishing media                   | : Use dry chemical powder.   |
| Unsuitable extinguishing media                 | : Avoid high pressure media which could cause the formation of a potentially explosible dust-air mixture.  |
| Specific hazards arising from the chemical     | : Fine dust clouds may form explosive mixtures with air.   |
| Hazardous thermal decomposition products       | : Decomposition products may include the following materials:<br>carbon oxides<br>nitrogen oxides<br>metal oxide/oxides  |
| Special protective actions for fire-fighters   | : Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training. Move containers from fire area if this can be done without risk. Use water spray to keep fire-exposed containers cool. |
| Special protective equipment for fire-fighters | : Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode.  |

# Section 6. Accidental release measures

#### Personal precautions, protective equipment and emergency procedures

| For non-emergency<br>personnel | : No action shall be taken involving any personal risk or without suitable training.<br>Evacuate surrounding areas. Keep unnecessary and unprotected personnel from<br>entering. Do not touch or walk through spilled material. Shut off all ignition sources.<br>No flares, smoking or flames in hazard area. Avoid breathing dust. Provide adequate<br>ventilation. Wear appropriate respirator when ventilation is inadequate. Put on<br>appropriate personal protective equipment.   |
|--------------------------------|--|
| For emergency responders       | : If specialized clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".  |
| Environmental precautions      | : Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air).  |
| Methods and materials for co   | ntainment and cleaning up  |
| Small spill                    | : Move containers from spill area. Use spark-proof tools and explosion-proof equipment.<br>Avoid dust generation. Do not dry sweep. Vacuum dust with equipment fitted with a<br>HEPA filter and place in a closed, labeled waste container. Dispose of via a licensed<br>waste disposal contractor.  |
| Large spill                    | : Move containers from spill area. Use spark-proof tools and explosion-proof equipment.<br>Approach release from upwind. Prevent entry into sewers, water courses, basements<br>or confined areas. Avoid dust generation. Do not dry sweep. Vacuum dust with<br>equipment fitted with a HEPA filter and place in a closed, labeled waste container.<br>Avoid creating dusty conditions and prevent wind dispersal. Dispose of via a licensed<br>waste disposal contractor. Note: see Section 1 for emergency contact information and<br>Section 13 for waste disposal. |

Product name PMS 695 C HYBRID

### Section 6. Accidental release measures

# Section 7. Handling and storage

| Precautions for safe handling                                      | 2  |
|--|--|
| Protective measures  | : Put on appropriate personal protective equipment (see Section 8). Avoid exposure -<br>obtain special instructions before use. Avoid exposure during pregnancy. Do not<br>handle until all safety precautions have been read and understood. Do not get in eyes<br>or on skin or clothing. Do not ingest. Avoid breathing dust. Avoid the creation of dust<br>when handling and avoid all possible sources of ignition (spark or flame). Prevent dust<br>accumulation. Use only with adequate ventilation. Wear appropriate respirator when<br>ventilation is inadequate. Keep in the original container or an approved alternative<br>made from a compatible material, kept tightly closed when not in use. Electrical<br>equipment and lighting should be protected to appropriate standards to prevent dust<br>coming into contact with hot surfaces, sparks or other ignition sources. Take<br>precautionary measures against electrostatic discharges. To avoid fire or explosion,<br>dissipate static electricity during transfer by grounding and bonding containers and<br>equipment before transferring material. Empty containers retain product residue and<br>can be hazardous. Do not reuse container. |
| Special precautions  | : If this material is part of a multiple component system, read the Safety Data Sheet(s) for the other component or components before blending as the resulting mixture may have the hazards of all of its parts.  |
| Advice on general<br>occupational hygiene                          | : Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.  |
| Conditions for safe storage,<br>including any<br>incompatibilities | : Do not store below the following temperature: 5°C (41°F). Store in accordance with local regulations. Store in a segregated and approved area. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Store locked up. Eliminate all ignition sources. Separate from oxidizing materials. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabeled containers. Use appropriate containment to avoid environmental contamination.  |

# Section 8. Exposure controls/personal protection

#### **Control parameters**

#### **Occupational exposure limits**

| Ingredient name                | Exposure limits                                      |
|--------------------------------|--|
| polyester resin                | ACGIH TLV (United States).                           |
|                                | TWA: 3 mg/m <sup>3</sup> Form: Respirable dust       |
|                                | TWA: 10 mg/m <sup>3</sup> Form: inhalable dust       |
| titanium dioxide               | OSHA PEL (United States, 5/2018).                    |
|                                | TWA: 15 mg/m <sup>3</sup> 8 hours. Form: Total dust  |
|                                | ACGIH TLV (United States, 1/2023).                   |
|                                | TWA: 2.5 mg/m <sup>3</sup> 8 hours. Form: respirable |
|                                | fraction, finescale particles                        |
| titanium dioxide (<10 microns) | OSHA PEL (United States, 5/2018).                    |
|                                | TWA: 15 mg/m³ 8 hours. Form: Total dust              |
| ·                              | United States Page: 5/13                             |

Product name PMS 695 C HYBRID

# Section 8. Exposure controls/personal protection

| propylidynetrimethanol<br>carbon black  | Key to abbreviations  | <ul> <li>ACGIH TLV (United States, 1/2023).<br/>TWA: 2.5 mg/m<sup>3</sup> 8 hours. Form: respirable<br/>fraction, finescale particles<br/>None.</li> <li>ACGIH TLV (United States, 1/2023).<br/>TWA: 3 mg/m<sup>3</sup> 8 hours. Form: Inhalable<br/>fraction</li> <li>OSHA PEL (United States, 5/2018).<br/>TWA: 3.5 mg/m<sup>3</sup> 8 hours.</li> </ul> |
|---|---|--|
| A = Acceptable Maximum Pe   |   | S = Potential skin absorption  |
| ACGIH       = American Conference of         C       = Ceiling Limit         F       = Fume         IPEL       = Internal Permissible Exp         OSHA       = Occupational Safety and         R       = Respirable | Governmental Industrial Hygienists.<br>osure Limit<br>Health Administration.<br>00 Subpart Z - Toxic and Hazardous Substances   | SR= Respiratory sensitizationSS= Skin sensitizationSTEL= Short term Exposure limit valuesTD= Total dustTLV= Threshold Limit ValueTWA= Time Weighted Average  |
| Recommended monitoring procedures   |   | riate monitoring standards. Reference to national the determination of hazardous substances will   |
| Appropriate engineering<br>controls<br>Environmental exposure<br>controls   | or mist, use process enclosures, local<br>to keep worker exposure to airborne of<br>limits. The engineering controls also<br>below any lower explosive limits. Use<br>: Emissions from ventilation or work pro- | user operations generate dust, fumes, gas, vapor<br>I exhaust ventilation or other engineering controls<br>contaminants below any recommended or statutory<br>need to keep gas, vapor or dust concentrations<br>e explosion-proof ventilation equipment.<br>ocess equipment should be checked to ensure<br>environmental protection legislation. In some   |
|   | cases, fume scrubbers, filters or engin<br>will be necessary to reduce emissions  | neering modifications to the process equipment   |
| Individual protection measur  |   |  |
| Hygiene measures  | eating, smoking and using the lavator<br>Appropriate techniques should be use   | bughly after handling chemical products, before<br>y and at the end of the working period.<br>ed to remove potentially contaminated clothing.<br>eusing. Ensure that eyewash stations and safety<br>location.  |
| Eye/face protection   | : Safety glasses with side shields.   |  |
| Skin protection   |   |  |
| Hand protection   | worn at all times when handling chem<br>necessary. Considering the paramete<br>during use that the gloves are still reta<br>noted that the time to breakthrough fo  | s complying with an approved standard should be<br>nical products if a risk assessment indicates this is<br>ers specified by the glove manufacturer, check<br>aining their protective properties. It should be<br>or any glove material may be different for different<br>mixtures, consisting of several substances, the<br>be accurately estimated.      |

Product name PMS 695 C HYBRID

# Section 8. Exposure controls/personal protection

| Body protection        | <ul> <li>Personal protective equipment for the body should be selected based on the task being<br/>performed and the risks involved and should be approved by a specialist before<br/>handling this product.</li> </ul>  |
|------------------------|--|
| Other skin protection  | <ul> <li>Appropriate footwear and any additional skin protection measures should be selected<br/>based on the task being performed and the risks involved and should be approved by a<br/>specialist before handling this product.</li> </ul>  |
| Respiratory protection | : Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator. If workers are exposed to concentrations above the exposure limit, they must use appropriate, certified respirators. Use a properly fitted, air-purifying or air-fed respirator complying with an approved standard if a risk assessment indicates this is necessary. The respiratory protection shall be in accordance to 29 CFR 1910.134. |

# Section 9. Physical and chemical properties

| <u>Appearance</u>                            |   |                             |                 |
|--|---|-----------------------------|-----------------|
| Physical state                               | : | Solid.                      |                 |
|  |   | Powder.                     |                 |
| Color  | 1 | Not available.              |                 |
| Odor   | 1 | Not available.              |                 |
| Odor threshold                               | : | Not available.              |                 |
| рН   | 4 | Not applicable.             |                 |
| Melting point                                | 4 | Not available.              |                 |
| Boiling point                                | 4 | Not available.              |                 |
| Flash point                                  | 4 | Closed cup: Not applicable  |                 |
| Auto-ignition temperature                    | 1 | Not applicable.             |                 |
| Decomposition temperature                    | 1 | Not available.              |                 |
| Flammability                                 | : | Not available.              |                 |
| Lower and upper explosive (flammable) limits | : | Not applicable.             |                 |
| Evaporation rate                             | 1 | Not available.              |                 |
| Vapor pressure                               | 1 | Not available.              |                 |
| Vapor density                                | 1 | Not applicable.             |                 |
| Relative density                             | : | 1.47                        |                 |
| Density(lbs / gal)                           | 1 | 12.27                       |                 |
|  |   | Media                       | Result          |
| Solubility(ies)                              | : | old water                   | Not soluble     |
| Partition coefficient: n-<br>octanol/water   | : | Not applicable.             |                 |
| Viscosity                                    | : | Kinematic (40°C (104°F)): I | Not applicable. |
| Volatility                                   | : | 0% (v/v), 0.021% (w/w)      |                 |
| % Solid. (w/w)                               | : | 99.979                      |                 |

Product name PMS 695 C HYBRID

|  |  | - |
|--|--|---|
|  |  |   |

| Section | 10. | <b>Stability</b> | and | reactivity |
|---------|-----|------------------|-----|------------|
|         |     |                  |     |            |

| Reactivity                         | : No specific test data related to reactivity available for this product or its ingredients.  |
|------------------------------------|---|
| Chemical stability                 | : The product is stable.  |
| Possibility of hazardous reactions | : Under normal conditions of storage and use, hazardous reactions will not occur.   |
| Conditions to avoid                | : When exposed to high temperatures may produce hazardous decomposition products.<br>Refer to protective measures listed in sections 7 and 8. |
| Incompatible materials             | : Keep away from the following materials to prevent strong exothermic reactions: oxidizing agents, strong alkalis, strong acids.              |
| Hazardous decomposition products   | : Depending on conditions, decomposition products may include the following materials: carbon oxides nitrogen oxides metal oxide/oxides       |

# Section 11. Toxicological information

#### Information on toxicological effects

#### Acute toxicity

| Product/ingredient name           | Result  | Species  | Dose        | Exposure |  |  |  |
|-----------------------------------|---|--|-------------|----------|--|--|--|
| titanium dioxide                  | LC50 Inhalation Dusts and mists                                     | Rat  | >6.82 mg/l  | 4 hours  |  |  |  |
|                                   | LD50 Dermal   | Rabbit   | >5000 mg/kg | -        |  |  |  |
|                                   | LD50 Oral   | Rat  | >5000 mg/kg | -        |  |  |  |
| titanium dioxide (<10<br>microns) | LC50 Inhalation Dusts and mists                                     | Rat  | >6.82 mg/l  | 4 hours  |  |  |  |
| ,                                 | LD50 Dermal   | Rabbit   | >5000 mg/kg | -        |  |  |  |
|                                   | LD50 Oral   | Rat  | >5000 mg/kg | -        |  |  |  |
| propylidynetrimethanol            | LD50 Dermal   | Rabbit   | 10 g/kg     | -        |  |  |  |
|                                   | LD50 Oral   | Rat  | 14000 mg/kg | -        |  |  |  |
| carbon black                      | LD50 Oral   | Rat  | >10 g/kg    | -        |  |  |  |
| Conclusion/Summary                | lusion/Summary : There are no data available on the mixture itself. |  |             |          |  |  |  |
| rritation/Corrosion               |   |  |             |          |  |  |  |
| Conclusion/Summary                |   |  |             |          |  |  |  |
| Skin                              | : There are no data available on the                                | ne mixture itself.                                   |             |          |  |  |  |
| Eyes                              | : There are no data available on the                                | : There are no data available on the mixture itself. |             |          |  |  |  |
| Respiratory                       | : There are no data available on the mixture itself.                |  |             |          |  |  |  |
| Sensitization                     |   |  |             |          |  |  |  |
| Conclusion/Summary                |   |  |             |          |  |  |  |
| Skin                              | : There are no data available on the                                | ne mixture itself.                                   |             |          |  |  |  |

- : There are no data available on the mixture itself.
- : There are no data available on the mixture itself.

**Conclusion/Summary** 

Respiratory

**Mutagenicity** 

Product name PMS 695 C HYBRID

### Section 11. Toxicological information

Conclusion/Summary : There are no data a

: There are no data available on the mixture itself.

#### **Classification**

| Product/ingredient name                 | OSHA | IARC     | NTP |
|---|------|----------|-----|
| Manium dioxide<br>titanium dioxide (<10 | -    | 2B<br>2B |     |
| microns)<br>carbon black                | -    | 2B       | -   |

Carcinogen Classification code:

IARC: 1, 2A, 2B, 3, 4 NTP: Known to be a human carcinogen; Reasonably anticipated to be a human carcinogen OSHA: + Not listed/not regulated: -

#### Reproductive toxicity

**Conclusion/Summary** : There are no data available on the mixture itself.

#### **Teratogenicity**

**Conclusion/Summary** : There are no data available on the mixture itself.

Specific target organ toxicity (single exposure)

Not available.

#### Specific target organ toxicity (repeated exposure)

Not available.

Target organs

: Contains material which may cause damage to the following organs: lungs, upper respiratory tract.

#### **Aspiration hazard**

Not available.

#### Information on the likely routes of exposure

#### Potential acute health effects

| Eye contact              | : Exposure to airborne concentrations above statutory or recommended exposure limits may cause irritation of the eyes.  |
|--------------------------|---|
| Inhalation               | : Exposure to airborne concentrations above statutory or recommended exposure limits may cause irritation of the nose, throat and lungs.                                |
| Skin contact             | : No known significant effects or critical hazards.   |
| Ingestion                | : No known significant effects or critical hazards.   |
| Over-exposure signs/symp | toms  |
| Eye contact              | : Adverse symptoms may include the following:<br>irritation<br>redness  |
| Inhalation               | : Adverse symptoms may include the following:<br>respiratory tract irritation<br>coughing<br>reduced fetal weight<br>increase in fetal deaths<br>skeletal malformations |

Product name PMS 695 C HYBRID

# Section 11. Toxicological information

|   | -   | J  |   |                |               |                |            |  |  |
|---|---|--|---|----------------|---------------|----------------|------------|--|--|
| Skin contact  | :   | Adverse symptoms may include the following:<br>reduced fetal weight<br>increase in fetal deaths<br>skeletal malformations  |   |                |               |                |            |  |  |
| Ingestion   | :   | reduced fetal weight   | Adverse symptoms may include the following:<br>reduced fetal weight<br>increase in fetal deaths |                |               |                |            |  |  |
| <b>Delayed and immediate effect</b>                       | cts   | and also chronic effe  | cts from she  | ort and long t | erm exposu    | i <u>re</u>    |            |  |  |
| Conclusion/Summary  | :   | There are no data available on the mixture itself. Repeated exposure of the eyes to a low level of dust can produce eye irritation. Repeated or prolonged inhalation of dust may lead to chronic respiratory irritation. Ingestion may cause nausea, diarrhea and vomiting. This takes into account, where known, delayed and immediate effects and also chronic effects of components from short-term and long-term exposure by oral, inhalation and dermal routes of exposure and eye contact. |   |                |               |                |            |  |  |
| Short term exposure                                       |   |  |   |                |               |                |            |  |  |
| Potential immediate effects                               | 1   | There are no data ava  | There are no data available on the mixture itself.  |                |               |                |            |  |  |
| Potential delayed effects<br>Long term exposure           | 1   | There are no data available on the mixture itself.   |   |                |               |                |            |  |  |
| Potential immediate effects                               | 1   | There are no data available on the mixture itself.   |   |                |               |                |            |  |  |
| Potential delayed effects<br>Potential chronic health eff | tial delayed effects : There are no data available on the mixture itself. |  |   |                |               |                |            |  |  |
| General   |   |  | d inhalation  | of duct may le | ad to chronic | respiratory ir | ritation   |  |  |
| Carcinogenicity   |   | Repeated or prolonged inhalation of dust may lead to chronic respiratory irritation.<br>Suspected of causing cancer. Risk of cancer depends on duration and level of exposure.   |   |                |               |                |            |  |  |
| Mutagenicity  |   | No known significant   | effects or crit   | ical hazards.  |               |                |            |  |  |
| Reproductive toxicity                                     |   | Suspected of damagin   |   |                | ild.          |                |            |  |  |
| Numerical measures of toxic                               |   |  | <b>.</b> ,  |                |               |                |            |  |  |
| Acute toxicity estimates                                  |   |  |   |                |               |                |            |  |  |
| Product/ingredient name                                   |   |  | Oral (mg/   | Dermal         | Inhalation    | Inhalation     | Inhalation |  |  |

| Product/ingredient name | Oral (mg/<br>kg) | Dermal<br>(mg/kg) | Inhalation<br>(gases)<br>(ppm) | (vapors) | Inhalation<br>(dusts and<br>mists) (mg/<br>I) |
|-------------------------|------------------|-------------------|--------------------------------|----------|---|
| PMS 695 C HYBRID        | N/A              | 110596.1          | N/A                            | N/A      | N/A   |
| propylidynetrimethanol  | 14000            | 10000             | N/A                            | N/A      | N/A   |

Product name PMS 695 C HYBRID

### Section 12. Ecological information

#### **Toxicity**

| Product/ingredient name        | Result                           | Species                        | Exposure |
|--------------------------------|----------------------------------|--------------------------------|----------|
| titanium dioxide (<10 microns) | Acute LC50 >100 mg/l Fresh water | Daphnia - <i>Daphnia magna</i> | 48 hours |
|                                | Acute LC50 >100 mg/l Fresh water | Daphnia - <i>Daphnia magna</i> | 48 hours |
|                                | Acute LC50 >1000 mg/l            | Fish                           | 96 hours |

#### Persistence and degradability

Not available.

#### **Bioaccumulative potential**

| Product/ingredient name | LogPow | BCF | Potential |
|-------------------------|--------|-----|-----------|
| propylidynetrimethanol  | -0.47  | -   | Low       |

#### **Mobility in soil**

Soil/water partition coefficient (Koc)

: Not available.

# Section 13. Disposal considerations

**Disposal methods** 

The generation of waste should be avoided or minimized wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible. This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.

Disposal should be in accordance with applicable regional, national and local laws and regulations. Refer to Section 7: HANDLING AND STORAGE and Section 8: EXPOSURE CONTROLS/PERSONAL PROTECTION for additional handling information and protection of employees. Section 6. Accidental release measures

#### DOT **IMDG** ΙΑΤΑ **UN number** Not regulated. Not regulated. Not regulated. **UN proper shipping** name **Transport hazard class** -(es) **United States** Page: 11/13

### 14. Transport information

Product name PMS 695 C HYBRID

### 14. Transport information

| Packing group   | -                      | - | -                      |
|---|------------------------|---|------------------------|
| Environmental hazards<br>Marine pollutant<br>substances | No.<br>Not applicable. |   | No.<br>Not applicable. |

#### **Additional information**

| DOT  | : None identified. |
|------|--------------------|
| IMDG | : None identified. |
| IATA | : None identified. |

Special precautions for user : Transport within user's premises: always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage.

Transport in bulk according : Not applicable. to IMO instruments

### Section 15. Regulatory information

#### United States

United States inventory (TSCA 8b) : All components are active or exempted.

SARA 302/304 SARA 304 RQ

: Not applicable.

**Composition/information on ingredients** 

No products were found.

#### SARA 311/312

| Classification | : COMBUSTIBLE DUSTS                |
|----------------|------------------------------------|
|                | CARCINOGENICITY - Category 2       |
|                | TOXIC TO REPRODUCTION - Category 2 |

#### **Composition/information on ingredients**

| Name  | %                    | Classification  |
|---|----------------------|---|
| International diaxide<br>titanium dioxide (<10 microns)<br>propylidynetrimethanol<br>carbon black | ≤1.0<br>≤1.0<br>≤1.0 | CARCINOGENICITY - Category 2<br>CARCINOGENICITY - Category 2<br>TOXIC TO REPRODUCTION - Category 2<br>COMBUSTIBLE DUSTS<br>CARCINOGENICITY - Category 2 |

Additional environmental information is contained on the Environmental Data Sheet for this product, which can be obtained from your PPG representative.

#### California Prop. 65

**WARNING**: Cancer - www.P65Warnings.ca.gov.

Product name PMS 695 C HYBRID

### Section 16. Other information

Hazardous Material Information System (U.S.A.)

Health : 1 \* Flammability : 0 Physical hazards : 0

(\*) - Chronic effects

Caution: HMIS® ratings are based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks. Although HMIS® ratings and the associated label are not required on MSDSs or products leaving a facility under 29 CFR 1910.1200, the preparer may choose to provide them. HMIS® ratings are to be used with a fully implemented HMIS® program. HMIS® is a registered trademark and service mark of the American Coatings Association, Inc.

The customer is responsible for determining the PPE code for this material. For more information on HMIS® Personal Protective Equipment (PPE) codes, consult the HMIS® Implementation Manual.

National Fire Protection Association (U.S.A.)

| Health : 1 Flamma<br>Date of previous issue<br>Organization that prepared<br>the SDS | bility : 0 Instability : 0<br>: 6/17/2021<br>: EHS   |
|--|--|
| Key to abbreviations   | : ATE = Acute Toxicity Estimate<br>BCF = Bioconcentration Factor<br>GHS = Globally Harmonized System of Classification and Labelling of Chemicals<br>IATA = International Air Transport Association<br>IBC = International Air Transport Association<br>IBC = International Maritime Dangerous Goods<br>LogPow = logarithm of the octanol/water partition coefficient<br>MARPOL = International Convention for the Prevention of Pollution From Ships, 1973<br>as modified by the Protocol of 1978. ("Marpol" = marine pollution)<br>N/A = Not available<br>SGG = Segregation Group<br>UN = United Nations |

#### Indicates information that has changed from previously issued version.

#### **Disclaimer**

The information contained in this data sheet is based on present scientific and technical knowledge. The purpose of this information is to draw attention to the health and safety aspects concerning the products supplied by PPG, and to recommend precautionary measures for the storage and handling of the products. No warranty or guarantee is given in respect of the properties of the products. No liability can be accepted for any failure to observe the precautionary measures described in this data sheet or for any misuse of the products.