SAFETY DATA SHEET



Date of issue/Date of revision9 December 2023Version 5

Section 1. Identification		
Product name	: RAL 7005 MATTE UD POLYESTER	
Product code	: PCTA79390	
Other means of identification	: Not available.	
Product type	: Powder.	
Relevant identified uses of	the substance or mixture and uses advised against	
Product use	: Industrial applications.	
Use of the substance/ mixture	: Coating. Paints. Painting-related materials.	
Uses advised against	: Not applicable.	
Manufacturer <u>Emergency telephone</u> <u>number</u>	 PPG Industries, Inc. One PPG Place Pittsburgh, PA 15272 (412) 434-4515 (U.S.) (514) 645-1320 (Canada) SETIQ Interior de la República: 800-00-214-00 (México) SETIQ Ciudad de México: (55) 5559-1588 (México) 	
Technical Phone Number	: 1-888-774-2001 (US and Canada)	

Section 2. Hazards identification

OSHA/HCS status	 This material is considered hazardous by the OSHA Hazard Communication Standard (29 CFR 1910.1200).
Classification of the substance or mixture	: COMBUSTIBLE DUSTS ACUTE TOXICITY (oral) - Category 4 SKIN SENSITIZATION - Category 1 GERM CELL MUTAGENICITY - Category 1 CARCINOGENICITY - Category 2 SPECIFIC TARGET ORGAN TOXICITY (REPEATED EXPOSURE) - Category 2
	✓ercentage of the mixture consisting of ingredient(s) of unknown acute toxicity: 10.3% (oral), 16.9% (dermal), 4.6% (inhalation)
GHS label elements	
Hazard pictograms	

 $\langle ! \rangle$

Product name RAL 7005 MATTE UD POLYESTER

Section 2. Hazards identification

Signal word	anger	
Hazard statements	armful if swallowed. lay cause an allergic skin reaction. lay cause genetic defects. uspected of causing cancer. lay cause damage to organs through prolonged or repeated exposure. lay form combustible dust concentrations in air.	
Precautionary statements		
Prevention	btain special instructions before use. Do not handle until all safety precautions een read and understood. Wear protective gloves, protective clothing and eye rotection. Do not breathe dust or mist. Do not eat, drink or smoke when using roduct. Wash thoroughly after handling. Contaminated work clothing must not lowed out of the workplace.	or face this
Response	exposed or concerned: Get medical advice or attention. IF SWALLOWED: Ca OISON CENTER or doctor if you feel unwell. Rinse mouth. Wash contaminate othing before reuse. IF ON SKIN: Wash with plenty of water. If skin irritation o ccurs: Get medical advice or attention.	ed
Storage	tore locked up.	
Disposal	ispose of contents and container in accordance with all local, regional, national ternational regulations.	and
Supplemental label elements	eep container tightly closed. Keep away from heat, sparks, open flames and ho urfaces No smoking. Sanding and grinding dusts may be harmful if inhaled. P ust accumulation. Emits toxic fumes when heated.	
Hazards not otherwise classified	ine dust clouds may form explosive mixtures with air. Handling and/or processi is material may generate a dust which can cause mechanical irritation of the ey kin, nose and throat.	

Section 3. Composition/information on ingredients

Substance/mixture	1	Mixture
Product name	÷	RAL 7005 MATTE UD POLYESTER

Ingredient name	%	CAS number
Manium dioxide	≥10 - ≤20	13463-67-7
Wollastonite	≥5.0 - ≤10	13983-17-0
1,3,5-tris(oxiranylmethyl)-1,3,5-triazine-2,4,6(1H,3H,5H)-trione	≥1.0 - ≤5.0	2451-62-9
carbon black	≤1.0	1333-86-4
titanium dioxide (<10 microns)	≤1.0	13463-67-7

SUB codes represent substances without registered CAS Numbers.

Any concentration shown as a range is to protect confidentiality or is due to batch variation.

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment and hence require reporting in this section.

Occupational exposure limits, if available, are listed in Section 8.

Product name RAL 7005 MATTE UD POLYESTER

Section 4. First aid measures

If ingestion, irritation, any type of overexposure or symptoms of overexposure occur during or persists after use of this product, contact a POISON CONTROL CENTER, EMERGENCY ROOM OR PHYSICIAN immediately; have Safety Data Sheet information available. Never give anything by mouth to an unconscious or convulsing person.

Description of necessary first aid measures

Eye contact	: Check for and remove any contact lenses. Immediately flush eyes with running water for at least 15 minutes, keeping eyelids open. Seek immediate medical attention.
Inhalation	 Remove to fresh air. Keep person warm and at rest. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel.
Skin contact	 Remove contaminated clothing and shoes. Wash skin thoroughly with soap and water or use recognized skin cleanser. Do NOT use solvents or thinners.
Ingestion	 If swallowed, seek medical advice immediately and show this container or label. Keep person warm and at rest. Do NOT induce vomiting.

Most important symptoms/effects, acute and delayed

Potential acute health effects Eye contact : Exposure to airborne concentrations above statutory or recommended exposure limits may cause irritation of the eyes. Inhalation : Exposure to airborne concentrations above statutory or recommended exposure limits may cause irritation of the nose, throat and lungs. Skin contact : May cause an allergic skin reaction. Ingestion : Harmful if swallowed. Over-exposure signs/symptoms Eye contact : Adverse symptoms may include the following: irritation redness : Adverse symptoms may include the following: Inhalation respiratory tract irritation coughing Skin contact : Adverse symptoms may include the following: irritation redness Ingestion : No specific data. Indication of immediate medical attention and special treatment needed, if necessary Notes to physician : In case of inhalation of decomposition products in a fire, symptoms may be delayed. The exposed person may need to be kept under medical surveillance for 48 hours. **Specific treatments** : No specific treatment. **Protection of first-aiders** : No action shall be taken involving any personal risk or without suitable training. If it is suspected that fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Wash contaminated clothing thoroughly with water before removing it, or wear gloves.

See toxicological information (Section 11)

Product name RAL 7005 MATTE UD POLYESTER

Section 5. Fire-fighting measures

Extinguishing media	
Suitable extinguishing media	: Use dry chemical powder.
Unsuitable extinguishing media	: Avoid high pressure media which could cause the formation of a potentially explosible dust-air mixture.
Specific hazards arising from the chemical	: Fine dust clouds may form explosive mixtures with air.
Hazardous thermal decomposition products	: Decomposition products may include the following materials: carbon oxides nitrogen oxides metal oxide/oxides
Special protective actions for fire-fighters	: Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training. Move containers from fire area if this can be done without risk. Use water spray to keep fire-exposed containers cool.
Special protective equipment for fire-fighters	: Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode.

Section 6. Accidental release measures

Personal precautions, protective equipment and emergency procedures

For non-emergency personnel	: No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilled material. Shut off all ignition sources. No flares, smoking or flames in hazard area. Avoid breathing dust. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment.
For emergency responders	
Environmental precautions	: Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air).
Methods and materials for co	ontainment and cleaning up
Small spill	: Move containers from spill area. Use spark-proof tools and explosion-proof equipment. Avoid dust generation. Do not dry sweep. Vacuum dust with equipment fitted with a HEPA filter and place in a closed, labeled waste container. Place spilled material in a designated, labeled waste container. Dispose of via a licensed waste disposal contractor.
Large spill	: Move containers from spill area. Use spark-proof tools and explosion-proof equipment. Approach release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Avoid dust generation. Do not dry sweep. Vacuum dust with equipment fitted with a HEPA filter and place in a closed, labeled waste container. Avoid creating dusty conditions and prevent wind dispersal. Dispose of via a licensed waste disposal contractor. Note: see Section 1 for emergency contact information and Section 13 for waste disposal.
	United States Page: 4/14

Product name RAL 7005 MATTE UD POLYESTER

Section 6. Accidental release measures

Section 7. Handling and storage

Precautions for safe handling	1	
Protective measures		Put on appropriate personal protective equipment (see Section 8). Persons with a history of skin sensitization problems should not be employed in any process in which this product is used. Avoid exposure - obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Do not get in eyes or on skin or clothing. Do not breathe dust. Do not ingest. Avoid the creation of dust when handling and avoid all possible sources of ignition (spark or flame). Prevent dust accumulation. Use only with adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Electrical equipment and lighting should be protected to appropriate standards to prevent dust coming into contact with hot surfaces, sparks or other ignition sources. Take precautionary measures against electrostatic discharges. To avoid fire or explosion, dissipate static electricity during transfer by grounding and bonding containers and equipment before transferring material. Empty containers retain product residue and can be hazardous. Do not reuse container.
Special precautions	:	If this material is part of a multiple component system, read the Safety Data Sheet(s) for the other component or components before blending as the resulting mixture may have the hazards of all of its parts.
Advice on general occupational hygiene	:	Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.
Conditions for safe storage, including any incompatibilities	:	Do not store below the following temperature: 5°C (41°F). Store in accordance with local regulations. Store in a segregated and approved area. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Store locked up. Eliminate all ignition sources. Separate from oxidizing materials. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabeled containers. Use appropriate containment to avoid environmental contamination.

Section 8. Exposure controls/personal protection

Control parameters

Occupational exposure limits

Ingredient name	Exposure limits
titanium dioxide	OSHA PEL (United States, 5/2018).
	TWA: 15 mg/m ³ 8 hours. Form: Total dust
	ACGIH TLV (United States, 1/2023).
	TWA: 2.5 mg/m ³ 8 hours. Form: respirable
	fraction, finescale particles
Wollastonite	ACGIH TLV (United States, 1/2023).
	TWA: 1 mg/m³ 8 hours. Form: Inhalable
	fraction
-	United States Page: 5/14

Product name RAL 7005 MATTE UD POLYESTER

Section 8. Exposure controls/personal protection

1,3,5-tris(oxiranylmethyl)-1,3,5-triazine-2,4,6(1H,3H,5H)-trione carbon black		ACGIH TLV (United States, 1/2023).		
		[1,3,5-Triglycidyl-s-triazinetrione]		
		TWA: 0.05 mg/m ³ 8 hours. ACGIH TLV (United States, 1/2023). TWA: 3 mg/m ³ 8 hours. Form: Inhalable		
		OSHA PEL (United States, 5/2018).		
		TWA: 3.5 mg/m ³ 8 hours.		
titanium dioxide (<10 microns)		OSHA PEL (United States, 5/2018).		
	,	TWA: 15 mg/m ³ 8 hours. Form: Total dust		
		ACGIH TLV (United States, 1/2023).		
		TWA: 2.5 mg/m ³ 8 hours. Form: respirable		
		fraction, finescale particles		
	Key to abbreviations			
A = Acceptable Maximum Pe		S = Potential skin absorption		
CGIH = American Conference of C = Ceiling Limit	f Governmental Industrial Hygienists.	SR = Respiratory sensitization SS = Skin sensitization		
F = Fume		STEL = Short term Exposure limit values		
IPEL = Internal Permissible Exp	osure Limit	TD = Total dust		
OSHA = Occupational Safety and	Health Administration.	TLV = Threshold Limit Value		
		TWA = Time Weighted Average		
R = Respirable $Z = OSHA 29 CER 1910 120$	00 Subpart 7 - Toxic and Hazardous Substances			
Z = OSHA 29 CFR 1910.120 onsult local authorities for a Recommended monitoring		opriate monitoring standards. Reference to nationa		
Z = OSHA 29 CFR 1910.120	acceptable exposure limits. : Reference should be made to appro	opriate monitoring standards. Reference to nationa or the determination of hazardous substances will		
Z = OSHA 29 CFR 1910.120 onsult local authorities for a Recommended monitoring	 acceptable exposure limits. Reference should be made to approguidance documents for methods for also be required. Use only with adequate ventilation. or mist, use process enclosures, loo to keep worker exposure to airborne limits. The engineering controls als below any lower explosive limits. Use Emissions from ventilation or work put hey comply with the requirements or a statement of the statement of	opriate monitoring standards. Reference to national or the determination of hazardous substances will If user operations generate dust, fumes, gas, vapor cal exhaust ventilation or other engineering controls e contaminants below any recommended or statuto o need to keep gas, vapor or dust concentrations se explosion-proof ventilation equipment. process equipment should be checked to ensure of environmental protection legislation. In some gineering modifications to the process equipment		
Z = OSHA 29 CFR 1910.120 onsult local authorities for a Recommended monitoring procedures opropriate engineering ontrols	 acceptable exposure limits. Reference should be made to approguidance documents for methods for also be required. Use only with adequate ventilation. or mist, use process enclosures, loo to keep worker exposure to airborne limits. The engineering controls als below any lower explosive limits. U Emissions from ventilation or work p they comply with the requirements of cases, fume scrubbers, filters or en will be necessary to reduce emissions 	opriate monitoring standards. Reference to national or the determination of hazardous substances will If user operations generate dust, fumes, gas, vapor cal exhaust ventilation or other engineering controls e contaminants below any recommended or statuto o need to keep gas, vapor or dust concentrations se explosion-proof ventilation equipment. process equipment should be checked to ensure of environmental protection legislation. In some gineering modifications to the process equipment		
Z = OSHA 29 CFR 1910.120 onsult local authorities for Recommended monitoring procedures opropriate engineering ontrols	 acceptable exposure limits. Reference should be made to approguidance documents for methods for also be required. Use only with adequate ventilation. or mist, use process enclosures, loo to keep worker exposure to airborne limits. The engineering controls als below any lower explosive limits. U Emissions from ventilation or work performed to the second provide the provide the second provide the pr	opriate monitoring standards. Reference to national or the determination of hazardous substances will If user operations generate dust, fumes, gas, vapor cal exhaust ventilation or other engineering controls e contaminants below any recommended or statuto o need to keep gas, vapor or dust concentrations se explosion-proof ventilation equipment. process equipment should be checked to ensure of environmental protection legislation. In some gineering modifications to the process equipment ns to acceptable levels.		
Z = OSHA 29 CFR 1910.120 onsult local authorities for a Recommended monitoring procedures opropriate engineering ontrols nvironmental exposure ontrols	 acceptable exposure limits. Reference should be made to approguidance documents for methods for also be required. Use only with adequate ventilation. or mist, use process enclosures, loo to keep worker exposure to airborne limits. The engineering controls als below any lower explosive limits. U Emissions from ventilation or work p they comply with the requirements of cases, fume scrubbers, filters or en will be necessary to reduce emission Wash hands, forearms and face the eating, smoking and using the lavat Appropriate techniques should be u Contaminated work clothing should contaminated clothing before reusing 	opriate monitoring standards. Reference to national or the determination of hazardous substances will If user operations generate dust, fumes, gas, vapor cal exhaust ventilation or other engineering controls e contaminants below any recommended or statuto o need to keep gas, vapor or dust concentrations se explosion-proof ventilation equipment. process equipment should be checked to ensure of environmental protection legislation. In some gineering modifications to the process equipment ns to acceptable levels.		

Product name RAL 7005 MATTE UD POLYESTER

Section 8. Exposure controls/personal protection

Hand protection	: Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. Considering the parameters specified by the glove manufacturer, check during use that the gloves are still retaining their protective properties. It should be noted that the time to breakthrough for any glove material may be different for different glove manufacturers. In the case of mixtures, consisting of several substances, the protection time of the gloves cannot be accurately estimated.
Gloves	: butyl rubber
Body protection	: Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.
Other skin protection	: Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.
Respiratory protection	: Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator. If workers are exposed to concentrations above the exposure limit, they must use appropriate, certified respirators. Use a properly fitted, air-purifying or air-fed respirator complying with an approved standard if a risk assessment indicates this is necessary. The respiratory protection shall be in accordance to 29 CFR 1910.134.

Section 9. Physical and chemical properties

Appearance

Physical state	:	Solid.	
		Powder.	
Color	1	Not available.	
Odor	1	Not available.	
Odor threshold	1	Not available.	
рН	4	Not applicable.	
Melting point	1	Not available.	
Boiling point	4	Not available.	
Flash point	1	Closed cup: Not applicable.	
Auto-ignition temperature	1	Not applicable.	
Decomposition temperature	1	Not available.	
Flammability	1	Not available.	
Lower and upper explosive (flammable) limits	1	Not applicable.	
Evaporation rate	1	Not available.	
Vapor pressure	1	Not available.	
Vapor density	1	Not applicable.	
Relative density	1	1.41	
Density(lbs / gal)	1	11.77	
		Media	Result
Solubility(ies)	1	old water	Not soluble

United States Page: 7/14

United States

Page: 8/14

Product name RAL 7005 MATTE UD POLYESTER

Section 9. Physical and chemical properties

Partition coefficient: n- octanol/water	: Not applicable.
Viscosity	: Kinematic (40°C (104°F)): Not applicable.
Volatility	: 0% (v/v), 0% (w/w)
% Solid. (w/w)	: 100

Section 10. Stability and reactivity

Reactivity	: No specific test data related to reactivity available for this product or its ingredients.
Chemical stability	: The product is stable.
Possibility of hazardous reactions	: Under normal conditions of storage and use, hazardous reactions will not occur.
Conditions to avoid	: When exposed to high temperatures may produce hazardous decomposition products. Refer to protective measures listed in sections 7 and 8.
Incompatible materials	: Keep away from the following materials to prevent strong exothermic reactions: oxidizing agents, strong alkalis, strong acids.
Hazardous decomposition products	: Depending on conditions, decomposition products may include the following materials: carbon oxides nitrogen oxides metal oxide/oxides

Section 11. Toxicological information

Information on toxicological effects

Acute toxicity

Product/ingredient name	Result	Species	Dose	Exposure		
titanium dioxide	LC50 Inhalation Dusts and mists	Rat	>6.82 mg/l	4 hours		
	LD50 Dermal	Rabbit	>5000 mg/kg	-		
	LD50 Oral	Rat	>5000 mg/kg	-		
1,3,5-tris(oxiranylmethyl) -1,3,5-triazine-2,4,6(1H,3H, 5H)-trione	LD50 Oral	Rat	138 mg/kg	-		
carbon black	LD50 Oral	Rat	>10 g/kg	-		
titanium dioxide (<10 microns)	LC50 Inhalation Dusts and mists	Rat	>6.82 mg/l	4 hours		
,	LD50 Dermal	Rabbit	>5000 mg/kg	-		
	LD50 Oral	Rat	>5000 mg/kg	-		
Conclusion/Summary	: There are no data available on the	ne mixture itself.				
Irritation/Corrosion						
Conclusion/Summary						
Skin	: There are no data available on the	ne mixture itself.				
Eyes	: There are no data available on the mixture itself.					
Respiratory	: There are no data available on the mixture itself.					

Product name RAL 7005 MATTE UD POLYESTER

Section 11. Toxicological information

Sensitization				
Conclusion/Summary				
Skin	4	There are	no data av	ailable on the mixture itself.
Respiratory	3	There are	no data av	ailable on the mixture itself.
Mutagenicity				
Conclusion/Summary	1	There are	no data a	ailable on the mixture itself.
Carcinogenicity				
Conclusion/Summary	1	There are	no data a	ailable on the mixture itself.
Classification				
Product/ingredient name		OSHA	IARC	NTP
titanium dioxide		-	2B	-

Product/ingredient name	USHA	IARC	NIP
titanium dioxide	-	2B	-
Wollastonite	-	3	-
carbon black	-	2B	-
titanium dioxide (<10	-	2B	-
microns)			

Carcinogen Classification code:

IARC: 1, 2A, 2B, 3, 4 NTP: Known to be a human carcinogen; Reasonably anticipated to be a human carcinogen OSHA: + Not listed/not regulated: -

Reproductive toxicity

Conclusion/Summary

: There are no data available on the mixture itself.

Teratogenicity

Conclusion/Summary : There are no data available on the mixture itself.

Specific target organ toxicity (single exposure)

Not available.

Specific target organ toxicity (repeated exposure)

Name		Route of exposure	Target organs
1,3,5-tris(oxiranylmethyl)-1,3,5-triazine-2,4,6(1H,3H,5H)- trione	Category 2	-	-

Target organs

: Contains material which causes damage to the following organs: skin, eyes. Contains material which may cause damage to the following organs: kidneys, lungs, the reproductive system, upper respiratory tract, , bone marrow, testes.

Aspiration hazard

Not available.

Information on the likely routes of exposure

Potential acute health effects

Eye contact	: Exposure to airborne concentrations above statutory or recommended exposure limits may cause irritation of the eyes.
Inhalation	: Exposure to airborne concentrations above statutory or recommended exposure limits may cause irritation of the nose, throat and lungs.

United States Page: 9/14

Product name RAL 7005 MATTE UD POLYESTER

Section 11. Toxicological information

Skin contact	:	May cause an allergic	skin reactior	۱.				
Ingestion	:	: Harmful if swallowed.						
Over-exposure signs/symp	ton	<u>15</u>						
Eye contact	:	Adverse symptoms m irritation redness	ay include the	e following:				
Inhalation	:		dverse symptoms may include the following: espiratory tract irritation					
Skin contact	:	Adverse symptoms m irritation redness	ay include the	e following:				
Ingestion	1	No specific data.						
Delayed and immediate effe	<u>cts</u>	<u>and also chronic effe</u>	<u>cts from sho</u>	ort and long t	<u>term exposu</u>	<u>ire</u>		
Conclusion/Summary	:	There are no data available low level of dust can p may lead to chronic revomiting. This takes in also chronic effects of inhalation and dermal	produce eye i espiratory irrit nto account, f components	rritation. Rep ation. Ingesti where known from short-te	eated or prol ion may caus , delayed and erm and long	onged inhalat e nausea, dia d immediate e	ion of dust rrhea and effects and	
Short term exposure				-				
Potential immediate effects	:	There are no data ava	ailable on the	mixture itself				
Potential delayed effects	1	There are no data ava	ailable on the	mixture itself	-			
<u>Long term exposure</u>								
Potential immediate effects	1	There are no data ava	ailable on the	mixture itself	-			
Potential delayed effects	:	There are no data ava	ailable on the	mixture itself	-			
Potential chronic health eff	iect	<u>s</u>						
General	:	May cause damage to prolonged inhalation of a severe allergic react	of dust may le	ad to chronic	respiratory ir	ritation. Once	e sensitized,	
Carcinogenicity	 Suspected of causing cancer. Risk of cancer depends on duration and level of exposure. 							
Mutagenicity	:	: May cause genetic defects.						
Reproductive toxicity	: No known significant effects or critical hazards.							
Numerical measures of toxic	<u>city</u>							
Acute toxicity estimates								
Product/ingredient name			Oral (mg/ kg)	Dermal (mg/kg)	Inhalation (gases) (ppm)	Inhalation (vapors) (mg/l)	Inhalation (dusts and mists) (mg/	

			/		I)
AL 7005 MATTE UD POLYESTER 1,3,5-tris(oxiranylmethyl)-1,3,5-triazine-2,4,6(1H,3H,	1887.7 100	N/A N/A	N/A N/A	N/A N/A	N/A N/A
5H)-trione	100				

Product name RAL 7005 MATTE UD POLYESTER

Section 12. Ecological information

Toxicity

Product/ingredient name	Result	Species	Exposure
	5	1 - 7 3 -	48 hours 48 hours

Persistence and degradability

Not available.

Bioaccumulative potential

Product/ingredient name	LogPow	BCF	Potential
√,3,5-tris(oxiranylmethyl) -1,3,5-triazine-2,4,6(1H,3H, 5H)-trione	-0.8	-	Low

Mobility in soil

Soil/water partition coefficient (Koc)

: Not available.

Section 13. Disposal considerations

Disposal methods

: The generation of waste should be avoided or minimized wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible. This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.

Disposal should be in accordance with applicable regional, national and local laws and regulations.

Refer to Section 7: HANDLING AND STORAGE and Section 8: EXPOSURE CONTROLS/PERSONAL PROTECTION for additional handling information and protection of employees. Section 6. Accidental release measures

14. Transport information

Product name RAL 7005 MATTE UD POLYESTER

14. Transport information

	DOT	IMDG	IATA
UN number	Not regulated.	Not regulated.	Not regulated.
UN proper shipping name	-	-	-
Transport hazard class (es)	-	-	-
Packing group	-	-	-
Environmental hazards	No.	No.	No.
Marine pollutant substances	Not applicable.	Not applicable.	Not applicable.

Additional information

DOT: None identified.IMDG: None identified.IATA: None identified.

Special precautions for user : Transport within user's premises: always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage.

Transport in bulk according : Not applicable. to IMO instruments

Section 15. Regulatory information

United States

United States inventory (TSCA 8b) : All components are active or exempted.

SARA 302/304

SARA 304 RQ : Not applicable.

Composition/information on ingredients

No products were found.

SARA 311/312

Classification

: COMBUSTIBLE DUSTS ACUTE TOXICITY (oral) - Category 4 SKIN SENSITIZATION - Category 1 GERM CELL MUTAGENICITY - Category 1 CARCINOGENICITY - Category 2 SPECIFIC TARGET ORGAN TOXICITY (REPEATED EXPOSURE) - Category 2

Composition/information on ingredients

Product name RAL 7005 MATTE UD POLYESTER

Section 15. Regulatory information

Name	%	Classification
titanium dioxide	≥10 - ≤20	CARCINOGENICITY - Category 2
1,3,5-tris(oxiranylmethyl)	≥1.0 - ≤5.0	COMBUSTIBLE DUSTS
-1,3,5-triazine-2,4,6(1H,3H,5H)-		ACUTE TOXICITY (oral) - Category 3
trione		SERIOUS EYE DAMAGE - Category 1
		SKIN SENSITIZATION - Category 1B
		GERM CELL MUTAGENICITY - Category 1B
		SPECIFIC TARGET ORGAN TOXICITY (REPEATED
		EXPOSURE) - Category 2
carbon black	≤1.0	COMBUSTIBLE DUSTS
		CARCINOGENICITY - Category 2
titanium dioxide (<10 microns)	≤1.0	CARCINOGENICITY - Category 2

SARA 313

	<u>Chemical name</u>	<u>CAS number</u>	Concentration
Supplier notification	: 7,3,5-tris(oxiranylmethyl)-1,3,5-triazine-2,4,6(1H,	2451-62-9	1 - 5
	3H,5H)-trione		
	lead massive	7439-92-1	0.000006

SARA 313 notifications must not be detached from the SDS and any copying and redistribution of the SDS shall include copying and redistribution of the notice attached to copies of the SDS subsequently redistributed.

Additional environmental information is contained on the Environmental Data Sheet for this product, which can be obtained from your PPG representative.

California Prop. 65

WARNING: Cancer - www.P65Warnings.ca.gov.

Section 16. Other information

Hazardous Material Information	n System (U.S.A.)
---------------------------------------	-------------------

```
Health : 2 * Flammability : 0 Physical hazards : 0
```

(*) - Chronic effects

Caution: HMIS® ratings are based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks. Although HMIS® ratings and the associated label are not required on MSDSs or products leaving a facility under 29 CFR 1910.1200, the preparer may choose to provide them. HMIS® ratings are to be used with a fully implemented HMIS® program. HMIS® is a registered trademark and service mark of the American Coatings Association, Inc.

The customer is responsible for determining the PPE code for this material. For more information on HMIS® Personal Protective Equipment (PPE) codes, consult the HMIS® Implementation Manual.

National Fire Protection Association (U.S.A.)									
Health :	2	Flammab	ilit	y	:	0	Instability	1	0
Date of prev	vious iss	sue	:	6 /'	18/	2021			
Organization the SDS	n that p	repared	:	Eŀ	IS				

Product name RAL 7005 MATTE UD POLYESTER

Section 16. Other information

Key to abbreviations	: ATE = Acute Toxicity Estimate
	BCF = Bioconcentration Factor
	GHS = Globally Harmonized System of Classification and Labelling of Chemicals
	IATA = International Air Transport Association
	IBC = Intermediate Bulk Container
	IMDG = International Maritime Dangerous Goods
	LogPow = logarithm of the octanol/water partition coefficient
	MARPOL = International Convention for the Prevention of Pollution From Ships, 1973 as modified by the Protocol of 1978. ("Marpol" = marine pollution)
	N/A = Not available
	SGG = Segregation Group
	UN = United Nations

Indicates information that has changed from previously issued version.

Disclaimer

The information contained in this data sheet is based on present scientific and technical knowledge. The purpose of this information is to draw attention to the health and safety aspects concerning the products supplied by PPG, and to recommend precautionary measures for the storage and handling of the products. No warranty or guarantee is given in respect of the properties of the products. No liability can be accepted for any failure to observe the precautionary measures described in this data sheet or for any misuse of the products.