SAFETY DATA SHEET



Date of issue/Date of revision **21 February 2023**

Version 5

Section 1. Identification

: PCUA10103 **Product name Product code** : PCUA10103 Other means of : Not available.

identification

Product type : Powder.

Relevant identified uses of the substance or mixture and uses advised against

Product use : Industrial applications.

Use of the substance/

mixture

: Coating. Paints. Painting-related materials.

Uses advised against : Not applicable.

Manufacturer : PPG Industries. Inc.

One PPG Place

Pittsburgh, PA 15272 : (412) 434-4515 (U.S.)

Emergency telephone (514) 645-1320 (Canada) number

SETIQ Interior de la República: 800-00-214-00 (México) SETIQ Ciudad de México: (55) 5559-1588 (México)

Technical Phone Number : 1-888-774-2001 (US and Canada)

Section 2. Hazards identification

OSHA/HCS status

: This material is considered hazardous by the OSHA Hazard Communication Standard (29 CFR 1910.1200).

Classification of the substance or mixture **COMBUSTIBLE DUSTS**

SPECIFIC TARGET ORGAN TOXICITY (SINGLE EXPOSURE) (Respiratory tract

irritation) - Category 3

SPECIFIC TARGET ORGAN TOXICITY (REPEATED EXPOSURE) - Category 1

Percentage of the mixture consisting of ingredient(s) of unknown acute toxicity: 63.5%

(oral), 95.9% (dermal), 63.5% (inhalation)

GHS label elements

Hazard pictograms





Signal word : Danger

> **United States** Page: 1/12

Date of issue 21 February 2023 Version 5

Section 2. Hazards identification

Hazard statements

: May cause respiratory irritation.

Causes damage to organs through prolonged or repeated exposure. (lungs)

May form combustible dust concentrations in air.

Precautionary statements

Prevention

: Use only outdoors or in a well-ventilated area. Do not breathe dust or mist. Do not eat, drink or smoke when using this product. Wash thoroughly after handling.

Response

: Cet medical advice or attention if you feel unwell. IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a POISON CENTER or doctor if you feel unwell.

Storage Disposal

: Store locked up. Store in a well-ventilated place. Keep container tightly closed.

: Dispose of contents and container in accordance with all local, regional, national and international regulations.

Supplemental label elements

: Keep container tightly closed. Keep away from heat, sparks, open flames and hot surfaces. - No smoking. Prevent dust accumulation. Emits toxic fumes when heated.

Hazards not otherwise classified

: Fine dust clouds may form explosive mixtures with air. Handling and/or processing of this material may generate a dust which can cause mechanical irritation of the eyes, skin, nose and throat.

Section 3. Composition/information on ingredients

Substance/mixture : Mixture Product name : PCUA10103

Ingredient name	%	CAS number
volyester resin	≥20 - ≤50	Not available.
Cyclohexane, 5-isocyanato-1-(isocyanatomethyl)-1,3,3-trimethyl-,	≥20 - ≤50	127184-53-6
homopolymer, caprolactam-blocked		
Wollastonite	≥5.0 - ≤10	13983-17-0

SUB codes represent substances without registered CAS Numbers.

Any concentration shown as a range is to protect confidentiality or is due to batch variation.

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment and hence require reporting in this section.

Occupational exposure limits, if available, are listed in Section 8.

Section 4. First aid measures

If ingestion, irritation, any type of overexposure or symptoms of overexposure occur during or persists after use of this product, contact a POISON CONTROL CENTER, EMERGENCY ROOM OR PHYSICIAN immediately; have Safety Data Sheet information available. Never give anything by mouth to an unconscious or convulsing person.

Description of necessary first aid measures

Eye contact

: Remove contact lenses, irrigate copiously with clean, fresh water, holding the eyelids apart for at least 10 minutes and seek immediate medical advice.

Inhalation

: Remove to fresh air. Keep person warm and at rest. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel.

United States Page: 2/12

Date of issue 21 February 2023 Version 5

Product code PCUA10103
Product name PCUA10103

Section 4. First aid measures

Skin contact : Remove contaminated clothing and shoes. Wash skin thoroughly with soap and water

or use recognized skin cleanser. Do NOT use solvents or thinners.

Ingestion : If swallowed, seek medical advice immediately and show this container or label. Keep

person warm and at rest. Do NOT induce vomiting.

Most important symptoms/effects, acute and delayed

Potential acute health effects

Eye contact: Exposure to airborne concentrations above statutory or recommended exposure limits

may cause irritation of the eyes.

Inhalation : May cause respiratory irritation.

Skin contactIngestionNo known significant effects or critical hazards.No known significant effects or critical hazards.

Over-exposure signs/symptoms

Eye contact: Adverse symptoms may include the following:

irritation redness

Inhalation : Adverse symptoms may include the following:

respiratory tract irritation

coughing

Skin contact : No specific data.
Ingestion : No specific data.

Indication of immediate medical attention and special treatment needed, if necessary

Notes to physician : In case of inhalation of decomposition products in a fire, symptoms may be delayed.

The exposed person may need to be kept under medical surveillance for 48 hours.

Specific treatments: No specific treatment.

Protection of first-aiders: No action shall be taken involving any personal risk or without suitable training. If it is

suspected that fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. It may be dangerous to the person providing aid to

give mouth-to-mouth resuscitation.

See toxicological information (Section 11)

Section 5. Fire-fighting measures

Extinguishing media

Suitable extinguishing media

Unsuitable extinguishing

media

: Use dry chemical powder.

: Avoid high pressure media which could cause the formation of a potentially explosible

dust-air mixture.

Specific hazards arising from the chemical

: Fine dust clouds may form explosive mixtures with air.

Hazardous thermal decomposition products

: Decomposition products may include the following materials:

carbon oxides nitrogen oxides metal oxide/oxides

United States Page: 3/12

Date of issue 21 February 2023 Version 5

Section 5. Fire-fighting measures

Special protective actions for fire-fighters

: Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training. Move containers from fire area if this can be done without risk. Use water spray to keep fire-exposed containers cool.

Special protective equipment for fire-fighters

: Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode.

Section 6. Accidental release measures

Personal precautions, protective equipment and emergency procedures

For non-emergency personnel

: No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilled material. Shut off all ignition sources. No flares, smoking or flames in hazard area. Avoid breathing dust. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment.

For emergency responders

: If specialized clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".

Environmental precautions

: Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air).

Methods and materials for containment and cleaning up

Small spill

: Move containers from spill area. Use spark-proof tools and explosion-proof equipment. Avoid dust generation. Do not dry sweep. Vacuum dust with equipment fitted with a HEPA filter and place in a closed, labeled waste container. Place spilled material in a designated, labeled waste container. Dispose of via a licensed waste disposal contractor.

Large spill

: Move containers from spill area. Use spark-proof tools and explosion-proof equipment. Approach release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Avoid dust generation. Do not dry sweep. Vacuum dust with equipment fitted with a HEPA filter and place in a closed, labeled waste container. Avoid creating dusty conditions and prevent wind dispersal. Dispose of via a licensed waste disposal contractor. Note: see Section 1 for emergency contact information and Section 13 for waste disposal.

Section 7. Handling and storage

Precautions for safe handling

Protective measures

Put on appropriate personal protective equipment (see Section 8). Do not breathe dust. Do not ingest. Avoid contact with eyes, skin and clothing. Avoid the creation of dust when handling and avoid all possible sources of ignition (spark or flame). Prevent dust accumulation. Use only with adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Electrical equipment and lighting should be protected to appropriate standards to prevent dust coming into contact with hot surfaces, sparks or other ignition sources. Take precautionary measures against electrostatic discharges. To avoid fire or explosion, dissipate static electricity during transfer by grounding and bonding containers and

United States Page: 4/12

Section 7. Handling and storage

Special precautions

equipment before transferring material. Empty containers retain product residue and can be hazardous. Do not reuse container.

Advice on general occupational hygiene

: If this material is part of a multiple component system, read the Safety Data Sheet(s) for the other component or components before blending as the resulting mixture may have the hazards of all of its parts.

Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.

Conditions for safe storage, including any incompatibilities

Do not store below the following temperature: 5°C (41°F). Store in accordance with local regulations. Store in a segregated and approved area. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Store locked up. Eliminate all ignition sources. Separate from oxidizing materials. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabeled containers. Use appropriate containment to avoid environmental contamination.

Section 8. Exposure controls/personal protection

Control parameters

Occupational exposure limits

Ingredient name	Exposure limits
volyester resin	None.
Cyclohexane, 5-isocyanato-1-(isocyanatomethyl)-1,3,3-trimethyl-, homopolymer, caprolactam-blocked	None.
Wollastonite	ACGIH TLV (United States, 1/2022).
	TWA: 1 mg/m³ 8 hours. Form: Inhalable fraction

Key to abbreviations

Α	= Acceptable Maximum Peak	S	 Potential skin absorption
ACGIH	= American Conference of Governmental Industrial Hygienists.	SR	 Respiratory sensitization
С	= Ceiling Limit	SS	 Skin sensitization
F	= Fume	STEL	 Short term Exposure limit values
IPEL	= Internal Permissible Exposure Limit	TD	= Total dust
OSHA	 Occupational Safety and Health Administration. 	TLV	= Threshold Limit Value
R	= Respirable	TWA	= Time Weighted Average
Z	= OSHA 29 CFR 1910.1200 Subpart Z - Toxic and Hazardous Substances		-

Consult local authorities for acceptable exposure limits.

procedures

Recommended monitoring: Reference should be made to appropriate monitoring standards. Reference to national guidance documents for methods for the determination of hazardous substances will also be required.

Appropriate engineering controls

: Use only with adequate ventilation. If user operations generate dust, fumes, gas, vapor or mist, use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure to airborne contaminants below any recommended or statutory limits. The engineering controls also need to keep gas, vapor or dust concentrations below any lower explosive limits. Use explosion-proof ventilation equipment.

United States Page: 5/12

Product code PCUA10103

Product name PCUA10103

Date of issue 21 February 2023 Version 5

Section 8. Exposure controls/personal protection

Environmental exposure controls

: Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

Individual protection measures

Hygiene measures

: Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.

Eye/face protection Skin protection

: Safety glasses with side shields.

Hand protection

: Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. Considering the parameters specified by the glove manufacturer, check during use that the gloves are still retaining their protective properties. It should be noted that the time to breakthrough for any glove material may be different for different glove manufacturers. In the case of mixtures, consisting of several substances, the protection time of the gloves cannot be accurately estimated.

Body protection

Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.

Other skin protection

: Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.

Respiratory protection

: Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator. If workers are exposed to concentrations above the exposure limit, they must use appropriate, certified respirators. Use a properly fitted, air-purifying or air-fed respirator complying with an approved standard if a risk assessment indicates this is necessary. The respiratory protection shall be in accordance to 29 CFR 1910.134.

Section 9. Physical and chemical properties

Appearance

: Solid. **Physical state**

Powder.

Color : Clear.

: Not available. Odor **Odor threshold** Not available. : Not applicable. pΗ : Not available. **Melting point Boiling point** Not available.

Flash point : Closed cup: Not applicable.

Auto-ignition temperature Not applicable. **Decomposition temperature** : Not available. **Flammability** : Not available.

> **United States** Page: 6/12

Product code PCUA10103 Date of issue 21 February 2023 Version 5

Product name PCUA10103

Section 9. Physical and chemical properties

Lower and upper explosive

(flammable) limits

: Not applicable.

Evaporation rate : Not available.

Vapor pressure : Not available.

Vapor density : Not applicable.

Relative density : 1.24

Density (lbs / gal) : 10.35

Media Result

Solubility(ies) : void water Not soluble

Partition coefficient: n-

octanol/water

: Not applicable.

Viscosity : Kinematic (40°C (104°F)): Not applicable.

Volatility : 0% (v/v), 0% (w/w)

% Solid. (w/w) : 100

Section 10. Stability and reactivity

Reactivity: No specific test data related to reactivity available for this product or its ingredients.

Chemical stability: The product is stable.

Possibility of hazardous

reactions

: Under normal conditions of storage and use, hazardous reactions will not occur.

Conditions to avoid : When exposed to high temperatures may produce hazardous decomposition products.

Refer to protective measures listed in sections 7 and 8.

Incompatible materials

: Keep away from the following materials to prevent strong exothermic reactions: oxidizing agents, strong alkalis, strong acids.

Hazardous decomposition products

: Depending on conditions, decomposition products may include the following materials: carbon oxides nitrogen oxides metal oxide/oxides

Section 11. Toxicological information

Information on toxicological effects

Acute toxicity

United States Page: 7/12

Product code PCUA10103

Date of issue 21 February 2023 Version 5

Product name PCUA10103

Section 11. Toxicological information

Product/ingredient name	Result	Species	Dose	Exposure
Cyclohexane, 5-isocyanato-1- (isocyanatomethyl) -1,3,3-trimethyl-, homopolymer, caprolactam- blocked	LC50 Inhalation Dusts and mists	Rat	>5.3 mg/l	4 hours
	LD50 Oral	Rat - Male, Female	>10000 mg/kg	-

Conclusion/Summary

: There are no data available on the mixture itself.

<u>Irritation/Corrosion</u>

Conclusion/Summary

Skin: There are no data available on the mixture itself.Eyes: There are no data available on the mixture itself.Respiratory: There are no data available on the mixture itself.

<u>Sensitization</u>

Conclusion/Summary

Skin: There are no data available on the mixture itself.Respiratory: There are no data available on the mixture itself.

Mutagenicity

Conclusion/Summary: There are no data available on the mixture itself.

Carcinogenicity

Conclusion/Summary: There are no data available on the mixture itself.

Classification

Product/ingredie	ent name	OSHA	IARC	NTP
₩ ollastonite		-	3	-

Carcinogen Classification code:

IARC: 1, 2A, 2B, 3, 4

NTP: Known to be a human carcinogen; Reasonably anticipated to be a human carcinogen

OSHA:

Not listed/not regulated: -

Reproductive toxicity

Conclusion/Summary: There are no data available on the mixture itself.

Teratogenicity

Conclusion/Summary: There are no data available on the mixture itself.

Specific target organ toxicity (single exposure)

Name	Category	Route of exposure	Target organs
polyester resin	Category 3	-	Respiratory tract irritation

Specific target organ toxicity (repeated exposure)

United States Page: 8/12

Date of issue 21 February 2023 Version 5

Product code PCUA10103
Product name PCUA10103

Section 11. Toxicological information

Name	Category	Route of exposure	Target organs
✓yclohexane, 5-isocyanato-1-(isocyanatomethyl)-1,3,3-trimethyl-, homopolymer, caprolactam-blocked	Category 1	inhalation	lungs

<u>Target organs</u>: Contains material which may cause damage to the following organs: lungs.

Aspiration hazard

Not available.

Information on the likely routes of exposure

Potential acute health effects

Eye contact : Exposure to airborne concentrations above statutory or recommended exposure limits

may cause irritation of the eyes.

Inhalation : May cause respiratory irritation.

Skin contactIngestionNo known significant effects or critical hazards.No known significant effects or critical hazards.

Over-exposure signs/symptoms

Eye contact : Adverse symptoms may include the following:

irritation redness

Inhalation : Adverse symptoms may include the following:

respiratory tract irritation

coughing

Skin contact : No specific data.
Ingestion : No specific data.

Delayed and immediate effects and also chronic effects from short and long term exposure

Conclusion/Summary: There are no data available on the mixture itself. Repeated exposure of the eyes to a

low level of dust can produce eye irritation. Repeated or prolonged inhalation of dust may lead to chronic respiratory irritation. Ingestion may cause nausea, diarrhea and vomiting. This takes into account, where known, delayed and immediate effects and also chronic effects of components from short-term and long-term exposure by oral,

inhalation and dermal routes of exposure and eye contact.

Short term exposure

Potential immediate: There are no data available on the mixture itself.

effects

Potential delayed effects: There are no data available on the mixture itself.

Long term exposure

Potential immediate : There are no data available on the mixture itself.

effects

Potential delayed effects: There are no data available on the mixture itself.

Potential chronic health effects

General : Causes damage to organs through prolonged or repeated exposure. Repeated or

prolonged inhalation of dust may lead to chronic respiratory irritation.

Carcinogenicity : No known significant effects or critical hazards.
 Mutagenicity : No known significant effects or critical hazards.
 Reproductive toxicity : No known significant effects or critical hazards.

United States Page: 9/12

Date of issue 21 February 2023 Version 5

Section 11. Toxicological information

Section 12. Ecological information

Toxicity

Not available.

Persistence and degradability

Product/ingredient name	Test	Result		Dose		Inoculum
Cyclohexane, 5-isocyanato-1- (isocyanatomethyl) -1,3,3-trimethyl-, homopolymer, caprolactam- blocked	OECD 301F Ready Biodegradability - Manometric Respirometry Test	1 % - Not re	eadily - 28 days	-		-
Product/ingredient name	Aquatic half-life		Photolysis		Biodeg	radability
Cyclohexane, 5-isocyanato-1- (isocyanatomethyl) -1,3,3-trimethyl-, homopolymer, caprolactam- blocked	-		-		Not read	dily

Bioaccumulative potential

Not available.

Mobility in soil

Soil/water partition coefficient (Koc)

: Not available.

Section 13. Disposal considerations

Disposal methods

: The generation of waste should be avoided or minimized wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible. This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.

Disposal should be in accordance with applicable regional, national and local laws and regulations.

United States Page: 10/12

Date of issue 21 February 2023 Version 5

Product code PCUA10103
Product name PCUA10103

Section 13. Disposal considerations

Refer to Section 7: HANDLING AND STORAGE and Section 8: EXPOSURE CONTROLS/PERSONAL PROTECTION for additional handling information and protection of employees. Section 6. Accidental release measures

14. Transport information

	DOT	IMDG	IATA
UN number	Not regulated.	Not regulated.	Not regulated.
UN proper shipping name	-	-	-
Transport hazard class (es)	-	-	-
Packing group	-	-	-
Environmental hazards Marine pollutant substances	No. Not applicable.	No. Not applicable.	No. Not applicable.

Additional information

DOT : None identified.

IMDG : None identified.

IATA : None identified.

Special precautions for user : Transport within user's premises: always transport in closed containers that are

upright and secure. Ensure that persons transporting the product know what to do in

the event of an accident or spillage.

Transport in bulk according : Not applicable.

to IMO instruments

Section 15. Regulatory information

United States

United States inventory (TSCA 8b): All components are active or exempted.

SARA 302/304

SARA 304 RQ : Not applicable.

<u>Composition/information on ingredients</u>

No products were found.

SARA 311/312

Classification : COMBUSTIBLE DUSTS

SPECIFIC TARGET ORGAN TOXICITY (SINGLE EXPOSURE) (Respiratory tract

irritation) - Category 3

SPECIFIC TARGET ORGAN TOXICITY (REPEATED EXPOSURE) - Category 1

Composition/information on ingredients

United States Page: 11/12

Date of issue 21 February 2023 Version 5

Section 15. Regulatory information

Name	%	Classification
olyester resin		COMBUSTIBLE DUSTS SPECIFIC TARGET ORGAN TOXICITY (SINGLE EXPOSURE) (Respiratory tract irritation) - Category 3
Cyclohexane, 5-isocyanato-1- (isocyanatomethyl) -1,3,3-trimethyl-, homopolymer, caprolactam-blocked		COMBUSTIBLE DUSTS SPECIFIC TARGET ORGAN TOXICITY (REPEATED EXPOSURE) - Category 1

Additional environmental information is contained on the Environmental Data Sheet for this product, which can be obtained from your PPG representative.

Section 16. Other information

Hazardous Material Information System (U.S.A.)

Health : 2

* Flammability : 0 Physical hazards :

* 1

(*) - Chronic effects

Caution: HMIS® ratings are based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks. Although HMIS® ratings and the associated label are not required on MSDSs or products leaving a facility under 29 CFR 1910.1200, the preparer may choose to provide them. HMIS® ratings are to be used with a fully implemented HMIS® program. HMIS® is a registered trademark and service mark of the American Coatings Association, Inc.

The customer is responsible for determining the PPE code for this material. For more information on HMIS® Personal Protective Equipment (PPE) codes, consult the HMIS® Implementation Manual.

National Fire Protection Association (U.S.A.)

Health: 2 Flammability: 0 Instability:

Date of previous issue : 6/19/2021

Organization that prepared the SDS

Key to abbreviations : ATE = Acute Toxicity Estimate

: EHS

BCF = Bioconcentration Factor

GHS = Globally Harmonized System of Classification and Labelling of Chemicals

IATA = International Air Transport Association

IBC = Intermediate Bulk Container

IMDG = International Maritime Dangerous Goods

LogPow = logarithm of the octanol/water partition coefficient

MARPOL = International Convention for the Prevention of Pollution From Ships, 1973

as modified by the Protocol of 1978. ("Marpol" = marine pollution)

N/A = Not available SGG = Segregation Group UN = United Nations

Indicates information that has changed from previously issued version.

Disclaimer

The information contained in this data sheet is based on present scientific and technical knowledge. The purpose of this information is to draw attention to the health and safety aspects concerning the products supplied by PPG, and to recommend precautionary measures for the storage and handling of the products. No warranty or guarantee is given in respect of the properties of the products. No liability can be accepted for any failure to observe the precautionary measures described in this data sheet or for any misuse of the products.

United States Page: 12/12