# **Material Safety Data Sheet**



Date of issue 3 April 2014

Version 14

## Product and company identification

Product name : MANOR HALL EXT FLAT LATEX DEEP BASE

**Code** : 70-130

**Supplier** : PPG Industries, Inc.

One PPG Place Pittsburgh, PA 15272 : (412) 434-4515 (U.S.)

Emergency telephone

number

(514) 645-1320 (Canada) 01-800-00-21-400 (Mexico)

**Technical Phone Number** : 1-800-441-9695 (8:00 am to 5:00 pm EST)

## 2. Hazards identification

Emergency overview : WARNING!

MAY BE HARMFUL IF INHALED OR SWALLOWED. CONTAINS MATERIAL THAT

MAY CAUSE TARGET ORGAN DAMAGE, BASED ON ANIMAL DATA.

Use only with adequate ventilation. Keep container tightly closed and sealed until

ready for use. Wash thoroughly after handling.

Potential acute health effects

Inhalation: May be harmful if inhaled.Ingestion: May be harmful if swallowed.

Skin: No known significant effects or critical hazards.Eyes: No known significant effects or critical hazards.

Over-exposure signs/symptoms

Inhalation: No specific data.Ingestion: No specific data.Skin: No specific data.Eyes: No specific data.

Medical conditions

aggravated by over-

exposure

: Pre-existing disorders involving any target organs mentioned in this MSDS as being at

risk may be aggravated by over-exposure to this product.

This Material Safety Data Sheet has been prepared in accordance with Canada's Workplace Hazardous Materials Information System (WHMIS) and the OSHA Hazard Communication Standard (29 CFR 1910.1200).

See toxicological information (Section 11)

## 3. Composition/information on ingredients

	CAS number	<u>ıber</u> <u>%</u>	
Limestone	1317-65-3	7 - 13	
Diatomaceous earth	61790-53-2	5 - 10	
titanium dioxide	13463-67-7	1 - 5	
N-methyl-2-pyrrolidone	872-50-4	0.1 - 1	

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment and hence require reporting in this section.

United States - Canada - Mexico Page: 1/7

### Product name MANOR HALL EXT FLAT LATEX DEEP BASE

## 4. First aid measures

If ingestion, irritation, any type of overexposure or symptoms of overexposure occur during or persists after use of this product, contact a POISON CONTROL CENTER, EMERGENCY ROOM OR PHYSICIAN immediately; have Material Safety Data Sheet information available. Never give anything by mouth to an unconscious or convulsing person.

Eye contact

: Check for and remove any contact lenses. Immediately flush eyes with running water for at least 15 minutes, keeping eyelids open. Seek immediate medical attention.

Skin contact

: Remove contaminated clothing and shoes. Wash skin thoroughly with soap and water or use recognized skin cleanser. Do NOT use solvents or thinners.

Inhalation

: Remove to fresh air. Keep person warm and at rest. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel.

Ingestion

: If swallowed, seek medical advice immediately and show this container or label. Keep person warm and at rest. Do NOT induce vomiting.

Notes to physician

No specific treatment. Treat symptomatically. Contact poison treatment specialist immediately if large quantities have been ingested or inhaled.

## 5. Fire-fighting measures

Flammability of the product

: In a fire or if heated, a pressure increase will occur and the container may burst.

Extinguishing media
Suitable

: Use an extinguishing agent suitable for the surrounding fire.

Not suitable

: None known.

Special exposure hazards

: Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training.

Hazardous combustion products

: Decomposition products may include the following materials: carbon oxides

metal oxide/oxides

Special protective equipment for fire-fighters

: Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode.

## 6. Accidental release measures

**Personal precautions** 

: No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilled material. Avoid breathing vapor or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment (see Section 8).

**Environmental precautions** 

: Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air).

Large spill

Stop leak if without risk. Move containers from spill area. Approach release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations (see Section 13). Dispose of via a licensed waste disposal contractor. Contaminated absorbent material may pose the same hazard as the spilled product. Note: see Section 1 for emergency contact information and Section 13 for waste disposal.

Small spill

: Stop leak if without risk. Move containers from spill area. Dilute with water and mop up if water-soluble or absorb with an inert dry material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.

United States - Canada - Mexico

Page: 2/7

### Product name MANOR HALL EXT FLAT LATEX DEEP BASE

#### Handling and storage 7.

### **Handling**

Put on appropriate personal protective equipment (see Section 8). Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Do not swallow. Do not get in eyes or on skin or clothing. Avoid breathing vapor or mist. If during normal use the material presents a respiratory hazard, use only with adequate ventilation or wear appropriate respirator. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Empty containers retain product residue and can be hazardous. Do not reuse container. If this material is part of a multiple component system, read the Material Safety Data Sheet(s) for the other component or components before blending as the resulting mixture may have the hazards of all of its parts.

### **Storage**

Store in accordance with local regulations. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabeled containers. Use appropriate containment to avoid environmental contamination. Do not store below the following temperature: 32F / 0C.

#### 8. Exposure controls/personal protection

Name	Result	ACGIH	OSHA	Ontario	Mexico	PPG
Limestone	TWA	Not established	15 mg/m³ TD 5 mg/m³ R	Not established	10 mg/m³	Not established
	STEL	Not established	Not established	Not established	20 mg/m³	Not established
Diatomaceous earth	TWA	Not established	20 mppcf Z 80 MG/M3 / (%SiO2) Z	3 mg/m³ R 10 mg/m³ 3 mg/m³	10 mg/m³	Not established
titanium dioxide	TWA	10 mg/m³	15 mg/m³ TD	10 mg/m³ TD	10 mg/m³ (as Ti)	Not established
	STEL	Not established	Not established	Not established	20 mg/m³ (as Ti)	Not established
N-methyl-2-pyrrolidone	TWA	Not established	Not established	400 mg/m³	Not established	10 ppm S

### Key to abbreviations

= Acceptable Maximum Peak ACGIH

= American Conference of Governmental Industrial Hygienists.

С = Ceiling Limit F = Fume **IPEL** 

= Internal Permissible Exposure Limit

= Respirable

OSHA

= Occupational Safety and Health Administration.

OSHA 29CFR 1910.1200 Subpart Z - Toxic and Hazardous Substances

## Consult local authorities for acceptable exposure limits.

## **Recommended monitoring** procedures

: If this product contains ingredients with exposure limits, personal, workplace atmosphere or biological monitoring may be required to determine the effectiveness of the ventilation or other control measures and/or the necessity to use respiratory protective equipment. Reference should be made to appropriate monitoring standards. Reference to national guidance documents for methods for the determination of hazardous substances will also be required.

S

SR

SS

STFL

TD

TLV

TWA

= Potential skin absorption

= Respiratory sensitization

= Threshold Limit Value

= Time Weighted Average

= Short term Exposure limit values

= Skin sensitization

Total dust

### **Engineering measures**

: If user operations generate dust, fumes, gas, vapor or mist, use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure to airborne contaminants below any recommended or statutory limits.

United States - Canada - Mexico

Page: 3/7

Product code 70-130 Date of issue 3 April 2014 Version 14

### Product name MANOR HALL EXT FLAT LATEX DEEP BASE

#### 8. Exposure controls/personal protection

Hygiene measures

: Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.

**Personal protection** 

**Eyes Hands**  : Safety glasses with side shields.

Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. Considering the parameters specified by the glove manufacturer, check during use that the gloves are still retaining their protective properties. It should be noted that the time to breakthrough for any glove material may be different for different glove manufacturers. In the case of mixtures, consisting of several substances, the protection time of the gloves cannot be accurately estimated.

Respiratory

If workers are exposed to concentrations above the exposure limit, they must use appropriate, certified respirators. Use a properly fitted, air-purifying or air-fed respirator complying with an approved standard if a risk assessment indicates this is necessary. Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator.

Skin

Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.

**Environmental exposure** 

controls

: Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

#### 9. Physical and chemical properties

**Physical state** : Liquid.

Flash point Closed cup: >93.33°C (>200°F)

Color : Not available. Odor Not available. pН : Not available. **Boiling/condensation point** : >37.78°C (>100°F) **Melting/freezing point** : Not available.

**Specific gravity** : 1.2 Density (Ibs / gal) : 10.01

Vapor pressure : 2.3 kPa (17.4 mm Hg) [room temperature]

Vapor density : Not available.

**Volatility** : 64% (v/v), 52.97% (w/w) **Evaporation rate** : 0.35 (butyl acetate = 1)

Partition coefficient: n-

octanol/water

: Not available.

**47.03** % Solid. (w/w)

United States - Canada - Mexico

Page: 4/7

Product code 70-130 Date of issue 3 April 2014 Version 14

### Product name MANOR HALL EXT FLAT LATEX DEEP BASE

## 10. Stability and reactivity

**Stability** 

**Conditions to avoid** Materials to avoid

Stable under recommended storage and handling conditions (see Section 7).

No specific data.

Reactive or incompatible with the following materials: acids, oxidizing materials, strong

Under normal conditions of storage and use, hazardous decomposition products

alkalis

**Hazardous decomposition** 

products **Hazardous polymerization**  should not be produced.

: Under normal conditions of storage and use, hazardous polymerization will not occur.

## 11. Toxicological information

## **Acute toxicity**

Product/ingredient name	Result	Species	Dose	Exposure
Manium dioxide	LD50 Oral	Rat	>10 g/kg	-
N-methyl-2-pyrrolidone	LD50 Oral	Rat	3.914 g/kg	-
	LD50 Dermal	Rabbit	8 g/kg	-
	LC50 Inhalation	Rat	>5100 mg/m <sup>3</sup>	4 hours
	Dusts and mists			

Conclusion/Summary **Chronic toxicity** 

: Not available.

Conclusion/Summary

: Not available.

**Target organs** 

: Contains material which may cause damage to the following organs: lungs, upper respiratory tract, skin, eyes.

**Carcinogenicity** 

Carcinogenicity

: Contains material which may cause cancer, based on animal data. Risk of cancer depends on duration and level of exposure.

### **Classification**

Product/ingredient name	ACGIH	IARC	NTP	OSHA
Diatomaceous earth	-	3	-	-
titanium dioxide	A4	2B	-	-

Carcinogen Classification code:

ACGIH: A1, A2, A3, A4, A5 IARC: 1, 2A, 2B, 3, 4 NTP: Proven, Possible

OSHA: +

Not listed or regulated as a carcinogen: -

**Developmental effects** 

: Contains material which may cause developmental abnormalities, based on animal

data.

**Fertility effects** 

Contains material which may impair male fertility, based on animal data. Contains material which may impair female fertility, based on animal data.

## 12. Ecological information

**Environmental effects** 

: No known significant effects or critical hazards.

## 13. Disposal considerations

Waste disposal

: The generation of waste should be avoided or minimized wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible. This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers

United States - Canada - Mexico

Page: 5/7

### Product name MANOR HALL EXT FLAT LATEX DEEP BASE

## 13. Disposal considerations

that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.

Disposal should be in accordance with applicable regional, national and local laws and regulations.

Refer to Section 7: HANDLING AND STORAGE and Section 8: EXPOSURE CONTROLS/PERSONAL PROTECTION for additional handling information and protection of employees. Section 6. Accidental release measures

## 14. Transport information

	DOT	TDG	Mexico	IMDG
UN number	Not regulated.	Not regulated.	Not regulated.	Not regulated.
UN proper shipping name	-	-	-	-
Transport hazard class(es)	-	-	-	-
Packing group	-	-	-	-
Environmental hazards	No.	No.	No.	No.
Marine pollutant substances	Not applicable.	Not applicable.	Not applicable.	Not applicable.

#### **Additional information**

DOT : None identified.

TDG : None identified.

Mexico : None identified.

IMDG : None identified.

Special precautions for user : Transport within user's premises: always transport in closed containers that are

upright and secure. Ensure that persons transporting the product know what to do in

the event of an accident or spillage.

## 15. Regulatory information

United States inventory (TSCA 8b): All components are listed or exempted.Australia inventory (AICS): All components are listed or exempted.

Canada inventory (DSL) : All components are listed or exempted.

China inventory (IECSC) : This product contains a component which may restrict import to the notifier and/or

to other parties holding a concurrent notification or agreement.

**Europe inventory (REACH)** : Please contact your supplier for information on the inventory status of this

material.

New Zealand ( NZIoC ) : Substance Use Restricted

Philippines inventory (PICCS) : At least one component is not listed.

**United States** 

SARA 302/304: No products were found.

CERCLA: Hazardous substances.: ammonia: 1000 lbs. (454 kg);

SARA 311/312 SDS Distribution - Chemical Inventory - Hazard Identification:

<u>Chemical name</u> <u>CAS # Acute Chronic Fire Reactive Pressure</u>

United States - Canada - Mexico Page: 6/7

Product code 70-130		Date of issue 3 April 2014			Version	14	
Product name MANOR HALL EXT FLAT LATEX DEEP BASE							
15 . Regulatory information							
<b>L</b> imestone	1317-65-3	N	N	N	N	N	
Diatomaceous earth	61790-53-2	N	N	N	N	N	
titanium dioxide	13463-67-7	N	Υ	N	N	N	
N-methyl-2-pyrrolidone	872-50-4	Υ	Υ	N	Υ	N	
	Product as-supplied :	N	Υ	N	N	N	

Additional environmental information is contained on the Environmental Data Sheet for this product, which can be obtained from your PPG representative.

### California Prop. 65

**WARNING:** This product contains a chemical known to the State of California to cause birth defects or other reproductive harm.

Canada

WHMIS (Canada) : Class D-2A: Material causing other toxic effects (Very toxic).

<u>Mexico</u>

Classification

Flammability: 1 Health: 2 Reactivity: 0

## 16. Other information

**Hazardous Material Information System (U.S.A.)** 

Health : 2 \* Flammability : 1 Physical hazards : 0

(\*) - Chronic

effects

Caution: HMIS® ratings are based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks Although HMIS® ratings are not required on MSDSs under 29 CFR 1910. 1200, the preparer may choose to provide them. HMIS® ratings are to be used with a fully implemented HMIS® program. HMIS® is a registered mark of the National Paint & Coatings Association (NPCA). HMIS® materials may be purchased exclusively from J. J. Keller (800) 327-6868.

The customer is responsible for determining the PPE code for this material.

National Fire Protection Association (U.S.A.)

Health: 2 Flammability: 1 Instability: 0

Date of previous issue : 3/10/2014.

Organization that prepared : EHS

the MSDS

▼ Indicates information that has changed from previously issued version.

### **Disclaimer**

The information contained in this data sheet is based on present scientific and technical knowledge. The purpose of this information is to draw attention to the health and safety aspects concerning the products supplied by PPG, and to recommend precautionary measures for the storage and handling of the products. No warranty or guarantee is given in respect of the properties of the products. No liability can be accepted for any failure to observe the precautionary measures described in this data sheet or for any misuse of the products.

United States - Canada - Mexico

Page: 7/7