# **Material Safety Data Sheet**



Date of issue 4 March 2014

Version 40

### Product and company identification

Product name : MANOR HALL INT LTX S/G DEEPTONE

Code : 87-200

**Supplier** : PPG Industries, Inc.

One PPG Place Pittsburgh, PA 15272

Emergency telephone

number

: (412) 434-4515 (U.S.) (514) 645-1320 (Canada) 01-800-00-21-400 (Mexico)

**Technical Phone Number** : 1-800-441-9695 (8:00 am to 5:00 pm EST)

### 2. Hazards identification

Emergency overview : WARNING

MAY BE HARMFUL IF INHALED OR SWALLOWED. SANDING AND GRINDING DUSTS MAY BE HARMFUL IF INHALED. MAY CAUSE RESPIRATORY TRACT AND EYE IRRITATION. CONTAINS MATERIAL THAT CAN CAUSE TARGET ORGAN DAMAGE. CANCER HAZARD - CONTAINS MATERIAL WHICH CAN CAUSE CANCER.

Avoid breathing vapor or mist. Avoid contact with eyes, skin and clothing. Use only with adequate ventilation. Keep container tightly closed and sealed until ready for use. Wash thoroughly after handling.

Potential acute health effects

**Inhalation** : May be harmful if inhaled. Slightly irritating to the respiratory system.

**Ingestion** : May be harmful if swallowed.

**Skin**: No known significant effects or critical hazards.

**Eyes** : Moderately irritating to eyes.

#### Over-exposure signs/symptoms

This product contains crystalline silica which can cause lung cancer or silicosis. The risk of cancer depends on the duration and level of exposure to dust from sanding surfaces or mist from spray applications.

Medical conditions aggravated by over-

: Pre-existing disorders involving any target organs mentioned in this MSDS as being at risk may be aggravated by over-exposure to this product.

exposure

This Material Safety Data Sheet has been prepared in accordance with Canada's Workplace Hazardous Materials Information System (WHMIS) and the OSHA Hazard Communication Standard (29 CFR 1910.1200).

See toxicological information (Section 11)

## 3. Composition/information on ingredients

<u>Name</u>	CAS number	<u>%</u>
Kaolin	1332-58-7	5 - 10
titanium dioxide	13463-67-7	1 - 5
1-(2-butoxy-1-methylethoxy)propan-2-ol	29911-28-2	1 - 5
ethanediol	107-21-1	0.1 - 1
cristobalite (<10 microns)	14464-46-1	0.1 - 1
Kieselguhr, soda ash flux-calcined	68855-54-9	0.1 - 1
pyrithione zinc	13463-41-7	0.1 - 1

United States - Canada - Mexico Page: 1/8

### Product name MANOR HALL INT LTX S/G DEEPTONE

### 3. Composition/information on ingredients

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment and hence require reporting in this section.

### 4. First aid measures

If ingestion, irritation, any type of overexposure or symptoms of overexposure occur during or persists after use of this product, contact a POISON CONTROL CENTER, EMERGENCY ROOM OR PHYSICIAN immediately; have Material Safety Data Sheet information available. Never give anything by mouth to an unconscious or convulsing person.

Eye contact : Check for and remove any contact lenses. Immediately flush eyes with running water for at least 15 minutes, keeping eyelids open. Seek immediate medical

attention.

Skin contact : Remove contaminated clothing and shoes. Wash skin thoroughly with soap and water or use recognized skin cleanser. Do NOT use solvents or thinners.

Inhalation : Remove to fresh air. Keep person warm and at rest. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by

trained personnel.

**Ingestion**: If swallowed, seek medical advice immediately and show this container or label.

Keep person warm and at rest. Do NOT induce vomiting.

Notes to physician : No specific treatment. Treat symptomatically. Contact poison treatment specialist

immediately if large quantities have been ingested or inhaled.

### 5. Fire-fighting measures

**Flammability of the product** : In a fire or if heated, a pressure increase will occur and the container may burst.

Extinguishing media

products

**Suitable**: Use an extinguishing agent suitable for the surrounding fire.

Not suitable : None known.

Special exposure hazards : Promptly isola

azards : Promptly isolate the scene by removing all persons from the vicinity of the incident if

there is a fire. No action shall be taken involving any personal risk or without suitable

Hazardous combustion : Deco

 Decomposition products may include the following materials: carbon oxides metal oxide/oxides

Special protective equipment for fire-fighters

: Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode.

### 6. Accidental release measures

Personal precautions : No action shall be taken involving any personal risk or without suitable training.

Evacuate surrounding areas. Keep unnecessary and unprotected personnel from

entering. Do not touch or walk through spilled material. Avoid breathing vapor or mist.

Provide adequate ventilation. Wear appropriate respirator when ventilation is

inadequate. Put on appropriate personal protective equipment (see Section 8).

Environmental precautions: Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains

and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air).

pollution (sewers, waterways, soil or air).

Stop leak if without risk. Move containers from spill area. Approach release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations (see Section 13). Dispose of via a licensed waste disposal contractor. Contaminated absorbent material may pose the same hazard as the spilled product. Note: see Section 1 for emergency contact information and Section 13 for waste

disposal.

**United States - Canada - Mexico** 

Powered by IHS

Page: 2/8

#### Product name MANOR HALL INT LTX S/G DEEPTONE

### 6. Accidental release measures

**Small spill** 

: Stop leak if without risk. Move containers from spill area. Dilute with water and mop up if water-soluble or absorb with an inert dry material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.

### 7. Handling and storage

**Handling** 

Put on appropriate personal protective equipment (see Section 8). Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Do not swallow. Do not get in eyes or on skin or clothing. Avoid breathing vapor or mist. Use only with adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Empty containers retain product residue and can be hazardous. Do not reuse container. If this material is part of a multiple component system, read the Material Safety Data Sheet(s) for the other component or components before blending as the resulting mixture may have the hazards of all of its parts.

**Storage** 

: Store in accordance with local regulations. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabeled containers. Use appropriate containment to avoid environmental contamination. Do not store below the following temperature: 32F / 0C.

# 8. Exposure controls/personal protection

Name	Result	ACGIH	OSHA	Ontario	Mexico	PPG
Kaolin	TWA	2 mg/m³ R	15 mg/m³ TD 5 mg/m³ R	2 mg/m³ R	10 mg/m³	Not established
	STEL	Not established	Not established	Not established	20 mg/m³	Not established
titanium dioxide	TWA	10 mg/m³	15 mg/m³ TD	10 mg/m³ TD	10 mg/m³ (as Ti)	Not established
	STEL	Not established	Not established	Not established	20 mg/m³ (as Ti)	Not established
ethanediol	STEL	100 mg/m³ C	Not established	100 mg/m³ C	100 mg/m³ C	Not established
cristobalite (<10 microns)	TWA	0.025 mg/m <sup>3</sup> R	250 MPPCF / 2 x (%SiO2+5) R Z 10 MG/M3 / 2 x (%SiO2+2) R Z 30 MG/M3 / 2 x (%SiO2+2) TD Z	0.05 mg/m³	0.05 mg/m <sup>3</sup>	Not established
Kieselguhr, soda ash flux- calcined	TWA	Not established	Not established	Not established	10 mg/m³ 3 mg/m³ R	Not established

Key to abbreviations

A = Acceptable Maximum Peak ACGIH = American Conference of Go

= American Conference of Governmental Industrial Hygienists.

S = Potential skin absorption

SR = Respiratory sensitization

United States - Canada - Mexico

### Product name MANOR HALL INT LTX S/G DEEPTONE

### 8. Exposure controls/personal protection

= Ceiling Limit SS = Skin sensitization

F = Fume STEL = Short term Exposure limit values

IPEL = Internal Permissible Exposure Limit TD = Total dust

OSHA = Occupational Safety and Health Administration. TLV = Threshold Limit Value
R = Respirable TWA = Time Weighted Average

Z = OSHA 29CFR 1910.1200 Subpart Z - Toxic and Hazardous Substances

#### Consult local authorities for acceptable exposure limits.

Recommended monitoring procedures

: If this product contains ingredients with exposure limits, personal, workplace atmosphere or biological monitoring may be required to determine the effectiveness of the ventilation or other control measures and/or the necessity to use respiratory protective equipment. Reference should be made to appropriate monitoring standards. Reference to national guidance documents for methods for the determination of hazardous substances will also be required.

**Engineering measures** 

Use only with adequate ventilation. If user operations generate dust, fumes, gas, vapor or mist, use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure to airborne contaminants below any recommended or statutory limits.

**Hygiene measures** 

: Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.

**Personal protection** 

**Eyes** : Safety glasses with side shields.

Hands

С

: Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. Considering the parameters specified by the glove manufacturer, check during use that the gloves are still retaining their protective properties. It should be noted that the time to breakthrough for any glove material may be different for different glove manufacturers. In the case of mixtures, consisting of several substances, the protection time of the gloves cannot be accurately estimated.

Respiratory

: If workers are exposed to concentrations above the exposure limit, they must use appropriate, certified respirators. Use a properly fitted, air-purifying or air-fed respirator complying with an approved standard if a risk assessment indicates this is necessary. Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator.

Skin

: Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.

Environmental exposure controls

: Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

# 9. Physical and chemical properties

Physical state : Liquid.

Flash point : Closed cup: >93.33°C (>200°F)

Color : Not available.

Odor : Not available.

pH : Not available.

Boiling/condensation point : 37.22°C (99°F)

Melting/freezing point : Not available.

Specific gravity : 1.13 Density (lbs / gal) : 9.43

Vapor pressure : 2.3 kPa (17.3 mm Hg) [room temperature]

Vapor density : Not available.

United States - Canada - Mexico Page: 4/8

### **Product name MANOR HALL INT LTX S/G DEEPTONE**

#### Physical and chemical properties 9.

: 72% (v/v), 63.03% (w/w) Volatility **Evaporation rate** : 0.34 (butyl acetate = 1)

Partition coefficient: n-

octanol/water

: Not available.

**3**6.97 % Solid. (w/w)

# 10. Stability and reactivity

**Stability** Stable under recommended storage and handling conditions (see Section 7).

**Conditions to avoid** No specific data.

: Reactive or incompatible with the following materials:,acids,oxidizing materials,strong **Materials to avoid** 

alkalis

**Hazardous decomposition** 

products

: Under normal conditions of storage and use, hazardous decomposition products

should not be produced.

**Hazardous polymerization** : Under normal conditions of storage and use, hazardous polymerization will not occur.

# 11. Toxicological information

#### **Acute toxicity**

Product/ingredient name	Result	Species	Dose	Exposure
Kaolin	LD50 Oral	Rat	>5000 mg/kg	-
titanium dioxide	LD50 Oral	Rat	>10 g/kg	-
1-(2-butoxy-1-methylethoxy)propan-2-ol	LD50 Oral	Rat	4.05 g/kg	-
	LD50 Dermal	Rabbit	5860 uL/kg	-
ethanediol	LD50 Oral	Rat	4700 mg/kg	-
	LD50 Dermal	Rabbit	9.53 g/kg	-
pyrithione zinc	LD50 Oral	Rat	177 mg/kg	-
• •	LD50 Dermal	Rabbit	100 mg/kg	-
	LC50 Inhalation	Rat	140 mg/m <sup>3</sup>	4 hours
	Dusts and mists			

Conclusion/Summary

**Chronic toxicity** 

: Not available.

: Not available.

**Conclusion/Summary** 

: Contains material which causes damage to the following organs: eyes. **Target organs** Contains material which may cause damage to the following organs: lungs, upper

respiratory tract, stomach.

Carcinogenicity

Carcinogenicity : Contains material which can cause cancer. Risk of cancer depends on duration and

level of exposure.

### **Classification**

Product/ingredient name	ACGIH	IARC	NTP	OSHA
Kaolin	A4	-	-	-
titanium dioxide	A4	2B	-	-
ethanediol	A4	-	-	-
cristobalite (<10 microns)	A2	1	Known to be a	-
			human	
			carcinogen.	

Carcinogen Classification code: ACGIH: A1, A2, A3, A4, A5 IARC: 1, 2A, 2B, 3, 4

NTP: Proven, Possible

OSHA: +

Not listed or regulated as a carcinogen: -

United States - Canada - Mexico

Page: 5/8

### Product name MANOR HALL INT LTX S/G DEEPTONE

### 11. Toxicological information

**Teratogenicity** 

: Contains material which may cause birth defects, based on animal data.

### 12. Ecological information

Environmental effects

: No known significant effects or critical hazards.

#### **Aquatic ecotoxicity**

Product/ingredient name	Result	Species	Exposure
<b>e</b> thanediol	Acute LC50 8050000 ug/L Fresh water	Fish - Fathead minnow - Pimephales promelas	96 hours
	Acute LC50 >10000000 ug/L Fresh water	Daphnia - Water flea - Daphnia magna	48 hours
	Chronic NOEC 6090000 ug/L Fresh water	Fish - Fathead minnow - Pimephales promelas	96 hours
pyrithione zinc	Acute LC50 2.68 ppb Fresh water	Fish - Fathead minnow - Pimephales promelas	96 hours
	Acute LC50 400 ppb Marine water	Fish - Sheepshead minnow - Cyprinodon variegatus	96 hours
	Acute EC50 8.25 ppb Fresh water	Daphnia - Water flea - Daphnia magna	48 hours

# 13. Disposal considerations

Waste disposal

: The generation of waste should be avoided or minimized wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible. This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.

Disposal should be in accordance with applicable regional, national and local laws and regulations.

Refer to Section 7: HANDLING AND STORAGE and Section 8: EXPOSURE CONTROLS/PERSONAL PROTECTION for additional handling information and protection of employees. Section 6. Accidental release measures

# 14. Transport information

	DOT	TDG	Mexico	IMDG
UN number	Not regulated.	Not regulated.	Not regulated.	Not regulated.
UN proper shipping name				<b>F</b>
Transport hazard class(es)	-			
Packing group	-	<b>-</b>	<b>-</b>	
Environmental hazards	No.	No.	No.	No.

United States - Canada - Mexico

Page: 6/8

#### Product name MANOR HALL INT LTX S/G DEEPTONE

### 14. Transport information

Marine pollutant<br/>substancesNot applicable.Not applicable.Not applicable.

#### **Additional information**

DOT : Mone identified.

TDG : Mone identified.

Mexico : Mone identified.

IMDG : Mone identified.

Special precautions for user : Transport within user's premises: always transport in closed containers that are

upright and secure. Ensure that persons transporting the product know what to do in

the event of an accident or spillage.

# 15. Regulatory information

United States inventory (TSCA 8b) : All components are listed or exempted.

Australia inventory (AICS) : All components are listed or exempted.

Canada inventory (AICS) : All components are listed or exempted.

Canada inventory ( DSL ) : All components are listed or exempted.

China inventory (IECSC) : ☒I components are listed or exempted.

**Europe inventory (REACH)** : Please contact your supplier for information on the inventory status of this

material.

Japan inventory (ENCS) : At least one component is not listed.

Korea inventory (KECI) : At least one component is not listed.

New Zealand ( NZIoC ) : Substance Use Restricted

Philippines inventory (PICCS) : At least one component is not listed.

#### **United States**

#### U.S. Federal regulations

United States - TSCA 5(e) - Substances consent order:

partially fluorinated alcohol, reaction products Listed

United States - TSCA 5(a)2 - Proposed significant new use rules:

partially fluorinated alcohol, reaction products

Listed

SARA 302/304: No products were found.

ERCLA: Hazardous substances.: pyrithione zinc: No RQ is being assigned to the generic or broad class.; ethanediol:

5000 lbs. (2270 kg);

### SARA 311/312 SDS Distribution - Chemical Inventory - Hazard Identification:

Chemical name	CAS#	<u>Acute</u>	<b>Chronic</b>	<u>Fire</u>	<b>Reactive</b>	<b>Pressure</b>
<b>K</b> aolin	1332-58-7	Υ	N	N	N	N
titanium dioxide	13463-67-7	N	Υ	N	N	N
1-(2-butoxy-1-methylethoxy)propan	- 29911-28-2	Υ	N	N	N	N
2-ol						
ethanediol	107-21-1	Υ	Υ	N	N	N
cristobalite (<10 microns)	14464-46-1	N	Υ	N	N	N
Produc	t as-supplied :	Υ	Υ	N	N	N

Additional environmental information is contained on the Environmental Data Sheet for this product, which can be obtained from your PPG representative.

#### California Prop. 65

**WARNING:** This product contains a chemical known to the State of California to cause cancer.

<u>Canada</u>

United States - Canada - Mexico Page: 7/8

#### Product name MANOR HALL INT LTX S/G DEEPTONE

### 15 . Regulatory information

WHMIS (Canada) : Class D-2A: Material causing other toxic effects (Very toxic). Class D-2B: Material

causing other toxic effects (Toxic).

**Mexico** 

Classification

Flammability: 1 Health: 2 Reactivity: 0

### 16. Other information

Hazardous Material Information System (U.S.A.)

Health: 2 \* Flammability: 1 Physical hazards: 0

(\*) - Chronic

effects

Caution: HMIS® ratings are based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks Although HMIS® ratings are not required on MSDSs under 29 CFR 1910. 1200, the preparer may choose to provide them. HMIS® ratings are to be used with a fully implemented HMIS® program. HMIS® is a registered mark of the National Paint & Coatings Association (NPCA). HMIS® materials may be purchased exclusively from J. J. Keller (800) 327-6868.

The customer is responsible for determining the PPE code for this material.

**National Fire Protection Association (U.S.A.)** 

Health: 2 Flammability: 1 Instability: 0

Date of previous issue : 8/6/2013.

Organization that prepared : EHS

the MSDS

Indicates information that has changed from previously issued version.

### **Disclaimer**

The information contained in this data sheet is based on present scientific and technical knowledge. The purpose of this information is to draw attention to the health and safety aspects concerning the products supplied by PPG, and to recommend precautionary measures for the storage and handling of the products. No warranty or guarantee is given in respect of the properties of the products. No liability can be accepted for any failure to observe the precautionary measures described in this data sheet or for any misuse of the products.

United States - Canada - Mexico Page: 8/8