

SAFETY DATA SHEET



Date of issue : 8 November 2021

Version : 7

Section 1. Identification

Product code : PT-G141/1L

Product name : G141 BLACK - BLUE TONE - REDUCED

Product type : Liquid.

Recommended use and restrictions

Use of the substance/
mixture : Coating.

Uses advised against : Not applicable.


Supplier's details : PPG INDUSTRIES NEW ZEALAND LTD
5 MONAHAN ROAD, MT WELLINGTON,
AUCKLAND
www.ppgnz.co.nz

Telephone Numbers:
09 573 1620, 0800 659378
021 940 920 (24 Hours)

Emergency telephone
number (with hours of
operation) : New Zealand 0800 000 096 (24 hours) / Australia 1800 883 254 (24 hours)
For international shipping emergencies: 1-412-391-1618

e-mail address of person
responsible for this SDS : ehsnz@ppg.com

Section 2. Hazards identification

HSNO Classification :  FLAMMABLE LIQUIDS - Category 2
SKIN IRRITATION - Category 2
EYE IRRITATION - Category 2
SKIN SENSITISATION - Category 1
CARCINOGENICITY - Category 2
REPRODUCTIVE TOXICITY - Category 2
SPECIFIC TARGET ORGAN TOXICITY - SINGLE EXPOSURE - Category 2
SPECIFIC TARGET ORGAN TOXICITY - REPEATED EXPOSURE - Category 2
LONG-TERM (CHRONIC) AQUATIC HAZARD - Category 3

Symbol :



GHS label elements

Signal word : Danger

Section 2. Hazards identification

Hazard statements : Highly flammable liquid and vapour.
 Causes skin irritation.
 May cause an allergic skin reaction.
 Causes serious eye irritation.
 Suspected of causing cancer.
 Suspected of damaging fertility or the unborn child.
 May cause damage to organs.
 May cause damage to organs through prolonged or repeated exposure.
 Harmful to aquatic life with long lasting effects.
 May form explosive peroxides.
 Prolonged or repeated contact may dry skin and cause irritation.

Precautionary statements

Prevention : Do not handle until all safety precautions have been read and understood. Wear protective gloves, protective clothing and eye or face protection. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Avoid release to the environment. Do not breathe vapour. Wash thoroughly after handling.

Response : If exposed or concerned: Call a POISON CENTER or doctor. Take off contaminated clothing and wash it before reuse. IF ON SKIN: Wash with plenty of water. If skin irritation or rash occurs: Get medical advice or attention. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice or attention.

Storage : Not applicable.

Disposal : Dispose of contents and container in accordance with all local, regional, national and international regulations.

Other hazards which do not result in classification : Prolonged or repeated contact may dry skin and cause irritation.

This material is classified as hazardous according to criteria in the Hazardous Substances (Minimum Degrees of Hazard) Notice 2017 and has been classified according to the Hazardous Substances (Classifications) Notice 2017.

This material is classified as DANGEROUS GOODS according to criteria in New Zealand Land Transport Rule: Dangerous Goods 2005.

Section 3. Composition/information on ingredients

Substance/mixture : Mixture

CAS number/other identifiers

Product code : PT-G141/1L

Hazardous ingredients	%	CAS number
<input checked="" type="checkbox"/> xylene	10 - <30	1330-20-7
n-butyl acetate	1 - <10	123-86-4
ethyl 3-ethoxypropionate	1 - <10	763-69-9
Solvent naphtha (petroleum), light aromatic	1 - <10	64742-95-6
ethylbenzene	1 - <10	100-41-4
1,2,4-trimethylbenzene	1 - <10	95-63-6
bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate	<1	41556-26-7
carbon black, respirable powder	<1	1333-86-4
methyl 1,2,2,6,6-pentamethyl-4-piperidyl sebacate	<1	82919-37-7

Section 3. Composition/information on ingredients

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment or have an OEL and hence require reporting in this section.

Occupational exposure limits, if available, are listed in Section 8.

Section 4. First aid measures

Description of necessary first aid measures

- Eye contact** : Remove contact lenses, irrigate copiously with clean, fresh water, holding the eyelids apart for at least 10 minutes and seek immediate medical advice.
- Inhalation** : Remove to fresh air. Keep person warm and at rest. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel.
- Skin contact** : Remove contaminated clothing and shoes. Wash skin thoroughly with soap and water or use recognised skin cleanser. Do NOT use solvents or thinners.
- Ingestion** : If swallowed, seek medical advice immediately and show the container or label. Keep person warm and at rest. Do NOT induce vomiting.

Most important symptoms/effects, acute and delayed

Potential acute health effects

- Eye contact** : Causes serious eye irritation.
- Inhalation** : No known significant effects or critical hazards.
- Skin contact** : May cause damage to organs following a single exposure in contact with skin. Causes skin irritation. Defatting to the skin. May cause an allergic skin reaction.
- Ingestion** : May cause damage to organs following a single exposure if swallowed.

Over-exposure signs/symptoms

- Eyes** : Adverse symptoms may include the following:
pain or irritation
watering
redness
- Inhalation** : Adverse symptoms may include the following:
reduced foetal weight
increase in foetal deaths
skeletal malformations
- Skin** : Adverse symptoms may include the following:
irritation
redness
dryness
cracking
reduced foetal weight
increase in foetal deaths
skeletal malformations
- Ingestion** : Adverse symptoms may include the following:
reduced foetal weight
increase in foetal deaths
skeletal malformations

Indication of immediate medical attention and special treatment needed, if necessary

- Specific treatments** : Not available.
- Notes to physician** : Treat symptomatically. Contact poison treatment specialist immediately if large quantities have been ingested or inhaled.

Section 4. First aid measures

- Protection of first-aiders** : No action shall be taken involving any personal risk or without suitable training. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Wash contaminated clothing thoroughly with water before removing it, or wear gloves.

See toxicological information (Section 11)

Section 5. Firefighting measures

Extinguishing media

- Suitable** : Use dry chemical, CO₂, water spray (fog) or foam.
- Not suitable** : Do not use water jet.
- Specific hazards arising from the chemical** : Highly flammable liquid and vapour. Runoff to sewer may create fire or explosion hazard. In a fire or if heated, a pressure increase will occur and the container may burst, with the risk of a subsequent explosion. This material is harmful to aquatic life with long lasting effects. Fire water contaminated with this material must be contained and prevented from being discharged to any waterway, sewer or drain.
- Hazardous thermal decomposition products** : Decomposition products may include the following materials:
carbon oxides
- Special precautions for fire-fighters** : Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training. Move containers from fire area if this can be done without risk. Use water spray to keep fire-exposed containers cool.
- Special protective equipment for fire-fighters** : Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode.

Section 6. Accidental release measures

- Personal precautions, protective equipment and emergency procedures** : If specialised clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".
- Environmental precautions** : Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air). Water polluting material. May be harmful to the environment if released in large quantities.
- Methods and material for containment and cleaning up**
- Small spill** : Stop leak if without risk. Move containers from spill area. Use spark-proof tools and explosion-proof equipment. Dilute with water and mop up if water-soluble. Alternatively, or if water-insoluble, absorb with an inert dry material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.
- Large spill** : Stop leak if without risk. Move containers from spill area. Use spark-proof tools and explosion-proof equipment. Approach the release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations (see Section 13). Dispose of via a licensed waste disposal contractor. Contaminated absorbent material may pose the same hazard as the spilt product. Note: see Section 1 for emergency contact information and Section 13 for waste disposal.

Section 7. Handling and storage

Precautions for safe handling

Put on appropriate personal protective equipment (see Section 8). Persons with a history of skin sensitization problems should not be employed in any process in which this product is used. Avoid exposure - obtain special instructions before use. Avoid exposure during pregnancy. Do not handle until all safety precautions have been read and understood. Do not get in eyes or on skin or clothing. Do not breathe vapour or mist. Do not ingest. Avoid release to the environment. Use only with adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Do not enter storage areas and confined spaces unless adequately ventilated. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Store and use away from heat, sparks, open flame or any other ignition source. Use explosion-proof electrical (ventilating, lighting and material handling) equipment. Use only non-sparking tools. Take precautionary measures against electrostatic discharges. Empty containers retain product residue and can be hazardous. Do not reuse container.

Conditions for safe storage, including any incompatibilities

Do not store above the following temperature: 50°C (122°F). Store in accordance with local regulations. Store in a segregated and approved area. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Store locked up. Eliminate all ignition sources. Separate from oxidising materials. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabelled containers. Use appropriate containment to avoid environmental contamination. See Section 10 for incompatible materials before handling or use.

Section 8. Exposure controls/personal protection

Control parameters

Ingredient name	Exposure limits
xylene	NZ HSWA 2015 (New Zealand, 11/2020). WES-TWA: 217 mg/m ³ 8 hours. WES-TWA: 50 ppm 8 hours.
n-butyl acetate	NZ HSWA 2015 (New Zealand, 11/2020). WES-STEL: 950 mg/m ³ 15 minutes. WES-STEL: 200 ppm 15 minutes. WES-TWA: 713 mg/m ³ 8 hours. WES-TWA: 150 ppm 8 hours.
ethylbenzene	NZ HSWA 2015 (New Zealand, 11/2020). WES-STEL: 543 mg/m ³ 15 minutes. WES-STEL: 125 ppm 15 minutes. WES-TWA: 434 mg/m ³ 8 hours. WES-TWA: 100 ppm 8 hours.
1,2,4-trimethylbenzene	NZ HSWA 2015 (New Zealand, 11/2020). WES-TWA: 25 ppm 8 hours. WES-TWA: 123 mg/m ³ 8 hours.
carbon black, respirable powder	NZ HSWA 2015 (New Zealand, 11/2020). WES-TWA: 3 mg/m ³ 8 hours.

Section 8. Exposure controls/personal protection

- Recommended monitoring procedures** : If this product contains ingredients with exposure limits, personal, workplace atmosphere or biological monitoring may be required to determine the effectiveness of the ventilation or other control measures and/or the necessity to use respiratory protective equipment. Reference should be made to appropriate monitoring standards. Reference to national guidance documents for methods for the determination of hazardous substances will also be required.
- Appropriate engineering controls** : Use only with adequate ventilation. Use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure to airborne contaminants below any recommended or statutory limits. The engineering controls also need to keep gas, vapour or dust concentrations below any lower explosive limits. Use explosion-proof ventilation equipment.
- Environmental exposure controls** : Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

Individual protection measures

- Hygiene measures** : Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Contaminated work clothing should not be allowed out of the workplace. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.
- Respiratory protection** : Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator. If workers are exposed to concentrations above the exposure limit, they must use appropriate, certified respirators. Use a properly fitted, air-purifying or air-fed respirator complying with an approved standard if a risk assessment indicates this is necessary.
- Hand protection** : Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. Considering the parameters specified by the glove manufacturer, check during use that the gloves are still retaining their protective properties. It should be noted that the time to breakthrough for any glove material may be different for different glove manufacturers. In the case of mixtures, consisting of several substances, the protection time of the gloves cannot be accurately estimated.
- Gloves** : butyl rubber
- Eye protection** : Chemical splash goggles.
- Skin protection** : Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.

Section 9. Physical and chemical properties

Appearance

- Physical state** : Liquid.
- Colour** : Black.
- Odour** : Not available.
- Odour threshold** : Not available.
- pH** : Not applicable.
- Melting point** : Not available.

Section 9. Physical and chemical properties

Boiling point	: 126°C (258.8°F)
Flash point	: Closed cup: 4°C (39.2°F)
Flammability (solid, gas)	: Not available.
Lower and upper explosive (flammable) limits	: Not available.
Vapour pressure	: Not available.
Relative density	: 0.99
Bulk Density (g/cm ³)	: 0.992
Solubility	: Insoluble in the following materials: cold water.
Partition coefficient: n-octanol/water	: Not applicable.
Auto-ignition temperature	: Not available.
Decomposition temperature	: Not available.
Viscosity	: Kinematic (40°C (104°F)): >21 mm ² /s (>21 cSt)

Section 10. Stability and reactivity

Stability	: The product may not be stable under certain conditions of storage or use.
Possibility of hazardous reactions	: Under normal conditions of storage and use, hazardous reactions will not occur.
Conditions to avoid	: Avoid all possible sources of ignition (spark or flame). Do not pressurise, cut, weld, braze, solder, drill, grind or expose containers to heat or sources of ignition.
Incompatible materials	: Reactive or incompatible with the following materials: oxidising materials strong acids strong alkalis
Hazardous decomposition products	: Depending on conditions, decomposition products may include the following materials: carbon oxides
Hazardous polymerisation	: Under normal conditions of storage and use, hazardous polymerisation will not occur.

Section 11. Toxicological information

Information on likely routes of exposure

Inhalation	: No known significant effects or critical hazards.
Ingestion	: <input checked="" type="checkbox"/> May cause damage to organs following a single exposure if swallowed.
Skin contact	: <input checked="" type="checkbox"/> May cause damage to organs following a single exposure in contact with skin. Causes skin irritation. Defatting to the skin. May cause an allergic skin reaction.
Eye contact	: Causes serious eye irritation.

Symptoms related to the physical, chemical and toxicological characteristics

Inhalation	: Adverse symptoms may include the following: reduced foetal weight increase in foetal deaths skeletal malformations
Ingestion	: Adverse symptoms may include the following: reduced foetal weight increase in foetal deaths skeletal malformations

Section 11. Toxicological information

Skin contact : Adverse symptoms may include the following:
 irritation
 redness
 dryness
 cracking
 reduced foetal weight
 increase in foetal deaths
 skeletal malformations

Eye contact : Adverse symptoms may include the following:
 pain or irritation
 watering
 redness

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Acute toxicity

Product/ingredient name	Result	Species	Dose	Exposure
xylene	LD50 Dermal	Rabbit	1.7 g/kg	-
	LD50 Oral	Rat	4.3 g/kg	-
n-butyl acetate	LC50 Inhalation Vapour	Rat	>21.1 mg/l	4 hours
	LC50 Inhalation Vapour	Rat	2000 ppm	4 hours
	LD50 Dermal	Rabbit	>17600 mg/kg	-
	LD50 Oral	Rat	10.768 g/kg	-
ethyl 3-ethoxypropionate	LD50 Dermal	Rabbit	>5 g/kg	-
	LD50 Oral	Rat	3200 mg/kg	-
Solvent naphtha (petroleum), light aromatic	LD50 Dermal	Rabbit	3.48 g/kg	-
	LD50 Oral	Rat	8400 mg/kg	-
ethylbenzene	LC50 Inhalation Vapour	Rat	17.8 mg/l	4 hours
	LD50 Dermal	Rabbit	17.8 g/kg	-
	LD50 Oral	Rat	3.5 g/kg	-
1,2,4-trimethylbenzene	LC50 Inhalation Vapour	Rat	18000 mg/m ³	4 hours
	LD50 Oral	Rat	5 g/kg	-
bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate	LD50 Oral	Rat	3.125 g/kg	-
	LD50 Oral	Rat	3.125 g/kg	-
carbon black, respirable powder	LD50 Oral	Rat	>10 g/kg	-
methyl 1,2,2,6,6-pentamethyl-4-piperidyl sebacate	LD50 Oral	Rat	3.125 g/kg	-

Conclusion/Summary : There are no data available on the mixture itself.

Irritation/Corrosion

Product/ingredient name	Result	Species	Score	Exposure	Observation
xylene	Skin - Moderate irritant	Rabbit	-	24 hours 500 mg	-

Conclusion/Summary

Skin : There are no data available on the mixture itself.

Eyes : There are no data available on the mixture itself.

Respiratory : There are no data available on the mixture itself.

Sensitisation

Conclusion/Summary

Section 11. Toxicological information

Skin : There are no data available on the mixture itself.

Respiratory : There are no data available on the mixture itself.

Potential chronic health effects

General : May cause damage to organs through prolonged or repeated exposure. Prolonged or repeated contact can defat the skin and lead to irritation, cracking and/or dermatitis. Once sensitized, a severe allergic reaction may occur when subsequently exposed to very low levels.

Skin contact : Once sensitized, a severe allergic reaction may occur when subsequently exposed to very low levels.

Carcinogenicity : Suspected of causing cancer. Risk of cancer depends on duration and level of exposure.

Mutagenicity : No known significant effects or critical hazards.

Teratogenicity : Suspected of damaging the unborn child.

Developmental effects : No known significant effects or critical hazards.

Fertility effects : Suspected of damaging fertility.

Chronic toxicity

Not available.

Carcinogenicity

Conclusion/Summary : There are no data available on the mixture itself.

Mutagenicity

Conclusion/Summary : There are no data available on the mixture itself.

Teratogenicity

Conclusion/Summary : There are no data available on the mixture itself.

Reproductive toxicity

Conclusion/Summary : There are no data available on the mixture itself.

Specific target organ toxicity

Name	Category	Route of exposure	Target organs
<input checked="" type="checkbox"/> xylene	Category 2	-	-
<input type="checkbox"/> ethylbenzene	Category 2	inhalation	-
<input type="checkbox"/> 1,2,4-trimethylbenzene	Category 2	inhalation	-

Aspiration hazard

Name
Solvent naphtha (petroleum), light aromatic

Numerical measures of toxicity

Acute toxicity estimates

Route	ATE value
<input checked="" type="checkbox"/> Oral	3015.95 mg/kg
<input type="checkbox"/> Dermal	10254.22 mg/kg
<input type="checkbox"/> Inhalation (vapours)	99 mg/l

Other information :

Section 11. Toxicological information

Prolonged or repeated contact may dry skin and cause irritation. Repeated exposure to high vapor concentrations may cause irritation of the respiratory system and permanent brain and nervous system damage. Inhalation of vapour/ aerosol concentrations above the recommended exposure limits causes headaches, drowsiness and nausea and may lead to unconsciousness or death. Avoid contact with skin and clothing.

Section 12. Ecological information

Ecotoxicity : This material is harmful to aquatic life with long lasting effects.

Aquatic and terrestrial toxicity

Product/ingredient name	Result	Species	Exposure
n-butyl acetate	Acute LC50 18 mg/l	Fish	96 hours
ethyl 3-ethoxypropionate	Acute LC50 60.9 mg/l	Fish	96 hours
Solvent naphtha (petroleum), light aromatic	Acute LC50 8.2 mg/l	Fish	96 hours
ethylbenzene	Acute EC50 1.8 mg/l Fresh water Chronic NOEC 1 mg/l Fresh water	Daphnia Daphnia - Ceriodaphnia dubia	48 hours -

Persistence/degradability

Product/ingredient name	Test	Result	Dose	Inoculum
n-butyl acetate	TEPA and OECD 301D	83 % - Readily - 28 days	-	-
ethylbenzene	-	79 % - Readily - 10 days	-	-

Product/ingredient name	Aquatic half-life	Photolysis	Biodegradability
xylene	-	-	Readily
n-butyl acetate	-	-	Readily
ethyl 3-ethoxypropionate	-	-	Readily
ethylbenzene	-	-	Readily

Bioaccumulative potential

Product/ingredient name	LogP _{ow}	BCF	Potential
xylene	3.12	7.4 to 18.5	low
n-butyl acetate	2.3	-	low
ethyl 3-ethoxypropionate	1.47	-	low
ethylbenzene	3.6	79.43	low
1,2,4-trimethylbenzene	3.63	120.23	low

Mobility in soil

Soil/water partition coefficient (K_{oc}) : Not available.

Other adverse effects : No known significant effects or critical hazards.

Do not allow to enter drains or watercourses.

Section 13. Disposal considerations

Disposal methods : The generation of waste should be avoided or minimised wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible. This material and

Section 13. Disposal considerations




its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Vapour from product residues may create a highly flammable or explosive atmosphere inside the container. Do not cut, weld or grind used containers unless they have been cleaned thoroughly internally. Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers.

Not suitable: : Do not allow to enter drains or watercourses.

The classification of the product may meet the criteria for a hazardous waste. Disposal should be in accordance with applicable regional, national and local laws and regulations.

Refer to Section 7: HANDLING AND STORAGE and Section 8: EXPOSURE CONTROLS/PERSONAL PROTECTION for additional handling information and protection of employees. Section 6. Accidental release measures

14. Transport information

	NZ	IMDG	IATA
UN number	UN1263	UN1263	UN1263
UN proper shipping name	PAINT	PAINT	PAINT
Transport hazard class(es)	3 	3 	3 
Packing group	II	II	II
Environmental hazards	No.	No.	No.
Marine pollutant substances	Not applicable.	Not applicable.	Not applicable.

Additional information

NZ : None identified.

Hazchem code : •3YE

IMDG : None identified.

IATA : None identified.

Special precautions for user : **Transport within user's premises:** always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage.

Transport in bulk according to IMO instruments : Not applicable.

Section 15. Regulatory information

New Zealand Inventory of Chemicals (NZIoC) : All components are listed or exempted.

HSNO Approval Number : HSR002669 Flammable, Toxic [6.7]

Emergency Management Regulations : Level 1: Labelling required when 1L is present in a workplace.

Level 2: MSDS required when any amount is present in a workplace. At least 2 x 4.5 kg powder fire extinguishers required when 250L is present in a workplace.

Level 3: Emergency Response Plans and Secondary Containment required when 1000L is stored.

Flammable Signage required when 250L is present in a workplace.

Classes 1 to 5 Control Regulations : Hazardous Atmosphere Zones required for quantities greater than: 100L (closed), 25L (decanting), 5L (open occasionally), 1L (open continuously). Hazardous Substances Location Certificate required for quantities greater than: 250L (containers up to 5L), 100L (containers >5L), 50L (open containers).

Approved Handler : Yes - For quantities greater than 500L in containers up to 5L; or 250 L in containers >5L.

International regulations

Chemical Weapon Convention List Schedules I, II & III Chemicals

Not listed.

Montreal Protocol

Not listed.

Stockholm Convention on Persistent Organic Pollutants

Not listed.

Rotterdam Convention on Prior Informed Consent (PIC)

Not listed.

UNECE Aarhus Protocol on POPs and Heavy Metals

Not listed.

Section 16. Other information

Date of issue : 8 November 2021

✔ Indicates information that has changed from previously issued version.

Key to abbreviations : STEL = Short Term Exposure Limit
TWA = Time-Weighted Average
WES = Work Exposure Standard

References : Not available.

Organisation that prepared the SDS : EHS

Disclaimer

Section 16. Other information

The information contained in this data sheet is based on present scientific and technical knowledge. The purpose of this information is to draw attention to the health and safety aspects concerning the products supplied by PPG, and to recommend precautionary measures for the storage and handling of the products. No warranty or guarantee is given in respect of the properties of the products. No liability can be accepted for any failure to observe the precautionary measures described in this data sheet or for any misuse of the products.