

PROFESSIONAL WOOD FINISHES

EXTERIOR WOOD STRIPPER

8851

Technical Data Sheet



Technical Specifications (21°C (70°F))

Product Type:	Water + Sodium Hydroxide
Volume solids:	9 ± 2%
Density*:	1.1 kg/L
Practical Coverage	
Approximately 4.5 to 14 sq. metres (50 to 150 sq. ft.) per 3.78 litres	
<i>Coverage figures do not include loss due to surface irregularities and porosity or material losses due to application method or mixing.</i>	
Flammability	Non flammable and Non combustible
Flash Point*	> 93.3°C (200°F)

Drying* @ 25°C/77°F - 50% Relative Humidity

Wait 5 to 45 minutes for wood stripper to soften or dissolve coating.

Product Description

DULUX® exterior stain stripper that will remove coatings, semi-transparent or solid stains, varnishes and water-based latex or solvent-based products.

Proven Durability

- Removes Latex or Oil coatings to prepare wood for a new finish.
- Remove stains caused by mould, mildew, and water from wood surfaces.
- Ready to use.

Intended Uses

Dulux exterior stain stripper will remove most of your coatings and the surface will be ready to apply a new coating.

Surfaces

- **Exterior wood surfaces:** decks, fences, outdoor furniture, shakes, shingles, wood and wood siding.

Limitations of Use

- For exterior use only.
- Read and carefully follow all safety instructions.
- Surfaces are slippery when wet; use caution when walking on wet surfaces.
- Throughly rinse these surfaces to remove all traces of Wood stripper before applying a finish.
- Stripper may cause darkening on tannin-rich woods, such as mahogany, cedar, redwood, etc. Wood brightener is recommended to remove this darkening from the wood. Test a small, inconspicuous area prior to use to ensure acceptable appearance.
- Do not allow stripper to come into contact with bare metal, fabrics, or surfaces that are to remain coated.
- **KEEP IN AN UPRIGHT POSITION**
- **PROTECT FROM FREEZING.**

*Technical Data Source: 8851

Before use, be sure to read and follow the instructions and warnings on the label and Safety Data Sheet. See other cautions on last page.

LIMITED WARRANTY: PPG Architectural Coatings Canada, Inc. warrants performance of its products to its intended use if properly applied in accordance with the label directions and the specifications of the technical data sheet. Having no control over the application methods and conditions or the circumstances related to its use, no other warranty, expressed or implied, statutory or otherwise is given. This limited warranty extends only to the original purchaser of the product and is not transferable or assignable. If the product fails to conform to this limited warranty, we will, at your option, furnish replacement product or refund the purchase price. This limited warranty excludes (1) labour or costs of labour for the application or removal of any product and (2) all other direct, indirect, incidental, special or consequential damages.

06/2019



Available at Dulux Paints Stores across Canada and Bétonel-Dulux Stores in Quebec

AREA PREPARATION

CAUTION: Carefully read and follow all safety precautions. Wear chemical-resistant gloves, safety goggles, and protective clothing. Surfaces are slippery when wet; use caution when walking on wet surfaces.

Surface must be dry. Spray all plants and vegetation liberally with water before and after application. Be sure to have water from a garden hose with nozzle and stiff bristle broom or brush. Spray all plants and vegetation liberally with water before and after application. Wear chemical-resistant gloves, safety goggles, and protective clothing.

PRECAUTION: Dry sanding will give rise to dust and/or hazardous fumes. Wet sanding should be used wherever possible. Wear suitable respiratory protective equipment when exposure cannot be avoided by adequate local ventilation. **WARNING!** If you scrape, sand, or remove old paint, you may release lead dust. **LEAD IS TOXIC.** Contact a regional Health Canada office for more information.

Application

Apply when air, surface, and product temperatures are between 10°C (50°F) and 32°C (90°F). Thoroughly shake or stir prior to use. **DO NOT THIN.** Use product full strength. Apply liberally with a nylon brush or roller. Wait 5–45 minutes for stain stripper to soften or dissolve coating. Coating will easily rinse off when ready. Scrub areas where needed with a stiff bristle brush. Work in the direction of the wood grain to minimize grain raising. Rinse wood thoroughly with water from a garden hose or power washer at a setting of 500 to 1200 psi to eliminate scrubbing. Do not allow stain stripper to dry. If drying occurs, mist with water and reapply. Do not allow stripper to come into contact with bare metal or surfaces that are to remain coated. Stripper may cause darkening on tannin-rich woods, such as mahogany, cedar, redwood, etc. Wood brightener is recommended to remove this darkening from the wood. Test a small, inconspicuous area prior to use to ensure acceptable appearance.

Cleanup

Clean tools with warm, soapy water immediately after use.

Storage and Transportation

KEEP IN AN UPRIGHT POSITION. Store in a cool, dry location in tightly closed, plastic container. Do not reuse container. Rinse container thoroughly before disposal

Disposal

Consult your municipality about proper disposal procedure of residue in accordance with the laws and respect the environment. Do not pour down a drain or storm sewer.

Safety Measures

DANGER. CORROSIVE. CAUSES BURNS. DANGEROUS FUMES FORM WHEN MIXED WITH OTHER PRODUCTS. Do not mix with acid. Do not swallow. Do not get in eyes. Do not get on skin or clothing. Do not breathe fumes. Use only in a well-ventilated area. Handle with care. Keep out of reach of children. Wear protective gloves and eye/face protection: Chemical splash goggles or face shield. Use chemical-resistant, impervious gloves. Wear appropriate respirator when ventilation is inadequate. Inhalation of high concentrations of vapour may affect the central nervous system. Repeated exposure to high vapour concentrations may cause irritation of the respiratory system and permanent brain and nervous system damage. High vapour concentrations can cause headaches, dizziness, drowsiness and nausea and may lead to unconsciousness. The product may not be stable under certain conditions of storage or use: high temperature/pressure hazard. Keep container tightly closed and sealed until ready for use. **Note: These warnings encompass the product series. Prior to use, read and follow product-specific SDS and label information.** **FIRST AID TREATMENT:** Contains: sodium hydroxide; 2-butoxyethanol. If swallowed, call a Poison Control Centre or doctor immediately. Do not induce vomiting. If in eyes, rinse with water for 15 minutes. If on skin, rinse well with water. If on clothes, remove clothes. If breathed in, move person to fresh air. For workplace use, an SDS is available from your retailer or by calling 1-800-463-7426. **EMERGENCY SPILL INFORMATION:** 514-645-1320.

For product information call: 1-800-387-3663
www.dulux.ca



PPG Architectural Coatings Canada, Inc.
1550, rue Ampère, Suite 500
Boucherville (Quebec), J4B 7L4

The *PPG Logo* is a registered trademark of PPG Industries Ohio, Inc., *Dulux* is a registered trademark of AkzoNobel and is licensed to PPG Architectural Coatings Canada, Inc. for use in Canada only. The *Multi-Coloured Swatches Design* is a registered trademark of PPG Architectural Finishes, Inc.