



Architectural Coatings

## QUICK COVER®

## 1300CS Series

### GENERAL DESCRIPTION

*Quick Cover by Olympic* Stain is recommended for use on properly prepared exterior or interior wood, including decks, fences, siding, railings, outdoor furniture and other wood surfaces. Apply to new, dry, pressure-treated wood, uncoated new or weathered wood, or previously coated wood with a weathered clear sealant or semi-transparent stain.

### RECOMMENDED SUBSTRATES

Wood

### FEATURES / BENEFITS

UV Resistant

Two-Hour Dry (Dry-to-touch one hour)

Grab and Go

Easy Water Cleanup

Dual Hiding Effect - Single coat for semi-transparent hiding and two coats for solid hiding

For Exterior Use or Interior Use

### CONFORMANCE STANDARDS

VOC compliant in all regulated areas

### TINTING AND BASE INFORMATION

1300CS      Cedar  
1301CS      Redwood

Ready-Mixed (Ready To Use) - Do not tint.

### PACKAGING

1-Gallon (3.78 L)

*Quick Cover by Olympic* Exterior Semi-Transparent Stain

### PRODUCT DATA

PRODUCT TYPE:	Acrylic
SHEEN:	Flat
VOLUME SOLIDS*:	6% +/- 2%
WEIGHT SOLIDS*:	8% +/- 2%
WEIGHT/GALLON*:	8.6 lbs. (3.9 kg) +/- 0.2 lbs. (91 g)
VOC:	< 100 g/L (0.8 lbs./gal.)

\*Product data calculated on product 1300CS

**COVERAGE:** Approximately 250 to 350 sq. ft. (23 to 33 sq. meters) per U.S. gallon (3.78 L) depending on application, wood texture, and porosity. Coverage figures do not include loss due to surface irregularities and porosity or material loss due to application method or mixing.

**DRYING TIME:** Dry time @ 77°F (25°C); 50% relative humidity.

To Touch:	1 hour
To Recoat:	2 hours

Application in high humidity or in temperatures below 50°F (10°C) may prolong drying times. Allow 24 to 48 hours of drying time before light foot traffic or replacing furniture.

**CLEANUP:** Clean brushes and tools with warm, soapy water.

**DISPOSAL:** Contact your local environmental regulatory agency for guidance on disposal of unused product. Do not pour down a drain or storm sewer.

**FLASH POINT:** Over 200°F (93°C)

### LIMITATIONS OF USE

Apply when no precipitation is expected for 24 hours, and when air and surface temperatures are 50°F (10°C) to 90°F (32°C) and will remain above 50°F (10°C) for the next two hours. Avoid staining in direct sunlight or on hot surfaces.

**PROTECT FROM FREEZING.**

## GENERAL SURFACE PREPARATION

Surface must be clean. Remove all dust, dirt, mildew, oil, loose wood fibers, and other contaminants. Remove loose, peeling stain by sanding, scraping, or wire brushing. To ensure proper penetration, weathered, dirty, or mildewed surfaces should be cleaned with a wood cleaner prior to applying stain. After rinsing, ensure surface is free of standing water. Remove grade stamps or pencil marks by sanding.

**WARNING!** If you scrape, sand, or remove old paint, you may release lead dust or fumes. LEAD IS TOXIC. EXPOSURE TO LEAD DUST OR FUMES CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE. Wear a properly fitted, NIOSH-approved respirator and prevent skin contact to control lead exposure. Clean up carefully with a HEPA vacuum and a wet mop. Before you start, find out how to protect yourself and your family by contacting the USEPA National Lead Information Hotline at 1-800-424-LEAD or log on to [www.epa.gov/lead](http://www.epa.gov/lead). Follow these instructions to control exposure to other hazardous substances that may be released during surface preparation.

**WOOD:** Countersink all nails, putty flush with surface. Unpainted wood or wood in poor condition should be sanded smooth and wiped clean, then stained.

**EXTRACTIVE BLEEDING:** Some woods, such as redwood and cedar contain natural water-soluble colorings or extractives that tend to "bleed" or migrate to the surface. If extractive bleeding occurs, allow the coating to dry completely, then wash with a mild detergent solution and rinse with clear water.

## APPLICATION INFORMATION

Stir thoroughly and often during use. When using more than one can of the same color, intermix to ensure color uniformity. USE WITH ADEQUATE VENTILATION. KEEP OUT OF REACH OF CHILDREN. Read all label and Safety Data Sheet (SDS) information prior to use. SDS are available through our web site or by calling 1-800-441-9695.

**Application Equipment:** Apply to a small area and allow stain to dry to ensure acceptable appearance and penetration. Apply one coat with a high-quality brush, paint/stain pad, or with spray equipment for a semi-transparent hiding effect. When applying by roller or spray, always back-brush for best results. To help avoid lap marks, apply to only a few boards at a time, and maintain a wet edge. Apply a second coat between 2 to 72 hours after first coat for a solid color hiding effect. After staining of picnic tables, benches, or indoor and outdoor furniture, topcoat with a high-quality gloss varnish to prevent staining of clothing.

**Airless Spray:** Pressure 1500-2000 psi, tip 0.009" - 0.013". Spray equipment must be handled with due care and in accordance with manufacturer's recommendation. High-pressure injection of coatings into the skin by airless equipment may cause serious injury.

**Brush:** Nylon/Polyester Brush

**Roller:** 3/8" - 3/4" nap roller cover

**Thinning:** Do not thin.

### Permissible temperatures during application:

Material: 50 to 90°F      10 to 32°C      Ambient: 50 to 100°F      10 to 38°C      Substrate: 50 to 100°F      10 to 38°C

## PRECAUTIONS

**WARNING! HARMFUL IF INHALED. HARMFUL IF SWALLOWED.** Sanding and grinding dusts may be harmful if inhaled. Do not breathe vapor or mist. Do not swallow. Keep container tightly closed and sealed until ready for use. Wash thoroughly after handling. Provide fresh air ventilation during and after application and drying. Avoid the inhalation of dust, particulates, spray or mist arising from the application of this preparation. Use personal protective equipment as required.

**Note: These warnings encompass the product series. Prior to use, read and follow product-specific SDS and label information. FIRST AID:** If swallowed, rinse mouth with water (only if the person is conscious). Call physician immediately. Do not induce vomiting unless directed to do so by medical personnel. If in eyes, rinse with water for 15 minutes. Check for and remove any contact lenses. If on skin, rinse well with water. Wash with soap and water. Get medical attention if irritation develops. If inhaled, remove to fresh air. Call physician immediately. Contains isothiazolinones. May cause allergic reaction. Keep out of the reach of children. For workplace use, an SDS is available from your retailer or by calling (412) 492 5555. EMERGENCY SPILL INFORMATION: (412) 434-4515 (U.S.).

© 2022 PPG Industries, Inc. All Rights Reserved. The PPG Logo is a registered trademark of PPG Industries Ohio, Inc. Quick Cover, Olympic, and Olympic & Design are registered trademarks of PPG Architectural Finishes, Inc.

PPG Architectural Finishes, Inc. believes the technical data presented is currently accurate; however, no guarantee of accuracy, comprehensiveness, or performance is given or implied. Improvements in coatings technology may cause future technical data to vary from what is in this bulletin. For complete, up-to-date technical information, visit our web site or call 1-800-441-9695.



PPG Architectural Finishes, Inc.  
One PPG Place  
Pittsburgh, PA 15272  
[www.olympic.com](http://www.olympic.com)

Technical Services  
1-800-441-9695

Architect/Specifier  
1-888-PPG-IDEA

PPG Architectural Coatings Canada Inc.  
1550 rue Ampère, Suite 500  
Boucherville (Quebec) J4B 7L4

1300CS - 10/2022