



Architectural Coatings

GENERAL DESCRIPTION

Glidden Max-Flex Exterior Fabric is an exterior paint + primer* spray paint with a revolutionary technology that provides maximized UV protection for exterior fabrics like vinyl, leather, rugs and other exterior fabrics. This product dries within 5 minutes and preserves the original look and feel.

*Multiple coats may be required. See COVERAGE for details.

RECOMMENDED SUBSTRATES

Canvas	Leather
Rugs	Vinyl

FEATURES / BENEFITS

Use on Vinyl, Leather, Rugs & More
Preserves Original Look & Feel
Maximized UV Protection
Dries Within 5 Minutes
Exterior Paint + Primer

PRODUCT INFORMATION

GMF2014	Cavalry
GMF2017	Elemental
GMF2031	Only Oatmeal
GMF2032	Onyx
GMF2033	Romantic Isle
GMF2034	Rum Punch
GMF2035	Suddenly Sapphire
GMF2036	Black

PACKAGING

Aerosol Net Wt. 12 oz. (340 g)

GLIDDEN MAX-FLEX®

GMF20XX Series

Glidden Max-Flex Exterior Fabric Exterior Paint + Primer

PRODUCT DATA

PRODUCT TYPE:	Lacquer
SHEEN:	Satin, 3-16 @ 60°
VOLUME SOLIDS*:	6% +/- 2%
WEIGHT SOLIDS*:	12% +/- 2%
WEIGHT/GALLON*:	6.4 lbs. (2.9 kg) +/- 0.2 lbs. (91 g)
MAX PWMIR*:	< 1.45

*Product data calculated from GMF2031.

COVERAGE: One can covers approximately 25 sq. ft. (2.3 sq. meters). Coverage figures do not include material loss due to surface irregularities and porosity, or material loss due to application method. Some surfaces including uncoated substrates, repaired surfaces, porous surfaces, stained areas, and drastic color changes may require multiple coats to achieve a uniform finish and complete hide.

DRYING TIME: Dry time @ 70°F (21°C); 50% relative humidity.

To Touch:	5 minutes
To Recoat:	5-10 minutes
Put In Use:	24-48 hours

Drying times listed may vary depending on temperature, humidity, film build, and air movement. Heavier application may take longer.

CLOGGING: If valve clogs, twist and pull off spray tip and rinse in a solvent, such as mineral spirits. Do not stick a pin or other objects in the stem.

CLEANUP: When finished spraying, hold can upside down and spray until clear gas appears, then wipe off tip before storing. Clean up wet paint with mineral spirits or paint thinner.

DISPOSAL: Contact your local environmental regulatory agency for guidance on disposal of empty can. Do not burn or place in home trash compactor.

FLASH POINT: -139°F (-95°C)

LIMITATIONS OF USE

Use outdoors or in a well-ventilated area, such as an open garage. Cover surrounding area to protect from overspray. Apply when no precipitation is expected for 24 hours, and when temperature is 50°F (10°C) to 90°F (32°C) and will remain above 50°F (10°C) for the next 24 hours. Avoid spraying in windy, dusty conditions.

GENERAL SURFACE PREPARATION

Surface must be clean and dry. Remove all loose, peeling paint, dirt, grease, and any other surface contaminants. Putty all nail holes and caulk all cracks and open seams. Sand all glossy, rough, and patched surfaces. .

WARNING! If you scrape, sand, or remove old paint, you may release lead dust or fumes. LEAD IS TOXIC. EXPOSURE TO LEAD DUST OR FUMES CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE. Wear a properly fitted, NIOSH-approved respirator and prevent skin contact to control lead exposure. Clean up carefully with a HEPA vacuum and a wet mop. Before you start, find out how to protect yourself and your family by contacting the USEPA National Lead Information Hotline at 1-800-424-LEAD or log on to www.epa.gov/lead. Follow these instructions to control exposure to other hazardous substances that may be released during surface preparation.

Note: Many manufacturers of fabric and rugs apply stain and water repellants to these surfaces. These repellants can affect adhesion of the paint to the surface. Always test by dripping some water onto the surface; if it "beads up", this indicates that there is a coating on the surface that may inhibit adhesion. If it soaks in, then spraying should be fine.

CANVAS: The surface must be cleaned thoroughly to remove any dust, dirt, and surface contaminants, and then painted.

RUGS: After each spray pass on a rug, before it dries, brush it with a bristle brush to get deep into the fibers to disperse the paint and remove excess. When following this method, rugs will dry with a soft texture and virtually no change from its original feel.

LEATHER: The surface must be cleaned thoroughly to remove any dust, dirt, and surface contaminants, and then painted.

VINYL: The surface must be cleaned thoroughly to remove any dust, dirt, and surface contaminants, and then painted. Exterior vinyl and similar plastic composites should not be painted with a color darker than the original color. Painting exterior vinyl or plastic composites with a darker color may cause them to warp.

APPLICATION INFORMATION

Shake can vigorously for 1 to 2 minutes and often during use. Hold can upright 6" to 10" (15 to 25 cm) from the surface and spray in a steady back-and-forth motion, slightly overlapping each stroke. Maintain the can the same distance from the surface. Keep the can in motion while spraying. Apply light coats over the entire surface until hiding is achieved, allowing 5 to 10 minutes between coats. Do not saturate surface.

Permissible temperatures during application:

Material: 50 to 90°F (10 to 32°C)

Ambient: 50 to 90°F (10 to 32°C)

Substrate: 50 to 90°F (10 to 32°C)

PRECAUTIONS

DANGER! AEROSOLS EXTREMELY FLAMMABLE. MAY CAUSE FLASH FIRE. CONTENTS UNDER PRESSURE. VAPOR HARMFUL. HARMFUL IF ABSORBED THROUGH SKIN. HARMFUL OR FATAL IF SWALLOWED. CAUSES RESPIRATORY TRACT, EYE AND SKIN IRRITATION. Sanding and grinding dusts may be harmful if inhaled. In a fire or if heated, a pressure increase will occur and the container may burst or explode. Can enter lungs and cause damage. Keep away from heat, sparks and flame. Keep away from flames, such as a pilot light, and any object that sparks, such as an electric motor. Do not puncture or incinerate container. Do not expose to heat or store at temperatures above 120°F. Do not breathe vapor or mist. Do not swallow. Do not get on skin or clothing. Avoid contact with eyes. Keep container tightly closed and sealed until ready for use. Wash thoroughly after handling. Provide fresh air ventilation during and after application and drying. Avoid the inhalation of dust, particulates, spray or mist arising from the application of this preparation. Use personal protective equipment as required. **Note: These warnings encompass the product series. Prior to use, read and follow product-specific SDS and label information.** **FIRST AID:** If swallowed, rinse mouth with water (only if the person is conscious). Call physician immediately. Do not induce vomiting unless directed to do so by medical personnel. If in eyes, rinse with water for 15 minutes. Check for and remove any contact lenses. In case of contact, immediately flush skin with plenty of water while removing contaminated clothing and shoes. Get medical attention immediately. If inhaled, remove to fresh air. Call physician immediately. If experiencing respiratory symptoms call a POISON CENTER or doctor/physician. Keep out of the reach of children. For workplace use, an SDS is available from your retailer or by calling (412) 492-5555. **EMERGENCY SPILL INFORMATION:** (412) 434-4515 (U.S.).

© 2023 PPG Industries, Inc., All Rights Reserved. The *PPG Logo* is a registered trademark of PPG Industries Ohio, Inc. *Glidden*, the *Glidden Logo* and *Glidden Max-Flex* are registered trademarks of PPG Architectural Finishes, Inc.

PPG Architectural Finishes, Inc. believes the technical data presented is currently accurate; however, no guarantee of accuracy, comprehensiveness, or performance is given or implied. Improvements in coatings technology may cause future technical data to vary from what is in this bulletin. For complete, up-to-date technical information, visit our web site or call 1-800-441-9695.



PPG Industries, Inc.
Architectural Coatings
One PPG Place
Pittsburgh, PA 15272
www.glidden.com

Technical Services
1-800-441-9695

Architect/Specifier
1-888-PPG-IDEA

PPG Architectural Coatings Canada Inc.
1550 rue Ampère, Suite 500
Boucherville (Quebec) J4B 7L4

GMF20XX - 5/2023