



# CEILING PAINT

GPL-0000

Architectural Coatings

Interior Ceiling Paint Flat

## GENERAL DESCRIPTION

Ceiling Paint is a spatter-resistant low-VOC vinyl-acrylic latex designed to meet the maintenance needs of residential repainters, remodelers, commercial contractors, facility and property managers. The great hide and coverage of this white ceiling paint helps mask minor surface imperfections and dries quickly to a smooth and clean finish. For interior use on new and previously painted wood, drywall and plaster.

## RECOMMENDED SUBSTRATES

Drywall  
Plaster  
Wood

## CONFORMANCE STANDARDS

VOC compliant in all regulated areas  
Can help earn LEED® 2009 credits

## APPLICATION INFORMATION

Mix thoroughly before use. Apply at package consistency. Apply with a quality 1/4" - 3/8" nap roller or nylon polyester brush. An extension pole is recommended for making longer strokes; making it easier to maintain a wet-edge. To reduce lap marks and ensure that you do not miss any areas, try to keep the light source at your back and start by painting away from the window. If there is more than one window, choose the largest window. USE WITH ADEQUATE VENTILATION. KEEP OUT OF REACH OF CHILDREN. Read all label and Material Safety Data Sheet (MSDS) information prior to use. MSDS are available through our website or by calling 1-800-454-3336.

**Application Equipment:** Apply with a high quality roller or brush.

**Brush:** Polyester/Nylon Brush

**Roller:** 1/4"- 3/8" nap roller cover

**Thinning:** Thinning is not required

### Permissible temperatures during application:

Material:	50 to 90°F	10 to 32°C
Ambient:	50 to 90°F	10 to 32°C
Substrate:	50 to 90°F	10 to 32°C

## TINTING AND BASE INFORMATION

GPL-0000 White

Tint the appropriate base with universal colorants.

## PRODUCT DATA

<b>PRODUCT TYPE:</b>	Vinyl Acrylic Resin
<b>FINISH:</b>	Flat
<b>SHEEN:</b>	Gloss: 2.5 - 6.5 units @ 85°
<b>VOLUME SOLIDS:</b>	15% +/- 1%
<b>WEIGHT SOLIDS:</b>	27% +/- 1%
<b>VOC:</b>	<50 g/L (0.4 lbs./gal.)
<b>WEIGHT/GALLON:</b>	9.71 lbs. (1.16 kg/L)

**PRACTICAL COVERAGE:** Apply at 200 - 300 sq. ft./gal. (5- 7 sq. m/L). Actual coverage may vary depending on surface texture, porosity, and application method.

<b>Wet Film Thickness:</b>	5.3 - 8.0 mils
<b>Wet Microns:</b>	134 - 203
<b>Dry Film Thickness:</b>	0.8 - 1.2 mils
<b>Dry Microns:</b>	20 - 30

Coverage figures do not include loss due to surface irregularities and porosity or material loss due to application method or mixing.

**DRYING TIME:** Dry time @ 77°F (25°C); 50% relative humidity

<b>To Touch:</b>	30 - 60 minutes
<b>To Recoat:</b>	2 - 4 hours

Drying times listed may vary depending on temperature, humidity, film build, color, and air movement.

**CLEANUP:** Clean hands and tools immediately with warm, soapy water. Clean spills right away with a damp cloth.

**WASHING INSTRUCTIONS:** After 30 days or when paint has fully cured, areas may be washed using a non-abrasive, mild detergent solution and cellulose sponge.

**DISPOSAL:** Contact your local environmental regulatory agency for guidance on disposal of unused product. Do not pour down a drain or storm sewer.

**FLASH POINT:** Over 200°F (93°C)

## FEATURES / BENEFITS

### Features

Less than 50 g/L VOC  
Low odor  
Good coverage  
Uniform flat finish  
Applies easily  
Spatter resistant  
Can help earn LEED 2009 credits

### Benefits

Meets the most stringent VOC regulations nationwide  
Ideal for painting in occupied spaces  
Hides minor surface imperfections  
Reduces glares and dries evenly  
User friendly application  
Results in less cleanup  
Contributes to sustainable design

## GENERAL SURFACE PREPARATION

Surfaces to be coated must be dry, clean, sound, and free from all contamination including loose and peeling paint, dirt, grease, oil, wax, concrete curing agents and bond breakers, chalk, efflorescence, mildew, rust, product fines, and dust. Remove loose paint, chalk, and efflorescence by wire brushing, scraping, sanding, and/or pressure washing. Putty all nail holes and caulk all cracks and open seams. Sand all glossy, rough, and patched surfaces. Feather back all rough edges to sound surface by sanding.

**WARNING!** If you scrape, sand, or remove old paint, you may release lead dust or fumes. LEAD IS TOXIC. EXPOSURE TO LEAD DUST OR FUMES CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE. Wear a properly fitted NIOSH-approved respirator and prevent skin contact to control lead exposure. Clean up carefully with a HEPA vacuum and a wet mop. Before you start, find out how to protect yourself and your family by contacting the USEPA National Lead Information Hotline at 1-800-424-LEAD or log on to [www.epa.gov/lead](http://www.epa.gov/lead). In Canada contact a regional Health Canada office. Follow these instructions to control exposure to other hazardous substances that may be released during surface preparation.

### NEW SURFACES:

**Drywall:** Joint compound must dry for two days before priming. Prime with the appropriate latex drywall primer.

**Wood:** Set nails, fill with latex spackle. Sand smooth. Dust clean. Prime with appropriate latex wood primer.

**Concrete, Plaster and Masonry:** Cure at least 30 days before painting. pH must be 10.0 or lower. Roughen slick poured or precast concrete and remove sealers by chemical cleaning or abrasive method such as sandsweeping. Rinse thoroughly with water and allow to dry. Must be internally dry. Remove loose aggregate. Prime with the appropriate latex bonding primer for concrete. Fill concrete block with a latex block filler. Prime plaster with the appropriate latex primer for plaster.

**PREVIOUSLY PAINTED SURFACES:** Wash to remove contaminants. Rinse thoroughly with water and allow to dry. Dull glossy areas by light sanding. Remove sanding dust. Remove loose paint. Prime bare areas with primer specified under **NEW SURFACES**.

## LIMITATIONS OF USE

Apply when air and surface temperatures are between 50°F (10°C) and 90°F (32°C). Do not apply when the surface or air temperature is below 50°F (10°C).

PROTECT FROM FREEZING.

## PACKAGING

1-Gallon (3.78 L)  
5-Gallon (18.9 L)

## PRECAUTIONS

**WARNING!** CAUSES EYE, SKIN AND RESPIRATORY TRACT IRRITATION. MAY BE HARMFUL IF SWALLOWED. USE ONLY WITH ADEQUATE VENTILATION. KEEP OUT OF THE REACH OF CHILDREN. For emergency information call (800) 545-2643. Note: These warnings encompass the product series. Prior to use, read and follow product-specific MSDS and label information. If sanding, wear a dust mask to avoid breathing of sanding dust. Do not breathe vapors or spray mist. Ensure fresh air entry during application and drying. Avoid contact with eyes and skin. If you experience eye watering, headaches, or dizziness, leave the area. If properly used, a respirator may offer additional protection. Obtain professional advice before using. Close container after each use. **FIRST AID:** For skin contact, wash thoroughly with soap and water. If any product remains, gently rub with petroleum jelly, vegetable or mineral/baby oil then wash again with soap and water. Repeat as needed. Remove contaminated clothing. For eye contact, flush immediately with plenty of water for at least 15 minutes. Get medical attention. If swallowed, get medical attention immediately. If inhalation causes discomfort, remove to fresh air. If discomfort persists or breathing difficulty occurs, get medical attention. **KEEP FROM FREEZING.** DS26-0306

Glidden Professional, the Glidden Professional Logo is a registered trademark of the PPG Group of Companies. The PPG logo is a registered trademark of PPG Industries Ohio, Inc. LEED is a registered trademark of the US Green Building Council.

PPG Architectural Finishes, Inc. believes the technical data presented is currently accurate; however, no guarantee of accuracy, comprehensiveness, or performance is given or implied. Improvements in coatings technology may cause future technical data to vary from what is in this bulletin. For complete, up-to-date technical information, visit our web site or call 1-800-454-3336.



PPG Architectural Coatings  
One PPG Place  
Pittsburgh, PA 15272  
[www.gliddenprofessional.com/THD](http://www.gliddenprofessional.com/THD)

Technical Services  
1-800-454-3336

A2.43 4/2014

Made in the  
**USA**