



Architectural Coatings

PORCH & FLOOR ANTI-SKID

PF6010 Series

Glidden Interior/Exterior Texture Paint Satin

GENERAL DESCRIPTION

Glidden Porch & Floor Anti-Skid, interior/exterior texture paint helps you create a beautiful, lasting look on porches, patios and pool decks. COOL SURFACE TECHNOLOGY™ limits surface temperature when compared to products of a similar color. It does not require a primer for easy application. It is highly durable and scratch resistant.

RECOMMENDED SUBSTRATES

Concrete	Incidental Ferrous Metal
Concrete Pavers	Wood

FEATURES / BENEFITS

Cool Surface Technology - Limits Surface Temperature By Up To 20%*

For Use On Porches, Patios & Pool Decks
No Primer Needed
Highly Durable
Scratch Resistant

*Limits hot weather surface temperature spikes of pedestrian and vehicular horizontal concrete surfaces when compared to products of similar color without *Cool Surface Technology*. Temperature containment may differ due to color, ambient temperature, direct sunlight, and time of day.

CONFORMANCE STANDARDS

VOC compliant in all regulated areas.
ANSI 326.3 wet Dynamic Coefficient of Friction of 0.77

TINTING AND BASE INFORMATION

PF6010	Pure White (Base 1)
PF6050	Base 2 (Must Be Tinted)*

*Must be tinted before use.

This product can be tinted into 26 unique colors that utilize *Cool Surface Technology*. Colors from the Cool-Surface color pallet will reduce the surface temperature of the coating when compared to both bare concrete and similar colors not utilizing surface-cooling technology.

Refer to the appropriate color formula book, automatic tinting equipment, and or computer color matching system for color formulas and tinting instructions.

PRODUCT DATA

PRODUCT TYPE:	100% Acrylic Latex
SHEEN*:	Satin, 2-12 @ 85°
VOLUME SOLIDS*:	48% +/- 2%
WEIGHT SOLIDS*:	63% +/- 2%
WEIGHT/GALLON*:	11.8 lbs. (5.4 kg) +/- 0.2 lbs. (91 g)
VOC:	< 50 g/L (0.4 lbs./gal.)

*Product data calculated on product PF6010.

COVERAGE: Approximately 150 to 300 sq. ft. (14 to 28 sq. meters) per U.S. gallon (3.78 L) on primed, smooth, nonporous surfaces.

Wet Film Thickness:	5.4 to 10.7 mils
Wet Microns:	137 to 272
Dry Film Thickness:	2.6 to 5.1 mils
Dry Microns:	66 to 130

Coverage figures do not include loss due to surface irregularities and porosity, or material loss due to application method or mixing. Some colors, drastic color changes, or porous surfaces may require additional coats to achieve a uniform finish.

DRYING TIME: Dry time @ 77°F (25°C); 50% relative humidity.

To Touch:	1 hours
To Recoat:	4 hours
To Service:	24 hours

Drying times listed may vary depending on temperature, humidity, film build, color, and air movement. Wait at least 30 days after painting before cleaning the surface with a non-abrasive, mild cleanser.

CLEANUP: Clean tools with warm, soapy water.

DISPOSAL: Contact your local environmental regulatory agency for guidance on disposal of unused product. Do not pour down a drain or storm sewer.

FLASH POINT: > 200°F (93°C)

PACKAGING

1-Gallon (3.78 L)

GENERAL SURFACE PREPARATION

Surface must be clean and dry. Remove all loose, peeling paint, dirt, mildew, grease, oil, chalk, rust, and any other surface contaminants. Blistering and peeling issues are commonly caused by moisture behind the paint film. Problems leading to excessive moisture in the substrate must be repaired prior to painting. Putty all nail holes and caulk all cracks and open seams. Sand all glossy, rough, and patched surfaces. New concrete should age a minimum of 30 days. Etching with acid is usually not required, but is recommended for optimum performance over smoothly troweled or new concrete. If acid etching, follow manufacturer's recommendations. This product is self-priming in most applications. When applied to an uncoated substrate or to bare wood, two coats are required with the first coat acting as the primer. Prime incidental metal surfaces with a metal primer.

WARNING! If you scrape, sand, or remove old paint, you may release lead dust or fumes. LEAD IS TOXIC. EXPOSURE TO LEAD DUST OR FUMES CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE. Wear a properly fitted, NIOSH-approved respirator and prevent skin contact to control lead exposure. Clean up carefully with a HEPA vacuum and a wet mop. Before you start, find out how to protect yourself and your family by contacting the USEPA National Lead Information Hotline at 1-800-424-LEAD or log on to www.epa.gov/lead. Follow these instructions to control exposure to other hazardous substances that may be released during surface preparation.

CONCRETE: New concrete should cure for at least 30 days and preferably 90 days prior to painting. The pH of the substrate must be less than 10 before painting.

CONCRETE PAVERS: Remove loose aggregate. Clean, rinse thoroughly with water and allow to dry before painting

INCIDENTAL FERROUS METAL: The surface must be cleaned thoroughly to remove any dust, rust, and surface contaminants, and then primed with a metal primer.

WOOD: Countersink all nails, putty flush with surface. Unpainted wood or wood in poor condition should be sanded smooth, wiped clean. Any knots or resinous areas must be primed before painting.

LIMITATIONS OF USE

Apply when air, product, and surface temperatures are above 50°F (10°C) and surface temperature is at least 5°F (3°C) above the dew point. Air and surface temperatures must remain above 50°F (10°C) for the next 24 hours. Avoid exterior application late in the day when dew and condensation is likely to form or if rain is expected. Keep standing water off of painted surface for a minimum of one week.

Application of this product will improve the safety of pedestrian trafficable surfaces by increasing the coefficient of friction of surface. However, given the light texture provided by the coating, surfaces may remain slippery when wet. **Please use caution.** Application methods and guidelines must be followed precisely in order to achieve the intended coefficient of friction.

Do not use a roller with a nap that is smaller than 3/8" (9.5 mm), effectiveness of anti-slip properties will diminish. Avoid excessive brushing and/or rolling, as this will decrease the coefficient of friction and diminish the effectiveness of the coating's anti-slip properties. Do not back-roll or back-brush this product.

Do not use on surfaces that are frequently damp. Not recommended for use on garage floors or carports that are subject to tire traffic. Not suitable for application on composite decking surfaces.

PROTECT FROM FREEZING.

APPLICATION INFORMATION

Stir thoroughly before and often during use to ensure proper distribution of the anti-skid texture in the finished coating. When using more than one can of the same color, intermix to ensure color uniformity. USE WITH ADEQUATE VENTILATION. KEEP OUT OF REACH OF CHILDREN. Read all label and Safety Data Sheet (SDS) information prior to use. SDS are available through our web site or by calling 1-800-441-9695.

Application Equipment: Apply with a high-quality brush, roller, or by texture spray equipment. Do not use a roller with a nap that is smaller than 3/8" (9.5 mm), effectiveness of anti-slip properties will diminish. Where necessary, apply a second coat and allow each coat to dry thoroughly before applying the next coat. Avoid excessive brushing and/or rolling, as this will decrease the coefficient of friction and diminish the effectiveness of the coating's anti-slip properties. Do not back-roll or back-brush this product.

Texture Spray: Graco TexSpray RTX5000px (or similar equipment): Use #4 nozzle and #4 WideTex spray disk to achieve proper coverage and fan pattern. Full air to the gun. If a "tighter" fan pattern is desired, additional compressed air (user supplied) can be added using the on-board air manifold. Fluid flow setting on the pump set to the "first dot" on the indicator gauge. This can be increased slightly, if necessary for wider, open substrates. Crosshatching with two passes is recommended to achieve full substrate coverage.

Brush: High-quality, Nylon/Polyester brush

Roller: 3/8" - 1" nap roller cover

Thinning: Do not thin.

Permissible temperatures during application:

Material: 50 to 90°F 10 to 32°C

Ambient: 50 to 90°F 10 to 32°C

Substrate: 50 to 90°F 10 to 32°C

PRECAUTIONS

WARNING! HARMFUL IF INHALED. Sanding and grinding dusts may be harmful if inhaled. This product contains crystalline silica which can cause lung cancer or silicosis. The risk of cancer depends on the duration and level of exposure to dust from sanding surfaces or mist from spray applications. Do not breathe vapor or mist. Do not swallow. Do not get on skin or clothing. Keep container tightly closed and sealed until ready for use. Wash thoroughly after handling. Provide fresh air ventilation during and after application and drying. Avoid the inhalation of dust, particulates, spray or mist arising from the application of this preparation. Use personal protective equipment as required. **Note: These warnings encompass the product series. Prior to use, read and follow product-specific SDS and label information.** **FIRST AID:** If swallowed, rinse mouth with water (only if the person is conscious). Do not induce vomiting unless directed to do so by medical personnel. If in eyes, rinse with water for 15 minutes. Check for and remove any contact lenses. If on skin, rinse well with water. Wash with soap and water. Get medical attention if irritation develops. If inhaled, remove to fresh air. Call physician immediately. CONTAINS: water (7732-18-5), Limestone (1317-65-3), proprietary acrylic resin (Not available), Nepheline syenite (37244-96-5), titanium dioxide (13463-67-7), crystalline silica, respirable powder (<10 microns) (14808-60-7). Contains isothiazolinones. May cause allergic reaction. Keep out of the reach of children. For workplace use, an SDS is available from your retailer or by calling (412) 492-5555. EMERGENCY SPILL INFORMATION: (412) 434-4515 (U.S.). WARNING: Cancer - www.P65Warnings.ca.gov.

© 2022 PPG Industries, Inc., All Rights Reserved. The *PPG Logo* is a registered trademark of PPG Industries Ohio, Inc. *Glidden* and the *Glidden Logo* are registered trademarks and *Cool Surface Technology* is a trademark of PPG Architectural Finishes, Inc.

PPG Architectural Finishes, Inc. believes the technical data presented is currently accurate; however, no guarantee of accuracy, comprehensiveness, or performance is given or implied. Improvements in coatings technology may cause future technical data to vary from what is in this bulletin. For complete, up-to-date technical information, visit our web site or call 1-800-441-9695.



PPG Industries, Inc.
Architectural Coatings
One PPG Place
Pittsburgh, PA 15272
www.glidden.com

Technical Services
1-800-441-9695

Architect/Specifier
1-888-PPG-IDEA

PPG Architectural Coatings Canada Inc.
1550 rue Ampère, Suite 500
Boucherville (Quebec) J4B 7L4

PF6010 - 9/2022