



Texture Touch Up 2 Textures In 1 Orange Peel/Knockdown

GENERAL DESCRIPTION

HOMAX® Orange Peel/Knockdown Water-Based Texture Touch Up is a clog resistant, low-odor, water-based formulation of our most popular "orange peel" and "knockdown" textures for textured drywall repair. Variations in orange peel texture (also called splatter or eggshell) help hide surface imperfections, while reflecting light and adding interest to a room. Our water-based formula excels at replicating orange peel and knockdown texture patterns so you can get professional results fast. Great for patching and texturing small rooms and accent walls.

RECOMMENDED SUBSTRATES

Gypsum Wallboard-Drywall

PRODUCT INFORMATION

HMX04081

Water Based

PACKAGING

8.1 oz. (230 g) Spray Can

PRODUCT DATA

PRODUCT TYPE: Water Based
SHEEN: Flat
VOLUME SOLIDS: 37% +/- 2%
WEIGHT SOLIDS: 48% +/- 2%
WEIGHT/GALLON: 9.1 lbs. (4.1 kg) +/- 0.2 lbs. (91 g)
MAX PWMIR FCP: < 0.80

COVERAGE: Can covers 20-40 sq. ft. (2.8-4.6 m²)

DRYING TIME: Texture turns WHITE when dry (1-2 hours). Allow to dry 60 minutes before painting. Heavier textures, cool temperatures, poor ventilation, and high humidity may increase dry time.

CLEANUP: Warm water.

DISPOSAL: Contact your local environmental regulatory agency for guidance on disposal of unused product.

FLASH POINT: -44°F (-42°C)

LIMITATIONS OF USE

FOR INTERIOR USE.

FEATURES / BENEFITS**FEATURES**

Clog-Resistant Formula

Touch-Up Size

Adjustable Texture Control

2 Textures in 1

Lightweight

Low Odor

Easy Cleanup

BENEFITS

Consistent, reliable application means fewer maintenance interruptions and less headaches

Perfect for small and quick projects

Easily adjust the texture to match fine to heavy splatters and knock downs

Dual-texture functionality streamlines application by providing a single product that achieves both Orange Peel & Knockdown textures.

Easy to Shake

Minimizes unpleasant smells and enables a quicker turnaround of your project

Washable with water

Read Label and Safety Data Sheet prior to use. See other cautions on last page.

Texture Touch Up 2 Textures In 1 Orange Peel/Knockdown

PREPARATION

READ AND FOLLOW ALL WARNINGS AND PRECAUTIONS. KEEP OUT OF REACH OF CHILDREN. VENTILATE AREA WELL. Protect surrounding area from overspray. Do not spray on clothing, furniture, or carpet. Make necessary drywall repairs before applying. WEAR EYE PROTECTION.

WARNING! If you scrape, sand, or remove old paint, you may release lead dust or fumes. LEAD IS TOXIC. EXPOSURE TO LEAD DUST OR FUMES CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE. Wear a properly fitted, NIOSH-approved respirator and prevent skin contact to control lead exposure. Clean up carefully with a HEPA vacuum and a wet mop. Before you start, find out how to protect yourself and your family by contacting the USEPA National Lead Information Hotline at 1-800-424-LEAD or log on to www.epa.gov/lead. Follow these instructions to control exposure to other hazardous substances that may be released during surface preparation.

DIRECTIONS FOR USE

Prime/Seal surface. **CAN MUST BE 72°F-90°F (22°C-32°C)**. If needed, warm under tap water.

- 1. SHAKE CAN** vigorously **1 MINUTE** after ball begins to rattle.
- 2. TURN** nozzle-lever $\frac{1}{4}$ -turn to right. Pull off red cap. Spray inverted 2 seconds into garbage/box.
- 3. PRACTICE ON SCRAP DRYWALL.** Spray 18-24" (46-61 cm) from surface. Turn nozzle-lever to adjust splatter size as needed.
- 4. SPRAY A LIGHT COAT** with 70% coverage, leaving space between splatters. **DO NOT FULLY COVER SURFACE.** As pressure drops, re-shake for 10 seconds. May be scraped off and reapplied if desired.
- 5. AFTER SPRAYING**, invert and spray 3 seconds to clear nozzle, replace cap. Store in dry, climate-controlled area.

FOR KNOCKDOWN, allow 2-3 minutes, depending on temperature and humidity, to set and draw knife lightly over texture (see video).

PAINT: Apply 2 coats or more for complete hide and to match gloss (follow paint manufacturer's directions).

PRECAUTIONS

For warning information, please refer to the product label and SDS available at the online listing for this product at www.pittsburghpaintsco.com. Keep container tightly closed and sealed until ready for use. SDS, spill, and emergency information are available by calling 1-833-477-1553.

© 2025 The Pittsburgh Paints Co. All Rights Reserved. Homax and the Homax House Design are registered trademarks of A-Paint Specialty, Inc.

The Pittsburgh Paints Co. believes the technical data presented is currently accurate; however, no guarantee of accuracy, comprehensiveness, or performance is given or implied. Improvements in coatings technology may cause future technical data to vary from what is in this bulletin. For complete, up-to-date technical information, call 1-800-441-9695.



**PITTSBURGH
PAINTS CO.**

The Pittsburgh Paints Co.
400 Bertha Lamme Drive
Cranberry Township, PA 16066
www.homaxproducts.com

Technical Services
1-800-441-9695

4081 - 12/2025