

**PRO GRADE® Wall & Ceiling Texture 2in1 Orange Peel/Knockdown****GENERAL DESCRIPTION**

Homax Pro Grade Wall & Ceiling Texture provides portable and convenient delivery of a full range of Orange Peel & Knockdown texture patterns that **DELIVERS AN INVISIBLE REPAIR®**. This time-saving, professional tool makes textured wall & ceiling repairs a faster and easier alternative to a hopper gun.

RECOMMENDED SUBSTRATES

Gypsum Wallboard-Drywall

PRODUCT INFORMATION

4560

Water Based

PACKAGING

16 oz. (454 g) Spray Can

PRODUCT DATA

PRODUCT TYPE: Water Based
SHEEN: Flat
VOLUME SOLIDS: 37% +/- 2%
WEIGHT SOLIDS: 48% +/- 2%
WEIGHT/GALLON: 9.1 lbs. (4.1 kg) +/- 0.2 lbs. (91 g)
MAX PWMIR FCP: < 0.80

COVERAGE: Up to 100 sq. ft. for fine, 75 sq. ft. for medium, and 50 sq. ft. for heavy textures.

DRYING TIME: Allow to dry 60 minutes before painting. Heavier textures, cool temperatures, poor ventilation, and high humidity may increase dry time. Texture lightens in color when dry.

CLEANUP: Warm water.

DISPOSAL: Contact your local environmental regulatory agency for guidance on disposal of unused product.

FLASH POINT: -44°F (-42°C)

LIMITATIONS OF USE

FOR INTERIOR USE.

FEATURES / BENEFITS**FEATURES**

Delivers an Invisible Repair®

2in1 Wall/Ceiling Texture

Clog-Resistant Formula

Lightweight, Same Great Coverage

Ergonomic Grip

Low Odor

BENEFITS

Seamlessly match existing interior orange peel & knockdown textures

Dual-purpose functionality streamlines application by providing a single product that works seamlessly on both walls & ceilings

Consistent, reliable application means fewer maintenance interruptions and less headaches

Up to 100 Sq. Ft. of Coverage

Reduces fatigue and enhances comfort and control by allowing for a more natural hand position

Minimizes unpleasant smells and enables a quicker turnaround of your project

Read Label and Safety Data Sheet prior to use. See other cautions on last page.

Pro Grade Wall & Ceiling Texture 2in1 Orange Peel/Knockdown

PREPARATION

READ AND FOLLOW ALL WARNINGS AND PRECAUTIONS. KEEP OUT OF REACH OF CHILDREN. VENTILATE AREA WELL. Protect surrounding area from overspray. Do not spray on clothing, furniture, or carpet. Make necessary drywall repairs before applying. WEAR EYE PROTECTION.

WARNING! If you scrape, sand, or remove old paint, you may release lead dust or fumes. LEAD IS TOXIC. EXPOSURE TO LEAD DUST OR FUMES CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE. Wear a properly fitted, NIOSH-approved respirator and prevent skin contact to control lead exposure. Clean up carefully with a HEPA vacuum and a wet mop. Before you start, find out how to protect yourself and your family by contacting the USEPA National Lead Information Hotline at 1-800-424-LEAD or log on to www.epa.gov/lead. Follow these instructions to control exposure to other hazardous substances that may be released during surface preparation.

DIRECTIONS FOR USE

Spot prime repair before texture application. Humidity is best at < 50% RH.

- (1) **ENSURE CAN** is 70°-80°F (21°-27°C) for best results. Run can under warm water to bring to proper temperature.
- (2) **SHAKE CAN VIGOROUSLY** upside down ONE MINUTE after ball starts to rattle. During use, occasionally stop and re-shake for several seconds to maintain pressure.
- (3) **ADJUST PATTERN:** Pointing nozzle away from face, tighten YELLOW spray tip to right for fine texture, loosen spray tip to left for heavy texture.
- (4) **UNLOCK:** Slide RED switch to unlock trigger. Spray upside down briefly into trash can to flush nozzle.
- (5) **SPRAY DISTANCE:** 12" to 20" (30 cm to 51 cm) from surface. Practice spraying on cardboard – adjusting pattern to match existing wall texture.
- (6) **FOR ORANGE PEEL:** Spray with rapid circular motion. Cover surface 50-80% with splatter.
- (7) **FOR KNOCKDOWN:** Practice technique on scrap drywall. Cover surface 40-50% with medium to heavy splatter. For heavier/bolder look, apply with more coverage. Note: Texture appearance will improve dramatically after knocked down. **ALLOW TEXTURE TO SET 2-4 MINUTES before LIGHTLY KNOCKING DOWN OR FLATTENING** using a 6" (15 cm) or larger wet drywall knife. For best results, hold knife lightly with no pressure on blade. If drag marks appear, shorten set time. Texture can be scraped off and reapplied when wet, until desired pattern is achieved.
- (8) **CLEAR NOZZLE** after use and during breaks; turn can upside down, spray until texture stops spraying from nozzle. Release trigger. **LOCK:** Hold can body, slide RED switch to lock position. Test to ensure lock is properly engaged.

PAINT: Apply 2 coats or more for complete hide and to match gloss (follow paint manufacturer's instructions).

PRECAUTIONS

For warning information, please refer to the product label and SDS available at the online listing for this product at www.pittsburghpaintsco.com. Keep container tightly closed and sealed until ready for use. SDS, spill, and emergency information are available by calling 1-833-477-1553.

© 2025 The Pittsburgh Paints Co. All Rights Reserved. The P Logo & Pittsburgh Paints, Homax & House Design, Delivers an Invisible Repair, and Pro Grade are registered trademarks of The Pittsburgh Paints Co.

The Pittsburgh Paints Co. believes the technical data presented is currently accurate; however, no guarantee of accuracy, comprehensiveness, or performance is given or implied. Improvements in coatings technology may cause future technical data to vary from what is in this bulletin. For complete, up-to-date technical information, call 1-800-441-9695.



**PITTSBURGH
PAINTS CO.**

PPG Architectural Finishes, Inc.
One PPG Place
Pittsburgh, PA 15272
www.homaxproducts.com

Technical Services
1-800-441-9695

4560 7/2025