

Architectural Coatings

Liquid Nails Tub Surround & Shower Wall Interior Construction Adhesive

GENERAL DESCRIPTION

Liquid Nails Tub Surround & Shower Wall Adhesive, LN-715, is a high-solids, VOC compliant adhesive. This unique formulation meets the requirements of all air quality regulations and will not soften or distort tub and shower surround materials. Certified by UL Environment to meet the GREENGUARD Gold Standard as a low emitting material.

RECOMMENDED SUBSTRATES

Bonds Most Plastic And Fiberglass Tub & Shower Surrounds To: Drywall, Plywood, Greenboard, Cement Board, Ceramic Tile (see tile instructions under "Directions")

FEATURES / BENEFITS

- No burn through
- Moisture, heat, steam & water resistant
- Great for plastic, fiberglass and polystyrene tub & shower units
- Color will not show through surround
- VOC compliant

CONFORMANCE STANDARDS

VOC compliant in all regulated areas



PRODUCT INFORMATION / PACKAGING

LN-715 10.0 FL OZ (295 mL) Tube (12 or 24 Tubes/Carton)

PRODUCT DATA

- BASE:** Latex
- COLOR:** White
- APPEARANCE:** Smooth paste
- APPLICATION TEMPERATURE:** 40°F to 100°F (5°C to 38°C)
- SERVICE TEMPERATURE:** -20°F to 200°F (-29°C to 93°C)
- SLUMP:** 0.15" maximum
- SHEAR STRENGTH:** 24 hours – 300 psi
7 days – 380 psi
- SHORE "A" HARDNESS:** 60
- VOLUME SHRINKAGE:** 40%
- WEIGHT PER GALLON:** 12.5 lbs. (5.54 kg)
- VISCOSITY:** 340,000 to 400,000 cps
- OPEN TIME:** 20-30 minutes at room temperature
- MINIMUM CURE TIME:** 24 hours at room temperature. Allow 5 Days to completely dry.
- FREEZE/THAW STABILITY:** Passes 5 cycles
- FLAMMABILITY:** Non-flammable
- SOLIDS:** 75%
- COVERAGE:** Approximately 30 linear ft. (9 linear meters) using a 1/4" (6 mm) bead. A typical surround will require approximately 3 tubes of adhesive for installation.
- SHELF LIFE:** One year from date of purchase
- ODOR:** Mild Acrylic
- MAX VOC:** < 7% by weight

LIMITATIONS OF USE

Not recommended for use under the water line or adhering to a non-porous surface. Not recommended for uses other than tub & shower surrounds.

FREEZE/THAW STABLE. Store product at 40°F (4°C) to 100°F (38°C).

GENERAL SURFACE PREPARATION/APPLICATION

WARNING! If you scrape, sand, or remove old paint, you may release lead dust or fumes. LEAD IS TOXIC. EXPOSURE TO LEAD DUST OR FUMES CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE. Wear a properly fitted, NIOSH-approved respirator and prevent skin contact to control lead exposure. Clean up carefully with a HEPA vacuum and a wet mop. Before you start, find out how to protect yourself and your family by contacting the USEPA National Lead Information Hotline at 1-800-424-LEAD or log on to www.epa.gov/lead. Follow these instructions to control exposure to other hazardous substances that may be released during surface preparation.

DIRECTIONS: Surfaces must be clean, dry, and structurally sound. Sand and roughen high-gloss paint or ceramic tile before application. Cut cartridge tip to ¼" (6 mm) bead size. Puncture inner foil seal and place cartridge into caulk gun. Apply adhesive to surround panel in a continuous bead approximately one inch from the edges of the panel. An "S" or "X" shaped bead may be applied to the center portion of the panel. Press the panel into place on the wall within 15 minutes of the adhesive application. For more tack, peel adhered panel from wall, wait 3 minutes, then press back into place. After 20 to 30 minutes, press firmly over all surfaces of surround. Bracing or taping may be needed if panels do not lie flat. Allow to dry 24 hours before caulking or sealing.

CLEANUP: Water for wet adhesive; mineral spirits when dry.

DISPOSAL: Contact your local environmental regulatory agency for guidance on disposal of unused product.

PERMISSIBLE TEMPERATURES DURING APPLICATION:

Material:	40 to 100°F	4 to 38°C
Ambient:	40 to 100°F	4 to 38°C
Substrate:	40 to 100°F	4 to 38°C

PRECAUTIONS

WARNING! HARMFUL IF INHALED. Sanding and grinding dusts may be harmful if inhaled. This product contains crystalline silica which can cause lung cancer or silicosis. The risk of cancer depends on the duration and level of exposure to dust from sanding surfaces. Do not breathe vapor. Do not swallow. Do not get on skin or clothing. Keep container tightly closed and sealed until ready for use. Wash thoroughly after handling. Provide fresh air ventilation during and after application and drying. Avoid the inhalation of dust or particulates arising from the application of this preparation. Use personal protective equipment as required. **FIRST AID:** If swallowed, rinse mouth with water (only if the person is conscious). Do not induce vomiting unless directed to do so by medical personnel. If in eyes, rinse with water for 15 minutes. Check for and remove any contact lenses. If on skin, rinse well with water. Wash with soap and water. Get medical attention if irritation develops. If inhaled, remove to fresh air. Call physician immediately. Keep out of the reach of children. For workplace use, an SDS is available from your retailer or by calling (412) 492-5555. **EMERGENCY SPILL INFORMATION:** (412) 434-4515 (U.S.).

© AkzoNobel, revisions © 2023 PPG Industries, Inc. All Rights Reserved. The PPG Logo is a registered trademark of PPG Industries Ohio, Inc. Liquid Nails is a registered trademark of PPG Architectural Finishes, Inc. UL Greenguard is a certification mark of UL LLC.

PPG Architectural Finishes, Inc. believes the technical data presented is currently accurate; however, no guarantee of accuracy, comprehensiveness, or performance is given or implied. Improvements in coatings technology may cause future technical data to vary from what is in this bulletin. For complete, up-to-date technical information, call 1-800-441-9695.

