



Architectural Coatings

Liquid Nails Tub Surround & Shower Wall Interior Construction Adhesive

GENERAL DESCRIPTION

Liquid Nails Tub Surround & Shower Wall Adhesive, LN-915, provides an exceptional waterproof bond under extreme conditions and won't harm most tub surrounds and shower walls. Light color won't show through surrounds. Recommended for most plastic tub and shower enclosures.

RECOMMENDED SUBSTRATES

Bonds Most Plastic* And Fiberglass Tub & Shower Surrounds To: Drywall, Plywood, Greenboard, Cement Board, Ceramic Tile (see tile instructions under "Directions")

* Recommended for polystyrene foamback tub kits when adhesive venting method described under "Directions" is followed

FEATURES / BENEFITS

No burn through
Moisture, heat, steam & water resistant
Great for plastic, fiberglass and polystyrene tub & shower units
Color will not show through surround

PRODUCT INFORMATION / PACKAGING

LN-915 10.0 FL OZ (295 mL) Tube (12 Tubes/Carton)

PRODUCT DATA

BASE: Synthetic Rubber

COLOR: Tan

APPEARANCE: Smooth paste

APPLICATION TEMPERATURE: 40°F to 100°F (5°C to 38°C)

SERVICE TEMPERATURE: -20°F to 140°F (-29°C to 60°C)

BRIDGING ABILITY: Bridges gaps up to 3/8"

SHEAR STRENGTH: Plywood to plywood
24 hours – 75 psi
48 hours - 150 psi
7 days – 275 psi

WEIGHT PER GALLON: 10.6 lbs. (4.81 kg)

VISCOSITY: 300,000 cps

OPEN TIME: 15-20 minutes at room temperature

MINIMUM CURE TIME: 24 hours at room temperature

FREEZE/THAW STABILITY: Will not freeze

FLAMMABILITY: Extremely flammable; non-flammable when dry

FLASH POINT: 1°F (-17°C)

SOLIDS: 75%

COVERAGE: 120 linear ft. (36.6 linear meters) using 1/8" (3 mm) bead. A typical surround will require approximately 1 tube of adhesive for installation.

SHELF LIFE: One year from date of purchase

ODOR: Strong Solvent

MAX VOC: < 40% by weight

LIMITATIONS OF USE

Not recommended for use under the water line or adhering to a non-porous surface. Not recommended for application of polystyrene foamback tub kits over ceramic tile. Not recommended for uses other than tub & shower surrounds.

FREEZE/THAW STABLE. Store product at 40°F (4°C) to 100°F (38°C).

GENERAL SURFACE PREPARATION/APPLICATION

WARNING! If you scrape, sand, or remove old paint, you may release lead dust or fumes. LEAD IS TOXIC. EXPOSURE TO LEAD DUST OR FUMES CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE. Wear a properly fitted, NIOSH-approved respirator and prevent skin contact to control lead exposure. Clean up carefully with a HEPA vacuum and a wet mop. Before you start, find out how to protect yourself and your family by contacting the USEPA National Lead Information Hotline at 1-800-424-LEAD or log on to www.epa.gov/lead. Follow these instructions to control exposure to other hazardous substances that may be released during surface preparation.

DIRECTIONS: Surfaces must be clean, dry, and structurally sound. Sand and roughen high-gloss paint or ceramic tile before application. Do not apply when temperatures exceed 90°F (32°C). Cut cartridge tip to 1/8" (3 mm) bead size only. Puncture inner foil seal and place cartridge into caulk gun. Important: Apply adhesive to surround panel in a continuous 1/8" (3 mm) bead approximately one inch from the edges of the panel. An "S" or "X" shaped bead may be applied to the center portion of the panel. Press the panel into place on the wall within 10 minutes of the adhesive application. For more tack, peel adhered panel from wall, wait 3 minutes, then press back into place. After 20 to 30 minutes, press firmly over all surfaces of surround. Tape to wall with masking tape and allow to dry 24 hours before caulking or sealings.

CLEANUP: Use mineral spirits or an adhesive remover. Caution: Mineral spirits or a remover may damage front of surround. To clean surround surface, soften adhesive with petroleum jelly, then wipe away with soft cloth.

DISPOSAL: Contact your local environmental regulatory agency for guidance on disposal of unused product.

PERMISSIBLE TEMPERATURES DURING APPLICATION:

Material:	40 to 100°F	4 to 38°C
Ambient:	40 to 100°F	4 to 38°C
Substrate:	40 to 100°F	4 to 38°C

PRECAUTIONS

DANGER! EXTREMELY FLAMMABLE LIQUID AND VAPOR. MAY CAUSE FLASH FIRE. HARMFUL IF INHALED. HARMFUL OR FATAL IF SWALLOWED. CAUSES RESPIRATORY TRACT IRRITATION. MAY CAUSE EYE IRRITATION. Sanding and grinding dusts may be harmful if inhaled. Inhalation of high concentrations of vapor may affect the central nervous system. Repeated exposure to high vapor concentrations may cause irritation of the respiratory system and permanent brain and nervous system damage. High vapor concentrations can cause headaches, dizziness, drowsiness and nausea and may lead to unconsciousness. This product contains crystalline silica which can cause lung cancer or silicosis. The risk of cancer depends on the duration and level of exposure to dust from sanding surfaces. Can enter lungs and cause damage. Keep away from heat, sparks and flame. Keep away from flames, such as a pilot light, and any object that sparks, such as an electric motor. Do not breathe vapor. Do not swallow. Do not get on skin or clothing. Avoid contact with eyes. Keep container tightly closed and sealed until ready for use. Wash thoroughly after handling. Provide fresh air ventilation during and after application and drying. Avoid the inhalation of dust or particulates arising from the application of this preparation. Use personal protective equipment as required. FIRST AID: If swallowed, rinse mouth with water (only if the person is conscious). Call physician immediately. Do not induce vomiting unless directed to do so by medical personnel. If in eyes, rinse with water for 15 minutes. Check for and remove any contact lenses. If on skin, rinse well with water. Wash with soap and water. Get medical attention if irritation develops. If inhaled, remove to fresh air. Call physician immediately. Keep out of the reach of children. For workplace use, an SDS is available from your retailer or by calling (412) 492-5555. EMERGENCY SPILL INFORMATION: (412) 434-4515 (U.S.).

© AkzoNobel, revisions © 2023 PPG Industries, Inc. All Rights Reserved. The PPG Logo is a registered trademark of PPG Industries Ohio, Inc. Liquid Nails is a registered trademark of PPG Architectural Finishes, Inc.

PPG Architectural Finishes, Inc. believes the technical data presented is currently accurate: however, no guarantee of accuracy, comprehensiveness, or performance is given or implied. Improvements in coatings technology may cause future technical data to vary from what is in this bulletin. For complete, up-to-date technical information, call 1-800-441-9695.



PPG Architectural Finishes, Inc.
One PPG Place
Pittsburgh, PA 15272
www.liquidnails.com

Technical Services
1-800-441-9695

Architect/Specifier
1-888-PPG-IDEA

PPG Architectural Coatings Canada Inc.
1550 rue Ampère, Suite 500
Boucherville (Quebec) J4B 7L4

LN-915 3/2023