

COVE BASE *& Stair Tread Adhesive*

CB-10

Interior

A water-resistant, latex-based construction adhesive with quick initial grab formulated to bond vinyl or rubber cove base and stair treads

PRODUCT DESCRIPTION

LIQUID NAILS[®] Cove Base & Stair Tread Adhesive, CB-10, is a water-resistant, latex-based construction adhesive. It offers quick initial grab without bracing. CB-10 is designed specifically to bond vinyl or rubber cove base and stair treads.

RECOMMENDED FOR

Bonding vinyl or rubber cove base and stair treads to:

- Drywall
- Wood
- Plaster
- Concrete and other common interior surfaces
- Paneling

NOT RECOMMENDED FOR

Uses other than cove base and stair tread installations, bonding to non-porous surfaces such as ceramics, metals, laminates, etc. Not for use on wood stair treads.

PRODUCT ADVANTAGES

- Quick initial grab
- No bracing required
- Water resistant
- Easy water clean up
- Bonds cove base and stair treads



Please research all installation instructions and read entire label and Material Safety Data Sheet for safety, health & environmental information prior to use. See other cautions on last page.



COVE BASE

& Stairs Treads Adhesive

SURFACE PREPARATION

Lay cove base strip flat for at least 24 hours prior to installation. Condition cove base and CB-10 adhesive to room temperature for 24 hours prior to installation. Do not apply at temperatures below 60°F. Surfaces must be clean and dry. One surface must be porous. Cut and pre-fit materials prior to installation.

APPLYING THE PRODUCT

Cove base: Apply two zigzag 1/4" adhesive beads to back of cove base, enough to cover 50% when applied, then press or roll firmly into place. Bonding to irregular or curved surfaces may require bracing until adhesive is set. Do not stretch cove base.

Stair treads: Apply 1/4" beads to the back of stair treads 4" apart. Be sure 60% of tread is covered with adhesive. Press tread into place.

Note: Not for use on wood stair treads

CLEAN UP

Use water for wet adhesive. Use mineral spirits or adhesive remover for dry adhesive.

DISPOSAL

Contains organic solvents which may cause adverse effects to the environment if disposed of improperly. Place **empty** containers in normal refuse for disposal. Contact your sanitation department or household hazardous waste coordinator for information concerning possible re-use or disposal of unused solvent-containing adhesives and/or sealants.

EAD-C9

LIMITED WARRANTY

PPG warrants satisfaction with this product when handled and applied according to label instructions. If product is not as warranted, PPG will, at your option, furnish replacement product or refund the purchase price. Please call 1-800-634-0015 for details. This limited warranty excludes labor or the cost of labor and is given as the exclusive warranty and remedy. **No warranty of merchantability, fitness for purpose or other warranty, express or implied, is made. PPG shall not be liable for any special, incidental or consequential damages.** Some states do not allow the exclusion or limitation of incidental or consequential damages, so the above exclusions/limitations may not apply. This limited warranty gives specific legal rights; you may have other rights that vary by state.

WARNING! HARMFUL OR FATAL IF SWALLOWED. CAUSES EYE, SKIN AND RESPIRATORY TRACT IRRITATION. USE ONLY WITH ADEQUATE VENTILATION. KEEP OUT OF THE REACH OF CHILDREN. Contains Crystalline Silica. If sanding, wear a dust mask to avoid breathing of sanding dust. Avoid contact with eyes and skin. **FIRST AID:** For skin contact, wash thoroughly with soap and water. If any product remains, gently rub with petroleum jelly, vegetable or mineral/baby oil then wash again with soap and water. Repeat as needed. Remove contaminated clothing. For eye contact, flush **immediately** with plenty of water for at least 15 minutes. **Get medical attention.** If swallowed, **get medical attention immediately.** If inhalation causes discomfort, remove to fresh air. If discomfort persists or breathing difficulty occurs, **get medical attention.** *For emergency information, customer service, MSDS information or additional safety and chronic hazard information, call 1-800-634-0015. KEEP FROM FREEZING.*

CB-10 TECHNICAL INFORMATION

Base: Synthetic rubber latex

Type: Resin rubber emulsion

Color: Tan

Appearance: Smooth

Application Temperature: 60–100° F
(16–38° C)

Service Temperature: -20–140° F
(-29–60° C)

Adhesion: Good to vinyl and rubber

Consistency: Smooth and buttery

Bridging Ability: Good

Shear Strength: 24 hours – 100 psi
48 hours – 130 psi
7 days – 160 psi

Trowelability: Good

Durability: Good

Elongation: Good

Flexibility: Good

Sag: None

Water Resistance: Good

Freeze-Thaw Stable: Yes, minimum
of 5 cycles

Bleed: None

Staining: None

Odor: Mild

Working Time: Up to 15 minutes

Drying Time: 30-40 minutes

Minimum Cure Time: 24 hours

Weight Per Gallon: 11.41 pounds (1.37 kg/l)

Viscosity: 550,000 CPS

Volatiles: 38%

Solids: 62%

Flash Point: Greater than 205°F (96°C)

Coverage: Cartridge covers 16 lineal ft. of 4"
cove base using two 1/4" beads.

Shelf Life: 12 months from date
of purchase

VOC: < 7% by wt. (< 70 g/L)