

DWP-30

Interior

A specially formulated cold weather formula for interior drywall construction — reduces the need for fasteners up to 50%

PRODUCT DESCRIPTION

LIQUID NAILS® Drywall Adhesive, DWP-30, is a specially formulated construction adhesive for interior drywall installation and correcting minor framing irregularities in colder temperatures. Acts fast, bonds strong and buffers sound. Exceeds ASTM specification C-557.

RECOMMENDED FOR

bonding drywall to:

- Galvanized steel
- Studding
- Ceiling systems
- Rafters
- Wood
- Foam
- Drywall
- Expanded insulation panels

NOT RECOMMENDED FOR

- Uses other than drywall installations
- Exterior wall construction
- Ceiling panels, ceiling tiles and acoustical panels

PRODUCT ADVANTAGES

- Reduces fastener use up to 50%
- Minimizes nail pops
- Fast grab adhesive
- Speeds up drywall installation
- Buffers sound
- Moisture-proof
- Exceeds ASTM C-557
- Cold weather formula



Please research all installation instructions and read entire label and Material Safety Data Sheet for safety, health & environmental information prior to use. See other cautions on last page.



DRYWALL

Construction Adhesive

SURFACE PREPARATION

Surface must be clean, dry and structurally sound.

APPLYING THE PRODUCT

Cut and pre-fit materials prior to installation. Cut nozzle to desired bead size marked on nozzle. Puncture inner seal with nail or wire. **Important:** For best results, set drywall onto adhesive within 15 minutes of application.

Walls: Apply a 1/4" adhesive bead directly onto studs and plates. Press drywall firmly against adhesive; adjust as necessary. Holding drywall's outer edges, nail every 12" on outer edges and every 16" over studs in field of the panel. Fasten center of field with nails every 16" over studs. **Note:** If studding is perfectly true, nailing inside field will not be required.

Ceilings: Apply a 1/4" adhesive bead to rafters. Fasten drywall's outer edges with nails, 12" on center. Fasten center of field with a nail at each rafter.

CLEAN UP

Use mineral spirits or an adhesive remover.

DISPOSAL

Contains organic solvents which may cause adverse effects to the environment if disposed improperly. Place **empty** containers in normal refuse for disposal. Contact your sanitation department or household hazardous waste coordinator for information concerning possible re-use or disposal of unused solvent containing adhesives and/or sealants. EAD-C9

LIMITED WARRANTY

PPG warrants satisfaction with this product when handled and applied according to label instructions. If product is not as warranted, PPG will, at your option, furnish replacement product or refund the purchase price. Please call 1-800-634-0015 for details. This limited warranty excludes labor or the cost of labor and is given as the exclusive warranty and remedy. **No warranty of merchantability, fitness for purpose or other warranty, express or implied, is made. PPG shall not be liable for any special, incidental or consequential damages.** Some states do not allow the exclusion or limitation of incidental or consequential damages, so the above exclusions/limitations may not apply. This limited warranty gives specific legal rights; you may have other rights that vary by state.

DANGER! FLAMMABLE. HARMFUL OR FATAL IF SWALLOWED. HARMFUL IF INHALED. MAY CAUSE CENTRAL NERVOUS SYSTEM EFFECTS, INCLUDING DIZZINESS, HEADACHE OR NAUSEA. CAUSES EYE, SKIN AND RESPIRATORY TRACT IRRITATION. USE ONLY WITH ADEQUATE VENTILATION. KEEP OUT OF THE REACH OF CHILDREN. Reports have associated repeated and prolonged occupational overexposure to solvents with permanent brain and nervous system damage. Intentional misuse by deliberately concentrating and inhaling the contents may be harmful or fatal. Contains Crystalline Silica. If sanding, wear a dust mask to avoid breathing of sanding dust. Keep away from heat, sparks and flame. **Do not smoke. Vapors may ignite.** Vapors may spread long distances. Extinguish all flames, burners, stoves, heaters and pilot lights and disconnect all electrical motors and appliances before use and until all vapors are gone. Do not breathe vapors. Prevent build-up of vapors by opening all windows and doors to achieve cross-ventilation. Avoid contact with eyes and skin. Close container after use. **FIRST AID:** For skin contact, wash thoroughly with soap and water. If any product remains, gently rub with petroleum jelly, vegetable or mineral/baby oil then wash again with soap and water. Repeat as needed. Remove contaminated clothing. For eye contact, flush immediately with plenty of water for at least 15 minutes. **Get medical attention.** If swallowed, **get medical attention immediately.** If inhalation causes physical discomfort, remove to fresh air. If discomfort persists or any breathing difficulty occurs, **get medical attention.** For emergency information, customer service, MSDS or additional safety and chronic hazard information, call 1-800-634-0015. KEEP FROM FREEZING.

DWP-30 TECHNICAL INFORMATION

Base: Synthetic rubber and resin
Type: Solvent elastomeric adhesive
Color: Light tan
Appearance: Smooth paste
Application Temperature: 40–100° F
(5–38° C)
Service Temperature: -20–140° F
(-29–60° C)
Recommended Storage Temperature:
40–100° F (4–38° C)
Adhesion: Excellent to all common
building materials
Consistency: Non-sag
Bridging Ability: Excellent; bridges
gaps to 3/8" (1 cm)
Extrudability: Very good
Shear Strength: 24 hours – 50 psi
48 hours – 75 psi
7 days – Exceeds 190 psi
Durability: Very good; estimated to
exceed 20 years
Flexibility: Very good
Water Resistance: Very good
Aging: Very good after accelerated
aging cycle
Freeze-Thaw Stable: Does not freeze
Bleed: None
Staining: May stain real or cultured
marble & granite
Odor: Very slight solvent odor
Working Time: Up to 15 minutes
Minimum Cure Time: 24 hours
Weight Per Gallon: 11.95 pounds (1.43 kg/l)
Viscosity: 360,000 CPS
Volatiles: 16%
Solids: 84%
Flammability: Flammable;
nonflammable when dry
Flash Point: 24° F (-5° C)
Coverage: Using full round 1/4" (64 cm)
bead: 10oz. (310 ml) - 30 lineal
feet (10 lineal meters); 28 oz.
(858 ml) - 85 lineal feet
(27 lineal meters)
Shelf Life: 12 months from date of purchase
Specifications: Exceeds ASTM
specification C-557
VOC: < 15% by wt. (196 g/L)

DWP-30 12/15

Liquid Nails is a registered trademark of the PPG Group of Companies.

© PPG Industries, Inc. 2015. All Rights Reserved.

PPG Architectural Coatings
400 Bertha Lamme Drive
Cranberry Township, PA 16066

www.liquidnails.com
1-800-634-0015

Made in the
USA