



# WINDOW & DOOR

Acrylic Latex Caulk  
plus SILICONE

LC-130

Interior & Exterior

**An indoor/outdoor flexible, acrylic caulk with silicone for added water resistance**

## PRODUCT DESCRIPTION

LIQUID NAILS® Super Caulk™ Window & Door, LC-130, is an indoor/outdoor caulk with outstanding flexibility. It provides an air- and water-tight seal. Contains silicone and will not crack or peel. LC-130 adheres to all surfaces.

## RECOMMENDED FOR

Sealing:

- Moldings
- Wood
- Brick
- Glass
- Painted surfaces
- Metal
- Vinyl
- Siding & trim
- Concrete
- Baseboards
- Aluminum
- Electrical & utility boxes
- Window/door frames
- Plaster
- Stucco
- Masonry
- Stone

## NOT RECOMMENDED FOR

- Applications below water-line
- Wet or green lumber
- On top of silicone
- Automotive uses
- Aquariums
- Gaps wider than 1/2"

## PRODUCT ADVANTAGES

- Excellent flexibility & durability
- Water resistant
- Will not crack or peel
- Premium all-weather protection
- Paintable\*
- Adheres to all common construction surfaces
- Easy water clean up
- Satisfaction guaranteed

*\*Paintable in two hours with oil or latex paint. For best results, wait 24 hours before painting, longer in humid conditions.*

## AVAILABLE COLORS

- Almond
- Clear
- Grey
- Sandstone
- White



Please research all installation instructions and read entire label and Material Safety Data Sheet for safety, health & environmental information prior to use. See other cautions on last page.



# WINDOW & DOOR

Acrylic Latex Caulk  
plus SILICONE

## SURFACE PREPARATION

Clean and dry surface thoroughly before applying this product. Remove any old caulk. Fill any deep joints with backer rod to within 1/2" of surface. Sealant should be applied in dry weather at temperatures above 40°F (4°C). Do not use this product when rain is expected within 24 hours.

## APPLYING THE PRODUCT

**Cartridge:** Load cartridge into standard caulking gun. Cut nozzle at 45° angle for desired bead size (marked on nozzle). Using consistent pressure, apply continuous bead into gap at 45° angle. Smooth over with wet gloved finger or tool until level with surface. Caulk skins over within 10 minutes.

**Painting Guidelines:** Paintable in 2 hours with oil or latex paint. For best results, wait 24 hours, longer under humid conditions.

## CLEAN UP

Use water or mineral spirits when wet. When dry, scrape away or use mineral spirits.

## DISPOSAL

Contains organic solvents which may cause adverse effects to the environment if disposed of improperly. Place **empty** containers in normal refuse for disposal. Remove residual product from the container, allow product to dry, and dispose of in conjunction with normal household waste. Contact your sanitation department or household hazardous waste coordinator for information concerning possible re-use of unused caulks and/or sealants.

## LIMITED WARRANTY

PPG warrants satisfaction with this product when handled and applied according to label instructions. If product is not as warranted, PPG will, at your option, furnish replacement product or refund the purchase price. Please call 1-800-634-0015 for details. This limited warranty excludes labor or the cost of labor and is given as the exclusive warranty and remedy. **No warranty of merchantability, fitness for purpose or other warranty, express or implied, is made. PPG shall not be liable for any special, incidental or consequential damages.** Some states do not allow the exclusion or limitation of incidental or consequential damages, so the above exclusions/limitations may not apply. This limited warranty gives specific legal rights; you may have other rights that vary by state.

**WARNING! CAUSES EYE, SKIN AND RESPIRATORY TRACT IRRITATION. MAY BE HARMFUL IF SWALLOWED. CONTAINS ETHYLENE GLYCOL WHICH CAN CAUSE SEVERE KIDNEY DAMAGE WHEN INGESTED AND HAS BEEN SHOWN TO CAUSE BIRTH DEFECTS IN LABORATORY ANIMALS. USE ONLY WITH ADEQUATE VENTILATION. KEEP OUT OF THE REACH OF CHILDREN. FIRST AID:** For skin contact, wash thoroughly with soap and water. If any product remains, gently rub with petroleum jelly, vegetable or mineral/baby, then wash again with soap and water. Repeat as needed. Remove contaminated clothing. For eye contact, flush **immediately** with plenty of water for at least 15 minutes. **Get medical attention.** If swallowed, **get medical attention immediately.** If inhalation causes discomfort, remove to fresh air. If discomfort persists or any breathing difficulty occurs, **get medical attention. For emergency information, customer service, MSDS information or additional safety and chronic hazard information, call 1-800-634-0015. KEEP FROM FREEZING.**

## LC-130

### TECHNICAL INFORMATION

**Base:** 100% Acrylic Latex  
**Type:** Waterborne  
**Color:** Available in 5 colors. See front  
**Appearance:** Smooth  
**Application Temperature:** 40–100° F  
(4–38° C)  
**Service Temperature:** -20–120° F  
(-29–49° C)  
**Adhesion:** Excellent to most common building substrates  
**Extrudability:** Excellent  
**Consistency:** Gun Grade caulk  
**Durability:** Excellent  
**Elongation:** 150%  
**Flexibility:** Excellent  
**Volume Shrinkage:** 25%  
**Slump:** Max 0.15"  
**Shore "A" Hardness:** 50  
**Water Resistance:** Very Good  
**Exterior Weathering:** Excellent  
**Aging:** Will not become brittle  
**Bleed:** None  
**Staining:** None  
**Freeze-Thaw Stable:** Passes 5 cycles  
**Odor:** Mild Acrylic  
**Tack Free Time:** Tack at drying time - none  
Tack at 24 hours - none  
**Drying Time:** Allow 72 hours to completely dry  
**Weight Per Gallon:** 13.5 pounds (6.12 kg)  
**Viscosity:** 400,000 CPS  
**Solids:** 82% (white and colors)  
55% (clear)  
**Flammability:** Nonflammable  
**Flash Point:** Greater than 200°F (93°C)  
**Coverage:** Using 1/4" (.64cm) bead:  
Cartridge - 30 lineal ft.  
(9.14 lineal meters) for 3 standard windows or 1 door  
**Total Joint Movement Capability:** 14% max  
**Shelf Life:** One year from date of purchase  
**Specifications:** Meets ASTM C-834 performance requirements  
**VOC:** <1.5% by wt. (White & Grey)  
<4.0% by wt. (Almond, Clear & Sandstone)