



Contractor Grade

# PAINTER'S CAULK

LC-135

Interior & Exterior

## ***A flexible, paintable vinyl acrylic latex caulk for indoor and outdoor use***

### **PRODUCT DESCRIPTION**

LIQUID NAILS® Painter's Caulk (LC-135) is flexible, paintable and gives a mildew resistant seal. It can be used for a variety of indoor and outdoor applications. This easy-working caulk cleans up with water and can be painted over after one hour.

### **RECOMMENDED FOR**

Caulking around:

- Baseboards
- Wood
- Metal
- Drywall
- Molding
- Concrete
- Electrical & utility outlets
- Window & door frames
- Siding & trim
- Painted surfaces
- Stucco
- Brick
- Masonry
- Plaster
- Glass
- Stone

### **NOT RECOMMENDED FOR**

Use below the water-line, automotive uses, on aquariums, on top of silicone, wet or green wood. Excessive joint movement might be experienced as wet or green wood dries.

### **PRODUCT ADVANTAGES**

- Flexible acrylic caulk
- Paintable after 1 hour
- Gives mildew resistant seal
- Water clean up
- Satisfaction guaranteed



Please research all installation instructions and read entire label and Material Safety Data Sheet for safety, health & environmental information prior to use. See other cautions on last page.



Contractor Grade

# PAINTER'S CAULK

## SURFACE PREPARATION

Clean and dry surface thoroughly before applying this product. Remove any old caulk or paint. Fill deep joints with solid filler to within 1/2" of surface. LC-135 should only be applied in dry weather at temperatures above 40°F. Do not caulk with this product when rain is expected within 24 hours.

## APPLYING THE PRODUCT

Load LC-135 cartridge into standard caulking gun. Cut nozzle at 45° angle for desired bead size (marked on nozzle). Apply continuous bead of LC-135 into gap, using uniform pressure to fill completely. Smooth over with wet finger or tool. Caulk skins over within 10 minutes, and should be level with surface.

**Painting Guidelines:** Paintable with oil or latex paints after 1 hour. For best results, allow 24 hours to dry. Humidity may extend dry time.

## CLEAN UP

Use water or mineral spirits when wet. For dry material, scrape and then wipe with mineral spirits.

## DISPOSAL

Contains organic solvents which may cause adverse effects to the environment if disposed of improperly. Place empty containers in normal refuse for disposal. Contact your sanitation department or household hazardous waste coordinator for information concerning possible re-use or disposal of unused solvent-containing adhesives and/or sealants.

EAD-C9

## LIMITED WARRANTY

PPG warrants satisfaction with this product when handled and applied according to label instructions. If product is not as warranted, PPG will, at your option, furnish replacement product or refund the purchase price. Please call 1-800-634-0015 for details. This limited warranty excludes labor or the cost of labor and is given as the exclusive warranty and remedy. **No warranty of merchantability, fitness for purpose or other warranty, express or implied, is made. PPG shall not be liable for any special, incidental or consequential damages.** Some states do not allow the exclusion or limitation of incidental or consequential damages, so the above exclusions/limitations may not apply. This limited warranty gives specific legal rights; you may have other rights that vary by state.

**WARNING! HARMFUL OR FATAL IF SWALLOWED. HARMFUL IF INHALED. MAY CAUSE CENTRAL NERVOUS SYSTEM EFFECTS, INCLUDING DIZZINESS, HEADACHE OR NAUSEA. CAUSES EYE, SKIN AND RESPIRATORY TRACT IRRITATION. USE ONLY WITH ADEQUATE VENTILATION. KEEP OUT OF THE REACH OF CHILDREN.** Reports have associated repeated and prolonged occupational overexposure to solvents with permanent brain and nervous system damage. Intentional misuse by deliberately concentrating and inhaling the contents may be harmful or fatal. Contains Crystalline Silica. If sanding, wear a dust mask to avoid breathing of sanding dust. Avoid contact with eyes and skin. **FIRST AID:** For skin contact, wash thoroughly with soap and water. If any product remains, gently rub with petroleum jelly, vegetable or mineral/baby, then wash again with soap and water. Repeat as needed. Remove contaminated clothing. For eye contact, flush **immediately** with plenty of water for at least 15 minutes. **Get medical attention.** If swallowed, **get medical attention immediately.** If inhalation causes discomfort, remove to fresh air. If discomfort persists or any breathing difficulty occurs, **get medical attention.** **For emergency information, customer service, MSDS information or additional safety and chronic hazard information, call 1-800-634-0015. KEEP FROM FREEZING.**

LC-135 9/18

Liquid Nails is a registered trademark of the PPG Group of Companies.  
© PPG Industries, Inc. 2018. All Rights Reserved.

## LC-135 TECHNICAL INFORMATION

**Base:** Vinyl acrylic  
**Type:** Water borne  
**Color:** White  
**Appearance:** Smooth  
**Application Temperature:** 40–100° F  
(3–38° C)  
**Service Temperature:** -20–120° F  
(-29–49° C)  
**Adhesion:** Good to most common building substrates  
**Extrudability:** Excellent  
**Consistency:** Gun grade caulk  
**Durability:** Very good  
**Elongation:** 200%  
**Flexibility:** Very good  
**Volume Shrinkage:** 25%  
**Slump:** Max 0.15"  
**Shore "A" Hardness:** 65 to 70  
**Total Joint Movement:** 8% max  
**Water Resistance:** Good  
**Exterior Weathering:** Very good  
**Aging:** Will not become brittle  
**Freeze-Thaw Stable:** Passes 5 cycles  
**Bleed:** None  
**Staining:** None  
**Odor:** Mild latex  
**Tack Free Time:** Tack at drying time - none  
Tack at 24 hours - none  
**Drying Time:** Sets in 24-48 hours. Allow 72 hours to completely dry  
**Weight Per Gallon:** 14 pounds (6.3 kg)  
**Viscosity:** 400,000 CPS  
**Solids:** 83%  
**Flammability:** Nonflammable  
**Flash Point:** Greater than 200°F (93°C)  
**Coverage:** Using 1/4" (.64cm) bead, 30 lineal feet (9 lineal meters)  
**Shelf Life:** One year from date of purchase  
**VOC:** < 1.5% by wt.

PPG Architectural Coatings  
400 Bertha Lamme Drive  
Cranberry Township, PA 16066

[www.liquidnails.com](http://www.liquidnails.com)  
1-800-634-0015

Made in the  
**USA**