

LN-206

Interior

A special no-drip formula for easy repairs and do-it-yourself projects.

PRODUCT DESCRIPTION

LIQUID NAILS® Adhesive Wood Projects Repair Adhesive (LN-206) is a special no-drip formula that stays put. For use in woodworking and wood repair projects. The adhesive is non-flammable, dries quickly, and will not run on vertical surfaces for faster finishing and less clean up.

RECOMMENDED FOR a variety of uses including:

- Tables
- Cabinets
- Chairs
- Benches
- Paper/cloth
- Hobbies
- Veneers
- Clocks
- Shelving
- Furniture
- Ready-to-assemble furniture

NOT RECOMMENDED FOR sheet goods, wood flooring or ceiling applications.

Please research all installation instructions and read entire label for safety, health & environmental information prior to use.

Look for other LIQUID NAILS products which are right for your specific project

PRODUCT ADVANTAGES

- No-drip formula
- Resealable cap / Precision applicator
- Water clean-up
- For fast, easy repairs
- Quick grabbing
- Fast drying
- Sandable
- Paintable

Read Label and Material Safety Data Sheet Prior to Use.
See other cautions on last page.



SURFACE PREPARATION

Surfaces must be clean, dry and structurally sound. Remove paint, varnish and old glue.

APPLYING THE PRODUCT

General application: Apply a thin adhesive bead evenly to one surface. If necessary, clamp materials for 30 minutes. Allow to dry overnight before handling.

Woodworking projects: Make sure that all parts fit snugly together. Apply a thin bead of adhesive evenly to one surface. Clamp for 30 minutes. Allow to dry overnight before handling.

Furniture projects/repairs: Make sure that joints fit snugly together. Apply a thin adhesive bead evenly to one surface. Clamp for 30 minutes. Allow to dry overnight before handling.

Paper, cloth or other porous materials: Apply a bead and spread evenly on one surface. Press surfaces together. Clamp or apply weight overnight, if necessary. Allow to dry.

CLEAN-UP

Wet adhesive can be cleaned up with a damp cloth. Dried adhesive can be scraped away or sanded.

DISPOSAL

Place empty containers in normal refuse for disposal. Remove residual product from the container, allow product to dry, and dispose of in conjunction with normal household waste. Contact your sanitation department or household hazardous waste coordinator for information concerning possible re-use of unused caulks and sealants. EAD-C8

LIMITED WARRANTY

AkzoNobel warrants satisfaction with this product when handled and applied according to label instructions. If this product is not as warranted, please call 1-800-634-0015 for refund or product replacement details. This warranty excludes labor or the cost of labor and is given as the exclusive warranty and remedy. **No warranty of merchantability, fitness for purpose or other warranty, express or implied, is made.** AkzoNobel shall not be liable for any special, incidental or consequential damages. Some states do not allow the exclusion of incidental or consequential damages, so the limitations may not apply. This warranty gives specific legal rights. You may also have other rights that vary from state to state.

LN-206

TECHNICAL INFORMATION

Base: Polyvinyl acetate emulsion

Type: Waterbase

Color: Off White

Appearance: Smooth paste

Application Temperature: 40° to 100° F
(5° to 38° C)

Service Temperature: 0° to 140° F
(-18° to 60° C)

Adhesion: Excellent to wood

Consistency: Smooth

Shear Strength (ASTM D 905): >1500 psi

Oxidation Resistance (158° F / 70° C):
Good at 500 hrs.

Durability: Good

Flexibility: Hard

Water Resistance: Fair

Exterior Weathering: Not recommended

Aging: Good

Freeze/Thaw Stable: Yes

Bleed: None

Staining: None

Odor: Slight

Working Time: 15 minutes

Drying Time: 30 minutes

Clamp Time: 30 minutes

Handling Time: 16 hours

Paintability: Good

Sandability: Good

Weight Per Gallon: 9.3 pounds (4.22 kg)

Viscosity: 110,000 CPS

Volatiles: 44%

Solids: 56%

Flammability: Non-flammable

Flash Point: None

Shelf Life: 12 months from date of purchase

MAX VOC: 36 g/L

WARNING! HARMFUL OR FATAL IF SWALLOWED. CAUSES EYE, SKIN AND RESPIRATORY TRACT IRRITATION. USE ONLY WITH ADEQUATE VENTILATION. KEEP OUT OF THE REACH OF CHILDREN.

Avoid contact with eyes and skin. **FIRST AID:** For skin contact, wash thoroughly with soap and water. If any product remains, gently rub with petroleum jelly, vegetable or mineral/baby oil then wash again with soap and water. Repeat as needed. Remove contaminated clothing. For eye contact, flush immediately with plenty of water for at least 15 minutes. **Get medical attention.** If swallowed, **get medical attention immediately.** If inhalation causes discomfort, remove to fresh air. If discomfort persists or breathing difficulty occurs, get medical attention.

For emergency information, customer service, MSDS or additional safety and chronic hazard information, call 1-800-634-0015. KEEP FROM FREEZING. MDS10-0805