



PANELING & Molding Adhesive

LN-710

Interior

A fast, sure hold latex-based adhesive that provides precision placement and minimizes nailing

PRODUCT DESCRIPTION

LIQUID NAILS® Paneling & Molding Adhesive, LN-710, is specially designed for projects like paneling and molding where instant hold is needed. The fast, sure hold provides precision placement and minimizes nailing, offering a 20 minute working time and an impact-resistance bond. Qualifies for points as a low emitting material under LEED v4.

RECOMMENDED FOR

- Paneling
- Furring strips
- Wood molding
- Plastic paneling & molding
- Plywood/hardboard
- MDF Board
- Foil & insulation board
- Wainscoting

Please note with plastic moldings and trim, the second surface should be porous. Dry time may be extended.

NOT RECOMMENDED FOR

- Uses other than paneling and molding installations
- Use between two non-porous surfaces
- Exterior use
- 1/8" MDF Paneling

PRODUCT ADVANTAGES

- Strong instant hold
- Minimizes nailing
- Impact resistant
- Retains precise placement
- 20 minute working time
- VOC compliant



Please research all installation instructions and read entire label and Material Safety Data Sheet for safety, health & environmental information prior to use. See other cautions on last page.



PANELING

& Molding Adhesive

SURFACE PREPARATION

Make sure that all surfaces are clean, dry and structurally sound before product is applied.

APPLYING THE PRODUCT

Place cartridge in gun, cut nozzle, and puncture inner seal with nail or wire. Apply a 1/4" bead of adhesive around the perimeter of parts to be bonded. Adhere materials within 20 minutes of gunning adhesive. Warped materials may require bracing and/or nailing.

INSTANT-GRAB METHOD:

Paneling: Apply 1/4" bead of adhesive approximately 1" from edge of panel around the perimeter. Apply two zigzag 1/4" beads in the middle of the panel. Press panel firmly into place. Remove panel from wall for one minute. Rejoin panel to wall.

Molding: Apply 1/4" zigzag bead to back of molding. Press molding firmly into place. Starting at one end, nail every 12".

Note: One surface must be porous

CLEAN UP

Water for wet adhesive. Scraping followed by wiping with mineral spirits for dried adhesive.

DISPOSAL

Contains organic solvents which may cause adverse effects to the environment if disposed of improperly. Place **empty** containers in normal refuse for disposal. Contact your sanitation department or household hazardous waste coordinator for information concerning possible re-use or disposal of unused solvent-containing adhesives and/or sealants. EAD-C9

LIMITED WARRANTY

PPG warrants satisfaction with this product when handled and applied according to label instructions. If product is not as warranted, PPG will, at your option, furnish replacement product or refund the purchase price. Please call 1-800-634-0015 for details. This limited warranty excludes labor or the cost of labor and is given as the exclusive warranty and remedy. **No warranty of merchantability, fitness for purpose or other warranty, express or implied, is made. PPG shall not be liable for any special, incidental or consequential damages.** Some states do not allow the exclusion or limitation of incidental or consequential damages, so the above exclusions/limitations may not apply. This limited warranty gives specific legal rights; you may have other rights that vary by state.

WARNING! HARMFUL OR FATAL IF SWALLOWED. HARMFUL IF INHALED. MAY CAUSE CENTRAL NERVOUS SYSTEM EFFECTS, INCLUDING DIZZINESS, HEADACHE OR NAUSEA. CAUSES EYE, SKIN AND RESPIRATORY TRACT IRRITATION. USE ONLY WITH ADEQUATE VENTILATION. KEEP OUT OF THE REACH OF CHILDREN. Reports have associated repeated and prolonged occupational overexposure to solvents with permanent brain and nervous system damage. Intentional misuse by deliberately concentrating and inhaling the contents may be harmful or fatal. Contains Crystalline Silica. If sanding, wear a dust mask to avoid breathing of sanding dust. Avoid contact with eyes and skin. **FIRST AID:** For skin contact, wash thoroughly with soap and water. If any product remains, gently rub with petroleum jelly, vegetable or mineral/baby oil then wash again with soap and water. Repeat as needed. Remove contaminated clothing. For eye contact, flush immediately with plenty of water for at least 15 minutes. **Get medical attention.** If swallowed, **get medical attention immediately.** If inhalation causes discomfort, remove to fresh air. If discomfort persists or any breathing difficulty occurs, **get medical attention.** For emergency information, customer service, MSDS information or additional safety and chronic hazard information, call 1-800-634-0015. **KEEP FROM FREEZING.**

LN-710

TECHNICAL INFORMATION

Base: Latex

Color: Tan

Appearance: Smooth

Application Temperature: 40–100° F
(5–38° C)

Service Temperature: 0–140° F
(–18–60° C)

Adhesion: Excellent

Extrudability: Easy

Consistency: Short and buttery

Bridging Ability: Excellent

Shear Strength: 24 hours – 150 psi
48 hours – 180 psi
7 days – 240 psi

Durability: Excellent; 20 year life

Flexibility: Excellent

Water Resistance: Excellent

Aging: Excellent; 20 year life

Bleed: Will not bleed

Odor: Mild

Open Time: 20 minutes

Minimum Cure Time: 24 hours

Weight Per Gallon: 11.5 pounds (1.38 kg/l)

Viscosity: 440,000 CPS

Volatiles: 28%

Solids: 72%

Flammability: Non-flammable

Flash Point: 1° F (-17°C)

Coverage: 30 lineal feet using 1/4" bead

Shelf Life: 12 months from date of purchase

VOC: < 7% by wt. (< 50 g/L)

LN-710 12/21 LN814556

Liquid Nails is a registered trademark of the PPG Group of Companies. UL, the UL logos and the UL mark are trademarks of UL LLC. © PPG Industries, Inc. 2021. All Rights Reserved.

PPG Architectural Coatings
400 Bertha Lamme Drive
Cranberry Township, PA 16066

www.liquidnails.com
1-800-634-0015

Made in the
USA