

LN-910

Interior

***A fast, sure hold solvent-based adhesive that provides precision placement and minimizes nailing***

### PRODUCT DESCRIPTION

LIQUID NAILS® Paneling & Molding Adhesive, LN-910, is a premium construction adhesive specially designed for projects like paneling and molding for a strong instant bond. The fast, sure hold provides precision placement and minimizes nailing. LN-910 offers a ten minute working time and an impact-resistant bond.

### RECOMMENDED FOR

- Paneling
- Furring strips
- Corkboard
- Wood molding
- Plywood/hardboard

### NOT RECOMMENDED FOR

- Uses other than paneling and molding installations
- Use between two non-porous surfaces
- Exterior use
- 1/8" MDF Paneling

### PRODUCT ADVANTAGES

- Strong instant hold
- Retains precise placement
- Minimizes nailing
- 10 minute working time



Please research all installation instructions and read entire label and Material Safety Data Sheet for safety, health & environmental information prior to use. See other cautions on last page.

**SURFACE PREPARATION**

Make sure that all surfaces are clean, dry and structurally sound before product is applied.

**APPLYING THE PRODUCT**

Cut and prefit materials prior to installation. Insert tube into standard caulking gun. Cut nozzle at 45° angle to desired bead size marked on nozzle. Puncture inner seal with nail or wire.

**INSTANT-GRAB METHOD:**

**Paneling:** Apply 1/4" bead of adhesive approximately 1" from edge of panel around the perimeter. Apply two zigzag 1/4" beads in the middle of the panel. Press panel firmly into place.

Due to panel inconsistencies, for best results, bracing and/or nailing may be required.

**Molding:** Apply 1/4" zigzag bead to back of molding. Press molding firmly into place. Starting at one end, nail every 12".

**CLEAN UP**

Use mineral spirits or an adhesive remover.

**DISPOSAL**

Contains organic solvents which may cause adverse effects to the environment if disposed of improperly. Place **empty** containers in normal refuse for disposal. Contact your sanitation department or household hazardous waste coordinator for information concerning possible re-use or disposal of unused solvent-containing adhesives and/or sealants. EAD-C9

**LIMITED WARRANTY**

PPG warrants satisfaction with this product when handled and applied according to label instructions. If product is not as warranted, PPG will, at your option, furnish replacement product or refund the purchase price. Please call 1-800-634-0015 for details. This limited warranty excludes labor or the cost of labor and is given as the exclusive warranty and remedy. **No warranty of merchantability, fitness for purpose or other warranty, express or implied, is made. PPG shall not be liable for any special, incidental or consequential damages.** Some states do not allow the exclusion or limitation of incidental or consequential damages, so the above exclusions/limitations may not apply. This limited warranty gives specific legal rights; you may have other rights that vary by state.

**DANGER! EXTREMELY FLAMMABLE. CAUSES EYE AND SKIN BURNS. HARMFUL OR FATAL IF SWALLOWED. HARMFUL IF INHALED. MAY CAUSE CENTRAL NERVOUS SYSTEM EFFECTS, INCLUDING DIZZINESS, HEADACHE OR NAUSEA. CAUSES RESPIRATORY TRACT IRRITATION. USE ONLY WITH ADEQUATE VENTILATION. KEEP OUT OF THE REACH OF CHILDREN.** Reports have associated repeated and prolonged occupational overexposure to solvents with permanent brain and nervous system damage. Intentional misuse by deliberately concentrating and inhaling the contents may be harmful or fatal. Contains Crystalline Silica. If sanding, wear a dust mask to avoid breathing of sanding dust. Keep away from heat, sparks and flame. **Do not smoke. Vapors may ignite explosively.** Vapors may spread long distances. Extinguish all flames, burners, stoves, heaters and pilot lights and disconnect all electrical motors and appliances before use and until all vapors are gone. Do not breathe vapors. Prevent build-up of vapors by opening all windows and doors to achieve cross-ventilation. Avoid contact with eyes and skin. Close container after use. **FIRST AID:** For skin contact, wash thoroughly with soap and water. If any product remains, gently rub with petroleum jelly, vegetable or mineral/baby oil, then wash again with soap and water. Repeat as needed. Remove contaminated clothing. For eye contact, flush immediately with plenty of water for at least 15 minutes. **Get medical attention.** If swallowed, **get medical attention immediately.** If inhalation causes physical discomfort, remove to fresh air. If discomfort persists or any breathing difficulty occurs, get medical attention. **For emergency information, customer service, MSDS or additional safety and chronic hazard information, call 1-800-634-0015. KEEP FROM FREEZING.**

**LN-910  
TECHNICAL INFORMATION**

**Base:** Styrene butadiene rubber

**Color:** Tan

**Appearance:** Smooth

**Application Temperature:** 40–100° F  
(5–38° C)

**Service Temperature:** -20–140° F  
(-29–60° C)

**Adhesion:** Excellent

**Extrudability:** Easy

**Consistency:** Short and buttery

**Bridging Ability:** Excellent

**Shear Strength:** 24 hours – 125 psi

48 hours – 250 psi

7 days – 325 psi

**Durability:** Excellent; 20 year life

**Flexibility:** Excellent

**Water Resistance:** Excellent

**Aging:** Excellent; 20 year life

**Bleed:** Will not bleed

**Odor:** Mild solvent

**Open Time:** 10 minutes

**Minimum Cure Time:** 24 hours

**Weight Per Gallon:** 9.3 pounds (1.11 kg/l)

**Viscosity:** 260,000 CPS

**Volatiles:** 33%

**Solids:** 67%

**Flammability:** Extremely flammable;  
non-flammable when dry

**Flash Point:** 1° F (-17°C)

**Coverage:** 30 lineal ft. using 1/4" bead for  
10 fl.oz.; 85 lineal ft. using 1/4"  
bead for 28 fl.oz.

**Shelf Life:** 12 months from date of purchase

**VOC:** < 40% by wt. (380 g/L)