

TUB SURROUND

& Shower Wall Adhesive

LN-915

Interior

A durable waterproof construction adhesive formulated not to burn through most bath surround products

PRODUCT DESCRIPTION

LIQUID NAILS® Tub Surround & Shower Wall Adhesive, LN-915, provides an exceptional waterproof bond under extreme conditions and won't harm most tub surrounds and shower walls. Light color won't show through surrounds. Recommended for most plastic tub and shower enclosures.

RECOMMENDED FOR

bonding most plastic tub and shower enclosures over structurally sound:

- Drywall
- Plywood
- Hardboard
- Ceramic tile
- Greenboard
- Cement backerboard

It is also recommended for polystyrene foamback tub kits when adhesive venting method described under "Directions" is followed.

NOT RECOMMENDED FOR

- Flooring applications
- Ceramics
- Mirrors
- Granite
- Application of polystyrene foamback tub kits over ceramic tile

PRODUCT ADVANTAGES

- No burn through
- Heat and steam resistant
- Great for polystyrene, plastic, and fiberglass tub & shower units
- Light color won't show through
- No bracing required
- Strong, waterproof bond



Please research all installation instructions and read entire label and Material Safety Data Sheet for safety, health & environmental information prior to use. See other cautions on last page.

TUB SURROUND

& Shower Wall Adhesive

SURFACE PREPARATION

Make sure that all surfaces are clean, dry, structurally sound and free of any loose paint or other materials. Sand and roughen high gloss paint.

APPLYING THE PRODUCT

Do not apply LN-915 when surface or adhesive temperature exceeds 90°F. Cut nozzle at 45° angle to a 1/8" bead size. Puncture inner seal with nail or wire. Apply in a continuous 1/8" bead, following the tub surround manufacturer's instructions. Some tub surround manufacturers require adhesive bead to be spread out with a trowel. Consult tub surround installation instructions for specific recommendations.

It is important for proper installation that each panel be vented according to the following directions. Venting method: Apply LN-915 adhesive and press panel firmly to wall, then pull away. Wait 3-5 minutes, then press panel firmly back into place. For proper adhesion, after 20-30 minutes go around entire tub surround and press firmly over all flat surfaces. If any edges lift up, tape them to the wall with masking tape until adhesive dries.

Let cure 24 hours. Bracing may be required.

CLEAN UP

Use mineral spirits or an adhesive remover. Soften adhesive on the front of tub surrounds with petroleum jelly only (to prevent damage to the finish), then wipe away with soft cloth.

DISPOSAL

Contains organic solvents which may cause adverse effects to the environment if disposed of improperly. Place **empty** containers in normal refuse for disposal. Contact your sanitation department or household hazardous waste coordinator for information concerning possible re-use or disposal of unused solvent-containing adhesives and/or sealants. EAD-C9

LIMITED WARRANTY

PPG warrants satisfaction with this product when handled and applied according to label instructions. If product is not as warranted, PPG will, at your option, furnish replacement product or refund the purchase price. Please call 1-800-634-0015 for details. This limited warranty excludes labor or the cost of labor and is given as the exclusive warranty and remedy. **No warranty of merchantability, fitness for purpose or other warranty, express or implied, is made. PPG shall not be liable for any special, incidental or consequential damages.** Some states do not allow the exclusion or limitation of incidental or consequential damages, so the above exclusions/limitations may not apply. This limited warranty gives specific legal rights; you may have other rights that vary by state.

DANGER! EXTREMELY FLAMMABLE. CAUSES EYE AND SKIN BURNS. HARMFUL OR FATAL IF SWALLOWED. HARMFUL IF INHALED. MAY CAUSE CENTRAL NERVOUS SYSTEM EFFECTS, INCLUDING DIZZINESS, HEADACHE OR NAUSEA. CAUSES RESPIRATORY TRACT IRRITATION.

USE ONLY WITH ADEQUATE VENTILATION. KEEP OUT OF THE REACH OF CHILDREN. Reports have associated repeated and prolonged occupational overexposure to solvents with permanent brain and nervous system damage. Intentional misuse by deliberately concentrating and inhaling the contents may be harmful or fatal. Contains Crystalline Silica. If sanding, wear a dust mask to avoid breathing of sanding dust. Keep away from heat, sparks and flame. **Do not smoke. Vapors may ignite explosively.** Vapors may spread long distances. Extinguish all flames, burners, stoves, heaters and pilot lights and disconnect all electrical motors and appliances before use and until all vapors are gone. Do not breathe vapors. Prevent build-up of vapors by opening all windows and doors to achieve cross-ventilation. Avoid contact with eyes and skin. Close container after use. **FIRST AID:** For skin contact, wash thoroughly with soap and water. If any product remains, gently rub with petroleum jelly, vegetable or mineral/baby oil, then wash again with soap and water. Repeat as needed. Remove contaminated clothing. For eye contact, flush immediately with plenty of water for at least 15 minutes. **Get medical attention.** If swallowed, **get medical attention immediately.** If inhalation causes physical discomfort, remove to fresh air. If discomfort persists or any breathing difficulty occurs, get medical attention. **For emergency information, customer service, MSDS or additional safety and chronic hazard information, call 1-800-634-0015. KEEP FROM FREEZING.**

LN-915 TECHNICAL INFORMATION

Base: Synthetic rubber & resin

Appearance: Smooth-paste

Application Temperature: 40–100° F
(5–38° C)

Service Temperature: -20–140° F
(-29–60° C)

Adhesion: Excellent to most plastic tub surrounds

Extrudability: Good at normal room temperature

Bridging Ability: Excellent; bridges gaps up to 3/8"

Shear Strength: Typical (plywood to plywood)
24 hours – 75 psi
48 hours – 150 psi
7 days – 275 psi

Durability: Excellent; estimated to exceed 20 years

Flexibility: Excellent

Water Resistance: Excellent

Exterior Weathering: Not recommended

Freeze-Thaw Stable: Will not freeze

Bleed: None

Staining: None

Odor: Strong solvent

Open Time: 15 - 20 minutes

Drying Time: Let dry for 24 hours

Weight Per Gallon: 10.6 pounds (1.27 kg/l)

Viscosity: 300,000 CPS

Volatiles: 25%

Solids: 75%

Flammability: Extremely flammable; non-flammable when dry

Flash Point: 1°F (-17°C)

Coverage: 30 lineal ft. using 1/4" bead for 10 fl.oz.

Shelf Life: 12 months from date of purchase

VOC: < 40% by wt. (327 g/L)