

**LIQUID  
NAILS<sup>®</sup>**  
BRAND

**ULTRA  
QUIK GRIP<sup>®</sup>**  
Construction Adhesive

**LN-990**

**Interior & Exterior**

***A premium construction adhesive offering a strong instant hold, excellent durability and great flexibility even in low temperatures***

**PRODUCT DESCRIPTION**

LIQUID NAILS<sup>®</sup> ULTRA QUIK GRIP<sup>®</sup> Adhesive, LN-990, features a strong instant hold with no bracing required. Minimizes the need for mechanical fasteners. Certified by UL Environment to meet the GREENGUARD Gold Standard as a low emitting material.

**RECOMMENDED FOR**

- Paneling
- Chair rails
- Foamboard
- Concrete
- Ceramic tile
- Plywood/waferboard
- Plaster
- Drywall
- Corkboard
- Furring strips
- Brick
- Lumber
- Glass
- Baseboards
- Plastic & vinyl

**NOT RECOMMENDED FOR**

- Mirrors
- Ceiling tile
- Metal
- Finished floors

**PRODUCT ADVANTAGES**

- Strong instant flexible hold
- Minimizes the need for fasteners
- Low odor
- Excellent durability
- Repositionable up to 10 minutes
- Easy water clean up
- No bracing required
- VOC compliant



Please research all installation instructions and read entire label and Material Safety Data Sheet for safety, health & environmental information prior to use. See other cautions on last page.

### **SURFACE PREPARATION**

Surfaces must be clean, dry, and structurally sound. Cut and pre-fit materials prior to installation.

### **APPLYING THE PRODUCT**

1. Insert tube into caulking gun.
2. Cut nozzle to desired bead size. (marked on nozzle).
3. Apply adhesive in temperature of 40° F or higher and press your material into place. Material should not be applied to skinned adhesive. Do not apply to damp concrete or masonry.

**Note:** One surface must be porous.

**Material to furring strips or studs:** Apply zigzag 1/4" adhesive bead to each strip or stud to be covered by material. Position material so edges meet at stud center. Press into place. Finishing nails required at top and bottom.

### **CLEAN UP**

Use water for wet adhesive. Use mineral spirits or an adhesive remover for dry adhesive.

### **DISPOSAL**

Place **empty** containers in normal refuse for disposal. Remove residual product from the container, allow product to dry, and dispose of in conjunction with normal household waste. Contact your sanitation department or household hazardous waste coordinator for information concerning possible re-use of unused caulks and sealants. EAD-C8

### **LIMITED WARRANTY**

PPG warrants satisfaction with this product when handled and applied according to label instructions. If product is not as warranted, PPG will, at your option, furnish replacement product or refund the purchase price. Please call 1-800-634-0015 for details. This limited warranty excludes labor or the cost of labor and is given as the exclusive warranty and remedy. **No warranty of merchantability, fitness for purpose or other warranty, express or implied, is made. PPG shall not be liable for any special, incidental or consequential damages.** Some states do not allow the exclusion or limitation of incidental or consequential damages, so the above exclusions/limitations may not apply. This limited warranty gives specific legal rights; you may have other rights that vary by state.

**WARNING! CAUSES EYE, SKIN AND RESPIRATORY TRACT IRRITATION. MAY BE HARMFUL IF SWALLOWED. POTENTIAL CANCER HAZARD. CONTAINS FORMALDEHYDE WHICH HAS BEEN SHOWN TO CAUSE UPPER RESPIRATORY TRACT CANCER AND ALLERGIC RESPIRATORY REACTION. MAY CAUSE ALLERGIC SKIN REACTION. USE ONLY WITH ADEQUATE VENTILATION. KEEP OUT OF THE REACH OF CHILDREN.** Contains Crystalline Silica. If sanding, wear a dust mask to avoid breathing of sanding dust. Avoid contact with eyes and skin. **FIRST AID:** For skin contact, wash thoroughly with soap and water. If any product remains, gently rub with petroleum jelly, vegetable or mineral/baby oil, then wash again with soap and water. Repeat as needed. Remove contaminated clothing. For eye contact, flush immediately with plenty of water for at least 15 minutes. **Get medical attention.** If swallowed, **get medical attention immediately.** If inhalation causes physical discomfort, remove to fresh air. If discomfort persists or any breathing difficulty occurs, get medical attention. **For emergency information, customer service, MSDS or additional safety and chronic hazard information, call 1-800-634-0015. KEEP FROM FREEZING.**

### **LN-990 TECHNICAL INFORMATION**

**Base:** Acrylic Polymer  
**Type:** Latex  
**Color:** White  
**Application Temperature:** 40–100° F  
(4–38° C)  
**Service Temperature:** -20–200° F  
(-29–93° C)  
**Adhesion:** Good to most common substrates  
**Consistency:** Smooth Paste  
**Volume Shrinkage:** 45%  
**Slump:** Max. 0.10" at 3/8" depth  
(ASTM D2202)  
**Tack Free Time:** 1 Hour  
**Durability:** Excellent  
**Flexibility:** Good to 30° F (-1° C)  
**Water Resistance:** Good  
**Freeze-Thaw Stable:** Passes 5 cycles  
**Bleed:** None  
**Staining:** None  
**Odor:** Mild Acrylic  
**Drying Time:** 16 hrs. at room temperature  
**Weight Per Gallon:** 9.1 pounds (1.10 kg/l)  
**Viscosity:** 1.4 million CPS  
**Volatiles:** 42%  
**Solids:** 58%  
**Flammability:** Nonflammable  
**Flash Point:** Exceeds 205°F (>95° C)  
**Shear strength (7 days):** >300 psi  
**Coverage:** Using full round 1/4" (.64 cm)  
bead: 30 lineal feet  
(9.1 lineal meters)  
**Shelf Life:** 12 months from date of purchase  
**VOC:** < 7% by wt. (< 70 g/L)