



OLYMPIC® Premium Interior Oil Based Wood Stains

GENERAL DESCRIPTION

OLYMPIC Premium Interior Oil Based Wood Stain is designed with a unique Absorption Control™ Formula to provide a beautiful, consistent finish - no blotching, streaking, or lap marks. Excellent for soft and hard, new and stripped wood. This remarkable low odor formula penetrates deep into the wood fibers, sealing and protecting it for years to come. Use alone or with OLYMPIC Premium Polyurethane Clear Finish. For use on softer wood, OLYMPIC Premium Wood Conditioner can be applied to obtain an even color.

RECOMMENDED USES

Furniture	Doors
Cabinets	Floors
Paneling	
Trim	

FEATURES / BENEFITS

Unique Absorption Control™ Formula Ensures Consistent Color
Ideal for Soft and Hard Woods
Helps Resist Fading
Prevents Blotching, Lapping and Streaking

DIRECTIONS FOR USE

Stir stain before use. Intermix containers to ensure color uniformity.

Pretest: Test a small hidden area prior to application to ensure acceptable appearance and penetration.

APPLICATION INFORMATION

Application Equipment: Apply with a clean cloth, brush, sponge, roller, paint pad, or by spray equipment.

Application Method: For even color acceptance on soft woods, such as pine, fir, alder, and spruce, use OLYMPIC Premium Wood Conditioner. Wipe the conditioner onto the wood and allow to penetrate for 5 minutes, then wipe off the excess. Apply stain with a clean cloth, brush, sponge, pad, roller or by spray equipment. Allow to penetrate for 5 to 15 minutes. Wipe off the excess stain with a clean cloth. The intensity of the color is controlled by the penetration time. To further increase color intensity, allow the stain to dry for 8 hours, then apply a second coat.

Thinning: No thinning is needed.

PRODUCT INFORMATION

41533	Colonial Maple
41534	Dark Walnut
41535	Natural
41554	Golden Oak
41555	Pickling White
41556	Mocha Brown
41557	Merlot
41558	Deep Ebony
41559	Golden Pecan
41566	Red Mahogany
41568	Special Walnut

PRODUCT DATA

PRODUCT TYPE:	Alkyd / Oil Resin
VOLUME SOLIDS:	29% to 30% +/- 2%
WEIGHT SOLIDS:	34% to 38% +/- 2%
VOC:	<550 g/L (4.58 lbs./gal.)
WEIGHT/GALLON:	6.9 lbs. (3.1 kg) to 7.4 lbs. (3.4 kg) +/- 0.2 lbs. (91 g)
FLASH POINT:	120°F (48.9°C)

COVERAGE: Approximately 500 sq. ft. (46.5 sq. meters) per gallon (3.78L). Coverage will vary with wood type, preparation and application.

DRYING TIME: Dry times vary with temperature, humidity, color and wood type. To test for dryness, lightly rub with a white cloth. If the cloth picks up color, wait at least one hour and retest.

Topcoat after the stain has dried for 8 hours. Allow a minimum of 24 hours drying time before general use.

CLEANUP: Clean up with mineral spirits or paint thinner.

Danger - Rags, steel wool or waste soaked with this product may spontaneously catch fire if improperly discarded. Immediately after use, place rags, steel wool or waste in a sealed water-filled metal container.

OLYMPIC® Premium Interior Oil Based Wood Stains

GENERAL SURFACE PREPARATION

Proper surface preparation is essential for the OLYMPIC limited warranty to apply. Remove grade stamps, pencil marks, etc. by sanding.

WARNING! If you scrape, sand, or remove old paint, you may release lead dust or fumes. LEAD IS TOXIC. EXPOSURE TO LEAD DUST OR FUMES CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE. Wear a properly fitted NIOSH-approved respirator and prevent skin contact to control lead exposure. Clean up carefully with a HEPA vacuum and a wet mop. Before you start, find out how to protect yourself and your family by contacting the USEPA National Lead Information Hotline at 1-800-424-LEAD or log on to www.epa.gov/lead. In Canada contact a regional Health Canada office. Follow these instructions to control exposure to other hazardous substances that may be released during surface preparation.

BARE WOOD: Always sand with the grain of the wood. For hard woods, such as oak and maple, begin sanding with 100 grit sandpaper, then proceed to 150 grit sandpaper, and finish with 200 grit or finer sandpaper. For soft woods, such as pine, begin sanding with 150 grit sandpaper and finish with 200 grit or finer sandpaper.

REFINISHING OLD WOOD: Remove all old finishes down to bare wood prior to application.

FINAL SURFACE PREPARATION: All wood must be dry and free of dust, dirt, grease or oils. Use a tack cloth or vacuum cleaner to remove any dust or dirt from the wood. Surfaces must be dry before staining.

FINISHING RECOMMENDATIONS: OLYMPIC Premium Interior Wood Stain can be used as a finish by itself. For a more durable finish, topcoat with OLYMPIC Premium Polyurethane Oil Based or Water Based Finish or a paste wax after the stain has dried for 8 hours. Protect floors and furniture with two or more coats of OLYMPIC Premium Polyurethane Finish.

LIMITATIONS OF USE

FOR INTERIOR USE ONLY. Do not apply when the air, coating or surface temperature is below 50°F (10°C).

Do not attempt to use on prewaxed wood flooring. Follow flooring manufacturer's coating recommendations.

These products are not intended for immersion service or other extreme conditions. Not recommended in situations characterized by high heat or presence of corrosive chemicals nor for heavy-duty use on floors.

PACKAGING

Available in one quart (946 mL) containers.

SAFETY PRECAUTIONS

Before using the products listed in this publication, carefully read each product label and follow directions for its use. Please read and observe all the warnings and precautionary information on the product labels. Material Safety Data Sheets are available through our Sales Representative, Retailer or by calling (412) 492-5555.

Spray equipment must be handled with due care and in accordance with manufacturer's recommendations. High pressure injection of coatings into the skin by airless equipment may cause serious injury.

Explosion-proof equipment must be used when coating with these materials in confined areas. Keep containers closed and away from heat, sparks, and flame when not in use.

USE WITH ADEQUATE VENTILATION. KEEP OUT OF REACH OF CHILDREN.

PPG Architectural Finishes, Inc. believes the technical data presented is currently accurate; however, no guarantee of accuracy, comprehensiveness, or performance is given or implied. Improvements in coatings technology may cause future technical data to vary from what is in this bulletin. For complete, up-to-date technical information, call 1-800-441-9695.



Olympic - US
PPG Industries, Inc.
Architectural Coatings
One PPG Place
Pittsburgh, PA 15272
www.ppgpittsburghpaints.com
www.ppgporterpaints.com

Technical Services
1-800-441-9695

Architect/Specifier
1-888-PPG-IDEA

Olympic - Canada
PPG Canada, Inc.
Architectural Coatings
4 Kenview Blvd
Brampton, ON L6T 5E4

T.D. 4004 10/2011
(Supersedes 5/2008)

Made in the
USA