



Olympic Wood Protector Stain + Sealant in One Semi-Transparent

GENERAL DESCRIPTION

Olympic Wood Protector Semi-Transparent Stain provides waterproofing protection with subtle color that allows the natural grain and texture to show, enhancing the natural beauty of wood. Wood Protector is recommended for use on any properly prepared exterior wood, including decks, fences, siding, railings, outdoor furniture, and other wood surfaces. Protects decks up to 3 years and fences and siding up to 5 years.

RECOMMENDED SUBSTRATES

Pressure-treated wood
Weathered wood
Wood decks
Wood siding

PRODUCT INFORMATION

53194 Neutral Base* (must be tinted)
53113 716 Cedar Naturaltone

*Must be tinted before use.

Some colors, drastic color changes, or porous substrates may require more than one coat to achieve a uniform finish.

FEATURES / BENEFITS

Waterproofing Protection
SUNBLOCK® UV Defense
Exclusive SCUFF GUARD® Technology
Provides Mildew Resistant Coating
Durable Acrylic/Oil Formula

PACKAGING

1-Gallon (3.78 L)
5-Gallon (18.9 L)

Not all products available in all sizes.

PRODUCT DATA

PRODUCT TYPE: Alkyd
VOLUME SOLIDS*: 31% +/- 2%
WEIGHT SOLIDS*: 36% +/- 2%
VOC*: <550 g/L (4.6 lbs./gal.)
WEIGHT/GALLON*: 7.0 lbs. (3.2 kg) +/- 0.2 lbs. (91 g)

*Product data calculated on 53194.

COVERAGE: Approximately 250 to 350 sq. ft. (23.2 to 32.5 sq. meters) per gallon (3.78 Liters) depending on application, wood texture and porosity. Coverage figures do not include loss due to surface irregularities and porosity or material loss due to application method or mixing.

DRYING TIME: Normally dries in 24 hours when applied in optimal temperatures of 50°F (10°C) to 85°F (29°C).

Application in high humidity or in temperatures below 50°F (10°C) may prolong drying and recoating times. Allow 24 to 48 hours of drying time before light foot traffic or replacing furniture.

Newly stained surfaces should be allowed to cure 30 days before washing.

Drying times listed may vary depending on temperature, humidity, film build, color, and air movement.

CLEANUP: Clean brushes and tools with mineral spirits.

DANGER – RAGS, STEEL WOOL, OR WASTE SOAKED WITH WOOD PROTECTOR SEMI-TRANSPARENT STAIN MAY SPONTANEOUSLY CATCH FIRE IF IMPROPERLY DISCARDED. IMMEDIATELY AFTER EACH USE, PLACE RAGS, STEEL WOOL, OR WASTE IN A SEALED, WATER-FILLED, METAL CONTAINER.

DISPOSAL: Contact your local environmental regulatory agency for guidance on disposal of unused product. Do not pour down a drain or storm sewer.

FLASH POINT: 107°F (42°C)

LIMITATIONS OF USE

Apply when no precipitation is expected for 24 hours, and when air and surface temperatures are 50°F to 90°F (10°C to 32°C) and will remain above 50°F (10°C) for the next 24 hours. Avoid staining in direct sunlight or on hot surfaces.

DO NOT THIN.

USE WITH ADEQUATE VENTILATION. KEEP OUT OF REACH OF CHILDREN. Read all label and Safety Data Sheet (SDS) information prior to use. SDS are available through our website or by calling 1-800-441-9695.

Read Label and Safety Data Sheet prior to use. See other cautions on last page.

Olympic Wood Protector Stain + Sealant in One Semi-Transparent

GENERAL SURFACE PREPARATION

Surface must be clean. Remove all dust, dirt, mildew, oil, loose wood fibers and other contaminants. Remove loose, peeling stain by sanding, scraping or wire brushing. To ensure proper adhesion, weathered, dirty or mildewed surfaces should be cleaned with *Olympic Deck Cleaner* prior to applying stain. After rinsing, ensure surface is free of standing water. Remove grade stamps or pencil marks by sanding.

WARNING! If you scrape, sand, or remove old paint, you may release lead dust or fumes. LEAD IS TOXIC. EXPOSURE TO LEAD DUST OR FUMES CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE. Wear a properly fitted NIOSH-approved respirator and prevent skin contact to control lead exposure. Clean up carefully with a HEPA vacuum and a wet mop. Before you start, find out how to protect yourself and your family by contacting the USEPA National Lead Information Hotline at 1-800-424-LEAD or log on to www.epa.gov/lead. In Canada, contact a regional Health Canada office. Follow these instructions to control exposure to other hazardous substances that may be released during surface preparation.

DECKS: Clean weathered, dirty or mildewed surfaces with *Olympic Deck Cleaner* prior to applying product.

FENCES OR SIDING: Remove and inhibit mildew with *Olympic Mildew Check® Multi-Purpose Wash*. Before use, be sure to read and follow the instructions and warnings on the label.

PRETEST: Test a small hidden area prior to application to ensure acceptable appearance and penetration.

PRIME: This product is self-priming over most substrates. Some woods, such as cedar and redwood, contain high amounts of tannin, a colored wood extract. The first coat of stain may show some discoloration, but the tannins will be trapped in the first coat of stain. A second coat will result in a uniform appearance.

EXTRACTIVE BLEEDING: Some woods, such as redwood and cedar contain high amounts of tannin, a colored wood extract. The first coat of stain may show some color discoloration, but the tannins will be trapped in the first coat of stain. A second coat will result in a uniform appearance.

APPLICATION INFORMATION

Apply when no precipitation is expected for 24 hours, and when air and surface temperatures are 50°F (10°C) to 90°F (32°C) and will remain above 50°F (10°C) for the next 24 hours. Avoid staining in direct sunlight or on hot surfaces. Intermix containers to ensure color uniformity. Stir thoroughly and often during use. Apply to a small area and allow stain to dry to ensure acceptable appearance and penetration. DO NOT THIN.

Apply one thin coat with a high quality brush, paint/stain pad or with spray equipment. When applying by roller or spray, always back-brush for best results. To help avoid lap marks, apply to only a few boards at a time, and maintain a wet edge.

Spray equipment must be handled with due care and in accordance with manufacturer's recommendations. High pressure injection of coatings into the skin by airless equipment may cause serious injury.

Permissible temperatures during application:

Material: 50 to 90°F 10 to 32°C

Ambient: 50 to 90°F 10 to 32°C

Substrate: 50 to 90°F 10 to 32°C

PRECAUTIONS

DANGER! COMBUSTIBLE LIQUID AND VAPOR. HARMFUL OR FATAL IF SWALLOWED. CAUSES RESPIRATORY TRACT AND EYE IRRITATION. Sanding and grinding dusts may be harmful if inhaled. Inhalation of high concentrations of vapor may affect the central nervous system. Repeated exposure to high vapor concentrations may cause irritation of the respiratory system and permanent brain and nervous system damage. High vapor concentrations can cause headaches, dizziness, drowsiness, and nausea and may lead to unconsciousness. Can enter lungs and cause damage. Keep away from heat and flame. Do not breathe vapor or mist. Do not swallow. Do not get on skin or clothing. Avoid contact with eyes. Keep container tightly closed and sealed until ready for use. Wash thoroughly after handling. Provide fresh air ventilation during and after application and drying. Avoid the inhalation of dust, particulates, spray, or mist arising from the application of this preparation. Use personal protective equipment as required. **Note: These warnings encompass the product series. Prior to use, read and follow product-specific SDS and label information. FIRST AID:** If swallowed, rinse mouth with water (only if the person is conscious). Call physician immediately. Do not induce vomiting unless directed to do so by medical personnel. If in eyes, rinse with water for 15 minutes. Check for and remove any contact lenses. If on skin, rinse well with water. Wash with soap and water. Get medical attention if irritation develops. If inhaled, remove to fresh air. If experiencing respiratory symptoms, call a POISON CENTER or doctor/physician. Contains isothiazolinones. May cause allergic reaction. Keep out of the reach of children. For workplace use, an SDS is available from your retailer or by calling (412) 492-5555. EMERGENCY SPILL INFORMATION: (412) 434-4515.

© 2021 PPG Industries, Inc. All Rights Reserved. *Olympic*, *Olympic & Design*, *Scuff Guard* and *SunBlock* are registered trademarks of PPG Architectural Finishes, Inc. The *PPG Logo* is a registered trademark of PPG Industries Ohio, Inc.

PPG Architectural Finishes, Inc. believes the technical data presented is currently accurate; however, no guarantee of accuracy, comprehensiveness, or performance is given or implied. Improvements in coatings technology may cause future technical data to vary from what is in this bulletin. For complete, up-to-date technical information, call 1-800-426-6306.

