

**OLYMPIC MAXIMUM® Clear Waterproofing Sealant****GENERAL DESCRIPTION**

OLYMPIC MAXIMUM Clear Sealant provides exceptional protection for wood. Its unique, penetrating formula enhances the natural look of wood while it strengthens, protects, and conditions wood fibers. Recommended for use on exterior wood decks, fences, siding, railings, outdoor furniture and other wood surfaces. Apply to new, dry, pressure-treated wood, uncoated new or weathered wood, or previously coated wood with a weathered, clear sealant or semi-transparent stain.

RECOMMENDED SUBSTRATES

Wood	Siding
Pressure-treated wood	Railings
Decks	Plywood
Fences	Outdoor Furniture

FEATURES / BENEFITS

Penetrating Formula for Strong Protection
Advanced *SunBlock*® U.V. Protection
Exclusive *Scuff Guard*® Formula
Provides a Mildew Resistant Coating
Enhanced Waterproofing Protection

LIMITATIONS OF USE

Apply when air and surface temperatures are 50°F to 90°F (10°C to 32°C) and will remain above 50°F (10°C) for the next 24 hours. Avoid application in direct sunlight or on hot surfaces. Caution: Avoid direct skin contact with hot surfaces. It is not recommended to apply product if rain is expected within 24 hours.

While this product provides a mildew resistant coating, growth may still occur if the substrate is not properly prepared prior to painting and/or if the substrate is consistently exposed to conditions conducive to mold, mildew, and algae. Examples of these conditions include, but are not limited to, under eaves, behind shrubbery and trees, and in areas that are consistently damp with little to no direct sunlight.

Not recommended for recently painted or sealed surfaces. Do not use on plastic, rubber, asphalt, tile, vinyl, concrete or any non-porous surface.

FOR EXTERIOR USE ONLY.

PRODUCT INFORMATION

57500 Clear Waterproofing Sealant

DO NOT TINT.

PRODUCT DATA

PRODUCT TYPE:	Oil Resin
VOLUME SOLIDS:	31% +/- 2%
WEIGHT SOLIDS:	37% +/- 2%
VOC:	<550 g/L (4.6 lbs./gal.)
WEIGHT/GALLON:	7.1 lbs. (3.2 kg) +/- 0.2 lbs. (91 g)

COVERAGE: Approximately 250 to 350 sq. ft. (23.2 to 32.5 sq. meters) per gallon (3.78 L) depending upon wood texture. One coat application is recommended.

Coverage figures do not include loss due to surface irregularities and porosity or material loss due to application method or mixing.

DRYING TIME: Normally dries in 24 hours when applied in temperatures of 50°F (10°C) to 85°F (29°C). High humidity or low temperature application may prolong drying time.

Drying times listed may vary depending on temperature, humidity, film build, and air movement.

CLEANUP: Clean brushes and tools with mineral spirits.

DANGER - RAGS, STEEL WOOL OR WASTE SOAKED WITH MAXIMUM CLEAR WATERPROOFING SEALANT MAY SPONTANEOUSLY CATCH FIRE IF IMPROPERLY DISCARDED. IMMEDIATELY AFTER EACH USE, PLACE RAGS, STEEL WOOL OR WASTE IN A SEALED WATER-FILLED METAL CONTAINER.

DISPOSAL: Contact your local environmental regulatory agency for guidance on disposal of unused product. Do not pour down a drain or storm sewer.

FLASH POINT: 108°F (42°C)

PACKAGING

5-Gallon (18.9 L)
1-Gallon (3.78 L)
Quart (946 mL)

OLYMPIC MAXIMUM Waterproofing Sealant Clear

GENERAL SURFACE PREPARATION

Proper surface preparation is essential for the *OLYMPIC* limited warranty to apply. Surface must be clean, dry and free of all dust, dirt, mildew, oil, loose wood fibers, and other contaminants. Previous coatings must be completely removed. Prior to sealant application, clean weathered, dirty, or mildewed surfaces with *OLYMPIC* Deck Cleaner. After rinsing, allow wood to dry. Remove grade stamps or pencil marks by sanding. **WARNING!** If you scrape, sand, or remove old paint, you may release lead dust or fumes. **LEAD IS TOXIC. EXPOSURE TO LEAD DUST OR FUMES CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE.** Wear a properly fitted NIOSH-approved respirator and prevent skin contact to control lead exposure. Clean up carefully with a HEPA vacuum and a wet mop. Before you start, find out how to protect yourself and your family by contacting the USEPA National Lead Information Hotline at 1-800-424-LEAD or log on to www.epa.gov/lead. Follow these instructions to control exposure to other hazardous substances that may be released during surface preparation.

FENCES, SIDING OR DECKS: Clean weathered, dirty or mildewed surfaces with *OLYMPIC* Deck Cleaner prior to applying product. Before use, be sure to read and follow the instructions and warnings on the label.

PRETEST: Test a small hidden area prior to application to ensure acceptable appearance and penetration.

EXTRACTIVE BLEEDING: Some woods, such as redwood and cedar contain natural water-soluble colorings or extractives that tend to “bleed” or migrate to the surface. If extractive bleeding occurs, allow the coating to dry completely, then wash with a mild detergent solution and rinse with clear water.

APPLICATION INFORMATION

Stir thoroughly before and often during use.

Pretest: Apply to a small area and allow to dry to ensure applicable appearance and penetration. For previously coated wood: If the product is not absorbed into the surface and is still tacky after 12 hours, the surface is not suitable for a waterproofing sealant. For damp wood: If wood is too damp to allow penetration, allow to dry further and retest for penetration.

Application Method: Apply one thin coat. To help avoid lapmarks, apply to only a few boards at a time keeping a wet edge. Do not saturate or puddle on horizontal surfaces.

Application Equipment: Apply with a high quality brush, paint / stain pad or by spray equipment. When spraying, always back brush for best results. To help avoid lap marks, apply to only a few boards at a time, and maintain a wet edge.

Thinning: DO NOT THIN.

PRECAUTIONS

DANGER! COMBUSTIBLE LIQUID AND VAPOR. HARMFUL OR FATAL IF SWALLOWED. CAUSES RESPIRATORY TRACT AND EYE IRRITATION. Inhalation of high concentrations of vapor may affect the central nervous system. Repeated exposure to high vapor concentrations may cause irritation of the respiratory system and permanent brain and nervous system damage. High vapor concentrations can cause headaches, dizziness, drowsiness and nausea and may lead to unconsciousness. Can enter lungs and cause damage. Keep away from heat and flame. Do not breathe vapor or mist. Do not swallow. Avoid contact with eyes. Keep container tightly closed and sealed until ready for use. Wash thoroughly after handling. Provide fresh air ventilation during and after application and drying. Avoid the inhalation of dust, particulates, spray or mist arising from the application of this preparation. Use personal protective equipment as required. **DANGER - RAGS, STEEL WOOL OR WASTE SOAKED WITH MAXIMUM CLEAR WATERPROOFING SEALANT MAY SPONTANEOUSLY CATCH FIRE IF IMPROPERLY DISCARDED. IMMEDIATELY AFTER EACH USE, PLACE RAGS, STEEL WOOL OR WASTE IN A SEALED WATER-FILLED METAL CONTAINER.** **Note: These warnings encompass the product series. Prior to use, read and follow product-specific MSDS and label information.** **FIRST AID:** If swallowed, rinse mouth with water (only if the person is conscious). Call physician immediately. Do not induce vomiting unless directed to do so by medical personnel. If in eyes, rinse with water for 15 minutes. Check for and remove any contact lenses. If on skin, rinse well with water. Wash with soap and water. Get medical attention if irritation develops. If inhaled, remove to fresh air. If experiencing respiratory symptoms call a POISON CENTER or doctor/physician. Keep out of the reach of children. For workplace use, an MSDS is available from your retailer or by calling (412) 492-5555. EMERGENCY SPILL INFORMATION: (412) 434-4515 (U.S.).

The PPG logo is a registered trademark of PPG Industries Ohio, Inc. *Olympic*, *Olympic & Design*, *MAXIMUM*, *Scuff Guard*, and *SunBlock* are registered trademarks of PPG Architectural Finishes, Inc.

PPG Architectural Finishes, Inc. believes the technical data presented is currently accurate; however, no guarantee of accuracy, comprehensiveness, or performance is given or implied. Improvements in coatings technology may cause future technical data to vary from what is in this bulletin. For complete, up-to-date technical information, call 1-800-426-6306.



Olympic - US
PPG Industries, Inc.
Architectural Coatings
One PPG Place
Pittsburgh, PA 15272
www.olympic.com

Technical Services
1-800-426-6306

Architect/Specifier
1-888-PPG-IDEA

Olympic - Canada
PPG Architectural Coatings Canada Inc.
2505, rue de la Métropole,
Longueuil (Québec) Canada J4G 1E5

T.D. 57500 2/2016