



OLYMPIC®

59000, 59000C

OLYMPIC Deck, Fence, & Siding Clear Waterproofing Sealant**GENERAL DESCRIPTION**

OLYMPIC Deck, Fence, & Siding Clear Waterproofing Sealant provides waterproofing protection with a clear finish that allows the wood to weather gray naturally, enhancing the natural beauty of wood.

Recommended for use on any properly prepared exterior wood, including decks, fences, siding, railings, outdoor furniture and other wood surfaces. Apply to new, dry, pressure-treated wood, uncoated new or weathered wood, or previously coated wood with a weathered, clear sealant or semi-transparent stain.

RECOMMENDED USES

Exterior wood surfaces	New wood
Decks	Pressure-treated wood
Fences	Weathered wood
Siding	Outdoor Furniture

FEATURES / BENEFITS

Protects Against Water Damage
SunBlock® UV Defense
Exclusive Scuff Guard® Technology
Provides Mildew Resistant Coating
Easy Water Cleanup

APPLICATION INFORMATION

Stir thoroughly before and occasionally during use. When using more than one container of the same color, intermix to ensure color uniformity.

Pretest: Apply to a small area and allow to dry to ensure acceptable appearance and penetration.

Application Equipment: Apply with a high quality brush, paint pad or spray equipment.

Application Method: Apply one thin coat. When spraying, always back brush for best results. To help avoid lapmarks, apply to only a few boards at a time keeping a wet edge. Do not saturate or puddle on horizontal surfaces.

Thinning: DO NOT THIN.

Permissible temperatures during application:

Material:	50 to 90°F	10 to 32°C
Ambient:	35 to 90°F	2 to 32°C
Substrate:	35 to 90°F	2 to 32°C

PRODUCT INFORMATION

59000, 59000C Clear Sealant

DO NOT TINT.

PRODUCT DATA

PRODUCT TYPE: Acrylic Oil
VOLUME SOLIDS: 15% +/- 2%
WEIGHT SOLIDS: 16% +/- 2%
VOC: <100 g/L (0.8 lbs./gal.)

WEIGHT/GALLON: 8.4 lbs. (3.8 kg) +/- 0.2 lbs. (91 g)

COVERAGE: Approximately 250 to 350 sq. ft. (23.2 to 32.5 sq. meters) per gallon (3.78 Liters) depending upon wood texture.

Coverage figures do not include loss due to surface irregularities and porosity or material loss due to application method or mixing.

DRYING TIME: Normally dries in 24 hours when applied in temperatures of 50°F (10°C) to 85°F (29°C). High humidity or low temperature application may prolong drying time. It is not recommended to apply product if rain is expected within 24 hours.

Drying times listed may vary depending on temperature, humidity, color and air movement.

CLEANUP: Clean brushes and tools with warm, soapy water.

DANGER: Rags, steel wool or waste soaked with this product may spontaneously catch fire if improperly discarded. Immediately after use, place rags, steel wool or waste in a sealed water-filled metal container. Refer to www.ppgpittsburghpaints.com, Spontaneous Combustion Advisory for additional information.

DISPOSAL: Contact your local environmental regulatory agency for guidance on disposal of unused product. Do not pour down a drain or storm sewer.

FLASH POINT: Over 200°F (93°C)

OLYMPIC Deck, Fence, & Siding Clear Waterproofing Sealant

GENERAL SURFACE PREPARATION

All surfaces must be dry, clean, and free of dirt, dust, mildew, oil, loose wood fibers, and other contaminants. Previous coatings must be completely removed. Prior to sealant application, clean weathered, dirty, or mildewed surfaces with *OLYMPIC* Deck Cleaner. After rinsing, ensure surface is free to standing water. Remove grade stamps or pencil marks. by sanding.

WARNING! If you scrape, sand, or remove old paint, you may release lead dust or fumes. **LEAD IS TOXIC. EXPOSURE TO LEAD DUST OR FUMES CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE.** Wear a properly fitted NIOSH-approved respirator and prevent skin contact to control lead exposure. Clean up carefully with a HEPA vacuum and a wet mop. Before you start, find out how to protect yourself and your family by contacting the USEPA National Lead Information Hotline at 1-800-424-LEAD or log on to www.epa.gov/lead. In Canada, contact a regional Health Canada office. Follow these instructions to control exposure to other hazardous substances that may be released during surface preparation.

DECKS, FENCES OR SIDING: Clean weathered, dirty or mildewed surfaces with *OLYMPIC* Deck Cleaner prior to applying product.

PRETEST: Test a small hidden area prior to application to ensure acceptable appearance and penetration. If the product is not absorbed into the surface or is still tacky after 12 hours, the surface is not suitable for a waterproofing sealant. Tacky areas may be wiped clean with mineral spirits or MEK (Methyl Ethyl Ketone).

EXTRACTIVE BLEEDING: Some woods, such as cedar and redwood, contain natural water-soluble colorings or extractives that tend to "bleed" or migrate to the surface. If extractive bleeding occurs, allow the coating to dry completely, then wash with a mild detergent solution and rinse with clear water.

LIMITATIONS OF USE

Apply when air, and surface temperatures are 35°F to 90°F (2°C to 32°C) and will remain above 35°F (2°C) for the next 24 hours. Avoid sealing in direct sunlight or on hot surfaces. It is not recommended to apply product if rain is expected within 24 hours.

While this product provides a mildew resistant coating, growth may still occur if the substrate is not properly prepared prior to painting and/or if the substrate is consistently exposed to conditions conducive to mold, mildew, and algae. Examples of these conditions include, but are not limited to, under eaves, behind shrubbery and trees, and in areas that are consistently damp with little to no direct sunlight.

FOR EXTERIOR USE ONLY. Not recommended for recently painted or sealed surfaces. Do not use on metallic, plastic, rubber, asphalt, tile, vinyl, concrete or any non-porous surface.

PROTECT FROM FREEZING.

SAFETY PRECAUTIONS

Before using the products listed in this publication, carefully read each product label and follow directions for its use. Please read and observe all the warnings and precautionary information on the product labels. Material Safety Data Sheets are available through our Sales Representative, Retailer or by calling (412) 492-5555.

Spray equipment must be handled with due care and in accordance with manufacturer's recommendations. High pressure injection of coatings into the skin by airless equipment may cause serious injury.

USE WITH ADEQUATE VENTILATION. KEEP OUT OF REACH OF CHILDREN.

PACKAGING

1-Gallon (3.78 L)

5-Gallon (18.9 L)

The PPG logo is a registered trademark of PPG Industries Ohio, Inc. *OLYMPIC*, *OLYMPIC* design, *SunBlock* and *Scuff Guard* are registered trademarks of PPG Architectural Finishes, Inc.

PPG Architectural Finishes, Inc. believes the technical data presented is currently accurate; however, no guarantee of accuracy, comprehensiveness, or performance is given or implied. Improvements in coatings technology may cause future technical data to vary from what is in this bulletin. For complete, up-to-date technical information, call 1-800-426-6306.



PPG Industries, Inc.
Architectural Coatings
One PPG Place
Pittsburgh, PA 15272
www.olympic.com

Technical Services
1-800-426-6306

Architect/Specifier
1-888-PPG-IDEA

PPG Architectural Coatings Canada Inc.
4 Kenview Boulevard
Brampton, ON L6T 5E4

T.D. 59000, 59000C
10/2013