



OLYMPIC® ELITE™

802102 Series

Olympic Elite Semi-Transparent/Semi-Solid Stain + Sealant

GENERAL DESCRIPTION

Olympic Elite Semi-Transparent/Semi-Solid is a premium stain + sealant formulated with pigments that deliver rich, color clarity while providing a durable **ALL-CLIMATE PROTECTION PACKAGE™**. *Olympic Elite* is recommended for use on any properly prepared exterior wood, including decks, fences, siding, railings, outdoor furniture, and other wood surfaces.

PRODUCT DATA

PRODUCT TYPE:	Acrylic/Oil
VOLUME SOLIDS*:	19% +/- 2%
WEIGHT SOLIDS*:	21% +/- 2%
WEIGHT/GALLON*:	8.4 lbs. (3.8 kg) +/- 0.2 lbs. (91 g)
VOC:	< 100 g/L (0.8 lbs./gal.)

*Product data calculated on 802102.

RECOMMENDED SUBSTRATES

Wood	Siding
Decks	Railings
Fences	Outdoor Furniture

FEATURES / BENEFITS

A Lifetime of Durability & Beauty
4 Season Protection
Waterproofing Protection
Resists Peeling & Cracking
Provides Mildew Resistant Finish
2-Hour Rain Ready

COVERAGE: Approximately 250 to 350 sq. ft. (23 to 33 sq. meters) per gallon (3.78 Liters) depending on application technique, wood texture and porosity. Coverage figures do not include loss due to surface irregularities and porosity or material loss due to application method or mixing.

DRYING TIME: Normally dries in 4 hours when applied in optimal temperatures of 50°F (10°C) to 85°F (29°C). Application in high humidity or in temperatures below 50°F (10°C) may prolong drying times. Allow 24 to 48 hours of drying time before light foot traffic or replacing furniture.

READY FOR RAIN: Allow paint film to dry for at least 2 hours prior to expected rain when temperatures are at or above 60°F (16°C) and 50 to 70% relative humidity. Lower temperatures, higher humidity, or deeper colors may increase drying time and rain readiness time.

CLEANUP: Clean brushes and tools with warm, soapy water.

DISPOSAL: Contact your local environmental regulatory agency for guidance on disposal of unused product. Do not pour down a drain or storm sewer.

FLASH POINT: Over 200°F (93°C)

PRODUCT INFORMATION

802102	Atlas Cedar/Tintable Base
802142	American Chestnut/Tintable Base

Refer to the appropriate color formula book, automatic tinting equipment, and or computer color matching system for color formulas and tinting instructions.

PACKAGING

1-Gallon (3.78 L)
5-Gallon (18.9 L)

Not all products available in all sizes.

LIMITATIONS OF USE

FOR EXTERIOR USE ONLY. FOR WOOD SUBSTRATES ONLY.

USE WITH ADEQUATE VENTILATION. KEEP OUT OF REACH OF CHILDREN. Read all label and Safety Data Sheet (SDS) information prior to use. SDS are available through our website or by calling 1-800-441-9695.

Apply when air and surface temperatures are between 35°F (2°C) and 90°F (32°C) and at least 5°F (3°C) above the dew point. Air and surface temperatures must remain between 35°F (2°C) and 90°F (32°C) for the next 24 hours. Avoid staining in direct sunlight or on hot surfaces.

While this product provides a mildew resistant coating, growth may still occur if the substrate is not properly prepared prior to painting and/or if the substrate is consistently exposed to conditions conducive to mold, mildew, and algae. Examples of these conditions include, but are not limited to, under eaves, behind shrubbery and trees, and in areas that are consistently damp with little to no direct sunlight.

PROTECT FROM FREEZING.

Read Label and Safety Data Sheet prior to use. See other cautions on last page.

801102

Olympic Elite Semi-Transparent/Semi-Solid Stain + Sealant**GENERAL SURFACE PREPARATION**

Surface must be clean and dry. Remove all dust, dirt, mildew, oil, loose wood fibers, and other contaminants. Previous coatings must be completely removed. To ensure proper penetration, weathered, dirty, or mildewed surfaces should be cleaned with a wood cleaner prior to applying stain. After rinsing, allow wood to dry. Sand all cleaned wood using 80-120 grit sandpaper for vertical surfaces and 60-80 grit sandpaper for horizontal surfaces. Always sand in direction of the wood grain and remove sanding dust. Test wood for absorbency by sprinkling water on the surface – if water is absorbed within 30 sec. to 2 min., depending on climate, the surface is ready for staining.

WARNING! If you scrape, sand, or remove old paint, you may release lead dust or fumes. LEAD IS TOXIC. EXPOSURE TO LEAD DUST OR FUMES CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE. Wear a properly fitted NIOSH-approved respirator and prevent skin contact to control lead exposure. Clean up carefully with a HEPA vacuum and a wet mop. Before you start, find out how to protect yourself and your family by contacting the USEPA National Lead Information Hotline at 1-800-424-LEAD or log on to www.epa.gov/lead. In Canada, contact a regional Health Canada office. Follow these instructions to control exposure to other hazardous substances that may be released during surface preparation.

NEW WOOD and PRESSURE TREATED LUMBER: Mill glaze must be removed and wood must pass water absorption test.

APPLICATION INFORMATION

Stir thoroughly and often during use. Apply to a small area and allow stain to dry to ensure acceptable appearance and penetration.

Application Method: Two coats are recommended for maximum durability. To help avoid lap marks, apply to only a few boards at a time, and maintain a wet edge. Apply second coat between 4 to 72 hours after first coat.

Application Equipment: Apply with a high-quality brush, paint/stain-pad, or with spray equipment. When applying by roller or spray, always back-brush for best results.

Spray equipment must be handled with due care and in accordance with manufacturer's recommendations. High pressure injection of coatings into the skin by airless equipment may cause serious injury.

Thinning: DO NOT THIN.

Permissible temperatures during application:

Material: 35 to 90°F (2 to 32°C)

Ambient 35 to 90°F (2 to 32°C)

Substrate: 35 to 90° (2 to 32°C)

PRECAUTIONS

For warning information, please refer to the SDS and label. Keep container tightly closed and sealed until ready for use. SDS, spill, and emergency information are available by calling 1-833-477-1553

© 2025 The Pittsburgh Paints Co. All Rights Reserved. *Olympic*, *Olympic and Design*, and *Paintbrush Design* are registered trademarks and *Elite* and *All-Climate Protection Package* are trademarks of The Pittsburgh Paints Co.

The Pittsburgh Paints Co. believes the technical data presented is currently accurate; however, no guarantee of accuracy, comprehensiveness, or performance is given or implied. Improvements in coatings technology may cause future technical data to vary from what is in this bulletin. For complete, up-to-date technical information, call 1-800-441-9695.



**PITTSBURGH
PAINTS CO.**

The Pittsburgh Paints Co.
400 Bertha Lamme Drive
Cranberry Township, PA 16066
www.olympic.com

Technical Services
1-800-441-9695

802102 - 8/2025