

Architectural Coatings

Pure Performance Paint & Primer in One Interior Eggshell Latex

GENERAL DESCRIPTION

Our premium low-odor, zero-VOC** (volatile organic compounds) eggshell latex is designed to meet the performance requirements of the institutional, commercial and residential markets. *Pure Performance* Paint & Primer in One Interior Eggshell Latex is formulated to provide excellent hiding and application properties in addition to low odor, zero VOC's**, and anti-microbial properties - a mold/mildew resisting compound has been incorporated in this paint to make the dry paint film mildew resistant. Ideal for use in occupied areas such as: hotel/motel resort properties, nursing homes, homes, schools, government facilities, retail space, office buildings, hospitals, and apartments.

RECOMMENDED USES

Concrete/Masonry Block	Plaster	Wood
Ferrous Metal	Gypsum Wallboard-Drywall	

CONFORMANCE STANDARDS

- ✔ VOC compliant in all regulated areas
- ✔ Can help earn LEED® 2009 Credits
- ✔ Meets GREENGUARD® Indoor Air Quality Certified® and GREENGUARD Children & Schools Certified™
- ✔ Meets the Collaborative for High Performance Schools (CHPS) Low-Emitting Materials criteria section 01350
- ✔ MPI® approval in category #144 Latex, Interior, Institutional Low Odor/VOC, (MPI Gloss Level 2)
- ✔ Meets MPI Green Performance Standard (GPS-1 & GPS-2)
- ✔ MPI approval in category #144 X-Green

PACKAGING

1-Gallon (3.78 L)
5-Gallon (18.9 L)
Quart (946 mL)
Not all products are available in all sizes.

LIMITATIONS OF USE

Apply when air, surface and product temperatures are above 50°F (10°C). PROTECT FROM FREEZING. Not recommended for use on floors.

While this product provides a mildew resistant coating, growth may still occur if the substrate is not properly prepared prior to painting and/or if the substrate is consistently exposed to conditions conducive to mold, mildew, and algae. Examples of these conditions include, but are not limited to areas that are consistently damp with little to no direct sunlight.

FEATURES / BENEFITS

Features

0 g/L VOC**
Low odor
100% acrylic
Antimicrobial properties
Good hiding power and coverage
Soap and water clean-up
MPI approval in Category # 144 Latex, Interior, Institutional Low Odor/VOC, (MPI Gloss Level 2)
MPI approval in Category #144 X-Green
Can help earn LEED 2009 credits

Benefits

Meets the most stringent VOC regulations nationwide
Ideal for painting in occupied spaces
Excellent durability and washable finish
Resists mold and mildew on the paint film
Saves money; less material required
Safe waterborne formula
Meets strict performance and aesthetic requirements

Meets MPI's most stringent environmental standard
Contributes to sustainable design

**Colorants added to this base paint may increase VOC level significantly depending on color choice.

TINTING AND BASE INFORMATION

Refer to the appropriate color formula book, automatic tinting equipment, and or computer color matching system for color formulas and tinting instructions.

9-300XI	Pure White
9-310	Pastel Base*
9-320	Midtone Base*
9-340	Ultra Deep Base*

*Must be tinted.

Some colors, drastic color changes, or porous substrates may require more than one coat to achieve a uniform finish.

PRODUCT DATA

PRODUCT TYPE:	100% Acrylic Latex
GLOSS:	Eggshell: 3 to 10 @60°
VOLUME SOLIDS*:	35% +/- 2%
WEIGHT SOLIDS*:	51% +/- 2%
VOC:	0 lbs./gal (0 g/L)**

WEIGHT/GALLON*:	11.1 lbs. (5.0 kg) +/- 0.2 lbs. (91 g)
------------------------	--

*Product data calculated on product 9-300XI.

COVERAGE*: Approximately 400 sq. ft./gal. (37 sq. m/3.78L) per U.S. gallon (3.78 L) on nonporous surfaces.

Wet Film Thickness:	4.0 mils
Wet Microns:	102
Dry Film Thickness:	1.4 mils
Dry Microns:	35

Coverage figures do not include loss due to surface irregularities and porosity or material loss due to application method or mixing.

DRYING TIME: Dry time @ 77°F (25°C); 50% relative humidity.

To Touch:	1 hour
To Recoat:	4 hours

Drying times listed may vary depending on temperature, humidity, film build, color, and air movement.

WASHING INSTRUCTIONS: Wait at least 14 days after painting before cleaning the surface with a non-abrasive mild cleaner.

CLEANUP: Clean tools with warm soapy water.

DISPOSAL: Contact your local environmental regulatory agency for guidance on disposal of unused product. Do not pour down a drain or storm sewer.

FLASH POINT:	Over 200°F (93°C)
---------------------	-------------------

GENERAL SURFACE PREPARATION

Surface must be dry. Remove all loose, peeling paint, dirt, grease, and any other surface contaminants. Putty all nail holes and caulk all cracks and open seams. Sand all glossy, rough, and patched surfaces. This product is self-priming for previously painted walls and ceilings in good condition. However, when applied to new drywall, two coats are required with the first coat acting as the primer. Prime all wood, plaster, masonry, metal and porous surfaces with the appropriate PPG primer.

WARNING! If you scrape, sand, or remove old paint, you may release lead dust or fumes. LEAD IS TOXIC. EXPOSURE TO LEAD DUST OR FUMES CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE. Wear a properly fitted NIOSH-approved respirator and prevent skin contact to control lead exposure. Clean up carefully with a HEPA vacuum and a wet mop. Before you start, find out how to protect yourself and your family by contacting the USEPA National Lead Information Hotline at 1-800-424-LEAD or log on to www.epa.gov/lead. In Canada contact a regional Health Canada office. Follow these instructions to control exposure to other hazardous substances that may be released during surface preparation.

CONCRETE/MASONRY BLOCK: Mortar should cure for at least 30 days and preferably 90 days prior to priming. Fill block with an appropriate block filler. Surfaces previously coated with water thinned cement-based paint must be prepared with extra care. If the material appears to be adhering tightly, a masonry sealer may be applied to seal the surface. Check adhesion by applying a piece of masking tape. If the sealer peels off and has loose particles, remove all chalking or crumbling material, re-seal and re-check adhesion.

FERROUS METAL: The surface must be cleaned thoroughly to remove any dust, rust, and surface contaminants, and then primed.

GYPSUM WALLBOARD-DRYWALL: Nails or screws should be countersunk, and they along with any indentations should be mudded flush with the surface, sanded smooth and cleaned to remove any dust, then prime prior to painting the substrate.

PLASTER: Plaster, hardcoat, skim coat, or other alkaline surfaces should be allowed to cure for at least 30 days prior to priming with an alkali resistant primer.

WOOD: Unpainted wood or wood in poor condition should be sanded smooth, wiped clean, then primed. Any knots or resinous areas must be primed before painting. Countersink all nails, putty flush with surface, then prime.

RECOMMENDED PRIMERS

Concrete/Masonry Block (Block Fillers)	6-7, 6-15
Concrete, Masonry (Primers, Sealers)	4-603, 17-921
Gypsum Drywall-Wallboard	6-2, 6-4, 6-4900, 9-900, 12-900, self-priming
Ferrous Metal	90-712, 90-912
Plaster	4-603, 9-900, 17-921
Wood	6-2, 6-4900, 9-900, 12-900, 17-921

APPLICATION INFORMATION

Stir thoroughly. Apply with a high quality brush, roller, paint pad or by spray equipment. Read all label and Material Safety Data Sheet (MSDS) information prior to use. MSDS are available through our website or by calling 1-800-441-9695.

Airless Spray: Pressure 2000 psi, tip 0.015" - 0.021"
Spray equipment must be handled with due care and in accordance with manufacturer's recommendation. High-pressure injection of coatings into the skin by airless equipment may cause serious injury.

Brush: Polyester/Nylon Brush

Roller: 3/8" - 3/4" nap roller cover

Thinning: No thinning is required.

Permissible temperatures during application:

Material:	50 to 90°F	10 to 32°C
Ambient:	50 to 100°F	10 to 38°C
Substrate:	50 to 100°F	10 to 38°C

PRECAUTIONS

WARNING! MAY BE HARMFUL IF INHALED OR SWALLOWED. MAY CAUSE RESPIRATORY TRACT IRRITATION. Sanding and grinding dusts may be harmful if inhaled. Contains material that can cause target organ damage. Avoid breathing vapor or mist. Wash thoroughly after handling. Keep container tightly closed and sealed until ready for use. Provide fresh air ventilation during and after application and drying. Avoid the inhalation of dust, particulates, spray or mist arising from the application of this preparation. Use personal protective equipment as required. **Note: These warnings encompass the product series. Prior to use, read and follow product-specific MSDS and label information.** **FIRST AID:** If swallowed, rinse mouth with water (only if the person is conscious). Do not induce vomiting unless directed to do so by medical personnel. If in eyes, rinse with water for 15 minutes. Check for and remove any contact lenses. If on skin, rinse well with water. Wash with soap and water. Get medical attention if irritation develops. If inhaled, remove to fresh air. If experiencing respiratory symptoms call a POISON CENTER or doctor/physician. Keep out of the reach of children. For workplace use, an MSDS is available from your retailer or by calling (412) 492-5555. **EMERGENCY SPILL INFORMATION:** (412) 434-4515 (U.S.).

The PPG logo is a registered trademark and PPG Paints and Ecological Solutions from PPG are trademarks of PPG Industries Ohio, Inc. Pure Performance is a registered trademark of PPG Architectural Finishes, Inc. The GREENGUARD Indoor Air Quality Certified Mark is a registered certification mark used under license through the GREENGUARD Environmental Institute. LEED is a registered trademark of the US Green Building Council. The Master Painters Institute and MPI are registered trademarks of Master Painters Institute, Inc.

PPG Architectural Finishes, Inc. believes the technical data presented is currently accurate; however, no guarantee of accuracy, comprehensiveness, or performance is given or implied. Improvements in coatings technology may cause future technical data to vary from what is in this bulletin. For complete, up-to-date technical information, visit our web site or call 1-800-441-9695.



PPG Industries, Inc.
Architectural Coatings
One PPG Place
Pittsburgh, PA 15272
www.ppgpro.com

Technical Services
1-800-441-9695
1-888-807-5123 fax

Architect/Specifier
1-888-PPG-IDEA

PPG Architectural Coatings Canada Inc.
2505, rue de la Metropole
Longueuil (Quebec) Canada J4G 1E5

TD 9-300XI 12/2016
(Supersedes 8/2014)

