



Architectural Coatings

Pure Performance Interior Latex Primer

GENERAL DESCRIPTION

Our premium low-odor, zero-VOC** (volatile organic compounds) primer is designed to meet the performance requirements of the institutional, commercial and residential markets. Pure Performance Interior Latex Primer is formulated to provide excellent sealing, hiding and application with low-odor and zero-VOC** properties. Ideal for use in occupied areas such as: hotel/motel resort properties, nursing homes, homes, schools, government facilities, retail space, office buildings, hospitals, and apartments.

RECOMMENDED USES

- Gypsum Wallboard-Drywall
- Plaster
- Wood

CONFORMANCE STANDARDS

- VOC compliant in all regulated areas
- Can help earn LEED® 2009 credits
- Meets GREENGUARD® Indoor Air Quality Certified® and GREENGUARD Children & Schools CertifiedSM
- Meets the Collaborative for High Performance (CHPS) Low-Emitting Materials criteria section 01350

APPLICATION INFORMATION

Stir thoroughly. Apply with a high quality brush, roller, paint pad or by spray equipment. Read all label and Material Safety Data Sheet (MSDS) information prior to use. MSDS are available through our website or by calling 1-800-441-9695.

Airless Spray: Pressure 2000 psi, tip 0.015" - 0.021"

Spray equipment must be handled with due care and in accordance with manufacturer's recommendation. High-pressure injection of coatings into the skin by airless equipment may cause serious injury.

Brush: Polyester/Nylon Brush
Roller: 3/8" - 3/4" nap roller cover

APPLICATION INFORMATION

Thinning: No thinning is required. If necessary, thin with up to 1/4 pt. (118 mL) of water per U.S. gallon (3.78 L) of primer may be added.

Permissible temperatures during application:

Material:	50 to 90°F	10 to 32°C
Ambient:	50 to 90°F	10 to 32°C
Substrate:	50 to 90°F	10 to 32°C

PRODUCT DATA

PRODUCT TYPE:	100% Acrylic Latex
GLOSS:	Flat: 2 to 6 (60° Gloss Meter)
VOLUME SOLIDS:	35% +/- 2%
WEIGHT SOLIDS:	50% +/- 2%
VOC**:	0 lbs./gal (0 g/L)

WEIGHT/GALLON: 10.8 lbs. (4.9 kg) +/- 0.2 lbs. (91 g)

COVERAGE: Approximately 400 sq. ft./gal. (37 sq. m/3.78L) per U.S. gallon (3.78 L) on nonporous surfaces.

Wet Film Thickness:	4.0 mils
Wet Microns:	102
Dry Film Thickness:	1.4 mils
Dry Microns:	36

Coverage figures do not include loss due to surface irregularities and porosity or material loss due to application method or mixing.

DRYING TIME: Dry time @77°F (25°C); 50% relative humidity.

To Touch:	1 hour
To Recoat:	4 hours

Drying times listed may vary depending on temperature, humidity, film build, color, and air movement.

WASHING INSTRUCTIONS: Wait at least 14 days after painting before cleaning the surface with a non-abrasive mild cleaner.

CLEANUP: Clean tools with warm soapy water.

DISPOSAL: Contact your local environmental regulatory agency for guidance on disposal of unused product. Do not pour down a drain or storm sewer.

FLASH POINT: Over 200°F (93°C)

FEATURES / BENEFITS

Features

- 0 g/L VOC**
- Low odor
- 100% Acrylic
- Moisture resistant
- Excellent adhesion
- Excellent enamel holdout
- Soap and water clean-up
- Can help earn LEED 2009 credits

Benefits

- Meets the most stringent environmental regulations nationwide
- Ideal for painting in occupied spaces
- Excellent durability and washable finish
- Minimizes water streaking
- Adheres to difficult substrates
- Promotes even sheen in topcoats
- Safe waterborne formula
- Contributes to sustainable design

**Colorants added to this base paint may increase VOC level significantly depending on color choice.

GENERAL SURFACE PREPARATION

Surfaces to be coated must be dry, clean, sound, and free from all contamination including loose and peeling paint, dirt, grease, oil, wax, concrete curing agents and bond breakers, chalk, efflorescence, mildew, rust, product fines, and dust. Remove loose paint, chalk, and efflorescence by wire brushing, scraping, sanding, and/or pressure washing. Putty all nail holes and caulk all cracks and open seams. Sand all glossy, rough, and patched surfaces. Feather back all rough edges to sound surface by sanding.

WARNING! If you scrape, sand, or remove old paint, you may release lead dust or fumes. LEAD IS TOXIC. EXPOSURE TO LEAD DUST OR FUMES CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE. Wear a properly fitted NIOSH-approved respirator and prevent skin contact to control lead exposure. Clean up carefully with a HEPA vacuum and a wet mop. Before you start, find out how to protect yourself and your family by contacting the USEPA National Lead Information Hotline at 1-800-424-LEAD or log on to www.epa.gov/lead. In Canada contact a regional Health Canada office. Follow these instructions to control exposure to other hazardous substances that may be released during surface preparation.

GYPSUM WALLBOARD-DRYWALL: Nails or screws should be countersunk, and they along with any indentations should be mudded flush with the surface, sanded smooth and cleaned to remove any dust before priming the substrate.

PLASTER: Plaster, hardcoat, skim coat, or other alkaline surfaces should be allowed to cure for at least 30 days prior to priming with an alkali resistant primer.

WOOD: Unpainted wood or wood in poor condition should be sanded smooth and wiped clean before priming the substrate. Spot prime knots or resinous areas before the application of the first full coat of primer. Nails or screws should be countersunk, and they along with any indentations should be mudded flush with the surface, sanded smooth and cleaned to remove any dust before priming the substrate.

LIMITATIONS OF USE

FOR INTERIOR USE ONLY. Apply when air, surface and product temperatures are between 50°F (10°C) and 90°F (32°C).

PROTECT FROM FREEZING.

Not recommended for use on floors.

PACKAGING

1-Gallon (3.78 L)

Quart (946 mL)

TINTING AND BASE INFORMATION

May be tinted to approximate color of the topcoat. Refer to the appropriate color formula book, automatic tinting equipment, and or computer color matching system for color formulas and tinting instructions.

9-900

White

Some colors, or drastic color changes, may require more than one coat to achieve a uniform finish

The PPG logo is a registered trademark and *Ecological Solutions from PPG* is a trademark of PPG Industries, Ohio, Inc. *Pure Performance* is a registered trademark of PPG Architectural Finishes, Inc. The *GREENGUARD* Indoor Air Quality Certified Mark is a registered certification mark used under license through the GREENGUARD Environmental Institute. *LEED* is a registered trademark of the US Green Building Council.

PPG Architectural Finishes, Inc. believes the technical data presented is currently accurate; however, no guarantee of accuracy, comprehensiveness, or performance is given or implied. Improvements in coatings technology may cause future technical data to vary from what is in this bulletin. For complete, up-to-date technical information, visit our web site or call 1-800-441-9695.



PPG Industries, Inc.
Architectural Coatings
One PPG Place
Pittsburgh, PA 15272
www.ppgpro.com

Technical Services
1-800-441-9695
1-888-807-5123 fax

Architect/Specifier
1-888-PPG-IDEA

PPG Canada, Inc.
Architectural Coatings
4 Kenview Blvd
Brampton, ON L6T 5E4

A1.23 1/2014
(Supersedes 3/2012)

Made in the
USA