

Architectural Coatings

SEAL GRIP® Stain Blocking Primer

Generic Type

Tinting and Base Information

Alkyd Enamel

55-31

Seal Grip Stain Blocking Primer -- Off White

General Description

Our premium aerosol spray product permits the user to achieve a quick dry, smooth, durable finish comparable to brush application in a primer with stain killing properties. Available in flat finish.

Recommended Uses

Siding

Wood

Features / Benefits

Quick Dry
Smooth, Durable Finish
Low Odor

Product Data

Gloss: Flat
DFT: 1.00 minimum to 2.00 maximum mils
Viscosity: N/A

*Product data calculated on product 55-31.

Drying Time:

To Touch: 10 minutes
To Handle: 45 minutes
To Recoat: 2 hours
To Full Cure: 5 days

Dry Time @77°F (25°C); 50% relative humidity

Limitations of Use

Apply only when air, surface and product temperatures are above 50°F (10°C). For best results, spray at temperatures 68°F to 78°F (20°C to 26°C). Store product at room temperature approximately 70°F (21°C). To prevent wrinkling or lifting, recoat within 2 hours or wait 5 days for thorough dry. Do not stick pins or wire into can openings. Apply two thin coats rather than one heavy coat. To protect from overspraying, mask off or otherwise protect surfaces and surroundings not to be painted. DANGER: Rags, steel wool or waste soaked with this product may spontaneously catch fire if improperly discarded. Immediately after use, place rags, steel wool or waste in a sealed water-filled metal container. Refer to www.pittsburghpaints.com, Spontaneous Combustion Advisory for additional information.

Architectural Coatings

SEAL GRIP® Stain Blocking Primer

General Surface Preparation

Surface must be clean and dry, free of dust, grease, wax and loose paint. New wood should be primed or undercoated before applying finish coat. Bare or previously painted metal should be primed with the appropriate primer. Glossy surfaces should be sanded or rubbed with steel wool to remove gloss. Surfaces should then be wiped clean before painting. **WARNING!** If you scrape, sand, or remove old paint, you may release lead dust or fumes. **LEAD IS TOXIC. EXPOSURE TO LEAD DUST OR FUMES CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE.** Wear a properly fitted NIOSH-approved respirator and prevent skin contact to control lead exposure. Clean up carefully with a HEPA vacuum and a wet mop. Before you start, find out how to protect yourself and your family by contacting the USEPA National Lead Information Hotline at 1-800-424-LEAD or log on to www.epa.gov/lead. In Canada contact a regional Health Canada office. Follow these instructions to control exposure to other hazardous substances that may be released during surface preparation.

Recommended Primers

Application Information

Recommended Spread Rates:

Wet Mils :	3.0	minimum to	6.0	maximum
Wet Microns:	76.2	minimum to	156.6	maximum
Dry Mils :	1.0	minimum to	2.0	maximum
Dry Microns:	25.4	minimum to	50.0	maximum

Application Equipment:

Thinning:

DO NOT THIN.

Directions for Use

Shake can for at least one minute, listening for rattle of mixing ball. During application, shake intermittently for approximately 10 seconds at 1 to 2 minute intervals. **USE WITH ADEQUATE VENTILATION. KEEP OUT OF REACH OF CHILDREN.**

Permissible temperatures during application:

Material:	50 to 90°F	10 to 32°C
Ambient:	50 to 100°F	10 to 38°C
Substrate:	50 to 100°F	10 to 38°C

Packaging: Aerosol

Not all products are available in all sizes.

PPGAF believes the technical data presented is currently accurate: however, no guarantee of accuracy, comprehensiveness, or performance is given or implied. Improvements in coatings technology may cause future technical data to vary from what is in this bulletin. For complete, up-to-date technical information, visit our web site or call 1-800-441-9695.



PPG Industries, Inc.
Architectural Coatings
One PPG Place
Pittsburgh, PA 15272
www.pittsburghpaints.com

Technical Services
1-800-441-9695
1-888-807-5123 fax

Architect/Specifier
1-888-PPG-IDEA

PPG Architectural Finishes
400 S. 13th Street
Louisville, KY 40203

PPG Canada, Inc.
Architectural Coatings
4 Kenview Blvd
Brampton, ON L6T 5E4

A3.35 10/2006