

DEFT® WOOD STAIN INTERIOR – OIL-BASED

DEFT INTERIOR WOOD STAIN OIL-BASED ENHANCES WOOD GRAIN, SEALING THE WOOD FOR A LASTING RICH, SEMI-TRANSPARENT COLOR.



Deft Interior Oil-Based Wood Stain is a premium blend of rich oils that penetrates deeply into wood pores enhancing the wood's natural beauty and imparting a rich, even color. *Deft* Oil-Based stain is excellent for interior wood surfaces, including floors, doors, trim and furniture.



PRODUCT FEATURES

Quick & Easy

- Fortified with Tung Oil
- Enhances wood grain
- Maximizes color consistency

Beautiful and Versatile

- Rich, semi-transparent colors enhance the wood grain
- Ultra-fine pigments provide brilliant clarity and uniform colors
- Light fast pigments are UV stable and resist color fading
- Tung Oil helps preserve the integrity of the wood for lasting beauty
- Use Tint Base (Natural) for a natural color finish, to create custom colors, or as a wood conditioner and stain controller

For Interior Wood Projects

- Furniture
- Floors
- Doors
- Molding
- Cabinets
- Paneling

CONFORMANCE STANDARD

VOC compliant in all regulated areas

PRODUCT DATA

*PRODUCT DATA CALCULATED ON DFT400

PRODUCT TYPE: Modified Urethane & Natural Oil

VOLUME SOLIDS: 71%

WEIGHT SOLIDS: 58%

VOC*: <250 g/L

WEIGHT/GALLON: 7.7 lb/Gal.

VISCOSITY* @77°F (25°C): 48-58 KU (Kreb's Units)

FLASH POINT: 110°F (43.3°C)

COVERAGE: Up to 400 sq.ft. (46.5 sq meters) per US gallon (3.78 L) on properly prepared surfaces. Coverage figures will vary with wood type, preparation and application.

DRYING TIME: Allow a minimum of 8 hours before application of a topcoat.

Dry times vary with temperature, humidity, color and wood type.

CLEANUP: Paint thinner or mineral spirits

DISPOSAL: Contact your local environmental regulatory agency for guidance on disposal on unused product. Do not pour down a drain or storm sewer.

PRODUCT AVAILABILITY

DFT400	Tint Base (Natural)	Quarts, Gallons
DFT401	Golden Oak	Quarts, Gallons
DFT402	Early American	Quarts, Gallons
DFT403	Cherry	Quarts, Gallons
DFT404	Red Mahogany	Quarts, Gallons
DFT405	Dark Walnut	Quarts, Gallons
DFT406	Spanish Oak	Quarts, Gallons
DFT407	Dark Mahogany	Quarts, Gallons



APPLICATION INFORMATION

Provide adequate ventilation. Stir well before and during use. **USE WITH ADEQUATE VENTILATION. KEEP OUT OF REACH OF CHILDREN.** Read all label and Material Safety Data Sheets (MSDS) information prior to use. MSDS are available through our website or by calling 1-800-441-9695.

APPLICATION EQUIPMENT: Apply with a clean cloth, brush, sponge, pad, roller or by spray equipment.

APPLICATION METHOD: When working with multiple cans, mix together for color consistency. Allow stain to penetrate for 5 to 15 minutes. Wipe off the excess stain with a clean cloth. Do not allow stain to dry before wiping. To further increase color intensity, allow the stain to dry for 1 hour, and then apply a second coat.

THINNING: No thinning is needed.

GENERAL SURFACE PREPARATION

Surface must be clean and dry.

BARE WOOD: Prepare bare wood for staining by sanding in the direction of the grain with sandpaper until smooth.

REFINISHING OLD WOOD: Previous finishes will inhibit penetration of the stain. Remove all old finishes down to bare wood prior to application.

FINAL SURFACE PREPARATION: Wood must be free of dust, dirt, grease and oils. Use a tack cloth or vacuum cleaner to remove any dust or dirt from the wood. Surfaces must be dry before staining.

WARNING! If you scrape, sand, or remove old paint, you may release lead dust or fumes. LEAD IS TOXIC. EXPOSURE TO LEAD DUST OR FUMES CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE. Wear a properly fitted NIOSH-approved respirator and prevent skin contact to control lead exposure. Clean up carefully with a HEPA vacuum and a wet mop. Before you start, find out how to protect yourself and your family by contacting the USEPA National Lead Information Hotline at 1-800-424-LEAD or log on to www.epa.gov/lead. In Canada contact a regional Health Canada office. Follow these instructions to control exposure to other hazardous substances that may be released during surface preparation.

COVERAGE: Up to 400 sq.ft. (46.5 sq meters) per US gallon (3.78 L) on properly prepared surfaces. Coverage figures will vary with wood type, preparation and application.

DRYING: Allow a minimum of 8 hours before application of a topcoat. Dry times vary with temperature, humidity, color and wood type.

CLEAN-UP: Clean all brushes and applicators with paint thinner or mineral spirits.

DISPOSAL: Contact your local environmental regulatory agency for guidance on disposal of unused product. Do not pour down a drain or storm sewer.

LIMITATIONS OF USE

FOR INTERIOR USE ONLY. Do not apply when the air, coating or surface temperature is below 50°F (10°C).

DANGER! COMBUSTIBLE LIQUID AND VAPOR. HARMFUL OR FATAL IF SWALLOWED. CAUSES RESPIRATORY TRACT IRRITATION. MAY BE HARMFUL IF INHALED. MAY CAUSE EYE AND SKIN IRRITATION. Sanding and grinding dusts may be harmful if inhaled. Aspiration hazard. Can enter lungs and cause damage. Prolonged or repeated contact can defat the skin and lead to irritation, cracking and/or dermatitis. Repeated exposure to high vapor concentrations may cause irritation of the respiratory system and permanent brain and nervous system damage. Inhalation of vapor/aerosol concentrations above the recommended exposure limits causes headaches, drowsiness and nausea and may lead to unconsciousness or death. Contains material that can cause target organ damage. Keep away from heat, sparks and flame. Do not breathe vapor or mist. Do not swallow. Do not get on skin or clothing. Avoid contact with eyes. Wash thoroughly after handling. Keep container tightly closed and sealed until ready for use. Provide fresh air ventilation during and after application and drying. Avoid the inhalation of dust, particulates, spray or mist arising from the application of this preparation. Use personal protective equipment as required. DANGER - RAGS, STEEL WOOL OR WASTE SOAKED WITH THIS PRODUCT MAY SPONTANEOUSLY CATCH FIRE IF IMPROPERLY DISCARDED. IMMEDIATELY AFTER EACH USE, PLACE RAGS, STEEL WOOL OR WASTE IN A SEALED WATER-FILLED METAL CONTAINER. FIRST AID IF swallowed, rinse mouth with water (only if the person is conscious). Call physician immediately. Do not induce vomiting unless directed to do so by medical personnel. If in eyes, rinse with water for 15 minutes. Check for and remove any contact lenses. If on skin, rinse well with water. Wash with soap and water. Get medical attention if irritation develops. If inhaled, remove to fresh air. If experiencing respiratory symptoms call a POISON CENTER or doctor/physician. Contains Linseed oil, polymd. (67746-08-1), Stoddard solvent (8052-41-3), Alkyd Resin (Not available.), Sunflower oil (8001-21-6), proprietary oil modified urethane (Not available.), PARACHLOROBENZOTRIFLUORIDE (98-56-6), Solvent naphtha (petroleum), light aromatic (64742-95-6), 1,2,4-trimethylbenzene (95-63-6), 2-butanone oxime (96-29-7) Photochemically reactive pursuant to SCAQMD Rule 102. Keep out of the reach of children. SEE MATERIAL SAFETY DATA SHEET FOR THIS PRODUCT For workplace use, an MSDS is available from your retailer or by calling (412) 492-5555. EMERGENCY SPILL INFORMATION: (412) 434-4515 (U.S.)(514) 645-1320 (Canada)01-800-00-21-400 (Mexico)