

DEFT® FAST DRY STAIN INTERIOR – OIL-BASED



DEFT FAST DRY STAIN INTERIOR OIL-BASED IS IDEAL FOR PROFESSIONAL RESULTS AS PART OF A ONE DAY WOOD FINISHING SYSTEM.

Deft Interior Oil-Based Fast Dry Stain is a fast drying, wiping stain designed to deliver professional results. It is recommended for use on interior woodwork including floors, trim, doors, beams, paneling, and furniture. As part of a one day wood finishing system, it can be used in conjunction with Deft Interior Water-Based Polyurethane.



PRODUCT FEATURES

Quick & Easy

- Alkyd/Oil-Based
- Professional fast dry wiping stain for wood
- 2 hour topcoat

Professional Results

- Enhances the wood grain with rich, semi-transparent colors
- Light fast pigments are UV stable and resist color fading
- Available in ready mix colors that also perform as tintable bases
- Fast dry formula recoats or topcoats in as little as two hours
- For use on furniture, cabinets, paneling, floors, trim, doors, beams and more

For Interior Wood Projects

- Furniture
- Cabinets
- Molding
- Doors
- Floors

CONFORMANCE STANDARD

VOC compliant – lower than Federal AIM

PRODUCT DATA

*PRODUCT DATA CALCULATED ON DFT570

PRODUCT TYPE: Alkyd/Oil Resin

VOLUME SOLIDS: 31% +/- 2%

WEIGHT SOLIDS: 39% +/- 2%

VOC*: <550 g/L

WEIGHT/GALLON: 7.3 lbs. (3.3 kg) +/- 0.2 lbs. (91 g)

VISCOSITY* @77°F (25°C): 50-60 KU (Kreb's Units)

FLASH POINT: 109°F (42.8°C)

COVERAGE: Approximately 500 sq. ft. (46.5 sq. meters) per gallon (3.78L). Coverage will vary with wood type, porosity, preparation and application.

DRYING TIME: Dry times are affected by humidity, temperature, and color of the stain being applied. Allow a minimum of 2 hours drying before recoating. Typically dries to touch in 15 minutes and to handle in 30 minutes. To test for dryness, lightly rub with a white cloth. If the cloth picks up the color, wait at least one hour and retest.

CLEANUP: Paint thinner or mineral spirits **Danger** - Rags, steel wool or waste soaked with this product may spontaneously catch fire if improperly discarded. Immediately after use, place rags, steel wool or waste in a sealed water-filled metal container.

DISPOSAL: Contact your local environmental regulatory agency for guidance on disposal on unused product. Do not pour down a drain or storm sewer.

PRODUCT AVAILABILITY

DFT570	Natural (Tint Base)	Quarts, Gallons
DFT571	Honey Oak	Quarts, Gallons
DFT572	Classic American	Quarts, Gallons
DFT574	Rich Mahogany	Quarts, Gallons
DFT575	Jacobean	Quarts, Gallons



APPLICATION INFORMATION

Stir well before and during use. **USE WITH ADEQUATE VENTILATION. KEEP OUT OF REACH OF CHILDREN.** Read all label and Material Safety Data Sheets (MSDS) information prior to use. MSDS are available through our website or by calling 1-800-441-9695.

APPLICATION EQUIPMENT: Apply with a bristle brush or a soft lint-free cloth.

APPLICATION METHOD: On bare wood, apply a uniform coat of *Def* Fast Dry Stain Interior – Oil-Based by brush or soft cloth. Wipe off excess stain with a soft, lint-free cloth after suitable penetration time. Test on scrap wood to determine the best time interval between application and wiping. To obtain more density or darker stain effects, repeat the stain application. When the stain is dry, apply the balance of the finish system.

THINNING: Not recommended.

GENERAL SURFACE PREPARATION

Proper surface preparation is essential for the *Def* limited warranty to apply. Stain only clean, dry, deglossed and profiled surfaces. Remove dirt, oils, grease, wax, release agents, sanding dust, paint remover, etc. with soap or TSP and water, paint thinner, or other appropriate cleaners, or by vacuuming as necessary. Fill openings and nail holes with a suitable filler. Test application in a clean, non-conspicuous area for proper color and penetration.

BARE WOOD: Always sand with the grain of the wood. For hard woods, such as oak and maple, begin sanding with 100 grit sandpaper, then proceed to 150 grit sandpaper, and finish with 200 grit or finer sandpaper. For soft woods, such as pine, begin sanding with 150 grit sandpaper and finish with 200 grit or finer sandpaper.

REFINISHING OLD WOOD: Remove all old finishes down to bare wood prior to application.

FINAL SURFACE PREPARATION: All wood must be dry and free of dust, dirt, grease or oils. Use a tack cloth or vacuum cleaner to remove any dust or dirt from the wood. Surfaces must be dry before staining.

FINISHING RECOMMENDATIONS: Protection with varnish or polyurethane is recommended.

WARNING! If you scrape, sand, or remove old paint, you may release lead dust or fumes. LEAD IS TOXIC. EXPOSURE TO LEAD DUST OR FUMES CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE. Wear a properly fitted NIOSH-approved respirator and prevent skin contact to control lead exposure. Clean up carefully with a HEPA vacuum and a wet mop. Before you start, find out how to protect yourself and your family by contacting the USEPA National Lead Information Hotline at 1-800-424-LEAD or log on to www.epa.gov/lead. In Canada contact a regional Health Canada office. Follow these instructions to control exposure to other hazardous substances that may be released during surface preparation.

LIMITATIONS OF USE

FOR INTERIOR USE ONLY. Do not apply when the air, coating or surface temperature is below 50°F (10°C).

Do not use as an opaque cleaner or near opaque stain.

Do not attempt to use on prewaxed wood flooring. Follow flooring manufacturer's coating recommendations.

These products are not intended for immersion service or other extreme conditions. Not recommended in situations characterized by high heat or presence of corrosive chemicals nor for heavy-duty use on floors.

PRECAUTIONS AND FIRST AID: Sanding and grinding dusts may be harmful if inhaled. Inhalation of high concentrations of vapor may affect the central nervous system. Repeated exposure to high vapor concentrations may cause irritation of the respiratory system and permanent brain and nervous system damage. High vapor concentrations can cause headaches, dizziness, drowsiness and nausea and may lead to unconsciousness. This product contains crystalline silica which can cause lung cancer or silicosis. The risk of cancer depends on the duration and level of exposure to dust from sanding surfaces or mist from spray applications. Can enter lungs and cause damage. Keep away from heat and flame. Do not breathe vapor or mist. Do not swallow. Do not get on skin or clothing. Avoid contact with eyes. Keep container tightly closed and sealed until ready for use. Wash thoroughly after handling. Provide fresh air ventilation during and after application and drying. Avoid the inhalation of dust, particulates, spray or mist arising from the application of this preparation. Use personal protective equipment as required. **DANGER – RAGS, STEEL WOOL OR WASTE SOAKED WITH DEFT INTERIOR FAST DRY STAIN MAY SPONTANEOUSLY CATCH FIRE IF IMPROPERLY DISCARDED. IMMEDIATELY AFTER EACH USE, PLACE RAGS, STEEL WOOL OR WASTE IN A SEALED WATER-FILLED METAL CONTAINER.** **FIRST AID:** If swallowed, rinse mouth with water (only if the person is conscious). Call physician immediately. Do not induce vomiting unless directed to do so by medical personnel. If in eyes, rinse with water for 15 minutes. Check for and remove any contact lenses. If on skin, rinse well with water. Wash with soap and water. Get medical attention if irritation develops. If inhaled, remove to fresh air. If experiencing respiratory symptoms call a POISON CENTER or doctor/physician. Contains: stoddard solvent (8052-41-3); linseed oil (8001-26-1); proprietary alkyd resin (not available); naphtha (petroleum), hydrotreated heavy (64742-48-9); soybean oil, polymer with pentaerythritol and phthalic anhydride (66070-60-8); 2-butanone oxime (96-29-7); xylene (1330-20-7); 1,2,4-trimethylbenzene (95-63-6); crystalline silica, respirable powder (<10 microns) (14808-60-7); ethylbenzene (100-41-4). **WARNING:** This product contains a chemical known to the State of California to cause cancer. Keep out of the reach of children. For workplace use, an MSDS is available from your retailer or by calling (412) 492-5555. **EMERGENCY SPILL INFORMATION:** (412) 434-4515 (U.S.).