

Sanding Sealer Interior Oil Based

Provides ultra smooth surface prior to topcoat



DEFT® Interior Oil Based Sanding Sealer is designed to create an ultra smooth surface prior to the application of a topcoat. The sanding sealer serves as the base coat and seals and protects the surface. *Deft* Interior Oil Based Sanding Sealer is ideal for stained or bare wood surfaces including furniture, floors, cabinets, doors, trim and paneling.

Proven Performance

- Prepares wood for a smooth, even topcoat
- Fast drying
- Sands easily

Plenty of uses

Deft Interior Oil Based Sanding Sealer seals the wood and protects the surface. It's ideal for:

- Floors
- Furniture
- Doors
- Trim
- Cabinets
- Paneling

Conformance Standard

VOC compliant – lower than Federal AIM



OLYMPIC® 41060 Soft Conversion to DFT60	Sanding Sealer	Quarts, Gallons
--	----------------	--------------------

Product Data

PRODUCT TYPE:	Alkyd/Oil
VOLUME SOLIDS:	30 ± 2%
WEIGHT SOLIDS:	36 ± 2%
VOC:	<550 g/L
WEIGHT/GALLON:	7.0 ± 0.2 lbs.
FLASH POINT:	63°F (17.2°C)
COVERAGE:	Approximately 500 to 700 sq.ft./gal; (46.5 to 65.0 sq.m/3.78 L) depending on surface texture and porosity
Wet Film Thickness:	2.7 to 3.7 mils
Wet Microns:	68.6 to 94.0
Dry Film Thickness:	0.8 to 1.1 mils
Dry Microns:	20.3 to 28.0

Coverage figures do not include loss due to surface irregularities and porosity or material loss due to application method or mixing.

DRYING TIME: Dry time @ 77°F (25°C); 50% relative humidity.

To Sand: 2 hours minimum

Drying times listed may vary depending on temperature, humidity, film build, color and air movement.

CLEANUP: Clean all brushes and applicators with mineral spirits or paint thinner.

DISPOSAL: Contact your local environmental regulatory agency for guidance on disposal on unused product. Do not pour down a drain or storm sewer



Application Information

Stir thoroughly before using. Do not shake. **USE WITH ADEQUATE VENTILATION. KEEP OUT OF REACH OF CHILDREN.** Read all label and Material Safety Data Sheets (MSDS) information prior to use. MSDS are available through our website or by calling 1-800-441-9695.

Application Equipment: Apply with a brush or paint pad. **DO NOT THIN.**

Application Method: Always apply with the grain of the wood using a smooth, even stroke. Use a natural bristle brush or foam applicator pad.

General Surface Preparation

Surface must be clean and dry. Remove all loose and peeling paint, dirt, grease and any other surface contaminants.

WARNING! If you scrape, sand, or remove old paint, you may release lead dust or fumes. **LEAD IS TOXIC. EXPOSURE TO LEAD DUST OR FUMES CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE.**

Wear a properly fitted NIOSH-approved respirator and prevent skin contact to control lead exposure. Clean up carefully with a HEPA vacuum and a wet mop. Before you start, find out how to protect yourself and your family by contacting the USEPA National Lead Information Hotline at 1-800-424-LEAD or log on to www.epa.gov/lead. In Canada contact a regional Health Canada office. Follow these instructions to control exposure to other hazardous substances that may be released during surface preparation.

DANGER! HARMFUL OR FATAL IF SWALLOWED. SKIN AND EYE IRRITANT. VAPOR HARMFUL. IRRITATES EYES, NOSE AND THROAT. FLAMMABLE. Keep away from heat/sparks/flames/ignition sources. Do not smoke. Turn off or extinguish stoves/heaters/electrical motors/ignition sources/flames during use and until all vapors/odors are gone. Prevent skin/eye contact. Provide fresh air ventilation during and after application and drying. If you experience eye watering, headaches, nausea, dizziness, or loss of coordination, increase fresh air or wear NIOSH approved respiratory protection or leave the area. Repeated exposure to high vapor concentrations may cause irritation of the respiratory system and permanent brain and nervous system damage. Intentional misuse by concentrating/inhaling the contents can be harmful/fatal. **USE ONLY WITH ADEQUATE VENTILATION. DANGER - RAGS, STEEL WOOL OR WASTE SOAKED WITH OLYMPIC PREMIUM OIL BASED SANDING SEALER MAY SPONTANEOUSLY CATCH FIRE IF IMPROPERLY DISCARDED. IMMEDIATELY AFTER EACH USE, PLACE RAGS, STEEL WOOL OR WASTE IN A SEALED WATER-FILLED METAL CONTAINER. FIRST AID:** If swallowed, do not induce vomiting. Call Physician immediately. If skin/eye contact occurs, flush the affected areas with warm water for at least 15 minutes. Remove contact lens. A mild soap may be used on the skin if available. If inhaled, removed from area to fresh air. If breathing is difficult, get medical attention immediately. Get immediate Emergency Medical Treatment if overexposed. Take label information. This product is intended for consumer use - for workplace use, an MSDS is available from your retailer or by calling (412) 492-5555. **READ MATERIAL SAFETY DATA SHEET (MSDS) BEFORE USE.** Close container after each use. **KEEP OUT OF REACH OF CHILDREN.** Emergency Medical/Spill Information in US: (412) 434-4515. **WARNING:** This product contains a chemical known to the state of California to cause birth defects and other reproductive harm.

BARE WOOD: Sand with 180 to 220 grit sandpaper along the wood grain until smooth. Remove all dust.

PREVIOUSLY COATED WOOD: If the clean surface is in good condition, sand with 180 – 220 grit sandpaper. Remove all dust. Test in a small area to ensure proper adhesion. If the finish is damaged or deteriorated, complete removal of the finish is recommended.

RECOAT: Sand with 180 to 220 grit sandpaper along the wood grain until smooth. Remove dust. Finish with *Deft* Water Based Polyurethane. **Do not topcoat with an oil based polyurethane.**

Limitations of Use

FOR INTERIOR USE ONLY. Not recommended as a finish coat or topcoat.

DO NOT TOPCOAT WITH AN OIL BASED POLYURETHANE.

This product contains zinc stearate.

Do not apply when the air, coating or surface temperature is below 50°F (10°C).

Do not attempt to use on prewaxed wood flooring. Follow flooring manufacturer's coating recommendations.

The product is not intended for immersion service or other extreme conditions. Not recommended in situations characterized by high heat or presence of corrosive chemicals nor for heavy-duty use on floors.