

FastDry Interior/Exterior Acrylic Gloss Enamel

GENERAL DESCRIPTION

Pittsburgh Paints & Stains FastDry is the solution for your toughest paint projects. *FastDry* paint is an interior and exterior formula ideal for cabinets, doors, trim, window frames, shelving and other difficult projects. It dries very quickly allowing you to finish the project sooner and provides a tack free finish that prevents sticking. It delivers a durable protective shell to protect against everyday events and the elements even on some of the most difficult substrates including fiberglass, ceramic tile, laminate, and metal. *Pittsburgh Paints & Stains FastDry* is an excellent product backed by a lifetime results guarantee.

RECOMMENDED SUBSTRATES

Aluminum	Galvanized Steel
Ceramic Tile	Gypsum Wallboard-Drywall
Concrete	Laminate
Concrete/Masonry Block	Plaster
Ferrous Metal	Wood (Interior)
Fiberglass	Vinyl and Architectural Plastics

FEATURES / BENEFITS

- * Ideal for cabinets, doors, trim, window frames, shelving & more
- * Dries to the touch in about 15 minutes to help finish the project sooner
- * Delivers a durable, protective shell
- * Excellent flow & leveling for a smooth enamel finish
- * Provides a tack free finish that prevents sticking
- * Serves as a paint & primer on previously coated wood, fiberglass, laminate, and ceramic tile surfaces
- * Stands up against repeated exposure to most light duty industrial cleaners
- * Outstanding adhesion to wood, laminate, ceramic tile, metal, etc.

PRODUCT INFORMATION

39-5000	White/Pastel Base
39-5100	Midtone Base*
39-5200	Neutral Base*

*Must be tinted before use.

Refer to the appropriate color formula book, automatic tinting equipment, and or computer color matching system for color formulas and tinting instructions.

PRODUCT DATA

PRODUCT TYPE:	Waterborne Acrylic
SHEEN:	Gloss, >70 @ 60°
VOLUME SOLIDS*:	37% +/- 2%
WEIGHT SOLIDS*:	48% +/- 2%
WEIGHT/GALLON*:	10.0 lbs. (4.5 kg) +/- 0.2 lbs. (91 g)
VOC:	< 250 g/L (2.1 lbs./gal.)

*Product data calculated on product 39-5000

COVERAGE: Approximately 400 sq. ft. (37.2 sq. meters) per U.S. Gallon (3.78L) on smooth, nonporous surfaces.

Wet Film Thickness:	4.0 mils
Wet Microns:	102
Dry Film Thickness:	1.5 mils
Dry Microns:	38

Coverage figures do not include loss due to surface irregularities and porosity or material loss due to application method or mixing. Some colors, drastic color changes, or porous substrates may require more than one coat to achieve a uniform finish.

DRYING TIME:	Dry time @ 77°F (25°C); 50% relative humidity.
To Touch:	15 - 20 minutes
To Recoat:	2 hours

Drying times listed may vary depending on temperature, humidity, film build, color, and air movement.

CLEANUP: Clean brushes and tools with warm, soapy water.

DISPOSAL: Contact your local environmental regulatory agency for guidance on disposal of unused product. Do not pour down a drain or storm sewer.

FLASH POINT:	Over 200°F (93°C)
---------------------	-------------------

PACKAGING

Quart (946 mL)
1-Gallon (3.78 L)

FastDry Interior/Exterior Acrylic Gloss Enamel**GENERAL SURFACE PREPARATION**

Surface must be clean and dry. Remove all loose, peeling paint, dirt, mildew, grease, oil, chalk, rust, and any other surface contaminants. Blistering and peeling issues are commonly caused by moisture behind the paint film. Problems leading to excessive moisture in the substrate must be repaired prior to painting. Putty all nail holes and caulk all cracks and open seams. Sand all glossy, rough, and patched surfaces. Plaster, concrete, and masonry surfaces must be completely dry, free of efflorescence, and allowed to cure for 30 days prior to painting. Repaired surfaces or lightly stained areas may require additional coats. Prime all bare wood, drywall, plaster, metal, and porous surfaces with the appropriate primer.

WARNING! If you scrape, sand, or remove old paint, you may release lead dust or fumes. LEAD IS TOXIC. EXPOSURE TO LEAD DUST OR FUMES CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE. Wear a properly fitted NIOSH-approved respirator and prevent skin contact to control lead exposure. Clean up carefully with a HEPA vacuum and a wet mop. Before you start, find out how to protect yourself and your family by contacting the USEPA National Lead Information Hotline at 1-800-424-LEAD or log on to www.epa.gov/lead. Follow these instructions to control exposure to other hazardous substances that may be released during surface preparation.

ALUMINUM: A primer is required for proper adhesion. Any coating applied directly to aluminum should be spot applied, allowed to cure overnight, and then evaluated for adhesion. If adhesion is good, the application may proceed.

CERAMIC TILE: No primer needed; sanding or etching with phosphoric acid is necessary. Topcoat should be spot applied as directed, allowed to cure overnight, then evaluated for adhesion. If adhesion is good, the application may proceed.

CONCRETE: New concrete should cure for at least 30 days and preferably 90 days prior to priming and painting. The pH of the substrate must be less than 10 before painting. If pH is greater than 10, prime with an alkali resistant primer.

CONCRETE/MASONRY BLOCK: Mortar should cure for at least 30 days and preferably 90 days prior to painting. Fill block with an appropriate block filler. Surfaces previously coated with water thinned cement-based paint must be prepared with extra care. If the material appears to be adhering tightly, a masonry sealer may be applied to seal the surface. Check adhesion by applying a piece of masking tape. If the sealer peels off and has loose particles, remove all chalking or crumbling material, re-seal and re-check adhesion.

FERROUS METAL: The surface must be cleaned thoroughly to remove any dust, rust, and surface contaminants, and then primed. No primer is required for interior applications.

FIBERGLASS: No primer needed; sanding or scuffing the surface is recommended. Primer and topcoat should be spot applied as directed, allowed to cure overnight, then evaluated for adhesion. If adhesion is good, the application may proceed.

GALVANIZED STEEL: A primer is required for proper adhesion. Caution must be used when selecting coatings for use on all galvanized metal surfaces. These substrates may have a factory-applied stabilizer, which is used to prevent white rusting during storage and shipping. Such stabilizers must be removed by either brush blasting, sanding or chemical treatment prior to priming.

GYPSUM WALLBOARD-DRYWALL: Nails or screws should be countersunk, and they along with any indentations should be mudded flush with the surface, sanded smooth and cleaned to remove any dust, prior to priming the substrate.

LAMINATE: No primer needed; sanding or scuffing the surface is recommended. Topcoat should be spot applied as directed, allowed to cure overnight, then evaluated for adhesion. If adhesion is good, the application may proceed.

PLASTER: Plaster, hardcoat, skim coat, or other alkaline surfaces should be allowed to cure for at least 30 days prior to priming with an alkali resistant primer.

WOOD (INTERIOR): Unpainted wood or wood in poor condition should be sanded smooth, wiped clean. Any knots or resinous areas must be primed before painting. Countersink all nails, putty flush with surface. For non-bleeding or previously painted wood, no primer is required.

VINYL & ARCHITECTURAL PLASTICS: Vinyl and similar architectural plastics may present potential adhesion problems. A primer may be required to promote proper adhesion. Consult the manufacturer's guidelines prior to painting. Primer and Topcoat should be spot applied, allowed to cure overnight, then evaluated for adhesion. If adhesion is good, the application may proceed. Do not paint vinyl or plastic with a color darker than the original to prevent potential warping due to heat absorption.

LIMITATIONS OF USE**FOR PROFESSIONAL USE ONLY.**

Apply only when air, surface, and product temperatures are between 50°F (10°C) and 90°F (32°C) and at least 5°F (3°C) above the dew point. It is important to maintain air and surface temperatures for 24 hours after application. Avoid painting in direct sunlight or on hot surfaces. Do not apply late in the day when dew and condensation are likely to form, or if rain is expected within 48 hours.

Not recommended for exterior horizontal surfaces unless these surfaces can be protected from dew and rain for 7 days. Wait at least 7 days after painting before cleaning the surface with a non-abrasive, mild cleanser. Not recommended for polypropylene or polyethylene plastics, roofs, garage floors or concrete floors subject to hot tires, continuous water immersion environments, such as bathtubs, sinks, shower basins and pools. Not recommended for very flexible substrates subject to abuse; such as canvas, nylon rope or rubber. Do not use on large wood structures or the bodies of homes.

USE WITH ADEQUATE VENTILATION. KEEP OUT OF REACH OF CHILDREN. Read all label and Safety Data Sheet (SDS) information prior to use. SDS are available through our website or by calling 1-800-441-9695.

PROTECT FROM FREEZING.

FastDry Interior/Exterior Acrylic Gloss Enamel

APPLICATION INFORMATION

Stir thoroughly. When using more than one can of the same color, intermix to ensure color uniformity. During application, it is important to maintain a wet edge due to the quick dry of the product. Rinse brush with warm water periodically during extended brush application. Two coats are recommended for maximum durability.

Application Equipment: Apply with a high quality brush, roller, paint pad or by spray equipment

Airless Spray: For airless spray application, use tip size .009" - .013" (fine finish tip) and a pressure range of 1500 to 2000 psi. Spray equipment must be handled with due care and in accordance with manufacturer's recommendation. High-pressure injection of coatings into the skin by airless equipment may cause serious injury.

Brush: Polyester/Nylon Brush

Roller: 3/8" or less nap roller cover

Thinning: Thinning may be required. If necessary, thin 5 to 10% (up to 12 oz. or 355 mL) with water per U.S. gallon (3.78 L) of paint. No thinning required for airless spray application.

Permissible temperatures during application:

Material:	50 to 90°F	10 to 32°C
Ambient:	50 to 90°F	10 to 32°C
Substrate:	50 to 90°F	10 to 32°C

PRECAUTIONS

WARNING! HARMFUL IF INHALED. HARMFUL IF ABSORBED THROUGH SKIN. HARMFUL IF SWALLOWED. CAUSES RESPIRATORY TRACT, EYE/SKIN IRRITATION. Inhalation of high concentrations of vapor may affect the central nervous system. Repeated exposure to high vapor concentrations may cause irritation of the respiratory system and permanent brain and nervous system damage. High vapor concentrations can cause headaches, dizziness, drowsiness and nausea and may lead to unconsciousness. Do not breathe vapor or mist. Do not swallow. Do not get on skin or clothing. Avoid contact with eyes. Keep container tightly closed and sealed until ready for use. Wash thoroughly after handling. Provide fresh air ventilation during and after application and drying. Avoid the inhalation of dust and particulates arising from the application of this preparation. Use personal protective equipment as required. **DANGER - RAGS, STEEL WOOL OR WASTE SOAKED WITH FAST DRY PAINT MAY SPONTANEOUSLY CATCH FIRE IF IMPROPERLY DISCARDED. IMMEDIATELY AFTER EACH USE, PLACE RAGS, STEEL WOOL OR WASTE IN A SEALED WATER-FILLED METAL CONTAINER.** **Note: These warnings encompass the product series. Prior to use, read and follow product-specific SDS and label information.** **FIRST AID:** If swallowed, rinse mouth with water (only if the person is conscious). Call physician immediately. Do not induce vomiting unless directed to do so by medical personnel. If in eyes, rinse with water for 15 minutes. Check for and remove any contact lenses. In case of contact, immediately flush skin with plenty of water while removing contaminated clothing and shoes. Get medical attention immediately. If inhaled, remove to fresh air. Call physician immediately. Keep out of the reach of children. For workplace use, an SDS is available from your retailer or by calling (412) 492-5555. **EMERGENCY SPILL INFORMATION:** (412) 434-4515 (U.S.).

© 2019 PPG Industries, Inc. All Rights Reserved. *Pittsburgh Paints & Stains* is a registered trademark and *FastDry* is a trademark of PPG Architectural Finishes, Inc. The *PPG Logo* is a registered trademark of PPG Industries Ohio, Inc.

PPG Architectural Finishes, Inc. believes the technical data presented is currently accurate; however, no guarantee of accuracy, comprehensiveness, or performance is given or implied. Improvements in coatings technology may cause future technical data to vary from what is in this bulletin. For complete, up-to-date technical information, call 1-800-441-9695.



PPG Architectural Finishes, Inc.
One PPG Place
Pittsburgh, PA 15272
www.pittsburghpaintsandstains.com

Technical Services
1-800-441-9695

Architect/Specifier
1-888-PPG-IDEA

PPG Architectural Coatings Canada Inc.
1550 rue Ampère, Suite 500
Boucherville (Quebec) J4B 7L4

39-5000 8/2019