

## ULTRA ADVANCED Waterproofing Sealant Toners

### GENERAL DESCRIPTION

Guaranteed to be our best stain, PITTSBURGH PAINTS® ULTRA ADVANCED Waterproofing Sealant Toners are exceptionally durable and easy to apply, and are available in extraordinary rich, attractive colors. Best in quality, Ultra Advanced will safeguard and enhance the natural beauty of exterior wood surfaces in the harshest conditions, with excellent durability and waterproofing protection, Ultra SunBlock® UV and Scuff Guard® protection while providing a mildew resistant coating. Simply our best – guaranteed!

### RECOMMENDED SUBSTRATES

Exterior wood surfaces	New wood
Decks	Pressure-treated wood
Siding	Weathered wood
Fences	Outdoor furniture
Previously coated wood with a solvent-based clear or toner	

### FEATURES / BENEFITS

Stain and sealant in one - protect and beautify in one step

- Excellent durability & waterproofing protection
- Ultra *SunBlock* UV and *Scuff Guard* protection
- Provides a mildew-resistant coating
- Ready for immediate use on new, dry, pressure-treated wood
- Application down to 35°F (2°C)

### APPLICATION INFORMATION

**FOR EXTERIOR USE ONLY.** Stir thoroughly and often during use. When using more than one can of the same color, intermix to ensure color uniformity.

**Pretest:** Test a small hidden area prior to application to ensure acceptable appearance and penetration.

**Application Equipment:** Apply with a high quality natural bristle brush, roller, paint pad, or by spray equipment.

Apply one thin coat. To help avoid lapmarks, apply to only a few boards at a time keeping a wet edge. When spraying or rolling always backbrush for best results.

**Thinning:** DO NOT THIN.

#### Permissible temperatures during application:

Material:	35 to 90°F	2 to 32°C
Ambient:	35 to 90°F	2 to 32°C
Substrate:	35 to 90°F	2 to 32°C

### PRODUCT INFORMATION

41-3501	Cedar Naturaltone
41-3502	Redwood Naturaltone
41-3503	Honey Gold

### PRODUCT DATA

<b>PRODUCT TYPE:</b>	Acrylic Oil
<b>VOLUME SOLIDS*:</b>	17% +/- 2%
<b>WEIGHT SOLIDS*:</b>	19% +/- 2%
<b>VOC*:</b>	232 g/L (1.9 lbs./gal.)
<b>WEIGHT/GALLON*:</b>	8.3 lbs. (3.8 kg) +/- 0.2 lbs. (91 g)

\*Product data calculated on 41-3501.

**COVERAGE:** Approximately 250 to 350 sq. ft. (23.2 to 32.5 sq. meters) per gallon (3.78 Liters) depending upon wood texture.

Coverage figures do not include loss due to surface irregularities and porosity or material loss due to application method or mixing.

**DRYING TIME:** Normally dries in 24 hours when applied in temperatures of 50°F (10°C) to 85°F (29°C). High humidity or low temperature application may prolong drying time. It is not recommended to apply product if rain is expected within 24 hours.

**CLEANUP:** Clean brushes and tools with warm soapy water.

**DANGER:** Rags, steel wool or waste soaked with ULTRA ADVANCED WATERPROOFING SEALANT TONER may spontaneously catch fire if improperly discarded. Immediately after each use, place rags, steel wool or waste in a sealed water-filled metal container. Refer to [www.pittsburghpaints.com](http://www.pittsburghpaints.com), Spontaneous Combustion Advisory for additional information.

**DISPOSAL:** Contact your local environmental regulatory agency for guidance on disposal of unused product. Do not pour down a drain or storm sewer.

**FLASH POINT\*:** 200°F (93°C)

## ULTRA ADVANCED Waterproofing Sealant Toners

## GENERAL SURFACE PREPARATION

Proper surface preparation is essential for the *PITTSBURGH PAINTS* limited warranty to apply. All surfaces must be clean, dry and free of dirt, dust, oil, mildew, loose wood fibers, and other contaminants. Previous coatings must be completely removed. Use an exterior wood cleaner to prepare new wood prior to coating, and to clean and restore weathered, dirty surfaces and remove mildew stains. After rinsing, ensure surface is free of standing water. Remove grade stamps or pencil marks by sanding.

**WARNING!** If you scrape, sand, or remove old paint, you may release lead dust or fumes. **LEAD IS TOXIC. EXPOSURE TO LEAD DUST OR FUMES CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE.** Wear a properly fitted NIOSH-approved respirator and prevent skin contact to control lead exposure. Clean up carefully with a HEPA vacuum and a wet mop. Before you start, find out how to protect yourself and your family by contacting the USEPA National Lead Information Hotline at 1-800-424-LEAD or log on to [www.epa.gov/lead](http://www.epa.gov/lead). In Canada, contact a regional Health Canada office. Follow these instructions to control exposure to other hazardous substances that may be released during surface preparation.

**DECKS:** Clean weathered, dirty or mildewed surfaces prior to applying product.

**FENCES OR SIDING:** Remove and inhibit mildew.

**PRETEST:** Test a small hidden area prior to application to ensure acceptable appearance and penetration.

**EXTRACTIVE BLEEDING:** Some woods, such as redwood and cedar contain natural water-soluble colorings or extractives that tend to “bleed” or migrate to the surface. If extractive bleeding occurs, allow the coating to dry completely, then wash with a mild detergent solution and rinse with clear water.

## LIMITATIONS OF USE

Apply when air and surface temperatures are 35°F (2°C) or above and will remain above 35°F (2°C) for the next 24 hours.

Avoid staining in direct sunlight or on hot surfaces. **FOR EXTERIOR USE ONLY.** Do not use on metallic, masonry, or interior surfaces.

**PROTECT FROM FREEZING.**

## PACKAGING

1-Gallon (3.78 L)

5-Gallon (18.9 L)

## SAFETY PRECAUTIONS

Before using the products listed in this publication, carefully read each product label and follow directions for its use. Please read and observe all the warnings and precautionary information on the product labels. Material Safety Data Sheets are available through our Sales Representative, Retailer or by calling (412) 492-5555.

Spray equipment must be handled with due care and in accordance with manufacturer's recommendations. High pressure injection of coatings into the skin by airless equipment may cause serious injury.

**USE WITH ADEQUATE VENTILATION. KEEP OUT OF REACH OF CHILDREN.**

The PPG logo is a registered trademark of PPG Industries Ohio, Inc. *PITTSBURGH PAINTS*, *SunBlock*, and *Scuff Guard* are registered trademarks of PPG Architectural Finishes, Inc.

PPG Architectural Finishes, Inc. believes the technical data presented is currently accurate; however, no guarantee of accuracy, comprehensiveness, or performance is given or implied. Improvements in coatings technology may cause future technical data to vary from what is in this bulletin. For complete, up-to-date technical information, call 1-800-441-9695.



PPG Industries, Inc.  
Architectural Finishes  
One PPG Place  
Pittsburgh, PA 15272  
[www.pittsburghpaints.com/menards](http://www.pittsburghpaints.com/menards)

Technical Services  
1-800-441-9695

Architect/Specifier  
1-888-PPG-IDEA

PPG Canada, Inc.  
Architectural Finishes  
4 Kenview Blvd  
Brampton, ON L6T 5E4

T.D. 41-3501 8/2012  
(Supersedes 8/2010)