

## Luxury Finish + Sealant In One Satin Semi-Transparent

### GENERAL DESCRIPTION

*Paramount* Luxury Finish + Sealant In One is a distinctive, high-end satin finish that brings the luxury look of interior hardwood to exterior spaces. Give your weathered decking the warm, rich look of reclaimed wood floors. For use on decks, fences, siding, outdoor furniture, exterior doors, garage doors and more.

### RECOMMENDED SUBSTRATES

|                       |                   |
|-----------------------|-------------------|
| Wood                  | Siding            |
| Pressure-treated wood | Railings          |
| Decks                 | Plywood           |
| Fences                | Outdoor Furniture |

### FEATURES / BENEFITS

- For Horizontal and Vertical Surfaces
- Transforms pressure-treated wood with varnish-like satin finish
- Seals and protects from UV and moisture
- Resists mold & mildew on finish
- High-transparency pigments for rich, durable color

### PRODUCT INFORMATION

|         |                             |
|---------|-----------------------------|
| 41-9001 | Honey Pine (May Be Tinted*) |
| 41-9002 | Warm Teak (May Be Tinted*)  |

\*Refer to the appropriate color formula book, automatic tinting equipment, and/or computer color matching system for color formulas and tinting instructions.

### PACKAGING

Quart (946 mL)  
1-Gallon (3.78 L)

### PRODUCT DATA

|                        |                                       |
|------------------------|---------------------------------------|
| <b>PRODUCT TYPE:</b>   | Alkyd                                 |
| <b>SHEEN:</b>          | Satin                                 |
| <b>VOLUME SOLIDS*:</b> | 58% +/- 2%                            |
| <b>WEIGHT SOLIDS*:</b> | 65% +/- 2%                            |
| <b>WEIGHT/GALLON*:</b> | 8.0 lbs. (3.6 kg) +/- 0.2 lbs. (91 g) |
| <b>VOC:</b>            | < 350 g/L (2.9 lbs./gal.)             |

\*Product data calculated on product 41-9001.

**COVERAGE:** On smooth surfaces, 350 to 450 sq. ft. (33 to 42 sq. meters) per U.S. gallon (3.78 L). Actual coverage may vary depending on the type, age, and texture of the wood, and application method.

**DRYING TIME:** Dry time @ 77°F (25°C); 50% relative humidity.  
To Touch: 24 hours  
To Recoat : 24 hours  
To Light Foot Traffic 72 hours

Wait seven days after applying the second coat to replace furniture. Drying times listed may vary depending on temperature, humidity, color, film build, and air movement. Final gloss achieved after 48-72 hours post-cure depending on the film build, humidity, temperature, and wood type.

**CLEANUP:** Clean tools immediately with mineral spirits. Clean spills right away with a damp cloth. **DANGER - RAGS, STEEL WOOL OR WASTE SOAKED WITH PITTSBURGH PAINTS & STAINS PARAMOUNT FINISH MAY SPONTANEOUSLY CATCH FIRE IF IMPROPERLY DISCARDED. IMMEDIATELY AFTER EACH USE, PLACE RAGS, STEEL WOOL OR WASTE IN A SEALED WATER-FILLED METAL CONTAINER.**

**DISPOSAL:** Contact your local environmental regulatory agency for guidance on disposal of unused product. Do not pour down a drain or storm sewer.

**FLASH POINT:** 136°F (58°C)

### LIMITATIONS OF USE

**FOR EXTERIOR USE. FOR WOOD SUBSTRATES ONLY.** Apply when air and surface temperature is between 50°F (10°C) and 90°F (32°C) and surface temperature is at least 5°F (3°C) above the dew point.. Do not apply in direct sunlight. Avoid painting late in the day when dew and condensation are likely to form, or if rain, snow or temperatures below 40°F (4°C) are expected within 48 hours.

While this product provides a mildew resistant coating, growth may still occur if the substrate is not properly prepared prior to painting and/or if the substrate is consistently exposed to conditions conducive to mold, mildew, and algae.

## Luxury Finish + Sealant In One Satin Semi-Transparent

## GENERAL SURFACE PREPARATION

All wood surfaces must be thoroughly clean, dry, and free of dirt, grease, grime, mildew, mill glaze, and previous coatings before application. Spray all wood surfaces with clean water, completely wetting the wood. Generously apply *Pittsburgh Paints & Stains Deck Cleaner* to the wood surfaces with a garden sprayer or a heavy nap roller cover. Let the solution dwell on the wood for 15 to 20 minutes as you scrub the surface with a hard bristle brush to help remove mill glaze or weathering. Do not allow solution to dry on the wood surface. Power-wash wood surface clean with fresh water using 500 to 800 psi with the nozzle 8 to 12 inches (20 to 30 cm) away to remove cleaning solution. Allow the surface to dry for 48 hours, or to have a moisture content of 18% or less before application. Sand all cleaned wood using 60 to 80 grit sandpaper for horizontal surfaces and 80 to 120 grit sandpaper for vertical surfaces. Always sand in direction of the wood grain and remove sanding dust. Finish should be applied within one week of preparation, provided that the surface remains free of dirt, grease, grime, and mildew.

**WARNING!** If you scrape, sand, or remove old paint, you may release lead dust or fumes. LEAD IS TOXIC. EXPOSURE TO LEAD DUST OR FUMES CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE. Wear a properly fitted, NIOSH-approved respirator and prevent skin contact to control lead exposure. Clean up carefully with a HEPA vacuum and a wet mop. Before you start, find out how to protect yourself and your family by contacting the USEPA National Lead Information Hotline at 1-800-424-LEAD or log on to [www.epa.gov/lead](http://www.epa.gov/lead). Follow these instructions to control exposure to other hazardous substances that may be released during surface preparation.

**NEW WOOD** - Clean and prepare all wood surfaces as specified above. Pressure treated wood must be properly seasoned, dry with a moisture content of 18% or less and free of salts and other water soluble materials. Water- repellent treated lumber requires one year minimum of weathering.

**EXOTIC HARDWOOD** - Ipe, mahogany, ironwood, tigerwood and teak woods exhibit a dense cell structure which may reduce the ability of a coating to penetrate the wood surface. Clean and prepare surface as specified above. Immediately prior to applying coating, wipe surface with acetone.

**PREVIOUSLY COATED WOOD** - Previous coatings must be completely removed prior to application. Once previous coatings are removed, clean and prepare surface as specified above. If previous coating is *Pittsburgh Paints & Stains Paramount Exterior Luxury Finish & Sealant in One*, refer to **MAINTENANCE** section.

**MAINTENANCE:** Maintenance needs will vary according to wear and tear on your surface and the climate in your region. Typical recoat cycle for this product is 2 to 3 years on horizontal surfaces and 4 to 5 years on vertical. If the finish is cracked or peeling, recoat will require complete removal of the previous coating using a stripper or sander. Follow the cleaning, surface preparation, and application instructions on the label. To avoid the need to strip/sand to completely remove the original coating before reapplication, apply a maintenance coat when wear to the surface becomes visible (typically every 12 to 18 months for horizontal and 24 to 48 months for vertical). Areas that have minimum wear should only be lightly coated. Exotic hardwood surfaces may require more frequent maintenance. Follow the cleaning recommendation and apply one coat.

**NOTE:** Tannin containing woods, such as redwood, red cedar, mahogany, Douglas fir, etc., contain tannic acid which tends to migrate to the surface and can discolor the finish. The discoloration is not harmful and can usually be removed by cleaning with a solution of four (4) ounces of oxalic acid to one gallon of warm water. Apply with a garden sprayer or heavy nap roller cover. Allow to sit on surface for 20 min. Rinse thoroughly with clean water. DO NOT ALLOW solution to dry on wood surface.

## Luxury Finish + Sealant In One Satin Semi-Transparent

## APPLICATION INFORMATION

**CAUTION: Surfaces are slippery when wet. Use caution when walking on wet surfaces.** Test wood for absorbency by sprinkling water on the surface – if water is absorbed within 30 sec. to 2 min., depending on climate, the surface is ready for finishing. If water is not absorbed, wait 30 days and re-test. Before starting, test your color choice on a small area. Buy sufficient product for the whole job. Intermix all product together before starting to avoid color variance. Stir thoroughly before and during application. Do not thin. Apply when air and surface temperature is between 50°F (10°C) and 90°F (32°C). Do not apply in direct sunlight, if rain, snow, heavy dew, or low temperatures below 40°F (4°C) are expected within 48 hours. USE WITH ADEQUATE VENTILATION. KEEP OUT OF REACH OF CHILDREN. Read all label and Safety Data Sheet (SDS) information prior to use. SDS are available through our web site or by calling 1-800-441-9695.

**Application Equipment:** Apply using a high-quality, natural bristle brush. First coat must be applied to all six sides, saturating all end grains, nail holes, and cracks in the wood. Apply an even coat, in the direction of the wood grain, avoiding heavy application. Maintain a wet edge to avoid lap marks. Wait 24 hours before applying the second coat. TWO-COAT APPLICATION IS RECOMMENDED FOR OPTIMAL PERFORMANCE.

**Brush:** Natural Bristle Brush

**Thinning:** Do not thin.

**Permissible temperatures during application:**

|            |            |            |
|------------|------------|------------|
| Material:  | 50 to 90°F | 10 to 32°C |
| Ambient:   | 50 to 90°F | 10 to 32°C |
| Substrate: | 50 to 90°F | 10 to 32°C |

## PRECAUTIONS

**DANGER! COMBUSTIBLE LIQUID AND VAPOR. HARMFUL IF INHALED. HARMFUL IF ABSORBED THROUGH SKIN. HARMFUL OR FATAL IF SWALLOWED. CAUSES RESPIRATORY TRACT, EYE AND SKIN IRRITATION. MAY CAUSE ALLERGIC SKIN REACTION.** Sanding and grinding dusts may be harmful if inhaled. Inhalation of high concentrations of vapor may affect the central nervous system. Repeated exposure to high vapor concentrations may cause irritation of the respiratory system and permanent brain and nervous system damage. High vapor concentrations can cause headaches, dizziness, drowsiness and nausea and may lead to unconsciousness. Can enter lungs and cause damage. Keep away from heat and flame. Do not breathe vapor or mist. Do not swallow. Do not get on skin or clothing. Avoid contact with eyes. Keep container tightly closed and sealed until ready for use. Wash thoroughly after handling. Provide fresh air ventilation during and after application and drying. Avoid the inhalation of dust, particulates, spray or mist arising from the application of this preparation. Use personal protective equipment as required. DANGER - RAGS, STEEL WOOL OR WASTE SOAKED WITH PITTSBURGH PAINTS & STAINS PARAMOUNT FINISH MAY SPONTANEOUSLY CATCH FIRE IF IMPROPERLY DISCARDED. IMMEDIATELY AFTER EACH USE, PLACE RAGS, STEEL WOOL OR WASTE IN A SEALED WATER-FILLED METAL CONTAINER. **Note: These warnings encompass the product series. Prior to use, read and follow product-specific SDS and label information. FIRST AID:** If swallowed, rinse mouth with water (only if the person is conscious). Call physician immediately. Do not induce vomiting unless directed to do so by medical personnel. If in eyes, rinse with water for 15 minutes. Check for and remove any contact lenses. In case of contact, immediately flush skin with plenty of water while removing contaminated clothing and shoes. Get medical attention immediately. If inhaled, remove to fresh air. Call physician immediately. Keep out of the reach of children. For workplace use, an SDS is available from your retailer or by calling (412) 492-5555. EMERGENCY SPILL INFORMATION: (412) 434-4515 (U.S.).

© 2024 PPG Industries, Inc. All Rights Reserved. The PPG Logo is a registered trademark of PPG Industries Ohio, Inc. Pittsburgh Paints & Stains is a trademark and Paramount is a registered trademark of PPG Architectural Finishes, Inc.

PPG Architectural Finishes, Inc. believes the technical data presented is currently accurate: however, no guarantee of accuracy, comprehensiveness, or performance is given or implied. Improvements in coatings technology may cause future technical data to vary from what is in this bulletin. For complete, up-to-date technical information, call 1-800-441-9695.



PPG Architectural Finishes, Inc.  
One PPG Place  
Pittsburgh, PA 15272  
[www.pittsburghpaintsandstains.com](http://www.pittsburghpaintsandstains.com)

Technical Services  
1-800-441-9695

Architect/Specifier  
1-888-PPG-IDEA

PPG Architectural Coatings Canada Inc.  
1550 rue Ampère, Suite 500  
Boucherville (Quebec) J4B 7L4

41-9001 - 11/2024