



TECHNICAL DATA SHEET
SICO PRESTIGE™ FOR CEILINGS 941-113, WHITE
INTERIOR STAIN-BLOCKING CEILING PAINT
Water-based product, flat for ceilings, ultra-flat finish

Product Description

SICO® PRESTIGE™, flat for ceilings is a stain-blocking ceiling paint ideal for use on properly prepared, interior ceilings where a durable, premium-quality, ultra-flat finish is desired. True one-coat hide^A.

Advantages

- **True One-Coat Hide^A**
- Stain-Blocking ceiling paint.
- Great Touch-Up.
- Ultra-Flat finish.
- Tintable to over 600 colours.
- Low Spatter.
- Formulated to resist mildew growth on the paint film.
- Easy to apply.
- Water-based product which allows tool clean-up with water.

Projects

Environment

Interior only.

Use

Residential and commercial sites.

Ceilings of any room.

Surfaces

Previously painted surfaces or not: drywall, wood and concrete.

Notes

^A**Only when tinted to colours from the SICO® One-Coat Ceiling Colour Palette.**

Not to be applied directly to bare ferrous metals (iron, steel).

Not formulated to be used on floors.

Some colours, or drastic colour changes, may require an additional coat of paint.

Do not mix with other paints or thinners.

Certifications

Contributes toward satisfying LEED® v4 EQ credits due to low VOC.

Technical Specifications (21°C (70°F))

Appearance

Opaque

Gloss Level

Ultra-Flat finish

- Gloss at 60°: 0 to 3%
- Gloss at 85°: 0 to 3%

Composition

- Diluent: Water
- Binder: Vinyl acrylic

Drying Time*

- Touch dry: 30-60 minutes
- Dust free: 2 to 3 hours
- Before recoating: 4 hours
- Full curing: 30 days

If relative humidity is higher than 50%, required time must be doubled.

Drying times listed may vary depending on temperature, humidity, colour, film build, and air movement.

Spreading Rate per Coat

Approximately 28 to 37 m² (300 to 400 ft²) for 3.78 L; on smooth, nonporous surfaces.

Coverage figures do not include material loss due to application. Some colours, drastic colour changes, or porous surfaces may require additional coats of paint to achieve a uniform finish.

Volatile Organic Compounds (VOCs)*

According to ASTM D3960-05: < 50 g/L

Solids by Volume*

31.5%

Flammability

Non flammable

Minimal Film Thickness*

(According to the maximum spreading rate)

- Wet: 4.0 mils (102 µm)
- Dry: 1.3 mils (32 µm)

Certification*

Not available

*Technical data source: 941-113

SATISFACTION GUARANTEED

The manufacturer warrants your complete satisfaction with the performance of this product for as long as you own or reside in your home when our product has been applied and maintained according to label directions. This satisfaction guarantee is non-transferable. The manufacturer does not warrant against problems with the product which are caused by factors beyond its control, such as structural defects, damage to the coating film by others, poor condition of the substrate, improper application, etc. If not satisfied as warranted, return the unused portion along with sales receipt to place of purchase. You will receive as your exclusive remedy either a refund of the price paid for the product or replacement with product of equal value. This warranty specifically excludes labour or costs of labour for the removal or application of any coating and indirect, special, consequential, and incidental damages.

Surface Preparation

Surface must be clean and dry. Remove all loose, peeling paint, dirt, grease, and any other surface contaminants. Putty all nail holes and caulk all cracks or open seams. Sand all glossy, rough, and patched surfaces.

- ▶ Clean with an appropriate cleaner for removing the contaminant. Remove mildew with a solution of household bleach (1 part household bleach to 3 parts of water). Wear rubber gloves and eye protection.
- ▶ Rinse thoroughly with clear water and let dry completely.
- ▶ Concrete, Stucco, or Masonry: Plaster, concrete, and masonry must be completely dry, free of efflorescence, and allowed to cure for 30 days prior to painting.
- ▶ Putty all nail holes and caulk all cracks or open seams.
- ▶ If wood exudes resin, scrape the excess and clean with alcohol or paint thinner. Sand for a smooth finish. Eliminate sanding residues. Seal knots and sap streaks with shellac before applying the product.

Listed below are the main base coat products that are recommended:

- **Primers:** This paint may be used as a primer coat on bare areas or total surface. However, for optimum results, especially on tough stains or on very porous or absorbent surfaces, it is recommended to apply the suitable basecoat.
- **Concrete, Stucco, or Masonry:** Plaster, concrete, and masonry must be completely dry, free of efflorescence, and allowed to cure for 30 days prior to painting. Remove surface dust and prime entire surface with an appropriate primer.
- **Previously Painted Alkyd Surfaces in Good Condition:** Prime surface with an appropriate primer. When applied to an uncoated substrate, two coats are required, with the first coat acting as the primer.
- Apply an appropriate specialty primer on all special substrates, such as tannin staining wood or bare metal. For severe stains, water marks, and other challenging conditions, such as bare metal or chalky surfaces, use an appropriate specialty primer.

Recommendations

Application Conditions

Temperature: 10 to 32°C (50 to 90°F)
(ideal 20°C ± 5°C [68°F ± 9°F])
Relative humidity: Ideal between 15 and 55%, maximum 85%.

Maintain these conditions during the application and the following 24 hours. Low temperature, high humidity, thick films or poor ventilation extend drying time.

Tools

- Paintbrush: Synthetic bristles (nylon, polyester).
- Roller:
 - Ceilings: nap size – 10 mm or 13 mm for smooth surfaces.

Cleaning Tools

Remove as much product quantity as possible and clean tools with warm, soapy water.

Storage and Transportation

Keep in a dry and ventilated area, between 10 and 30°C (50 and 86°F).

PROTECT FROM FREEZING.

Disposal

Consult your municipality about proper disposal procedure of residue in accordance with the laws and respect the environment. Do not pour down a drain or storm sewer.

PRECAUTION: Dry sanding will give rise to dust and/or hazardous fumes. Wear suitable respiratory protective equipment. **WARNING!** If you scrape, sand, or remove old paint, you may release lead dust. **LEAD IS TOXIC.** Contact a regional Health Canada office for more information.

Application

Stir thoroughly. Do not thin. Apply with a high-quality brush, roller (nap size – 10 mm or 13 mm for smooth surfaces, and up to 20 mm for rough or textured surfaces), paint pad, or by airless spray equipment. When using more than one container of the same colour, intermix to ensure colour uniformity. Apply only when air, surface, and product temperatures are between 10°C (50°F) and 32°C (90°F).

Remove masking tape after each coat to avoid lifting up paint when work is completed.

For more information, visit the website at www.sico.ca or call our customer service: 1-800-463-7426.

Safety Measures

MAY BE HARMFUL IF SWALLOWED. MAY CAUSE EYE AND SKIN IRRITATION. Avoid breathing vapours, spray or mists. Avoid contact with skin and eyes. Wear protective gloves/clothing and eye/face protection. Keep out of reach of children. **FIRST AID TREATMENT:** If swallowed, call a Poison Control Centre or doctor immediately. If in eyes or on skin, rinse well with water. If breathed in, move person to fresh air. Contains: titanium dioxide; Limestone; Diatomaceous earth; Kaolin; Silicic acid; crystalline silica, respirable powder (<10 microns). Sanding and grinding dusts may be harmful if inhaled. This product contains crystalline silica which can cause lung cancer or silicosis. The risk of cancer depends on the duration and level of exposure to dust from sanding surfaces or mist from spray applications. Contains isothiazolinones. May cause allergic reaction. Keep container tightly closed and sealed until ready for use. For workplace use, an SDS is available from your retailer or by calling 1-800-463-7426. **EMERGENCY SPILL INFORMATION:** (412) 434-4515 (U.S.), (514) 645-1320 (Canada).

Surface Maintenance

- Wait for its full curing before washing the product or testing its adhesion: minimum 30 days (longer in conditions of high humidity or low temperature). Use a non-abrasive cleaner and a soft cloth.
- If required, touch up bare areas with this product or a primer and apply another coat on the whole surface.

PPG Architectural Finishes, Inc. believes the technical data presented is currently accurate; however, no guarantee of accuracy, comprehensiveness, or performance is given or implied. Improvements in coatings technology may cause future technical data to vary from what is in this bulletin. For complete, up-to-date technical information, visit our web site or call 1-866-660-2220.



PPG Architectural Coatings Canada, Inc.
1550 rue Ampère, Suite 500
Boucherville (Quebec), J4B 7L4

The PPG Logo is a registered trademark of PPG Industries Ohio, Inc. Sico is a registered trademark and Sico Prestige is a trademark of PPG Architectural Finishes, Inc.