



Architectural Coatings

Sico Perma-Flex All Surface Interior/Exterior Paint + Primer

GENERAL DESCRIPTION

Sico Perma-Flex All Surface is an interior/exterior paint + primer* spray paint with revolutionary technology that provides exceptional coverage. It provides an ultra-durable finish on a wide range of surfaces like wood, plastic, glass and more. It covers surfaces with fewer spray passes and dries within 5 minutes with a flawless, durable finish, so your projects can be completed easier and faster.

*Separate primer or multiple coats may be required. See COVERAGE for details.

RECOMMENDED SUBSTRATES

Table with 2 columns: Substrate Type and Material. Rows include Ceramic, Ferrous Metal, Glass, Plastic, Vinyl, Wood.

FEATURES / BENEFITS

- Ultra durable finish
Flawless finish
Dries within 5 minutes
No drips or streaks
Interior/Exterior Paint + Primer

PRODUCT INFORMATION

Table with 2 columns: Product Code and Color/Finish. Lists 16 different paint finishes from SPF1012 to SPF1033.

PACKAGING

Aerosol Net Weight 340 g

PRODUCT DATA

Table with 2 columns: Property and Value. Includes PRODUCT TYPE (Lacquer), SHEEN (Matte, Satin, Gloss), VOLUME SOLIDS*, WEIGHT SOLIDS*, WEIGHT/GALLON*, and MAX PWMIR*.

*Product data calculated from SPF1020.

COVERAGE: One can covers approximately 2.3 sq. metres (25 sq. ft.). Coverage figures do not include material loss due to surface irregularities and porosity, or material loss due to application method.

Table with 2 columns: Property and Value. Includes DRYING TIME (Dry time @ 21°C), To Touch (5 minutes), To Recoat (5-10 minutes), and Put In Use (24-48 hours).

Drying times listed may vary depending on temperature, humidity, film build, and air movement. Heavier application may take longer.

CLOGGING: If valve clogs, twist and pull off spray tip and rinse in a solvent, such as mineral spirits. Do not stick a pin or other objects in the stem.

CLEANUP: When finished spraying, hold can upside down and spray until clear gas appears, then wipe off tip before storing. Clean up wet paint with mineral spirits or paint thinner.

DISPOSAL: Contact your municipality for guidance on disposal of empty can. Do not burn or place in home trash compactor.

FLASH POINT: -95°C (-139°F)

LIMITATIONS OF USE

Use outdoors or in a well-ventilated area, such as an open garage. Cover surrounding area to protect from overspray. Apply when no precipitation is expected for 24 hours, and when temperature is 10°C (50°F) to 32°C (90°F) and will remain above 10°C (50°F) for the next 24 hours.

Not recommended for use on polyethylene.

GENERAL SURFACE PREPARATION

Surface must be clean and dry. Remove all dust, dirt, mildew, oil, loose peeling paint, and other contaminants. Putty all nail holes and caulk all cracks and open seams. Sand all glossy, rough, and patched surfaces.

WARNING! If you scrape, sand, or remove old paint, you may release lead dust. LEAD IS TOXIC. Contact a regional Health Canada office for more information.

CERAMIC and GLASS: The surface must be cleaned thoroughly to remove any dust, dirt, and surface contaminants, and then painted.

FERROUS METAL: The surface must be cleaned thoroughly to remove any dust, rust, and surface contaminants, and then painted.

WOOD: Countersink all nails, putty flush with surface. Unpainted wood or wood in poor condition should be sanded smooth, wiped clean.

VINYL and ARCHITECTURAL PLASTIC: Vinyl and similar architectural plastics may present potential adhesion problems. Some plastics made of polyethylene, such as plastic storage bins, are manufactured in a way that may hinder paint adhesion. Product is not recommended for use on polyethylene due to its adhesion properties. For other plastics, test in a hidden area first. Product should be spot applied, allowed to cure overnight, then evaluated for adhesion. If adhesion is good, the application may proceed. Check adhesion by applying a piece of masking tape. When the masking tape is removed, if the coating peels off, the surface must be scuff sanded prior to proceeding to ensure mechanical adhesion. Exterior vinyl and similar plastic composites should not be painted with a color darker than the original color. Painting exterior vinyl or plastic composites with a darker color may cause them to warp.

APPLICATION INFORMATION

Shake can vigorously for 1 to 2 minutes and often during use. Hold can upright 15 to 25 cm (6" to 10") from the surface and spray in a steady back-and-forth motion, slightly overlapping each stroke. Maintain the can the same distance from the surface. Keep the can in motion while spraying. Apply light coats over the entire surface until hiding is achieved, allowing 5 to 10 minutes between coats. Do not saturate surface.

Permissible temperatures during application

Material: 10 to 32°C (50 to 90°F)

Ambient: 10 to 32°C (50 to 90°F)

Substrate: 10 to 32°C (50 to 90°F)

PRECAUTIONS

EXTREME DANGER VERY FLAMMABLE CONTENTS UNDER PRESSURE IRRITANT. CONTAINER MAY EXPLODE IF HEATED. CONTENTS MAY CATCH FIRE. MAY IRRITATE EYES. Do not smoke. Do not puncture. Do not burn. Do not get in eyes. Use only in a well-ventilated area. Keep away from flames, such as a pilot light, and any object that sparks, such as an electric motor. Store away from heat. Keep out of reach of children. Wear protective gloves and eye/face protection: Chemical splash goggles. Use chemical-resistant, impervious gloves. **Note: These warnings encompass the product series. Prior to use, read and follow product-specific SDS and label information. FIRST AID TREATMENT:** Contains: acetone; propane; butane; toluene; isobutyl acetate; 4-methylpentan-2-one; titanium dioxide; ethyl 3-ethoxypropionate; butanone; 2-methoxy-1-methylethyl acetate; 2-(propyloxy)ethanol; xylene; ethylbenzene; methanol; carbon black; titanium dioxide; Aluminum powder (stabilized); iron hydroxide oxide yellow. If swallowed, call a Poison Control Centre or doctor immediately. Do not induce vomiting. If in eyes, rinse with water for 15 minutes. If breathed in, move person to fresh air. Sanding and grinding dusts may be harmful if inhaled. Keep container tightly closed and sealed until ready for use. For workplace use, an SDS is available from your retailer or by calling 1-800-463-7426 (Canada). EMERGENCY SPILL INFORMATION: (412) 434-4515 (U.S.), (514) 645-1320 (Canada).

The PPG Logo is a registered trademark of PPG Industries Ohio, Inc. Sico is a registered trademark of PPG Architectural Finishes, Inc. Perma-Flex is a registered trademark of PPG Architectural Coatings Canada, Inc.

PPG Architectural Finishes, Inc. believes the technical data presented is currently accurate; however, no guarantee of accuracy, comprehensiveness, or performance is given or implied. Improvements in coatings technology may cause future technical data to vary from what is in this bulletin. For complete, up-to-date technical information, visit our web site or call 1-866-660-2220.



PPG Industries, Inc.
Architectural Coatings
One PPG Place
Pittsburgh, PA 15272

Technical Services
1-866-660-2220

Architect/Specifier
1-888-PPG-IDEA

PPG Architectural Coatings Canada, Inc.
1550 rue Ampère, Suite 500
Boucherville (Quebec) J4B 7L4

SPF10XX - 09/2023