

**GENERAL DESCRIPTION**

Sico Perma-Flex Exterior Fabric is an exterior paint + primer\* spray paint with revolutionary technology that provides maximized UV protection for exterior fabrics like vinyl, leather, rugs, and more. Sico Perma-Flex Exterior Fabric provides exceptional coverage on solid colored non-patterned fabrics, while preserving the original look and feel of your item.

\*Multiple coats may be required. See COVERAGE for details.

**RECOMMENDED SUBSTRATES**

Canvas	Leather
Rugs	Vinyl

**FEATURES / BENEFITS**

- Use on vinyl, leather, rugs and more
- Preserves original look and feel of your item
- Maximized UV protection
- Dries within 5 Minutes
- Exterior Paint + Primer

**PRODUCT INFORMATION**

SPF2014	Cavalry Satin
SPF2017	Elemental Satin
SPF2031	Only Oatmeal Satin
SPF2032	Onyx Satin
SPF2033	Romantic Isle Satin
SPF2034	Rum Punch Satin
SPF2035	Suddenly Sapphire Satin
SPF2036	Black Satin

**PACKAGING**

Aerosol Net Weight (340 g)

**PRODUCT DATA**

**PRODUCT TYPE:** Lacquer  
**SHEEN:** Satin, 3-16 @ 60°  
**VOLUME SOLIDS\*:** 6% +/- 2%  
**WEIGHT SOLIDS\*:** 12% +/- 2%  
**WEIGHT/GALLON\*:** 6.4 lbs. (2.9 kg) +/- 0.2 lbs. (91 g)  
**MAX PWMIR\*:** < 1.45

\*Product data calculated from SPF2031.

**COVERAGE:** One can covers approximately 2.3 sq. metres (25 sq. ft.). Coverage figures do not include material loss due to surface irregularities and porosity, or material loss due to application method. Some surfaces including uncoated substrates, repaired surfaces, porous surfaces, stained areas, patterned surfaces, and drastic colour changes may require multiple coats to achieve a uniform finish. Some patterned surfaces may always be visible after application. Avoid applying very thick or too many coats to ensure fabric stays flexible.

**DRYING TIME:** Dry time @ 21°C (70°F); 50% relative humidity.  
 To Touch: 5 minutes  
 To Recoat: 5-10 minutes  
 Put In Use: 24-48 hours

Drying times listed may vary depending on temperature, humidity, film build, and air movement. Heavier application may take longer.

**CLOGGING:** If valve clogs, twist and pull off spray tip and rinse in a solvent, such as mineral spirits. Do not stick a pin or other objects in the stem.

**CLEANUP:** When finished spraying, hold can upside down and spray until clear gas appears, then wipe off tip before storing. Clean up wet paint with mineral spirits or paint thinner.

**DISPOSAL:** Contact your municipality for guidance on disposal of empty can. Do not burn or place in home trash compactor.

**FLASH POINT:** -95°C (-139°F)

**LIMITATIONS OF USE****EXTERIOR ONLY.**

Cover surrounding area to protect from overspray. Apply when no precipitation is expected for 24 hours, and when temperature is 10°C (50°F) to 32°C (90°F) and will remain above 10°C (50°F) for the next 24 hours. Avoid spraying in windy, dusty conditions.

## GENERAL SURFACE PREPARATION

Surface must be clean and dry. Remove all dust, dirt, mildew, oil, loose peeling paint, and other contaminants. Putty all nail holes and caulk all cracks and open seams. Sand all glossy, rough, and patched surfaces.

**WARNING!** If you scrape, sand, or remove old paint, you may release lead dust. LEAD IS TOXIC. Contact a regional Health Canada office for more information.

**Note:** Many manufacturers of fabric and rugs apply stain and water repellants to these surfaces. These repellants can affect adhesion of the paint to the surface. Always test by dripping some water onto the surface; if it "beads up", this indicates that there is a coating on the surface that may inhibit adhesion. If it soaks in, then spraying should be fine.

**CANVAS:** The surface must be cleaned thoroughly to remove any dust, dirt, and surface contaminants, and then painted.

**RUGS AND COARSE FABRIC:** After each spray pass on a rug, before it dries, brush it with a bristle brush to get deep into the fibers to disperse the paint and remove excess. When following this method, rugs will dry with a soft texture and virtually no change from its original feel.

**LEATHER:** The surface must be cleaned thoroughly to remove any dust, dirt, and surface contaminants, and then painted.

**VINYL:** The surface must be cleaned thoroughly to remove any dust, dirt, and surface contaminants, and then painted. Exterior vinyl and similar plastic composites should not be painted with a color darker than the original color. Painting exterior vinyl or plastic composites with a darker color may cause them to warp.

## APPLICATION INFORMATION

Shake can vigorously for 1 to 2 minutes and often during use. Hold can upright 15 to 25 cm (6" to 10") from the surface and spray in a steady back-and-forth motion, slightly overlapping each stroke. Maintain the can the same distance from the surface. Keep the can in motion while spraying. Apply light coats over the entire surface until hiding is achieved, allowing 5 to 10 minutes between coats. Do not saturate surface.

### Permissible temperatures during application:

Material: 10 to 32°C (50 to 90°F)

Ambient: 10 to 32°C (50 to 90°F)

Substrate: 10 to 32°C (50 to 90°F)

## PRECAUTIONS

**EXTREME DANGER VERY FLAMMABLE CONTENTS UNDER PRESSURE IRRITANT.** CONTAINER MAY EXPLODE IF HEATED. CONTENTS MAY CATCH FIRE. MAY IRRITATE EYES. Do not smoke. Do not puncture. Do not burn. Do not get in eyes. Use only in a well-ventilated area. Keep away from flames, such as a pilot light, and any object that sparks, such as an electric motor. Store away from heat. Keep out of reach of children. Wear protective gloves and eye/face protection: Chemical splash goggles. Use chemical-resistant, impervious gloves. Wear appropriate respirator when ventilation is inadequate. **Note: These warnings encompass the product series. Prior to use, read and follow product-specific SDS and label information. FIRST AID TREATMENT:** Contains: acetone; propane; butane; toluene; isobutyl acetate; 4-methylpentan-2-one; 2-methoxy-1-methylethyl acetate; ethyl 3-ethoxypropionate; butanone; n-butyl acetate; xylene; titanium dioxide; ethylbenzene; methanol; 2-(propyloxy)ethanol; carbon black. If swallowed, call a Poison Control Centre or doctor immediately. Do not induce vomiting. If in eyes, rinse with water for 15 minutes. If breathed in, move person to fresh air. Sanding and grinding dusts may be harmful if inhaled. Keep container tightly closed and sealed until ready for use. For workplace use, an SDS is available from your retailer or by calling 1-800-463-7426 (Canada). EMERGENCY SPILL INFORMATION: (412) 434-4515 (U.S.), (514) 645-1320 (Canada).

The PPG Logo is a registered trademark of PPG Industries Ohio, Inc. Sico is a registered trademark of PPG Architectural Finishes, Inc. Perma-Flex is a registered trademark of PPG Architectural Coatings Canada, Inc.

PPG Architectural Finishes, Inc. believes the technical data presented is currently accurate; however, no guarantee of accuracy, comprehensiveness, or performance is given or implied. Improvements in coatings technology may cause future technical data to vary from what is in this bulletin. For complete, up-to-date technical information, visit our web site or call 1-866-660-2220.



PPG Industries, Inc.  
Architectural Coatings  
One PPG Place  
Pittsburgh, PA 15272

Technical Services  
1-866-660-2220

Architect/Specifier  
1-888-PPG-IDEA

PPG Architectural Coatings Canada, Inc.  
1550 rue Ampère, Suite 500  
Boucherville (Quebec) J4B 7L4

SPF20XX - 05/2024