



PPG TIMELESS Advanced Penetrating Oil Technology Stain & Sealant In One

GENERAL DESCRIPTION

PPG TIMELESS Transparent Penetrating Wood Oil colors provide high-clarity color that allows wood's natural grain and texture to show through. Penetrating formula provides waterproofing and UV defense to strengthen and protect wood fibers, helping to ensure the wood's natural beauty lasts. Recommended for use on exterior wood decks, fences, siding, railings, outdoor furniture and other wood surfaces. Apply to new, dry, pressure-treated wood, uncoated new or weathered wood, or previously coated wood with a weathered, clear sealant or semi-transparent stain.

RECOMMENDED SUBSTRATES

Wood	Siding
Pressure-treated wood	Railings
Decks	Plywood
Fences	Outdoor Furniture

FEATURES / BENEFITS

Durable protection against the elements
Provides powerful mold, mildew & algae-resistant coating
Powerful UV absorbers protect color & wood
Water repellents protect against cracking, splitting & warping of wood

LIMITATIONS OF USE

FOR EXTERIOR USE ONLY. PROTECT FROM FREEZING.

Apply when air and surface temperatures are 35°F to 90°F (2°C to 32°C) and will remain above 35°F (2°C) for the next 24 hours. Avoid application in direct sunlight or on hot surfaces. Caution: Avoid direct skin contact with hot surfaces. It is not recommended to apply product if rain is expected within 24 hours.

While this product provides a mildew resistant coating, growth may still occur if the substrate is not properly prepared prior to painting and/or if the substrate is consistently exposed to conditions conducive to mold, mildew, and algae. Examples of these conditions include, but are not limited to, under eaves, behind shrubbery and trees, and in areas that are consistently damp with little to no direct sunlight.

Not recommended for recently painted or sealed surfaces. Do not use on plastic, rubber, asphalt, tile, vinyl, concrete or any non-porous surface.

PRODUCT INFORMATION

PPG1100V	Natural
PPG1110V	Cedar
PPG1120V	Mahogany
PPG1130V	Jatoba
PPG1140V	Oxford Brown

DO NOT TINT.

PRODUCT DATA

PRODUCT TYPE:	Acrylic/Oil Resin
VOLUME SOLIDS*:	17% +/- 2%
WEIGHT SOLIDS*:	19% +/- 2%
VOC:	<100 g/L (0.8 lbs./gal.)
WEIGHT/GALLON*:	8.5 lbs. (3.9 kg) +/- 0.2 lbs. (91 g)

*Product data calculated on product PPG1110V

COVERAGE: Approximately 250 to 350 sq. ft. (23.2 to 32.5 sq. meters) per gallon (3.78 L) depending upon wood texture.

Coverage figures do not include loss due to surface irregularities and porosity or material loss due to application method or mixing.

DRYING TIME: Normally dries in 24 hours when applied in optimal temperatures of 50°F (10°C) to 85°F (29°C). Application in high humidity or in temperatures below 50°F (10°C) may prolong drying time. Allow 24 to 48 hours of drying time before light foot traffic or replacing furniture.

CLEANUP: Clean brushes and tools with warm soapy water.

DANGER - RAGS, STEEL WOOL OR WASTE SOAKED WITH PPG TIMELESS STAIN MAY SPONTANEOUSLY CATCH FIRE IF IMPROPERLY DISCARDED. IMMEDIATELY AFTER EACH USE, PLACE RAGS, STEEL WOOL OR WASTE IN A SEALED WATER-FILLED METAL CONTAINER.

DISPOSAL: Contact your local environmental regulatory agency for guidance on disposal of unused product. Do not pour down a drain or storm sewer.

FLASH POINT: Over 200°F (93°C)

PACKAGING

3-Gallon (11.36 L)
1-Gallon (3.78 L)

PPG TIMELESS Advanced Penetrating Oil Technology Stain & Sealant In One

GENERAL SURFACE PREPARATION

Proper surface preparation is essential for the PPG TIMELESS Stain limited warranty to apply. Surface must be clean, dry and free of all dust, dirt, mildew, oil, loose wood fibers, and other contaminants. Previous coatings must be completely removed. Prior to application, clean weathered, dirty, or mildewed surfaces with a wood cleaner. After rinsing, allow wood to dry. Remove grade stamps or pencil marks by sanding.

WARNING! If you scrape, sand, or remove old paint, you may release lead dust or fumes. LEAD IS TOXIC. EXPOSURE TO LEAD DUST OR FUMES CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE. Wear a properly fitted NIOSH-approved respirator and prevent skin contact to control lead exposure. Clean up carefully with a HEPA vacuum and a wet mop. Before you start, find out how to protect yourself and your family by contacting the USEPA National Lead Information Hotline at 1-800-424-LEAD or log on to www.epa.gov/lead. Follow these instructions to control exposure to other hazardous substances that may be released during surface preparation.

FENCES, SIDING OR DECKS: Clean weathered, dirty or mildewed surfaces with a wood cleaner prior to applying product. Before use, be sure to read and follow the instructions and warnings on the label.

EXTRACTIVE BLEEDING: Some woods, such as redwood and cedar contain natural water-soluble colorings or extractives that tend to “bleed” or migrate to the surface. If extractive bleeding occurs, allow the coating to dry completely, then wash with a mild detergent solution and rinse with clear water.

APPLICATION INFORMATION

Intermix containers to ensure color uniformity. Stir thoroughly and often during use.

PRETEST: Apply to a small area and allow to dry to ensure applicable appearance and penetration. For previously coated wood: If the product is not absorbed into the surface and is still tacky after 12 hours, the surface is not suitable for application. For damp wood: If wood is too damp to allow penetration, allow to dry further and retest for penetration.

APPLICATION METHOD: Apply one thin coat. To help avoid lapmarks, apply to only a few boards at a time keeping a wet edge. Do not saturate or puddle on horizontal surfaces.

APPLICATION EQUIPMENT: Apply with a high quality brush, paint/stain pad or by spray equipment. When spraying, always back brush for best results.

THINNING: DO NOT THIN.

PRECAUTIONS

DANGER! HARMFUL OR FATAL IF SWALLOWED. Sanding and grinding dusts may be harmful if inhaled. Can enter lungs and cause damage. Do not breathe vapor or mist. Do not swallow. Keep container tightly closed and sealed until ready for use. Wash thoroughly after handling. Provide fresh air ventilation during and after application and drying. Avoid the inhalation of dust, particulates, spray or mist arising from the application of this preparation. Use personal protective equipment as required. DANGER - RAGS, STEEL WOOL OR WASTE SOAKED WITH PPG TIMELESS STAIN MAY SPONTANEOUSLY CATCH FIRE IF IMPROPERLY DISCARDED. IMMEDIATELY AFTER EACH USE, PLACE RAGS, STEEL WOOL OR WASTE IN A SEALED WATER-FILLED METAL CONTAINER.

Note: These warnings encompass the product series. Prior to use, read and follow product-specific MSDS and label information. **FIRST AID:** If swallowed, rinse mouth with water (only if the person is conscious). Call physician immediately. Do not induce vomiting unless directed to do so by medical personnel. If in eyes, rinse with water for 15 minutes. Check for and remove any contact lenses. If on skin, rinse well with water. Wash with soap and water. Get medical attention if irritation develops. If inhaled, remove to fresh air. If experiencing respiratory symptoms call a POISON CENTER or doctor/physician. Keep out of the reach of children. For workplace use, an MSDS is available from your retailer or by calling (412) 492-5555. EMERGENCY SPILL INFORMATION: (412) 434-4515 (U.S.).

© 2016 PPG Industries, Inc. All Rights Reserved. The PPG Logo is a registered trademark of PPG Industries Ohio, Inc. Timeless is a trademark of PPG Architectural Finishes, Inc.

PPG Architectural Finishes, Inc. believes the technical data presented is currently accurate; however, no guarantee of accuracy, comprehensiveness, or performance is given or implied. Improvements in coatings technology may cause future technical data to vary from what is in this bulletin. For complete, up-to-date technical information, call 1-800-441-9695.



PPG Industries, Inc.
Architectural Coatings
One PPG Place
Pittsburgh, PA 15272
www.ppg.com

Technical Services
1-800-441-9695

Architect/Specifier
1-888-PPG-IDEA

PPG Architectural Coatings Canada Inc.
2505, rue de la Métropole,
Longueuil (Québec) Canada J4G 1E5

PPG1100V 6/2017