



## OLYMPIC® Premium Interior Oil Based Sanding Sealer

## GENERAL DESCRIPTION

OLYMPIC® Premium Oil Based Sanding Sealer is formulated to create an ultra smooth surface prior to the application of an oil or water based topcoat. This product will allow you to achieve professional looking results while saving you time and money. OLYMPIC Premium Oil Based Sanding Sealer is strongly recommended for use on stained or unfinished interior wood surfaces including floors, doors, trim, furniture, cabinets or paneling. It's fast drying and easy to sand, allowing for multiple applications in one day.

## RECOMMENDED SUBSTRATES

|        |           |
|--------|-----------|
| Floors | Furniture |
| Doors  | Cabinets  |
| Trim   | Paneling  |

## FEATURES / BENEFITS

Prepares Wood for a Smooth, Even Topcoat  
Fast Drying  
Sands Easily  
For Use on Wood Floors

## DIRECTIONS FOR USE

Stir thoroughly before and during use.

## APPLICATION INFORMATION

**Application Equipment:** Apply one even coat with a natural bristle brush.

**Application Method:** Apply one even coat with the grain of the wood using a smooth, even stroke.

Allow a minimum of 2 hours drying time before sanding with 200 grit or finer sandpaper. Topcoat with OLYMPIC Premium Interior Water Based Polyurethane or Fast Dry Varnish.

**Thinning:** No thinning is needed.

## PRODUCT INFORMATION

41060 Sanding Sealer

## PRODUCT DATA

|                       |                                       |
|-----------------------|---------------------------------------|
| <b>PRODUCT TYPE:</b>  | Alkyd/Oil Resin                       |
| <b>VOLUME SOLIDS:</b> | 30% +/- 2%                            |
| <b>WEIGHT SOLIDS:</b> | 36% +/- 2%                            |
| <b>VOC:</b>           | <550 g/L (4.58 lbs./gal.)             |
| <b>WEIGHT/GALLON:</b> | 7.0 lbs. (3.2 kg) +/- 0.2 lbs. (91 g) |
| <b>FLASH POINT:</b>   | 63°F (17.2°C)                         |

**COVERAGE:** Approximately 500 - 700 sq. ft. (46.5- 65.0 sq. meters) per gallon (3.78L). Coverage will vary with wood type, porosity, preparation and application.

|                     |                  |
|---------------------|------------------|
| Wet Film Thickness: | 2.7 to 3.7 mils  |
| Wet Microns:        | 68.6 to 94       |
| Dry Film Thickness: | 0.8 to 1.10 mils |
| Dry Microns:        | 20.3 to 28       |

**DRYING TIME:** Dry times are affected by humidity, temperature, film build, and moisture content of the wood. Allow a minimum of 2 hours drying time before sanding with 200 grit or finer sandpaper.

**CLEANUP:** Clean up with mineral spirits or paint thinner.

Danger - Rags, steel wool or waste soaked with this product may spontaneously catch fire if improperly discarded. Immediately after use, place rags, steel wool or waste in a sealed water-filled metal container.

## OLYMPIC® Premium Interior Oil Based Sanding Sealer

## GENERAL SURFACE PREPARATION

Proper surface preparation is essential for the OLYMPIC limited warranty to apply. All surfaces must be dry and free from wax, oil, grease, and dirt.

**WARNING!** If you scrape, sand, or remove old paint, you may release lead dust or fumes. LEAD IS TOXIC. EXPOSURE TO LEAD DUST OR FUMES CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE. Wear a properly fitted NIOSH-approved respirator and prevent skin contact to control lead exposure. Clean up carefully with a HEPA vacuum and a wet mop. Before you start, find out how to protect yourself and your family by contacting the USEPA National Lead Information Hotline at 1-800-424-LEAD or log on to [www.epa.gov/lead](http://www.epa.gov/lead). In Canada contact a regional Health Canada office. Follow these instructions to control exposure to other hazardous substances that may be released during surface preparation.

Always sand with the grain of the wood. For hard woods, such as oak and maple, begin sanding with 100 grit sandpaper, then proceed to 150 grit sandpaper, and finish with 200 grit or finer sandpaper. For soft woods, such as pine, begin sanding with 150 grit sandpaper and finish with 200 grit or finer sandpaper.

Remove dust completely. Stain wood if desired.

Topcoat with OLYMPIC Premium Interior Water Based Polyurethane or Fast Dry Varnish. OLYMPIC Oil Based Polyurethane and Interior/Exterior Spar Finish are not recommended as a topcoat.

## LIMITATIONS OF USE

FOR INTERIOR USE ONLY. Not recommended as a finish coat or topcoat. Do not topcoat with a oil based polyurethane. Always sand with the grain of the wood.

Do not apply when the air, coating or surface temperature is below 50°F (10°C).

Do not attempt to use on prewaxed wood flooring. Follow flooring manufacturer's coating recommendations.

This product is not intended for immersion service or other extreme conditions. Not recommended in situations characterized by high heat or presence of corrosive chemicals nor for heavy-duty use on floors.

## PACKAGING

Available in 1-Gallon (3.78L) and 1-Quart (945 mL) containers.

## SAFETY PRECAUTIONS

Before using the products listed in this publication, carefully read each product label and follow directions for its use. Please read and observe all the warnings and precautionary information on the product labels. Material Safety Data Sheets are available through our Sales Representative, Retailer or by calling (412) 492-5555.

Keep containers closed and away from heat, sparks, and flame when not in use.

USE WITH ADEQUATE VENTILATION. KEEP OUT OF REACH OF CHILDREN.

PPG Architectural Finishes, Inc. believes the technical data presented is currently accurate; however, no guarantee of accuracy, comprehensiveness, or performance is given or implied. Improvements in coatings technology may cause future technical data to vary from what is in this bulletin. For complete, up-to-date technical information, call 1-800-441-9695.



PPG Industries, Inc.  
Architectural Coatings  
One PPG Place  
Pittsburgh, PA 15272  
[www.ppgpittsburghpaints.com](http://www.ppgpittsburghpaints.com)  
[www.ppgporterpaints.com](http://www.ppgporterpaints.com)

Technical Services  
1-800-441-9695

Architect/Specifier  
1-888-PPG-IDEA

PPG Canada, Inc.  
Architectural Coatings  
4 Kenview Blvd  
Brampton, ON L6T 5E4

T.D. 4016 10/2011  
(Supersedes 5/2008)

Made in the  
**USA**