



OLYMPIC®

41061

OLYMPIC® Premium Interior Water Based Sanding Sealer

GENERAL DESCRIPTION

OLYMPIC® Premium Water Based Sanding Sealer is formulated to create an ultra smooth surface prior to the application of an oil or water based topcoat. This product will allow you to achieve professional looking results while saving you time and money. Specially designed for use on stained or unfinished interior wood surfaces including floors, doors, trim, furniture, cabinets or paneling. It's fast drying and easy to sand, allowing for multiple applications in one day. It is low in odor and cleans up easily with soap and water.

RECOMMENDED SUBSTRATES

Floors	Furniture
Doors	Cabinets
Trim	Paneling

FEATURES / BENEFITS

Prepares Wood for a Smooth, Even Topcoat
Fast Drying
Sands Easily
For Use on Wood Floors
Soap and Water Cleanup

DIRECTIONS FOR USE

Stir thoroughly before and during use.

APPLICATION INFORMATION

Application Equipment: Apply one even coat with a synthetic brush or foam applicator pad.

Application Method: Apply one even coat with the grain of the wood using a smooth, even stroke.

Allow a minimum of 2 hours drying time before sanding with 200 grit or finer sandpaper. Sand with the grain of the wood. Topcoat with OLYMPIC Premium Interior Water Based or Oil Based Polyurethane, Fast Dry Varnish or Interior/Exterior Spar Finish.

Thinning: No thinning is needed.

PRODUCT INFORMATION

41061 Sanding Sealer

PRODUCT DATA

PRODUCT TYPE:	Styrene Acrylic
VOLUME SOLIDS:	28% +/- 2%
WEIGHT SOLIDS:	30% +/- 2%
VOC:	235 g/L (2.0 lbs./gal.)
WEIGHT/GALLON:	8.5 lbs. (3.9 kg) +/- 0.2 lbs. (91 g)
FLASH POINT:	Seta Flash 210°F (98.9°C)

COVERAGE: Approximately 400 - 535 sq. ft. (37.2 - 50 sq. meters) per gallon (3.78L). Coverage will vary with wood type, porosity, preparation and application.

Wet Film Thickness:	3 to 4 mils
Wet Microns:	76.2 to 101.6

Dry Film Thickness:	0.8 to 1.1 mils
Dry Microns:	20.3 to 28.0

DRYING TIME: Dry times are affected by humidity, temperature, film build, and moisture content of the wood. Allow a minimum of 2 hours drying time before sanding with 200 grit or finer sandpaper.

CLEANUP: Clean up with soap and water.

OLYMPIC® Premium Interior Water Based Sanding Sealer

GENERAL SURFACE PREPARATION

Proper surface preparation is essential for the OLYMPIC limited warranty to apply. All surfaces must be dry and free from wax, oil, grease, and dirt.

WARNING! If you scrape, sand, or remove old paint, you may release lead dust or fumes. LEAD IS TOXIC. EXPOSURE TO LEAD DUST OR FUMES CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE. Wear a properly fitted NIOSH-approved respirator and prevent skin contact to control lead exposure. Clean up carefully with a HEPA vacuum and a wet mop. Before you start, find out how to protect yourself and your family by contacting the USEPA National Lead Information Hotline at 1-800-424-LEAD or log on to www.epa.gov/lead. In Canada contact a regional Health Canada office. Follow these instructions to control exposure to other hazardous substances that may be released during surface preparation.

Always sand with the grain of the wood. For hard woods, such as oak and maple, begin sanding with 100 grit sandpaper, then proceed to 150 grit sandpaper, and finish with 200 grit or finer sandpaper. For soft woods, such as pine, begin sanding with 150 grit sandpaper and finish with 200 grit or finer sandpaper.

Remove dust completely. Stain wood if desired.

Topcoat with OLYMPIC Premium Interior Water Based or Oil Based Polyurethane, Fast Dry Varnish or Interior/Exterior Spar Finish.

LIMITATIONS OF USE

FOR INTERIOR USE ONLY. Not recommended as a finish coat or topcoat. Always sand with the grain of the wood.

Do not apply when the air, coating or surface temperature is below 50°F (10°C).

Do not attempt to use on prewaxed wood flooring. Follow flooring manufacturer's coating recommendations.

This product is not intended for immersion service or other extreme conditions. Not recommended in situations characterized by high heat or presence of corrosive chemicals nor for heavy-duty use on floors.

PROTECT FROM FREEZING.

PACKAGING

Available in 1-Gallon (3.78L) and 1-Quart (945 mL) containers.

SAFETY PRECAUTIONS

Before using the products listed in this publication, carefully read each product label and follow directions for its use. Please read and observe all the warnings and precautionary information on the product labels. Material Safety Data Sheets are available through our Sales Representative, Retailer or by calling (412) 492-5555.

USE WITH ADEQUATE VENTILATION. KEEP OUT OF REACH OF CHILDREN.

PPG Architectural Finishes, Inc. believes the technical data presented is currently accurate; however, no guarantee of accuracy, comprehensiveness, or performance is given or implied. Improvements in coatings technology may cause future technical data to vary from what is in this bulletin. For complete, up-to-date technical information, call 1-800-441-9695.



PPG Industries, Inc.
Architectural Coatings
One PPG Place
Pittsburgh, PA 15272
www.ppgpittsburghpaints.com
www.ppgporterpaints.com

Technical Services
1-800-441-9695

Architect/Specifier:
1-888-PPG-IDEA

PPG Canada, Inc.
Architectural Coatings
4 Kenview Blvd
Brampton, ON L6T 5E4

T.D. 4017 10/2011
(Supersedes 5/2010)

Made in the
USA