



OLYMPIC® Premium Interior Fast Dry Wood Stain Oil Based

GENERAL DESCRIPTION

OLYMPIC® Premium Interior Fast Dry Stain is an excellent alkyd, fast drying, wiping stain designed to deliver professional results. It is recommended for use on interior woodwork including floors, trim, doors, beams, paneling, and furniture. As part of a one day wood finishing system, it can be used in conjunction with the OLYMPIC Fast Dry Varnish for topcoating.

RECOMMENDED USES

Furniture	Doors
Cabinets	Floors
Paneling	
Trim	

FEATURES / BENEFITS

Professional Fast Dry Wiping Stain for Wood
Alkyd/Oil Based
For Trim, Doors, Floors, Cabinets, Furniture and More
2 Hour Topcoat

DIRECTIONS FOR USE

Stir or shake thoroughly. Stir occasionally during application as necessary. Intermix containers to ensure color uniformity.

Pretest: Test a small hidden area or piece of scrap wood prior to application to ensure acceptable appearance and penetration.

APPLICATION INFORMATION

Application Equipment: Apply with a bristle brush or a soft lint-free cloth.

Application Method: On bare wood, apply a uniform coat of OLYMPIC Fast Dry Premium Interior Stain by brush or soft cloth. Wipe off excess stain with a soft, lint-free cloth after suitable penetration time. Test on scrap wood to determine the best time interval between application and wiping. To obtain more density or darker stain effects, repeat the stain application. When the stain is dry, apply the balance of the finish system.

Thinning: Not recommended.

PRODUCT INFORMATION

41570	Natural	(Formerly PP300)
41571	Honey Oak	(Formerly PP301)
41572	Classic American	(Formerly PP302)
41573	Regal Cherry	(Formerly PP303)
41574	Rich Mahogany	(Formerly PP304)
41575	Jacobean	(Formerly PP305)

Tinting: Products serve as ready-mix colors and as tintable bases. All are tintable with up to 10 oz. (295 mL) of colorant per gallon of stain.

PRODUCT DATA

PRODUCT TYPE:	Alkyd / Oil Resin
VOLUME SOLIDS*:	31% +/- 2%
WEIGHT SOLIDS*:	39% +/- 2%
VOC*:	<550 g/L (4.58 lbs./gal.)
WEIGHT/GALLON*:	7.3 lbs. (3.3 kg) +/- 0.2 lbs. (91 g)
FLASH POINT:	109°F (42.8°C)

*Product data calculated on 41570.

COVERAGE: Approximately 500 sq. ft. (46.5 sq. meters) per gallon (3.78L). Coverage will vary with wood type, porosity, preparation and application.

DRYING TIME: Dry times are affected by humidity, temperature, and color of the stain being applied. Allow a minimum of 2 hours drying before recoating. Typically dries to touch in 15 minutes and to handle in 30 minutes. To test for dryness, lightly rub with a white cloth. If the cloth picks up the color, wait at least one hour and retest.

CLEANUP: Clean up with mineral spirits or paint thinner.

Danger - Rags, steel wool or waste soaked with this product may spontaneously catch fire if improperly discarded. Immediately after use, place rags, steel wool or waste in a sealed water-filled metal container.

OLYMPIC® Premium Interior Fast Dry Oil Based Wood Stain

GENERAL SURFACE PREPARATION

Proper surface preparation is essential for the OLYMPIC limited warranty to apply. Stain only clean, dry, deglossed and profiled surfaces. Remove dirt, oils, grease, wax, release agents, sanding dust, paint remover, etc. with soap or TSP and water, paint thinner, or other appropriate cleaners, or by vacuuming as necessary. Fill openings and nail holes with a suitable filler. Test application in a clean, non-conspicuous area for proper color and penetration.

WARNING! If you scrape, sand, or remove old paint, you may release lead dust or fumes. LEAD IS TOXIC. EXPOSURE TO LEAD DUST OR FUMES CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE. Wear a properly fitted NIOSH-approved respirator and prevent skin contact to control lead exposure. Clean up carefully with a HEPA vacuum and a wet mop. Before you start, find out how to protect yourself and your family by contacting the USEPA National Lead Information Hotline at 1-800-424-LEAD or log on to www.epa.gov/lead. In Canada contact a regional Health Canada office. Follow these instructions to control exposure to other hazardous substances that may be released during surface preparation.

BARE WOOD: Always sand with the grain of the wood. For hard woods, such as oak and maple, begin sanding with 100 grit sandpaper, then proceed to 150 grit sandpaper, and finish with 200 grit or finer sandpaper. For soft woods, such as pine, begin sanding with 150 grit sandpaper and finish with 200 grit or finer sandpaper.

REFINISHING OLD WOOD: Remove all old finishes down to bare wood prior to application.

FINAL SURFACE PREPARATION: All wood must be dry and free of dust, dirt, grease or oils. Use a tack cloth or vacuum cleaner to remove any dust or dirt from the wood. Surfaces must be dry before staining.

FINISHING RECOMMENDATIONS: Protection with varnish or polyurethane is recommended.

LIMITATIONS OF USE

FOR INTERIOR USE ONLY. Do not apply when the air, coating or surface temperature is below 50°F (10°C).

Do not use as an opaque cleaner or near opaque stain.

Do not attempt to use on prewaxed wood flooring. Follow flooring manufacturer's coating recommendations.

These products are not intended for immersion service or other extreme conditions. Not recommended in situations characterized by high heat or presence of corrosive chemicals nor for heavy-duty use on floors.

PACKAGING

One gallon (3.78 L) and one quart (946 mL) containers.

SAFETY PRECAUTIONS

Before using the products listed in this publication, carefully read each product label and follow directions for its use. Please read and observe all the warnings and precautionary information on the product labels. Material Safety Data Sheets are available through our Sales Representative, Retailer or by calling (412) 492-5555.

Keep containers closed and away from heat, sparks, and flame when not in use.

USE WITH ADEQUATE VENTILATION. KEEP OUT OF REACH OF CHILDREN.

PPG Architectural Finishes, Inc. believes the technical data presented is currently accurate; however, no guarantee of accuracy, comprehensiveness, or performance is given or implied. Improvements in coatings technology may cause future technical data to vary from what is in this bulletin. For complete, up-to-date technical information, call 1-800-441-9695.



Olympic - US
PPG Industries, Inc.
Architectural Coatings
One PPG Place
Pittsburgh, PA 15272
www.ppgpittsburghpaints.com
www.ppgporterpaints.com

Technical Services
1-800-441-9695

Architect/Specifier
1-888-PPG-IDEA

Olympic - Canada
PPG Canada, Inc.
Architectural Coatings
4 Kenview Blvd
Brampton, ON L6T 5E4

T.D. 4028 10/2011
(Supersedes 5/2008)

Made in the
USA